# **SAFETY DATA SHEET**



Date of issue/Date of revision3 October 2024Version 1.01

# Section 1. Identification of the substance/mixture and of the company/undertaking

Product code	: 000001099289		
Product name	: SIGMALINE 855 REP BASE RAL 5022		
Other means of identification	: 00218685		
Product type	: Liquid.		
Relevant identified uses of the substance or mixture and uses advised against			
Product use	<ul> <li>Coating.</li> <li>Professional applications, Used by spraying.</li> </ul>		
Uses advised against	: Product is not intended, labelled or packaged for consumer use.		

Supplier's details	: PPG Coatings (Thailand) Co., Ltd. 15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand T: 662-319-4190 #224 F: 662-319-4189
Emergency telephone	: CHEMTREC 001-800-13-203-9987 (CCN 17704)

number (with hours of operation)

# Section 2. Hazards identification

Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (dermal) - Category 5 SKIN CORROSION/IRRITATION - Category 3 SKIN SENSITIZATION - Category 1B Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 37.5%
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 55.1%

#### **GHS label elements**

# Section 2. Hazards identification

Hazard pictograms	
Signal word	: Warning
Hazard statements	: Combustible liquid. May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Keep away from flames and hot surfaces. No smoking. Avoid breathing vapor. Contaminated work clothing should not be allowed out of the workplace.
Response	: FON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse.
Storage	: Store in a well-ventilated place. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	· None known

Other hazards which do not : None known. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

#### CAS number/other identifiers

<b>CAS number</b> : Not applicable.		
Ingredient name	%	CAS number
barium sulfate	25- <50	7727-43-7
Talc , not containing asbestiform fibres	10- <20	14807-96-6
Phenol, methylstyrenated	5- <10	68512-30-1
Propylidynetrimethanol, propoxylated	5- <10	25723-16-4

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8. SUB codes represent substances without registered CAS Numbers. Product name SIGMALINE 855 REP BASE RAL 5022

# Section 4. First aid measures

Description of necessary first aid measures			
Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>		
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.		
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>		
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>		

Most important symptoms/e	ffects, acute and delayed		
Potential acute health effect	t <u>s</u>		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.		
Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/symp	<u>toms</u>		
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include the following: irritation redness		
Ingestion	: No specific data.		
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>		
Specific treatments	: No specific treatment.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and<br/>explosion-proof equipment. Dilute with water and mop up if water-soluble.<br/>Alternatively, or if water-insoluble, absorb with an inert dry material and place in an<br/>appropriate waste disposal container. Dispose of via a licensed waste disposal<br/>contractor.

Product name SIGMALINE 855 REP BASE RAL 5022

### Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
▶arium sulfate	Ministry of Labor (Thailand, 8/2017) TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Respirable dust. TWA 8 hours: 15 mg/m <sup>3</sup> . Form: inhalable dust.
Talc , not containing asbestiform fibres	<b>Ministry of Labor (Thailand, 8/2017)</b> TWA 8 hours: 2 mg/m <sup>3</sup> . Form: Respirable dust.

Product name SIGMALINE 855 REP BASE RAL 5022

# Section 8. Exposure controls/personal protection

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	:	Safety glasses with side shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	1	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

Appearance			
Physical state	:	Liquid.	
Color	1	Blue.	
Odor	:	Aromatic. [Slight]	
Odor threshold	:	Not available.	
рН	:	insoluble in water.	
Melting point	:	Not available.	
Boiling point	1	>37.78°C (>100°F)	
Flash point	:	Closed cup: 65°C (149°F)	
Evaporation rate	:	Not available.	
Flammability (solid, gas)	:	liquid	
Lower and upper explosive (flammable) limits	:	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	:	1.81	
Solubility(ies)		Media R	esult
<b>Colubinity</b> (100)		cold water No	ot soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Auto-ignition temperature	:	Not available.	
Decomposition temperature	:	Stable under recommended s	storage and handling conditions (see Section 7).
Viscosity	:	Øynamic (room temperature) Kinematic (room temperature Kinematic (40°C): >21 mm²/s	e): Not available.
Viscosity	:	> 100 s (ISO 6mm)	

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Product name SIGMALINE 855 REP BASE RAL 5022

# Section 10. Stability and reactivity

 Hazardous decomposition
 : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
barium sulfate	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Phenol, methylstyrenated	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Propylidynetrimethanol, propoxylated	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2500 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Namo			Category	Route c
Specific target organ toxi	cit	<u>y (single exposure)</u>		
<b>Conclusion/Summary</b>	:	There are no data available	e on the mixture	e itself.
Teratogenicity				
<b>Conclusion/Summary</b>	:	There are no data available	e on the mixture	e itself.
Reproductive toxicity				
Conclusion/Summary	:	There are no data available	e on the mixture	e itself.
<b>Carcinogenicity</b>				
Conclusion/Summary	:	There are no data available	e on the mixture	e itself.
<b>Mutagenicity</b>				
Respiratory	:	There are no data available	e on the mixture	e itself.
Skin	:	There are no data available	e on the mixture	e itself.
Conclusion/Summary				
Sensitization				
Respiratory	:	There are no data available	e on the mixture	e itself.
Eyes	:	There are no data available	e on the mixture	e itself.
Skin	:	There are no data available	e on the mixture	e itself.
Conclusion/Summary				

Name	Category	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

Section 11. Toxicological information

Information on the likely : Not available. routes of exposure

Potential acute health effects		
Eye contact	o known significant effects or critical hazards.	
Inhalation	o known significant effects or critical hazards.	
Skin contact	ay be harmful in contact with skin. Causes mild skin irritation. May cause ergic skin reaction.	e an
Ingestion	o known significant effects or critical hazards.	
Symptoms related to the phy	chemical and toxicological characteristics	
Eye contact	dverse symptoms may include the following: in or irritation atering dness	
Inhalation	o specific data.	
Skin contact	lverse symptoms may include the following: itation dness	
Ingestion	o specific data.	
Delayed and immediate effect	d also chronic effects from short and long term exposure	
Short term exposure		
Potential immediate effects	ot available.	
Potential delayed effects	ot available.	
Long term exposure		
Potential immediate effects	ot available.	
Potential delayed effects	ot available.	
Potential chronic health eff		
General	ce sensitized, a severe allergic reaction may occur when subsequently exvery low levels.	xposed
Carcinogenicity	known significant effects or critical hazards.	
Mutagenicity	known significant effects or critical hazards.	
Reproductive toxicity	known significant effects or critical hazards.	

#### Numerical measures of toxicity

Acute toxicity estimates

# Section 11. Toxicological information

Route	ATE value	
Øral Dermal	14594.28 mg/kg 2693.2 mg/kg	

#### Other information

Sanding and grinding dusts may be harmful if inhaled.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Propylidynetrimethanol, propoxylated	Acute LC50 >100 mg/l	Fish	96 hours
Conclusion/Summary	: There are no data available on the m	ixture itself.	

#### Persistence/degradability

#### Not available.

Product/ingredient name	Test	Result	Dos	e Inoculu	ım
Propylidynetrimethanol, propoxylated	OECD 301A	84 % - Readily - 26	days -	-	
Conclusion/Summary	: There are no	data available on the	mixture itself.		
Product/ingredient name	Aquatic half-life		Photolysis	Biodeg	radability
Propylidynetrimethanol, propoxylated	-		-	Readily	

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Phenol, methylstyrenated	3.627	-	Low
Propylidynetrimethanol, propoxylated	0.01 to 1.5	-	Low

#### Mobility in soil

: Not available.

coefficient (Koc) Other adverse effects

Soil/water partition

: No known significant effects or critical hazards.

Product name SIGMALINE 855 REP BASE RAL 5022

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

UN: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

# Section 15. Regulatory information

#### Harmful Chemicals List : Listed

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 3 October 2024
Date of previous issue	: 6/17/2024
Version	: 1.01
Prepared by	: EHS
Key to abbreviations	<ul> <li>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway</li> <li>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.