## SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 10 October 2024 Version 2.06

## Section 1. Identification

Product code	: 000001099024
Product name	: SIGMASHIELD 1200 HARDENER BLACK
Product type	: Liquid.
Other means of identification 00195824	
Relevant identified uses of th	e substance or mixture and uses advised against
Product use	<ul> <li>Fardener.</li> <li>Professional applications, Used by spraying.</li> </ul>
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's information	: PPG Asian Paints Private Limited 6A Shanti Nagar Santa Cruz (East) Mumbai - 400055 India
Emergency telephone number:	: +91 22 6815 8700

## Section 2. Hazards identification

	India Page: 4	1/1:
	Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.	
Hazard statements	: Harmful if swallowed. Toxic in contact with skin or if inhaled.	
Signal word	: Danger	
GHS label elements Hazard pictograms		
	aquatic environment: 12%	
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the	
	Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 5.5%	
	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
	SKIN SENSITISATION - Category 1	
	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
	ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION/IRRITATION - Category 1A	
substance or mixture	ACUTE TOXICITY (dermal) - Category 3	
Classification of the	: ACUTE TOXICITY (oral) - Category 4	

## Section 2. Hazards identification

Precautionary statements		
Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Do not touch eyes. Contaminated work clothing should not be allowed out of the workplace.
Response	:	Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. IF SWALLOWED: Get emergency medical help immediately. Get medical help. Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Get emergency medical help immediately. Wash with plenty of water. Take off immediately all contaminated clothing. Immediately rinse with water for several minutes. If skin irritation or rash occurs: Get medical help. Take off immediately all contaminated clothing and wash it before reuse. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help. Get medical help if you feel unwell.
Storage	1	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not		None known.

result in classification

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

#### **CAS number/other identifiers**

**CAS number** : Not applicable.

Ingredient name	%	CAS number
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	50 - 100	6864-37-5
benzyl alcohol	10 - <20	100-51-6
N-(3-(trimethoxysilyl)propyl)ethylenediamine	3 - <5	1760-24-3
2,4,6-tris(dimethylaminomethyl)phenol	1 - <3	90-72-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

Description of necessa	ary first aid measures
Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

## Section 4. First aid measures

Most important symptoms/e	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: Toxic if inhaled.
Skin contact	: Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
<u>Over-exposure signs/symp</u>	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Firefighting measures Extinguishing media Suitable actinguishing

Suitable extinguishing media Unsuitable extinguishing media	<ul><li>: Use an extinguishing agent suitable for the surrounding fire.</li><li>: None known.</li></ul>
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Section 5. Firefighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and material for con	tainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	

## Section 7. Handling and storage

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

Control parameters							
Occupational exposure limits	<u>s</u>						
None.							
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.					
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.					
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.					
Individual protection measure	<u>es</u>						
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.					
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.					
Skin protection							
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.					
Gloves	:	nitrile neoprene					
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.					
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.					

#### Product code 000001099024 Product name SIGMASHIELD 1200 HARDENER BLACK

## Section 8. Exposure controls/personal protection

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance									
Physical state		Liquid.							
Colour		Black.	•						
Odour	1	Amine-like.							
Odour threshold	1	Not available.							
Melting point/freezing point	1	Not available.							
Boiling point or initial boiling point and boiling range	:	>37.78°C (>100°F)	7.78°C (>100°F)						
Flammability	1	Not available.							
Lower and upper explosive (flammable) limits	:	Not available.							
Flash point	1	Closed cup: 106°C (	(222.8°F)						
Auto-ignition temperature	1	Ingredient name		°C		°F		Method	
		2,2'-dimethyl-4,4'-methyl (cyclohexylamine)	enebis	275		527			
Decomposition temperature	:	Not available.							
рН	1	Not applicable.							
Viscosity	-	Øynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): >21 mm²/s							
		Media	Re	sult					
Solubility(ies)	-	cold water	No	t soluble	е				
Partition coefficient: n- octanol/water	:	Not applicable.							
Vapour pressure	1		Vapour Pressure at 20°C		20°C	Vapour pressure at 50°C			
		Ingredient name	mm Hg	kPa	Meth	od	mm Hg	kPa	Method
		2,4,6-tris (dimethylaminomethyl) phenol	0.056	0.0075	EU A.4	ļ			
Relative density	:	0.97			÷				
Relative vapour density Particle characteristics	;	Not available.							
Median particle size	:	Not applicable.							
Evaporation rate	:	Not available.							

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides
Hazardous polymerisation	: Under normal conditions of storage and use, hazardous polymerisation will not occur.

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2.2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	LC50 Inhalation Dusts and mists	Rat	420 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Dermal	Rabbit	>2000 mg/kg	-
5	LD50 Oral	Rat	2413 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion	
0	

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Sensitisation</u>	
<b>Conclusion/Summary</b>	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.

Date of issue 10 October 2024

## Section 11. Toxicological information

#### **Carcinogenicity**

- **Conclusion/Summary** : There are no data available on the mixture itself.
- Reproductive toxicity
- **Conclusion/Summary** : There are no data available on the mixture itself.

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	Category 2	-	-

#### Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on likely routes of exposure	Not available.	
Potential acute health effects		
Eye contact	Causes serious eye damage.	
Inhalation	Toxic if inhaled.	
Skin contact	Causes severe burns. Toxic in contact with skin. May cause an allergic s reaction.	kin
Ingestion	Harmful if swallowed.	
	al, chemical and toxicological characteristics	
Eye contact	Adverse symptoms may include the following: pain watering redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur	
Ingestion	Adverse symptoms may include the following: stomach pains	
Delayed and immediate effec	s well as chronic effects from short and long-term exposure	
Short term exposure Potential immediate effects	Not available.	

## Section 11. Toxicological information

Potential delayed effects	1	Not available.
Long term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health ef	fect	<u>s</u>
Not available.		
General	:	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Ǿral	571.79 mg/kg
Dermal	360.44 mg/kg
Inhalation (dusts and mists)	0.62 mg/l

#### Other information

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

## Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
N-(3-(trimethoxysilyl)propyl) ethylenediamine	EC50 597 mg/l	Fish	96 hours
2,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours

#### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,4,6-tris (dimethylaminomethyl)phenol		4 % - Not readily - 28 days	-	-

#### Product code 000001099024 Product name SIGMASHIELD 1200 HARDENER BLACK

#### Date of issue 10 October 2024

Version 2.06

Section 12. Ecological information
------------------------------------

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol 2,4,6-tris (dimethylaminomethyl)phenol	-	-	Readily Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
	1.8 0.87 0.219	-	Low Low Low

#### Mobility in soil

Soil/water partition	
coefficient (Koc)	

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN2922	UN2922	UN2922
UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.
	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)
Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)
Packing group	II	II	II
	1	l	

India

## Section 14. Transport information

	-		
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.

#### **Additional information**

UN

**IMDG** : The marine pollutant mark is not required when transported in sizes of  $\leq 5$  L or  $\leq 5$  kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** :**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

## Section 15. Regulatory information

#### International regulations

Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 10 October 2024
Date of previous issue	: 6/5/2024
Version	: 2.06
Prepared by	: EHS
key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

Procedure used to derive the classification

## Section 16. Other information

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
ACUTE TOXICITY (dermal) - Category 3	Calculation method
ACUTE TOXICITY (inhalation) - Category 3	Calculation method
SKIN CORROSION/IRRITATION - Category 1A	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	Calculation method

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

India