### SAFETY DATA SHEET

Date of issue : 11 October 2024

: 2.02 Version

### **Section 1. Identification**

: 17000-157629/4L **Product code** 

: PSX 700 COLORANT 62 OXIDE YELLOW **Product name** 

: Liquid. **Product type** Recommended use and restrictions

Use of the substance/

mixture

: Pigment paste

**Uses advised against** : Not applicable.

Supplier's details : PPG INDUSTRIES NEW ZEALAND LTD

5 MONAHAN ROAD, MT WELLINGTON,

**AUCKLAND** www.ppgnz.co.nz

Telephone Numbers: 09 573 1620, 0800 659378 021 940 920 (24 Hours)

**Emergency telephone** number (with hours of

operation)

: New Zealand 0800 000 096 (24 hours) / Australia 1800 883 254 (24 hours)

For international shipping emergencies: 1-412-391-1618

e-mail address of person responsible for this SDS

: ehsnz@ppg.com

### Section 2. Hazards identification

: REPRODUCTIVE TOXICITY - Category 2 **HSNO Classification** 

**Symbol** 



**GHS** label elements

Signal word : Warning

**Hazard statements** : Suspected of damaging fertility or the unborn child.

**Precautionary statements** 

: Do not handle until all safety precautions have been read and understood. Wear **Prevention** 

protective gloves, protective clothing and eye or face protection.

: IF exposed or concerned: Get medical advice or attention. Response

**Storage** : Not applicable.

: Dispose of contents and container in accordance with all local, regional, national **Disposal** 

and international regulations.

Other hazards which do not : None known.

result in classification

**New Zealand** Page: 1/10 Product code 17000-157629/4L Date of issue 11 October 2024 Version 2.02

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and has been classified according to the Hazardous Substances (Classifications) Notice 2017.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Land Transport Rule: Dangerous Goods 2005.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

**CAS** number/other identifiers

**Product code** : 17000-157629/4L

Hazardous ingredients	%	CAS number
voluene	<1	108-88-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

evelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eyes : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin**: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

New Zealand Page: 2/10

Product code 17000-157629/4L

Date of issue 11 October 2024 Version 2.02

#### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### Section 4. First aid measures

Ingestion : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments : Not available.

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Firefighting measures

#### Extinguishing media

**Suitable** : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

carbon oxides metal oxide/oxides

fighters

Special precautions for fire : Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

> **New Zealand** Page: 3/10

Product code 17000-157629/4L Date of issue 11 October 2024

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### Section 7. Handling and storage

## Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Version 2.02

# Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

Ingredient name Exposure limits	
voluene	HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 4/2022) Absorbed through skin, Ototoxicant. WES-TWA 8 hours: 20 ppm. WES-TWA 8 hours: 75 mg/m³.
	WES-STEL 15 minutes: 377 mg/m³. WES-STEL 15 minutes: 100 ppm.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

New Zealand Page: 4/10

Product code 17000-157629/4L Date of issue 11 October 2024 Version 2.02

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### Section 8. Exposure controls/personal protection

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Hand protection** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Eye protection

: Safety glasses with side shields.

Skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour Yellow. **Odour** : Aromatic. : Not available. **Odour threshold** Hq : Not applicable. **Melting point** : Not available. **Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

Flammability (solid, gas) : Not available. Lower and upper explosive

(flammable) limits

: Not available.

Vapour pressure : Not available.

Relative density 1.44

Media Result Solubility(ies)

cold water Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

**Viscosity** : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

**Viscosity** : 60 - 100 s (ISO 6mm)

> **New Zealand** Page: 5/10

Product code 17000-157629/4L Date of issue 11 October 2024 Version 2.02

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### Section 10. Stability and reactivity

**Stability** : The product may not be stable under certain conditions of storage or use.

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

**Conditions to avoid** 

: No specific data.

Incompatible materials

: Reactive or incompatible with the following materials:

oxidising materials strong acids strong alkalis

**Hazardous decomposition** 

products

Depending on conditions, decomposition products may include the following

materials: carbon oxides metal oxide/oxides

**Hazardous polymerisation** : Under normal conditions of storage and use, hazardous polymerisation will not

occur.

### Section 11. Toxicological information

#### Information on likely routes of exposure

Inhalation : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact** : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

: No specific data. **Eye contact** 

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
toluene	LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rabbit	49 g/m³ 8.39 g/kg 5580 mg/kg	4 hours - -

**Conclusion/Summary** 

: There are no data available on the mixture itself.

Irritation/Corrosion **Conclusion/Summary** 

: There are no data available on the mixture itself. Skin : There are no data available on the mixture itself. Eyes : There are no data available on the mixture itself. Respiratory

**Sensitisation** 

**New Zealand** Page: 6/10 Product code 17000-157629/4L Date of issue 11 October 2024 Version 2.02

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **Section 11. Toxicological information**

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : Suspected of damaging the unborn child.
 Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Chronic toxicity

Not available.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity

Name		Route of exposure	Target organs
voluene	Category 2	-	-

#### **Aspiration hazard**

Not available.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Not available.

#### Other information :

rimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

### **Section 12. Ecological information**

**Ecotoxicity** : No known significant effects or critical hazards.

**Aquatic and terrestrial toxicity** 

Not available.

#### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Muene	-	-	Readily

New Zealand Page: 7/10

Product code 17000-157629/4L

Date of issue 11 October 2024

Version 2.02

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### Section 12. Ecological information

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	Low

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Not suitable:

: Do not allow to enter drains or watercourses.

The classification of the product may meet the criteria for a hazardous waste. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### 14. Transport information

	NZ	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

New Zealand Page: 8/10

Date of issue 11 October 2024 Product code 17000-157629/4L Version 2.02

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### 14. Transport information

#### Additional information

NZ : None identified. Hazchem code : Not applicable. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

### Section 15. Regulatory information

**New Zealand Inventory of** 

Chemicals (NZIoC)

: All components are listed or exempted.

**HSNO Approval Number** 

: HSR002670 Subsidiary Hazard

**Emergency Management** 

Regulations

: Level 1: Not applicable.

Level 2: MSDS required when any amount is present in a workplace.

Level 3: Not applicable.

**Approved Handler** : Not applicable.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

### Section 16. Other information

**Date of issue** : 11 October 2024 Date of previous issue : 11/20/2022

Indicates information that has changed from previously issued version.

**New Zealand** Page: 9/10 Product code 17000-157629/4L Date of issue 11 October 2024 Version 2.02

Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **Section 16. Other information**

**Key to abbreviations** : STEL = Short Term Exposure Limit

TWA = Time-Weighted Average WES = Work Exposure Standard

References : Not available.

Organisation that prepared : EHS

the SDS

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

New Zealand Page: 10/10