# **SAFETY DATA SHEET**



### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 11 October 2024

Version 3.02

Date of issue 11 October 2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: PSX 700 COLORANT 62 OXIDE YELLOW
Product code	: 00291651
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses of	of the substance or mixture and uses advised against
Product use	: Professional applications.
Use of the substance/ mixture	: Pígment paste
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

### **SECTION 2: Hazards identification**

Classification of the substance or mixture	: TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 70.3% (oral), 99.1% (dermal), 70.3% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H361 - Suspected of damaging fertility or the unborn child.
Precautionary statements	

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 2: Hazards identification**

Prevention	:	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> </ul>
Response	:	P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.

See toxicological information (Section 11)

### **SECTION 3: Composition/information on ingredients**

Substance/mixture Product name	: Mixture : PSX 700 COLORANT 62 OXIDE YELLOW
Other means of identification	: Not applicable.

Ingredient name	%	CAS number
toluene	<1.0	108-88-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

#### **Description of necessary first aid measures**

Eye contact Inhalation	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact Ingestion	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> <li>If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

#### Most important symptoms/effects, acute and delayed

Potential acute health effects			
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		

#### **Over-exposure signs/symptoms**

See toxicological information (Section 11)

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 4: First aid measures**

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### **SECTION 5: Firefighting measures**

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning up		
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 6: Accidental release measures**

Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth,
Wash spillages into an effluent treatment plant or proceed as follows. Contain and
collect spillage with non-combustible, absorbent material e.g. sand, earth,
vermiculite or diatomaceous earth and place in container for disposal according to
local regulations (see Section 13). Dispose of via a licensed waste disposal
contractor. Contaminated absorbent material may pose the same hazard as the
spilled product. Note: see Section 1 for emergency contact information and Section
13 for waste disposal.

### **SECTION 7: Handling and storage**

### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

**Occupational exposure limits** 

Ingredient name			Exposure limits	
toluene			NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 20 ppm.	
	Key to abbreviations			
С	= Ceiling Limit	STEL	<ul> <li>Short term exposure limit</li> </ul>	
IPEL	= Internal Permissible Exposure Limit	TLV	= Threshold Limit Value	

TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Mexico Page: 4/11

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

# **SECTION 8: Exposure controls/personal protection**

•		• •
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety glasses with side shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# **SECTION 9: Physical and chemical properties**

Appearance	
Physical state	: Liquid.
Color	: Yellow.
Odor	: Aromatic.
Odor threshold	: Not available.
Molecular weight	: Not applicable.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 9: Physical and chemical properties**

-			
Flash point	:	Closed cup: Not applicable.	
Auto-ignition temperature	:	Not available.	
Decomposition temperature	1	Not available.	
Flammability	4	Not available.	
Lower and upper explosive (flammable) limits	1	Not available.	
Evaporation rate	1	Not available.	
Vapor pressure	1	Not available.	
Vapor density	1	Not available.	
Relative density	1	1.44	
Density(lbs / gal)	:	12.02	
Colubility/ico)	:	Media Result	
Solubility(ies)		cold water Not soluble	
Solubility in water	:	Not available.	
Partition coefficient: n- octanol/water	1	Not applicable.	
Viscosity	:	<ul> <li>Dynamic (room temperature): Not available.</li> <li>Kinematic (room temperature): Not available.</li> <li>Kinematic (40°C (104°F)): &gt;21 mm²/s (&gt;21 cSt)</li> </ul>	
% Solid. (w/w)		99.232	

# **SECTION 10: Stability and reactivity**

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials carbon oxides metal oxide/oxides

### **SECTION 11: Toxicological information**

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
toluene	LC50 Inhalation Vapor	Rat	49 g/m³	4 hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LD50 Oral	Rat	5580 mg/kg	-

Mexico	Page: 6/11

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 11: Toxicological information**

Conclusion/Summary	: There a	re no data	available on the mixture itself.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There a	re no data	available on the mixture itself.	
Eyes	: There a	re no data	available on the mixture itself.	
Respiratory	: There a	re no data	available on the mixture itself.	
Sensitization				
Conclusion/Summary				
Skin	: There a	re no data	available on the mixture itself.	
Respiratory	: There a	re no data	available on the mixture itself.	
Mutagenicity				
<b>Conclusion/Summary</b>	: There a	re no data	available on the mixture itself.	
<b>Carcinogenicity</b>				
<b>Conclusion/Summary</b>	: There a	re no data	available on the mixture itself.	
<b>Classification</b>				
Product/ingredient na	me OSHA	IARC	NTP	
				-

toluene

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

\_

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### **Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

3

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
toluene	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
toluene	Category 2	-	-

Target organs : Contains mate

: Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes.

#### **Aspiration hazard**

Name	Result
toluene	ASPIRATION HAZARD - Category 1

#### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

# **SECTION 11: Toxicological information**

Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympt	<u>oms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effe	cts and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects Long term exposure	: There are no data available on the mixture itself.
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	<u>ects</u>
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Numerical measures of toxi	<u>city</u>

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	(mg/kg)		(mg/l)	Inhalation (dusts and mists) (mg/l)
toluene	5580	8390	N/A	49	N/A

Mexico	Page: 8/11

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 12: Ecological information**

#### **Toxicity**

Not available.

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	Low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

#### Other adverse effects

: No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### **SECTION 14: Transport information**

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
			Mexico Page: 9/1 <sup>-</sup>

SECTION '	14: Transport informa	ation	
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.
Additional inform	nation		
Mexico	: None identified.		
IMDG	: None identified.		
ΙΑΤΑ	: None identified.		

Transport in bulk according : Not applicable. to IMO instruments

### **SECTION 15: Regulatory information**

#### International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

### **SECTION 16: Other information**

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of previous issue	: 10/9/2024
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available

### Product name PSX 700 COLORANT 62 OXIDE YELLOW

### **SECTION 16: Other information**

SGG = Segregation Group UN = United Nations

#### Indicates information that has changed from previously issued version.

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.