# **SAFETY DATA SHEET**



Date of issue/Date of revision 11 October 2024

**Version 1** 

# Section 1. Identification of the substance/mixture and of the company/undertaking

**Product code** : 000001103829

Product name : PSX 700 COLORANT 42 OXIDE RED

Other means of : 00293926

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Pigment paste

Professional applications, Used by spraying, Application by non spray methods...

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

**Supplier's details**: PPG Coatings (Thailand) Co., Ltd.

15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand

T: 662-319-4190 #224 F: 662-319-4189

Emergency telephone number (with hours of

operation)

: CHEMTREC 001-800-13-203-9987 (CCN 17704)

# Section 2. Hazards identification

Classification of the substance or mixture

: Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 61%

**GHS label elements** 

Signal word : No signal word.

**Hazard statements**: No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Thailand Page: 1/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

### Section 2. Hazards identification

Disposal : Not applicable.

Other hazards which do not : None known.

result in classification

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Ingredient name	%	CAS number
toluene	0.3 - <1	108-88-3

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### Description of necessary first aid measures

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the **Eye contact** 

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Inhalation **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

#### Over-exposure signs/symptoms

**Eve contact** : No specific data. Inhalation : No specific data.

**Thailand** Page: 2/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

### Section 4. First aid measures

Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

hina

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon oxides nitrogen oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Thailand Page: 3/11

Product code 000001103829 Date of issue 11 October 2024

**Product name PSX 700 COLORANT 42 OXIDE RED** 

### Section 6. Accidental release measures

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Version 1

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent

treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for

emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8).

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

toluene Ministry of Labor (Thailand, 8/2017)

TWA 8 hours: 200 ppm. STEL 10 minutes: 500 ppm.

CEIL: 300 ppm.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous

substances will also be required.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne

contaminants.

**Thailand** Page: 4/11 Product code 000001103829

Date of issue 11 October 2024

Version 1

**Product name PSX 700 COLORANT 42 OXIDE RED** 

# Section 8. Exposure controls/personal protection

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection : Safety glasses with side shields.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates

this is necessary.

Gloves : For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Red.

Odor : Characteristic.
Odor threshold : Not available.
pH : insoluble in water.
Melting point : Not available.

**Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

**Evaporation rate** : Not available.

Flammability (solid, gas) : liquid

Thailand Page: 5/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

# Section 9. Physical and chemical properties

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure: Not available.Vapor density: Not available.

Relative density : 1.69

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature

: Not available.

**Decomposition temperature** 

Stable under recommended storage and handling conditions (see Section 7).

Viscosity

Dynamic (room temperature): Not available. Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm<sup>2</sup>/s

**Viscosity** : 60 - 100 s (ISO 6mm)

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/

oxides

# Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
toluene	LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rabbit	49 g/m³ 8.39 g/kg 5580 mg/kg	4 hours - -

**Conclusion/Summary**: There are no data available on the mixture itself.

Thailand Page: 6/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

# **Section 11. Toxicological information**

### **Irritation/Corrosion**

**Conclusion/Summary** 

Skin
Eyes
There are no data available on the mixture itself.
Respiratory
There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
toluene	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
toluene	Category 2	-	-

#### **Aspiration hazard**

Name	Result
toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Thailand Page: 7/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

# Section 11. Toxicological information

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

effects

: Not available.

**Potential delayed effects** 

: Not available.

Long term exposure

**Potential immediate** 

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Not available.

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

# Section 12. Ecological information

### **Toxicity**

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

### Persistence/degradability

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

	Thailand	Page: 8/11
--	----------	------------

**Product name PSX 700 COLORANT 42 OXIDE RED** 

# Section 12. Ecological information

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	Low

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

### **Additional information**

UN : None identified.IMDG : None identified.IATA : None identified.

Thailand Page: 9/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

# **Section 14. Transport information**

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

# Section 15. Regulatory information

**Harmful Chemicals List** 

Safety, health and environmental regulations specific for the product

Listed

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

### **International regulations**

#### **Montreal Protocol**

Not listed.

### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

### Section 16. Other information

#### **History**

Date of issue/Date of

revision

: 11 October 2024

Date of previous issue : No previous validation

**Version** : 1 **Prepared by** : EHS

**Key to abbreviations** : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Indicates information that has changed from previously issued version.

**Notice to reader** 

**Thailand** Page: 10/11

**Product name PSX 700 COLORANT 42 OXIDE RED** 

### **Section 16. Other information**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Thailand Page: 11/11