# **SAFETY DATA SHEET**



### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 11 October 2024

Version 1.01

Date of issue 11 October 2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE
Product code	: 000001103817
Other means of identification	: 00291652
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Pigment paste
Uses advised against	Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

# **SECTION 2: Hazards identification**

Classification of the substance or mixture	<ul> <li>ACUTE TOXICITY (dermal) - Category 5 TOXIC TO REPRODUCTION - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 62.3% (oral), 93% (dermal), 67.8% (inhalation)</li> </ul>
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H313 - May be harmful in contact with skin. H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements

Mexico Page: 1/11

# **SECTION 2: Hazards identification**

Prevention	:	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> </ul>
Response	:	P308 + P313 - IF exposed or concerned: Get medical advice or attention. P302 + P312 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.

See toxicological information (Section 11)

## **SECTION 3: Composition/information on ingredients**

Substance/mixture	: Mixture
Product name	: PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE
Other means of identification	: 00291652

Ingredient name	%	CAS number
barium sulfate	≥5.0 - ≤8.7	7727-43-7
toluene	<1.0	108-88-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May be harmful in contact with skin.
Ingestion	: No known significant effects or critical hazards.

### **SECTION 4: First aid measures**

**Over-exposure signs/symptoms** 

See toxicological information (Section 11)

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

# **SECTION 5: Firefighting measures**

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides sulfur oxides phosphorus oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders		No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

#### Product name PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE

# **SECTION 6: Accidental release measures**

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# **SECTION 7: Handling and storage**

Precautions for safe handling	9	
Protective measures	-	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# **SECTION 8: Exposure controls/personal protection**

<u>Control parameters</u> <u>Occupational exposure limits</u>

### Product name PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE

# **SECTION 8: Exposure controls/personal protection**

Ingredient name		Exposure limits
barium sulfate toluene		NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 10 mg/m³. NOM-010-STPS-2014 (Mexico, 4/2016)
loidene		TWA 8 hours: 20 ppm.
	Key to abbreviations	
C = Ceiling Limit IPEL = Internal Permissible Expo	sure Limit	STEL=Short term exposure limitTLV=Threshold Limit ValueTWA=Time Weighted Average
Consult local authorities for	acceptable exposure limits.	
Recommended monitoring procedures		appropriate monitoring standards. Reference to for methods for the determination of hazardous ed.
Appropriate engineering controls	local exhaust ventilation or oth	st, fumes, gas, vapor or mist, use process enclosures er engineering controls to keep worker exposure to any recommended or statutory limits.
Environmental exposure controls	they comply with the requirem cases, fume scrubbers, filters	work process equipment should be checked to ensure ents of environmental protection legislation. In some or engineering modifications to the process o reduce emissions to acceptable levels.
ndividual protection measure	<u>98</u>	
Hygiene measures	eating, smoking and using the Appropriate techniques should	ce thoroughly after handling chemical products, befor lavatory and at the end of the working period. I be used to remove potentially contaminated clothing before reusing. Ensure that eyewash stations and e workstation location.
Eye/face protection Skin protection	: Safety glasses with side shield	ls.
Hand protection	be worn at all times when han this is necessary. Considering check during use that the glov should be noted that the time different for different glove ma	s gloves complying with an approved standard should dling chemical products if a risk assessment indicates g the parameters specified by the glove manufacturer es are still retaining their protective properties. It to breakthrough for any glove material may be nufacturers. In the case of mixtures, consisting of ction time of the gloves cannot be accurately
Gloves	: For prolonged or repeated har	ndling, use the following type of gloves:
	Recommended: neoprene, na	tural rubber (latex), nitrile rubber, Chloroprene
Body protection		t for the body should be selected based on the task involved and should be approved by a specialist
Other skin protection	: Appropriate footwear and any	additional skin protection measures should be ing performed and the risks involved and should be e handling this product.

### Product name PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE

# **SECTION 8: Exposure controls/personal protection**

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
------------------------	--

# **SECTION 9: Physical and chemical properties**

<u>Appearance</u>			
Physical state	1	Liquid.	
Color	1	Yellow.	
Odor	:	Aromatic.	
Odor threshold	:	Not available.	
Molecular weight	4	Not applicable.	
рН	÷	Not applicable.	
Melting point		Not available.	
Boiling point	4	>37.78°C (>100°F)	
Flash point	1	Closed cup: Not applicabl	e.
Auto-ignition temperature	1	Not available.	
Decomposition temperature		Not available.	
Flammability		Not available.	
Lower and upper explosive (flammable) limits	:	Not available.	
Evaporation rate	1	Not available.	
Vapor pressure	1	Not available.	
Vapor density	1	Not available.	
Relative density	:	1.62	
Density(lbs / gal)	:	13.52	
		Media	Result
Solubility(ies)	1	cold water	Not soluble
Solubility in water	:	Not available.	
Partition coefficient: n- octanol/water	1	Not applicable.	
Viscosity	-	Dynamic (room temperatu Kinematic (room tempera Kinematic (40°C (104°F))	ture): Not available.
% Solid. (w/w)	1	99.32	·

# **SECTION 10: Stability and reactivity**

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.

Mexico Page: 6/11

### **SECTION 10: Stability and reactivity**

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials carbon oxides sulfur oxides phosphorus oxides metal oxide/oxides

# **SECTION 11: Toxicological information**

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result			Species	Dose	Exposure		
barium sulfate	LD50 Derr	nal		Rat	>2000 mg/kg	-		
	LD50 Oral			Rat	>5000 mg/kg	-		
toluene	LC50 Inha		or	Rat	49 g/m <sup>3</sup>	4 hours		
	LD50 Derr	nal		Rabbit	8.39 g/kg	-		
	LD50 Oral			Rat	5580 mg/kg	-		
Conclusion/Summary	: There a	re no data	a available on	the mixture i	tself.			
Irritation/Corrosion								
Conclusion/Summary								
Skin	: There a	: There are no data available on the mixture itself.						
Eyes	: There a	: There are no data available on the mixture itself.						
Respiratory	: There a	: There are no data available on the mixture itself.						
Sensitization								
Conclusion/Summary								
Skin	: There a	re no data	a available on	the mixture i	tself.			
Respiratory	: There a	re no data	a available on	the mixture i	tself.			
<u>Mutagenicity</u>								
Conclusion/Summary	: There a	re no data	a available on	the mixture i	tself.			
Carcinogenicity								
Conclusion/Summary	: There a	re no data	a available on	the mixture i	tself.			
<b>Classification</b>								
Product/ingredient name	OSHA	IARC	NTP					
•								

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### **Reproductive toxicity**

Conclusion/Summary: There are no data available on the mixture itself.TeratogenicityConclusion/Summary: There are no data available on the mixture itself.Specific target organ toxicity (single exposure)

# **SECTION 11: Toxicological information**

Name		Category	Route of exposure	Target organs	
toluene		Category 3	-	Narcotic effects	
Specific target organ	toxicity (repeated exposure)		ł		
Name		Category	Route of exposure	Target organs	
toluene		Category 2	-	-	
Target organs       : Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes.         Contains material which may cause damage to the following organs: blood, lungs.					

#### **Aspiration hazard**

Name	Result
toluene	ASPIRATION HAZARD - Category 1

#### Information on the likely routes of exposure

Potential acute health effect	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May be harmful in contact with skin.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	oms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effe	ts and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Long term exposure	

# **SECTION 11: Toxicological information**

Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Potential chronic health effe	ects	
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging fertility or the unborn child.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE barium sulfate	N/A N/A	3155.5 2500	N/A N/A	N/A N/A	N/A N/A
toluene	5580	8390	N/A	49	N/A

# **SECTION 12: Ecological information**

#### **Toxicity**

Not available.

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	Low

#### Mobility in soil

Soil/water partition coefficient (Koc) : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

Mexico Page: 9/11

#### Product name PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE

# **SECTION 13: Disposal considerations**

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# **SECTION 14: Transport information**

	Mexico Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

- Mexico : None identified.
- IMDG : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

#### Product name PSX 700 COLORANT 63 YELLOW BISMUTH VANDATE

### **SECTION 15: Regulatory information**

#### International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

# **SECTION 16: Other information**

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of previous issue Organization that prepared the SDS	: <b>10/11/2024</b> : EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations</li> </ul>

#### Indicates information that has changed from previously issued version.

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.