SAFETY DATA SHEET

Date of issue/Date of revision

: 17 October 2024

Version

: 3.06





SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifierProduct name:

: SIGMAGUARD CSF 585 HARDENER

: 000001099278

Other means of identification

Product code

0219189; 00219193; 00293059; 00295221

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Hardener.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Varossieau Suriname NV, Mastanaweg 4, Paramaribo, SURINAME Tel: 00597 484447 Fax: 00597 483785	
e-mail address of person responsible for this SDS	: Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone : 0031 (0)20 4075210 number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412 The mediatic classified as hereadous according to Devulation (EQ) 12

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2	Label	elements

Hazard pictograms



			0
Prevention	: W	ear protective gloves, protective clothing and	l eye or face protection.
Precautionary statements			
Hazard statements		auses severe skin burns and eye damage. armful to aquatic life with long lasting effects.	
Signal word	: Da	anger	
		•	



Code : 0000010992	278	Date of issue/Date of revision	: 17 October 2024
SIGMAGUARD CSF 585 HA	ARDENER		

SECTION 2: Hazards identification

SECTION 2. Hazarus		
Response	:	IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P304 + P310, P301 + P310, P303 + P361 + P353, P310, P501
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requiren	ner	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	REACH #: 01-2119557899-12 EC: 618-561-0 CAS: 9046-10-0 (n = 2-6)	≥50 - ≤75	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2	≥1.0 - ≤5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

English (GB)	Suriname	2/13
--------------	----------	------

Code : 000001099278 SIGMAGUARD CSF 585 HARDENER Date of issue/Date of revision

: 17 October 2024

SECTION 3: Composition/information on ingredients

Туре

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid m	easures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effect		
Eye contact	es serious eye damage.	
Inhalation	own significant effects or critical hazards.	
Skin contact	es severe burns.	
Ingestion	own significant effects or critical hazards.	
Over-exposure signs/sympt		
Eye contact	rse symptoms may include the following: ing ess	
Inhalation	pecific data.	
Skin contact	rse symptoms may include the following: or irritation ess ring may occur	
Ingestion	rse symptoms may include the following: ach pains	
4.3 Indication of any immedia	al attention and special treatment needed	
Notes to physician	e of inhalation of decomposition products in a fire, symptoms m xposed person may need to be kept under medical surveillance	
Our exattle two etces and a	- if - the star and	

Specific treatments : No specific treatment.

SECTION	5: Firefighting measures		
SIGMAGUARE	D CSF 585 HARDENER		
Code :	000001099278	Date of issue/Date of revision	: 17 October 2024

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	om the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
co	ntainment and cleaning up
:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
	: : :

English (GB)

4/13

Suriname

Code : 000001099278

SIGMAGUARD CSF 585 HARDENER

Date of issue/Date of revision :

: 17 October 2024

SECTION 6: Accidental release measures

2

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure indices known.

Recommended monitoring procedures

Ing : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Code	: 000001099278	Date of issue/Date of revision	: 17 October 2024
SIGMAGUAR	D CSF 585 HARDENER		

			1		
Product/ingredient name	Туре	Exposure	Value	Population	Effects
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	DNEL	Long term Inhalation	1.36 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	2.5 mg/kg bw/day	Workers	Systemic
2,4,6-tris(dimethylaminomethyl)phenol	DNEL	Long term Oral	0.075 mg/kg bw/ day	General population	Systemic
	DNEL	Short term Dermal	0.075 mg/kg bw/ day	General population	Systemic
	DNEL	Long term Dermal	0.075 mg/kg bw/ day	General population	Systemic
	DNEL	Short term Inhalation	0.13 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	0.13 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.53 mg/m ³	Workers	Systemic
	DNEL DNEL	Short term Dermal Short term Inhalation	0.6 mg/kg bw/day 2.1 mg/m³	Workers Workers	Systemic Systemic

PNECs

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	-	Fresh water	0.015 mg/l	Assessment Factors
	-	Marine water	0.014 mg/l	Assessment Factors
	-	Sewage Treatment Plant	7.5 mg/l	Assessment Factors
	-	Fresh water sediment	0.132 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.125 mg/kg dwt	Equilibrium Partitioning
	-	Soil	0.018 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls	
Appropriate engineering controls	 If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection measu	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Chemical splash goggles and face shield.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

English (GB)	Suriname	6/13

2020/078			
Code : 0000010992	78	Date of issue/Date of revision	: 17 October 2024
SIGMAGUARD CSF 585 HA	RDENER		
Gloves	: nitrile neoprene		
Body protection	•	e equipment for the body should be selected risks involved and should be approved by a uct.	
Other skin protection	based on the task	ear and any additional skin protection meas being performed and the risks involved and andling this product.	
Respiratory protection	hazards of the pro are exposed to con certified respirators with an approved s	on must be based on known or anticipated ed duct and the safe working limits of the select ncentrations above the exposure limit, they s. Use a properly fitted, air-purifying or air-f standard if a risk assessment indicates this ing to EN140. Filter type: organic vapour (cted respirator. If workers must use appropriate, ed respirator complying is necessary. Wear a
Environmental exposure controls	they comply with th cases, fume scrub	entilation or work process equipment should ne requirements of environmental protectior bers, filters or engineering modifications to o reduce emissions to acceptable levels.	n legislation. In some

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Colourless.
Odour	: Amine-like.
Odour threshold	: Not available.
Melting point/freezing point	: Not determined.
Initial boiling point and boiling range	: >37.78°C
Flammability	: Not determined. There are no data available on the mixture itself.
Upper/lower flammability or explosive limits	: Not available.
Flash point	: Closed cup: 80°C
Auto-ignition temperature	: 426°C (798.8°F)
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
рН	: Not applicable. insoluble in water.
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): <14 mm²/s
Viscosity	: < 30 s (ISO 6mm)
Solubility(ies)	(1)
Media	Result
cold water	Not soluble
Partition coefficient: n-octanol water	/ : Not applicable.
Vapour pressure	

Code	: 000001099278	Date of issue/Date of revision	: 17 October 2024
SIGMAGUAR	D CSF 585 HARDENER		

SECTION 9: Physical and chemical properties

		Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
			mm Hg	kPa	Method	mm Hg	kPa	Method
		Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	0.675	0.09		1.575	0.21	
Relative density	:	0.98						
Explosive properties		The product itself is r vapour or dust with a	•		the formation	of an ex	plosible n	nixture of
Oxidising properties	:	Product does not pre	sent an o	xidizing	hazard.			
Particle characteristics								
Median particle size		Not applicable.						

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	LD50 Dermal	Rat	2980 mg/kg	-
()	LD50 Oral	Rat	2885 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal LD50 Oral	Rat Rat	1280 mg/kg 1200 mg/kg	-
Conclusion/Summary : There an rritation/Corrosion	e no data available on the m	ixture itself.		
Conclusion/Summary				
Skin : There are	no data available on the mi	xture itself.		

English (GB)

2020/878			
Code : 000001099278 SIGMAGUARD CSF 585 HARD		issue/Date of revision	: 17 October 2024
SECTION 11: Toxicol	ogical information		
Eyes	: There are no data available on the	mixture itself.	
Respiratory	: There are no data available on the	mixture itself.	
<u>Sensitisation</u>			
Conclusion/Summary			
Skin	: There are no data available on the		
Respiratory	: There are no data available on the	e mixture itself.	
Mutagenicity			
Conclusion/Summary	: There are no data available on the	e mixture itself.	
Carcinogenicity			
Conclusion/Summary	: There are no data available on the	e mixture itself.	
Reproductive toxicity	T I		
Conclusion/Summary	: There are no data available on the	mixture itseit.	
Teratogenicity	There are no data available or the	s mainte una ita alf	
Conclusion/Summary	: There are no data available on the	mixture itself.	
Specific target organ toxicit Not available.	<u>/ (single exposure)</u>		
Specific target organ toxicit	<u>y (repeated exposure)</u>		
Not available.			
Aspiration hazard			
Not available.			
Information on likely routes of exposure	: Not available.		
Potential acute health effect	<u>s</u>		
Inhalation	: No known significant effects or crit	tical hazards.	
Ingestion	: No known significant effects or crit	tical hazards.	
Skin contact	: Causes severe burns.		
Eye contact	: Causes serious eye damage.		
Symptoms related to the ph	vsical, chemical and toxicological o	<u>haracteristics</u>	
Inhalation	: No specific data.		
Ingestion	: Adverse symptoms may include th stomach pains	ie following:	
Skin contact	: Adverse symptoms may include th pain or irritation redness blistering may occur	e following:	
Eye contact	 Adverse symptoms may include th pain watering redness 	ie following:	
Delayed and immediate effe	cts as well as chronic effects from s	short and long-term expos	ure
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		

English (GB)

9/13

Suriname

Long term exposure Potential immediate

effects

: Not available.

Code : 000001099278 SIGMAGUARD CSF 585 HARDENER Date of issue/Date of revision

: 17 October 2024

SECTION 11: Toxicological information

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	EC50 15 mg/l	Algae	72 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 >100 mg/l Acute LC50 >100 mg/l	Daphnia Fish	48 hours 96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,4,6-tris (dimethylaminomethyl)phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	4 % - Not readily - 28 days	-	-
Conclusion/Summary	: There are no data	a available on the mixture itself.		

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	-	-	Not readily
2,4,6-tris(dimethylaminomethyl)phenol	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low

12.4 Mobility in soil

Code	: 000001099278	Date of issue/Date of revision	: 17 October 2024
SIGMAGUAR	D CSF 585 HARDENER		

SECTION 12: Ecological information

Soil/water partition coefficient (K_{oc})

: Not available.

Mobility

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

J. I Waste treatment meth	
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalog	ue (EWC)
Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Code	: 000001099278	Date of issue/Date of revision	: 17 October 2024
SIGMAGUAR	D CSF 585 HARDENER		

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	111	Ш	III
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
Tunnel code	: (E)
IMDG	: None identified.
ΙΑΤΑ	: None identified.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not applicable.
according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture,

placing on the market and use of certain dangerous substances, mixtures and articles

Other national and international regulations.

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

English (GB)

Code : 00000109927 SIGMAGUARD CSF 585 HAF	-	Date of issue/Date of revision : 17 October 202	
SECTION 15: Regula	atory information		
15.2 Chemical safety assessment	: No Chemical Safety As	sessment has been carried out.	
SECTION 16: Other	information		
Indicates information that	has changed from previousl	y issued version.	
Abbreviations and acronyms	1272/2008] DNEL = Derived No Ef EUH statement = CLP- PNEC = Predicted No I RRN = REACH Registr	abelling and Packaging Regulation [Regulation (EC) No. fect Level specific Hazard statement Effect Concentration ration Number	
		to Regulation (EC) No. 1272/2008 [CLP/GHS]	
Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	fication	Justification Calculation method Calculation method Calculation method	
Full text of abbreviated H statements	H312 Harmful in co H314 Causes seve H318 Causes serio	Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. Harmful to aquatic life with long lasting effects.	
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Aquatic Chronic 3 Eye Dam. 1 Skin Corr. 1C	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Catego SERIOUS EYE DAMAGE/EYE IRRITATION - Category SKIN CORROSION/IRRITATION - Category 1C	
<u>History</u>			
Date of issue/ Date of revision	: 17 October 2024		
Date of previous issue	: 9 October 2024		
Prepared by	: EHS		
Version	: 3.06		
<u>Disclaimer</u>			
information is to draw attentio recommend precautionary me	n to the health and safety as easures for the storage and e products. No liability can	present scientific and technical knowledge. The purpose of the spects concerning the products supplied by us, and to handling of the products. No warranty or guarantee is given i be accepted for any failure to observe the precautionary of the products.	