# SAFETY DATA SHEET



Date of issue/Date of revision 17 October 2024 Version 3.03

### **Section 1. Identification**

Product code : 00241599

Product name : SIGMAGUARD CSF 650 BASE REDBROWN 6179

Other means of identification

: Not available.

Product type

: Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.

Professional applications, Used by spraying.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

Supplier's details : PT PPG Coatings Indonesia

Jl. Rawagelam III No.1

13930 Jakarta Indonesia

Tel +62 21 4605710 PMC.Safety@PPG.com

**Emergency telephone** 

number

: CHEMTREC 001-803-017-9114 (CCN 17704)

# Section 2. Hazards identification

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

AQUATIC HAZARD (LONG-TERM) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 38%

### GHS label elements, including precautionary statements

Hazard pictograms :





Signal word : Warning

**Hazard statements** : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear protective gloves. Wear eye or face protection. Avoid release to the

environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Indonesia Page: 1/11

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

### Section 2. Hazards identification

: Collect spillage. IF ON SKIN: Wash with plenty of water. If skin irritation or rash Response

occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice or attention.

: Not applicable. **Storage** 

: Dispose of contents and container in accordance with all local, regional, national **Disposal** 

and international regulations.

Other hazards which do not : None known.

result in classification

### Section 3. Composition/information on ingredients

Substance/mixture

#### **CAS** number/other identifiers

**CAS** number : Not applicable. **EC** number : Mixture.

Ingredient name	%	CAS number
is-[4-(2,3-epoxipropoxi)phenyl]propane	25- <50	1675-54-3
1,6-bis(2,3-epoxypropoxy)hexane	5- <10	16096-31-4
benzyl alcohol	5- <10	100-51-6
Talc , not containing asbestiform fibres	3- <5	14807-96-6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Indonesia Page: 2/11

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

### Section 4. First aid measures

Inhalation : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being

discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

carbon oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Indonesia <sup>:</sup> Page: 3/11

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways. drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

> Indonesia Page: 4/11

**Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179** 

### Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
ralc , not containing asbestiform fibres	Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018) TWA 8 hours: 2 mg/m³. Form: respirable particles.

#### **Recommended monitoring** procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

# Appropriate engineering

**Environmental exposure** 

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**Hygiene measures** 

controls

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection **Skin protection Hand protection**

- : Chemical splash goggles.
- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: butyl rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Indonesia Page: 5/11

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

### Section 8. Exposure controls/personal protection

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is

necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Various

Odor : Aromatic. [Slight]
Odor threshold : Not available.

pH : Not applicable.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 100°C (212°F)

Evaporation rate : Not available.
Flammability/Combustible : Not available.
properties (solid, gas)

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure: Not available.Vapor density: Not available.

Relative density : 1.4

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : 426°C (798.8°F) **Decomposition temperature** : Not available.

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm<sup>2</sup>/s

**Viscosity** : 60 - 100 s (ISO 6mm)

Indonesia Page: 6/11

**Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179** 

# Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
s-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral	Rat Rabbit Rat	>5 mg/l >2000 mg/kg 1200 mg/kg	4 hours -

# Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion
Product/ingradiant no

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

#### **Conclusion/Summary**

Skin Eyes

Respiratory

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

#### **Sensitization**

3	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing

#### **Conclusion/Summary**

Indonesia <sup>:</sup> Page: 7/11

**Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179** 

### **Section 11. Toxicological information**

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** : There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Indonesia <sup>1</sup> Page: 8/11

**Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179** 

# **Section 11. Toxicological information**

Long term exposure

**Potential immediate** 

: There are no data available on the mixture itself.

effects

: There are no data available on the mixture itself. **Potential delayed effects** 

Potential chronic health effects

: Once sensitized, a severe allergic reaction may occur when subsequently exposed **General** 

to very low levels.

Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Route	ATE value
<b>Ø</b> ral	11319.42 mg/kg

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days

#### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy) hexane	0.822	-	Low
benzyl alcohol	0.87	-	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Indonesia Page: 9/11

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

# Section 12. Ecological information

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Indonesia Page: 10/11

Product name SIGMAGUARD CSF 650 BASE REDBROWN 6179

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

Law No. 74/2001 - Banned

None of the components are listed.

#### Law No. 74/2001 - Restricted

None of the components are listed.

Law No. 74/2001 - : Not determined

Chemicals that may be used

**International regulations** 

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

**History** 

Date of issue/Date of :

revision

: 17 October 2024

Date of previous issue: 3/4/2024Version: 3.03Prepared by: EHS

**Key to abbreviations** : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Indonesia Page: 11/11