SAFETY DATA SHEET

Date of issue/Date of revision

: 17 October 2024

Version

: 1.05





SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: SIGMAGUARD CSF 585 BASE BLUE 1
Product code	: 000001099277
Other means of identi	cation
00219192; 00219194; 0	0310817

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paints Egypt Villa#8, street 279	
New Maadi, Cairo	
Egypt	
Tel: 00202 516 223 797	
Fax: 00202 516 38 04	
e-mail address of person	: PS.ACEMEA@ppg.com
responsible for this SDS	

1.4 Emergency telephone : +20 2 6840902 number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eve Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Signal word

: Warning

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)	1
2020/878	

Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024
SIGMAGU	ARD CSF 585 BASE BLUE 1		

SECTION 2: Hazards identification Hazard statements : Causes skin irritation. May cause an allergic skin reaction. Causes serious eve irritation

	Causes serious eye irritation. Toxic to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.	
Response	: Collect spillage.	
Storage	: Not applicable.	
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P261, P264, P391, P501 	
Supplemental label elements	: Contains epoxy constituents. May produce an allergic reaction.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.	
Special packaging requiren	<u>nents</u>	
Containers to be fitted with child-resistant fastenings	: Not applicable.	
Tactile warning of danger	: Not applicable.	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
1,6-Hexanediol, reaction products with epichlorohydrin	REACH #: 01-2119463471-41 EC: 618-939-5 CAS: 933999-84-9	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
Octadecanoic acid, 12-hydroxy-, reaction	REACH #: 01-2119979085-27	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
		English	(GB)	Egypt	2/13

 Code
 <th::000001099277</th>
 Date of issue/Date of revision
 : 17 October 2024

 SIGMAGUARD CSF 585 BASE BLUE 1

SECTION 3: Composition/information on ingredients products with ethylenediamine EC: 309-629-8 CAS: 100545-48-0 See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

This mixture contains \geq 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

4.2 WOSt important sy	mptoms and effects, both acute and delayed
Potential acute healt	h effects
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	s/symptoms
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any i	mmediate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

English	(GB)
---------	------

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Code : 000001099277 Date of issue/Date of revision : 17 October 2024 SIGMAGUARD CSF 585 BASE BLUE 1 SECTION 4: First aid measures Specific treatments : No specific treatment. SECTION 5: Firefighting measures 5.1 Extinguishing media Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media Unsuitable extinguishing : None known. media 5.2 Special hazards arising from the substance or mixture Hazards from the : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with substance or mixture this material must be contained and prevented from being discharged to any waterway, sewer or drain. **Hazardous combustion** : Decomposition products may include the following materials: carbon oxides products metal oxide/oxides 5.3 Advice for firefighters **Special precautions for** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable fire-fighters training. **Special protective** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing equipment for fire-fighters for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste

disposal contractor.

Code: 000001099277Date of issue/Date of revision: 17 October 2024

SIGMAGUARD CSF 585 BASE BLUE 1

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values				
F alc , not containing asbestiform fibres	ACGIH TLV (United States, 7/2023) A4. TWA 8 hours: 2 mg/m ³ . Form: Respirable fraction.				
titanium dioxide	Law Number 4 of 1994, Environmental Law, Annex 8 - N limits for air pollutants inside workplaces (Egypt, 8/201 [titanium dioxide] TWA 8 hours: 10 mg/m ³ .				
	English (GB)	Egypt	5/13		

2020/878		
Code : 000001099277	Date of issue/Date of revision	: 17 October 2024
SIGMAGUARD CSF 585 BASE	BLUE 1	
No exposure indices known.		
Recommended monitoring procedures	: Reference should be made to monitoring standards, such a Standard EN 689 (Workplace atmospheres - Guidance for by inhalation to chemical agents for comparison with limit v strategy) European Standard EN 14042 (Workplace atmos application and use of procedures for the assessment of exbiological agents) European Standard EN 482 (Workplace requirements for the performance of procedures for the me agents) Reference to national guidance documents for me of hazardous substances will also be required.	the assessment of exposure values and measurement spheres - Guide for the xposure to chemical and e atmospheres - General easurement of chemical
8.2 Exposure controls		
Appropriate engineering controls	: Good general ventilation should be sufficient to control wor contaminants.	ker exposure to airborne
Individual protection measu	—	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling eating, smoking and using the lavatory and at the end of th Appropriate techniques should be used to remove potentia Contaminated work clothing should not be allowed out of th contaminated clothing before reusing. Ensure that eyewas showers are close to the workstation location.	ne working period. Ally contaminated clothing. he workplace. Wash
Eye/face protection	: Chemical splash goggles.	
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an a worn at all times when handling chemical products if a risk necessary. Considering the parameters specified by the g during use that the gloves are still retaining their protective noted that the time to breakthrough for any glove material in glove manufacturers. In the case of mixtures, consisting o protection time of the gloves cannot be accurately estimated frequently repeated contact may occur, a glove with a protect (breakthrough time greater than 480 minutes according to When only brief contact is expected, a glove with a protect (breakthrough time greater than 30 minutes according to E The user must check that the final choice of type of glove s product is the most appropriate and takes into account the as included in the user's risk assessment.	assessment indicates this is love manufacturer, check properties. It should be may be different for different of several substances, the ed. When prolonged or ection class of 6 EN 374) is recommended. cion class of 2 or higher EN 374) is recommended. selected for handling this
Gloves	: butyl rubber	
Body protection	: Personal protective equipment for the body should be sele- performed and the risks involved and should be approved handling this product.	by a specialist before
Other skin protection	Appropriate footwear and any additional skin protection me based on the task being performed and the risks involved a specialist before handling this product.	
Respiratory protection	:	
Environmental exposure controls	: Emissions from ventilation or work process equipment sho they comply with the requirements of environmental protec cases, fume scrubbers, filters or engineering modifications will be necessary to reduce emissions to acceptable levels	tion legislation. In some to the process equipment

Code : 000001099277

Date of issue/Date of revision :

: 17 October 2024

SIGMAGUARD CSF 585 BASE BLUE 1

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Blue.
Odour	: Characteristic.
Odour threshold	: Not available.
Melting point/freezing point	: Not determined.
Initial boiling point and boiling range	: >37.78°C
Flammability	: Not determined. There are no data available on the mixture itself.
Upper/lower flammability or explosive limits	: Not available.
Flash point	: Closed cup: 130°C
Auto-ignition temperature	: Not available.
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
рН	: Not applicable. insoluble in water.
Viscosity	 Øynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): >21 mm²/s
Viscosity	: 60 - 100 s (ISO 6mm)
Solubility(ies)	:
Modia	Posult

Media	Result
cold water	Not soluble
Partition coefficient: n-octanol/ : water	Not applicable.

: Product does not present an oxidizing hazard.

mator	
Vapour	pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
bis-[4-(2,3-epoxipropoxi) phenyl]propane	<0.000075006	<0.00001				

Relative density Explosive properties

: 1.41

2

: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties Particle characteristics Median particle size

: Not applicable.

9.2 Other information

No additional information.

Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024
SIGMAGUARI	D CSF 585 BASE BLUE 1		

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
1,6-Hexanediol, reaction products with epichlorohydrin	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Male, Female	2189 mg/kg	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LC50 Inhalation Dusts and mists	Rat	5.05 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the	Rabbit	0.4	24 hours	-
	conjunctivae				
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

- : There are no data available on the mixture itself.
- Eyes : There are no data available on the mixture itself.

Respiratory

Skin

: There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi)phenyl]propane Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	skin skin		Sensitising Sensitising

Conclusion/Summary

English (GB)
-----------	-----

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Code : 000001099277 Date of issue/Date of revision : 17 October 2024 SIGMAGUARD CSF 585 BASE BLUE 1 SECTION 11: Toxicological information Skin : There are no data available on the mixture itself. : There are no data available on the mixture itself. Respiratory **Mutagenicity Conclusion/Summary** : There are no data available on the mixture itself. Carcinogenicity : There are no data available on the mixture itself. **Conclusion/Summary Reproductive toxicity Conclusion/Summary** : There are no data available on the mixture itself. **Teratogenicity Conclusion/Summary** : There are no data available on the mixture itself. Specific target organ toxicity (single exposure) Not available. Specific target organ toxicity (repeated exposure) Not available. **Aspiration hazard** Not available. : Not available. Information on likely routes of exposure Potential acute health effects Inhalation : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Eye contact : Causes serious eye irritation. Symptoms related to the physical, chemical and toxicological characteristics Inhalation : No specific data. Ingestion : No specific data. Skin contact : Adverse symptoms may include the following: irritation redness Eye contact Adverse symptoms may include the following: pain or irritation watering redness Delayed and immediate effects as well as chronic effects from short and long-term exposure Short term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available. Long term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)	
2020/878	

SECTION	11: Toxicological information		
SIGMAGUARI	D CSF 585 BASE BLUE 1		
Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024

SECTION 11: Toxicological information

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.
Sanding and grinding dusts	may be harmful if inhaled.
11.2 Information on other	hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia</i> <i>magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
1,6-Hexanediol, reaction products with epichlorohydrin	Acute EC50 47 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 30 mg/l Fresh water	Fish	96 hours
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 >10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary

There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1,6-Hexanediol, reaction products with epichlorohydrin	OECD 301D Ready Biodegradability - Closed Bottle	47 % - Not readily - 28 days	-	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Test 301D Ready Biodegradability - Closed Bottle Test	22 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-Hexanediol, reaction products with epichlorohydrin Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	-	-	Not readily Not readily Inherent

English (GB)

 Code
 <th::000001099277</th>
 Date of issue/Date of revision
 : 17 October 2024

 SIGMAGUARD CSF 585 BASE BLUE 1

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,6-Hexanediol, reaction products with epichlorohydrin	0.822	-	Low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	High

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
· · · · · · · · · · · · · · · · · · ·	

Hazardous waste : Yes. European waste catalogue (EWC)

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous sub	stances
ackaging		
Methods of disposal	 The generation of waste should be avoided or minimised wherever pose packaging should be recycled. Incineration or landfill should only be co recycling is not feasible. 	
Type of packaging	European waste catalogue (EWC)	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Care taken when handling emptied containers that have not been cleaned or Empty containers or liners may retain some product residues. Avoid dis material and runoff and contact with soil, waterways, drains and sewers	rinsed out. spersal of spilt

English (GB)	
--------------	--

 Code
 <th: 000001099277</th>
 Date of issue/Date of revision
 : 17 October 2024

SIGMAGUARD CSF 585 BASE BLUE 1

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	Ш	Ш	Ш
14.5 Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information				
ADR/RID	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
Tunnel code	(-)			
IMDG	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.			
ΙΑΤΑ	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.			
14.6 Special pre user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			
14.7 Transport i according to IM instruments				

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
<u>EU Regulation (EC) No. 1907/2006 (REACH)</u>
<u>Annex XIV - List of substances subject to authorisation</u>
<u>Annex XIV</u>
None of the components are listed.
<u>Substances of very high concern</u>
None of the components are listed.
<u>Annex XVII - Restrictions</u> : Not applicable.
on the manufacture,
placing on the market

dangerous substances, mixtures and articles

and use of certain

Other national and international regulations.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Code : 000001099277 Date of issue/Date of revision : 17 October 2024 SIGMAGUARD CSF 585 BASE BLUE 1 **SECTION 15: Regulatory information**

Explosive precursors	: Not applicable.
Ozone depleting substar	<u>nces (1005/2009/EU)</u>
Not listed.	

15.2 Chemical safety : No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	CLP = Classification, Lab 1272/2008] DNEL = Derived No Effect EUH statement = CLP-sp PNEC = Predicted No Effect	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 	
Full text of abbreviated H statements	H317 May cause an a H319 Causes serious H411 Toxic to aquatio	 H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. 	
Full text of classifications [CLP/GHS]	: Aquatic Chronic 2 Aquatic Chronic 3 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1B	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B	
<u>History</u>			
Date of issue/ Date of revision	: 17 October 2024		
Date of previous issue	: 29 May 2024		
Prepared by	: EHS		
Version	: 1.05		
<u>Disclaimer</u>			

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.