# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

# SAFETY DATA SHEET

Date of issue/Date of revision

: 17 October 2024



: 1.05

Version

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: SIGMAGUARD CSF 585 BASE BLUE 1
Product code	: 000001099277
Product type	: Liquid.
Other means of identification	: 00219192; 00219194; 00310817
1.2 Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

#### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person : Product.Stewardship.EMEA@ppg.com responsible for this SDS

#### 1.4 Emergency telephone number

**Supplier** 

+31 20 4075210

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Signal word Hazard statements : Warning

: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

Code : 000001099277 SIGMAGUARD CSF 585 BASE BLUE 1	Date of issue/Date of revision	: 17 October 2024
<b>SECTION 2: Hazards identification</b>		

Precautionary statements		
Prevention	1	Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.
Response	1	Collect spillage.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
		P280, P273, P261, P264, P391, P501
Supplemental label elements	1	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

## **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Туре
pís-[4-(2,3-epoxipropoxi)phenyl] propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
1,6-Hexanediol, reaction products with epichlorohydrin	REACH #: 01-2119463471-41 EC: 618-939-5 CAS: 933999-84-9	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	REACH #: 01-2119979085-27 EC: 309-629-8 CAS: 100545-48-0	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### <u>Type</u>

[1] Substance classified with a health or environmental hazard

Code : 000001099277

Date of issue/Date of revision

: 17 October 2024

SIGMAGUARD CSF 585 BASE BLUE 1

## **SECTION 3: Composition/information on ingredients**

This mixture contains  $\geq$  1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Potential acute health eff	iects
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sy</u>	<u>imptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any imm	nediate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
<b>SECTION 5: Firefi</b>	ghting measures
5.1 Extinguishing media	

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

#### 5.2 Special hazards arising from the substance or mixture

Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024
SIGMAGUAF	RD CSF 585 BASE BLUE 1		

## SECTION 5: Firefighting measures

•	-
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024
SIGMAG	UARD CSE 585 BASE BLUE 1		

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **Occupational exposure limits**

No exposure limit value known.

No exposure indices known.

## Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs** 

Code : 000001099277 SIGMAGUARD CSF 585 BASE BLUE 1 Date of issue/Date of revision

: 17 October 2024

### **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
bis-[4-(2,3-epoxipropoxi) phenyl]propane	DNEL	Long term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
1	DNEL	Short term Inhalation	12.25 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m <sup>3</sup>	Workers	Systemic
1,6-Hexanediol, reaction products with epichlorohydrin	DNEL	Short term Dermal	13.6 µg/cm²	General population	Local
	DNEL	Long term Dermal	13.6 µg/cm²	General population	Local
	DNEL	Short term Dermal	22.6 µg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Dermal	22.6 µg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Inhalation	0.27 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.44 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	5.29 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	5.29 mg/m³	General population	Systemic
	DNEL	Long term Dermal	6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.57 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	10.57 mg/m³	Workers	Systemic
Octadecanoic acid,	DNEL	Long term Inhalation	0.055 mg/m³	General population	Local
12-hydroxy-, reaction					
products with					
ethylenediamine	DNEL	Long term Inhalation	0.308 mg/m³	Workers	Local
			5.500 mg/m		2000

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Fresh water sediment	0.006 mg/l 0.001 mg/l 0.996 mg/kg dwt 0.1 mg/kg dwt 0.196 mg/kg dwt 10 mg/l 11 mg/kg	Assessment Factors Assessment Factors Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning Assessment Factors Assessment Factors

#### 8.2 Exposure controls

## Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Conforms to Regulation (EC)	No. 19	907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758
Code : 0000010992 SIGMAGUARD CSF 585 BA		Date of issue/Date of revision         : 17 October 2024           LUE 1
SECTION 8: Exposu	ire c	controls/personal protection
Hygiene measures		Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles.
Skin protection		
Hand protection		Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. butyl rubber
Body protection		Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection		Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection		Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Blue.
Odour	: Characteristic.
Odour threshold	: Not available.
Melting point/freezing point	:
Initial boiling point and boiling range	: >37.78°C (>100°F)
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Not available.
Flash point	: Closed cup: 130°C (266°F)

English (GB)

United Kingdom (UK)

ode : 00000109927 IGMAGUARD CSF 585 BAS	-		Date of issue/D	ate of revision	:	17 October 2024
ECTION 9: Physica		mical p	properties			
Auto-ignition temperature		vailable.				
pH		pplicable.				
		••	nsoluble in water			
Viscosity						
Solubility(ies)	:	·				
Media	Re	sult				
cold water	Not soluble					
Miscible with water	: No.					
Partition coefficient: n-octa water	nol/ : Not a	pplicable.				
Vapour pressure	:					
	Var	our Press	ure at 20°C	V	apour pres	sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
<b>pi</b> s-[4-(2,3-epoxipropoxi)phenyl] propane	<0.000075006	<0.00001				
Relative density	: 1.41					
Explosive properties			elf is not explosive vith air is possible		ition of an e	explosible mixture
		ict door no	ot present an oxic	lizina hazard		
Oxidising properties <u>Particle characteristics</u>	: Prodi	uct does no	n present an oxic	iizing nazaru.		

## **SECTION 10: Stability and reactivity**

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredie	ents.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occu	ır.
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition p Refer to protective measures listed in sections 7 and 8.	oroducts.
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions oxidising agents, strong alkalis, strong acids.	:
10.6 Hazardous decomposition products	Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides	

## **SECTION 11: Toxicological information**

11.1 Information on toxicological effects <u>Acute toxicity</u>

Code : 000001099277 SIGMAGUARD CSF 585 BASE BLUE 1 Date of issue/Date of revision

: 17 October 2024

## **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
s-[4-(2,3-epoxipropoxi)	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
1,6-Hexanediol, reaction products with epichlorohydrin	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Male, Female	2189 mg/kg	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LC50 Inhalation Dusts and mists	Rat	5.05 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
s-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-Hexanediol, reaction products with	15000 2189	23000 N/A	N/A N/A	N/A N/A	N/A N/A
epichlorohydrin					
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	N/A	N/A	N/A	N/A	5.05

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
øis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

**Conclusion/Summary** : Not available.

: There are no data available on the mixture itself.

Eyes Respiratory

Skin

: There are no data available on the mixture itself. : There are no data available on the mixture itself.

## **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitising
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	skin	Guinea pig	Sensitising

Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<b>Mutagenicity</b>	
Conclusion/Summary	: There are no data available on the mixture itself.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.

Code : 00000109927	7 Date of issue/Date of revision : 17 October 2024
SIGMAGUARD CSF 585 BAS	
SECTION 11: Toxico	logical information
Reproductive toxicity	
Conclusion/Summary Teratogenicity	: There are no data available on the mixture itself.
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxici Not available.	<u>ty (single exposure)</u>
Specific target organ toxici Not available.	ty (repeated exposure)
Aspiration hazard Not available.	
Information on likely routes of exposure	: Not available.
Potential acute health effect	<u>s</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	: Not available.
General	<ul> <li>Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.</li> </ul>
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

**Other information** 

: Not available.

English (GB)

Code : 000001099277 SIGMAGUARD CSF 585 BASE BLUE 1 Date of issue/Date of revision : 17 October 2024

## **SECTION 12: Ecological information**

#### **12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
ofs-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
1,6-Hexanediol, reaction products with epichlorohydrin	Acute EC50 47 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 30 mg/l Fresh water	Fish	96 hours
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
euryieneulamine	Acute EC50 >10 mg/l Acute LC50 >10 mg/l	Daphnia - <i>Daphnia magna</i> Fish - <i>Oncorhynchus mykiss</i>	48 hours 96 hours
Conclusion/Summary	: Not available.	•	•

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
<b>1</b> ,6-Hexanediol, reaction products with epichlorohydrin		47 % - Not readily - 28 days	-	-
······	Biodegradability - Closed Bottle Test			
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	301D Ready Biodegradability - Closed Bottle Test	22 % - 28 days	-	-

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
pís-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
1,6-Hexanediol, reaction products with epichlorohydrin	-	-	Not readily
Octadecanoic acid,	-	-	Inherent
12-hydroxy-, reaction products with ethylenediamine			

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
	0.822	-	Low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	High

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024
SIGMAGL	JARD CSF 585 BASE BLUE 1		

## **SECTION 12: Ecological information**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

 Methods of disposal
 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Hazardous waste

#### Waste catalogue

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
Packaging		
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>	
Type of packaging	Waste catalogue	
Container	15 01 06 mixed packaging	

 Type of packaging
 Waste catalogue

 Container
 15 01 06
 mixed packaging

 Special precautions
 : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	111	111	Ш
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(bis-[4- (2,3-epoxipropoxi) phenyl]propane)	Not applicable.

English (GB)

<mark>Code</mark> SIGMAGU	: 000001099277 JARD CSF 585 BASE BLUE 1	Date of issue/Date of revision	: 17 October 2024
SECTIO	ON 14. Transport informa	ation	

#### SECTION 14: Transport Information

Additional info	<u>rmation</u>
ADR/RID	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code	: (-)
ADN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
14.6 Special pre user	ecautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport according to IM	

## instruments

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Explosive precursors** : Not applicable.

#### **Ozone depleting substances**

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
GMAGUARD CSF 585 BASE BLUE 1	3

Labelling

: Not applicable.

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

Category	

E2

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement</li> </ul>
	N/A = Not available

Code	: 000001099277	Date of issue/Date of revision	: 17 October 2024

SIGMAGUARD CSF 585 BASE BLUE 1

24

### **SECTION 16: Other information**

PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
VDVP - Vory Dereistant and Vory Pieceoumulativ

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

#### Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Full text of classifications**

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

#### **History**

Date of issue/ Date of revision	: 17 October 2024
Date of previous issue	: 29 May 2024
Prepared by	: EHS
Version	: 1.05

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.