# SAFETY DATA SHEET



Date of issue 22

22 October 2024

Version 1.02

# Section 1. Product and company identification

Product name : 2550 WB URETHANE GLOSS CATALYST - B

Product code : 00462416
Other means of identification : Not available.

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Coating. Paints. Painting-related materials.

| Uses advised against | Reason |
|----------------------|--------|
| Not applicable.      |        |

Supplier's details:

**Supplier** : PPG INDUSTRIES CHILE S.A.

Puerto Madero 9710, Of. 23

Pudahuel - Chile

Teléfono: +56 (2) 2571 0750 Fax: +56 (2) 2571 0752

Email address: : HazComLatam@ppg.com

**Emergency telephone number** 

+56 (2) 2777 1994 (RITA CHILE)

### Section 2. Hazards identification

Classification of the substance or mixture

: ACUTE TOXICITY (dermal) - Category 5 ACUTE TOXICITY (inhalation) - Category 4

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

AQUATIC HAZARD (LONG-TERM) - Category 3

Target organs : Contains material which may cause damage to the following organs: upper

respiratory tract, skin, central nervous system (CNS).

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal

toxicity: 18.6%

|  | English (US) Chile | 1/13 |
|--|--------------------|------|
|--|--------------------|------|

Code 22 October 2024 00462416 Date of issue Version 1.02

2550 WB URETHANE GLOSS CATALYST - B **Product name** 

### Section 2. Hazards identification

#### **GHS label elements**

**Hazard pictograms** 





Signal word : Danger

**Hazard statements** : May be harmful in contact with skin.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** : Wear protective gloves. Wear eye or face protection. Wear respiratory protection.

Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after

handling.

Response : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call

a POISON CENTER or doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice or attention.

: Store in a well-ventilated place. Keep container tightly closed. **Storage** 

: Dispose of contents and container in accordance with all local, regional, national **Disposal** 

and international regulations.

Other hazards which do not : None known.

result in classification

Classification according to

NCh382:

: Not regulated.

Label according to

NCh2190:

: Not Regulated as a Dangerous Good.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of

identification

Not available.

**CAS** number/other identifiers

**CAS** number : Not applicable.

English (US) Chile 2/13

| Code 004624  | Date of i                           | issue 22 October 20 | )24 Version | 1.02 |
|--------------|-------------------------------------|---------------------|-------------|------|
| Product name | 2550 WB URETHANE GLOSS CATALYST - E | 3                   |             |      |

# Section 3. Composition/information on ingredients

| Ingredient name  | %           | CAS number  |
|--|-------------|-------------|
|  | 60 - 100    | 28182-81-2  |
| Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)   | 15 - <20    | 666723-27-9 |
| -1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer |             |             |
| cyclohexyldimethylamine  | 1 - <2      | 98-94-2     |
| hexamethylene-di-isocyanate  | 0.2 - < 0.5 | 822-06-0    |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

# Section 4. First aid measures

#### **Description of necessary first aid measures**

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the **Eye contact** eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel. **Skin contact** 

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Indication of immediate medical attention and special treatment needed, if necessary

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician **Specific treatments** 

: The exposed person may need to be kept under medical surveillance for 48 hours.

No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

**Skin contact** : May be harmful in contact with skin. Causes skin irritation. May cause an allergic

skin reaction.

: No known significant effects or critical hazards. Ingestion

See toxicological information (Section 11)

English (US) Chile 3/13 Code 00462416 Date of issue 22 October 2024 Version 1.02

2550 WB URETHANE GLOSS CATALYST - B **Product name** 

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products

Decomposition products may include the following materials: carbon oxides

nitrogen oxides sulfur oxides

Cyanate and isocyanate. hydrogen cyanide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

English (US) Chile 4/13 Code 00462416 Date of issue 22 October 2024 Version 1.02

2550 WB URETHANE GLOSS CATALYST - B **Product name** 

### Section 6. Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

#### Special provisions

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes. rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

# Section 7. Handling and storage

#### **Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

> Precautions should be taken to minimize exposure to atmospheric humidity or water. CO2 will be formed, which, in closed containers, could result in pressurization.

English (US) Chile 5/13 
 Code
 00462416
 Date of issue
 22 October 2024
 Version
 1.02

Product name 2550 WB URETHANE GLOSS CATALYST - B

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Fexamethylene diisocyanate, oligomers (Iminooxadiazindione type)

Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)

Not regulated.

-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane

homopolymer

cyclohexyldimethylamine Not regulated.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection
Skin protection
Hand protection

: Chemical splash goggles.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: butyl rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Use an air-fed respirator unless a site-specific assessment determines that an air-fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

English (US) Chile 6/13

Code 00462416 Date of issue 22 October 2024 Version 1.02

Product name 2550 WB URETHANE GLOSS CATALYST - B

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.

Color : Yellow. [Light]
Odor : Characteristic.
pH : Not applicable.
Melting point : Not available.

**Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: 185°C (365°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 1.15

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : In a fire, hazardous decomposition products may be produced.

**Incompatible materials**: Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols,

water. Uncontrolled exothermic reactions occur with amines and alcohols.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following materials:

Cyanate and isocyanate. carbon oxides nitrogen oxides sulfur oxides hydrogen

cyanide

English (US) Chile 7/13

Code 00462416 Date of issue 22 October 2024 Version 1.02 **Product name** 2550 WB URETHANE GLOSS CATALYST - B

# Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

| Product/ingredient name   | Result  | Species               | Dose                                | Exposure          |
|---|---|-----------------------|-------------------------------------|-------------------|
| Fexamethylene<br>diisocyanate, oligomers<br>(Iminooxadiazindione type)  | LD50 Dermal                                       | Rat                   | >2000 mg/kg                         | -                 |
| ,,,,  | LD50 Oral   | Rat - Male,<br>Female | >5000 mg/kg                         | -                 |
| Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino) -1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer | LD50 Oral   | Rat                   | >5000 mg/kg                         | -                 |
| cyclohexyldimethylamine   | LC50 Inhalation Vapor<br>LD50 Dermal<br>LD50 Oral | Rat<br>Rat<br>Rat     | 9 mg/l<br>370 mg/kg<br>0.272 g/kg   | 1 hours<br>-<br>- |
| hexamethylene-di-<br>isocyanate   | LC50 Inhalation Dusts and mists                   | Rat                   | 124 mg/m³                           | 4 hours           |
| •   | LC50 Inhalation Vapor<br>LD50 Dermal<br>LD50 Oral | Rat<br>Rabbit<br>Rat  | 151 mg/m³<br>0.57 g/kg<br>0.71 g/kg | 4 hours<br>-      |

### **Conclusion/Summary** Irritation/Corrosion

Not available.

: There are no data available on the mixture itself.

### **Conclusion/Summary**

Skin : There are no data available on the mixture itself. : There are no data available on the mixture itself. **Eyes** Respiratory : There are no data available on the mixture itself.

#### **Sensitization**

Not available.

#### **Conclusion/Summary**

Skin : There are no data available on the mixture itself. Respiratory : There are no data available on the mixture itself. **Mutagenicity** 

Not available.

### **Conclusion/Summary Carcinogenicity**

Not available.

: There are no data available on the mixture itself.

# **Conclusion/Summary**

Reproductive toxicity

: There are no data available on the mixture itself.

Not available.

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Teratogenicity** 

English (US) Chile 8/13 Code 00462416 Date of issue 22 October 2024 Version 1.02

Product name 2550 WB URETHANE GLOSS CATALYST - B

# Section 11. Toxicological information

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Name  | Category   | Route of exposure | Target organs                |
|---|------------|-------------------|------------------------------|
| Hexamethylene diisocyanate, oligomers (Iminooxadiazindione type)  | Category 3 | -                 | Respiratory tract irritation |
| Cyclohexanamine, N,N-dimethyl-, compds. with 3-<br>(cyclohexylamino)-1-propanesulfonic acid-blocked<br>1,6-diisocyanatohexane homopolymer | Category 3 | -                 | Respiratory tract irritation |
| hexamethylene-di-isocyanate   | Category 3 | -                 | Respiratory tract irritation |

#### Specific target organ toxicity (repeated exposure)

Not available.

Target organs : Contains material which may cause damage to the following organs: upper

respiratory tract, skin, central nervous system (CNS).

**Aspiration hazard** 

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

Skin contact : May be harmful in contact with skin. Causes skin irritation. May cause an allergic

skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

English (US) Chile 9/13

 Code
 00462416
 Date of issue
 22 October 2024
 Version
 1.02

Product name 2550 WB URETHANE GLOSS CATALYST - B

# **Section 11. Toxicological information**

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary** 

There are no data available on the mixture itself. Skin contact to isocyanate monomer may lead to allergic lung reaction. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Repeated exposure may lead to permanent respiratory disability. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

**Potential delayed effects** 

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

| Product/ingredient name   | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | Inhalation<br>(vapors)<br>(mg/l) | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|---|------------------|-------------------|--------------------------------|----------------------------------|--|
| 2550 WB URETHANE GLOSS CATALYST - B<br>Hexamethylene diisocyanate, oligomers<br>(Iminooxadiazindione type)                                | 27200.0<br>N/A   | 2345.6<br>2500    | N/A<br>N/A                     | 52.3<br>N/A                      | 1.9<br>1.5                                   |
| Cyclohexanamine, N,N-dimethyl-, compds. with 3-<br>(cyclohexylamino)-1-propanesulfonic acid-blocked<br>1,6-diisocyanatohexane homopolymer | N/A              | N/A               | N/A                            | 11                               | N/A  |
| cyclohexyldimethylamine<br>hexamethylene-di-isocyanate  | 272<br>710       | 370<br>570        | N/A<br>N/A                     | 4.5<br>0.151                     | N/A<br>0.124                                 |

Other information : Not available.

English (US) Chile 10/13

# Section 12. Ecological information

### **Ecotoxicity**

| Product/ingredient name   | Result   | Species   | Exposure                         |
|---|--|---|----------------------------------|
| Hexamethylene diisocyanate, oligomers (Iminooxadiazindione type)  | Acute EC50 >1000 mg/l  | Algae - scenedesmus subspicatus   | 72 hours                         |
| Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino) -1-propanesulfonic acid-blocked 1,6-diisocyanatohexane | Acute EC50 >100 mg/l<br>Acute LC50 >100 mg/l<br>Acute EC50 >100 mg/l | Daphnia - daphnia magna<br>Fish - Danio rerio (zebra fish)<br>Daphnia - Daphnia magna | 48 hours<br>96 hours<br>48 hours |
| homopolymer   | Acute IC50 72 mg/l   | Aquatic plants - Desmodesmus subspicatus  | 72 hours                         |
|   | Acute LC50 35.2 mg/l   | Fish - zebra fish   | 96 hours                         |

### Persistence/degradability

| Product/ingredient name   | Test | Result        | Dose | Inoculum |
|---|------|---------------|------|----------|
| Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino) -1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer | -    | 0 % - 28 days | -    | -        |

| Product/ingredient name                       | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Hexamethylene diisocyanate, oligomers         | -                 | -          | Not readily      |
| (Iminooxadiazindione type)                    |                   |            |                  |
| Cyclohexanamine, N,N-                         | -                 | -          | Not readily      |
| dimethyl-, compds. with 3-                    |                   |            |                  |
| (cyclohexylamino)<br>-1-propanesulfonic acid- |                   |            |                  |
| blocked                                       |                   |            |                  |
| 1,6-diisocyanatohexane                        |                   |            |                  |
| homopolymer                                   |                   |            |                  |

### **Bioaccumulative potential**

| Product/ingredient name     | LogPow | BCF | Potential |
|-----------------------------|--------|-----|-----------|
| ⊮examethylene diisocyanate, | 5.54   | 3.2 | Low       |
| oligomers                   |        |     |           |
| (Iminooxadiazindione type)  |        |     |           |
| cyclohexyldimethylamine     | 2.01   | -   | Low       |
| hexamethylene-di-isocyanate | 0.02   | -   | Low       |

### **Mobility in soil**

|  | English (US) | Chile | 11/13 |
|--|--------------|-------|-------|
|--|--------------|-------|-------|

Code 22 October 2024 00462416 Date of issue Version 1.02

**Product name** 2550 WB URETHANE GLOSS CATALYST - B

# Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

|                             | UN              | Brazil (ANTT)   | IMDG            | IATA            |
|-----------------------------|-----------------|-----------------|-----------------|-----------------|
| UN number                   | Not regulated.  | Not regulated.  | Not regulated.  | Not regulated.  |
| UN proper shipping name     | -               | -               | -               | -               |
| Transport hazard class(es)  | -               | -               | -               | -               |
| Packing group               | -               | -               | -               | -               |
| Environmental hazards       | No.             | No.             | No.             | No.             |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

#### **Additional information**

UN : None identified. : None identified. **Brazil** Risk number : Not available. **IMDG** : None identified. IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

English (US) Chile 12/13 Code 00462416 Date of issue 22 October 2024 Version 1.02

2550 WB URETHANE GLOSS CATALYST - B **Product name** 

# Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: NCh 382 - Hazardous substances - General terminology and classification.

NCh 2245 - Material Safety Data Sheet for Chemicals - Contents and section order.

D. S. 148 - Sanitary regulations on hazardous waste management.

D. S. 298 - Transport of dangerous goods by road.

D. S. 374 – Limit for Lead content in paints.

D. S. 594 - Regulation on basic sanitary and environmental conditions at workplace.

### Section 16. Other information

#### **History**

**Date of previous issue** 3/28/2023 **Version** 1.02

**EHS** 

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships.

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

**UN = United Nations** 

: ABNT NBR 14725-4: 2014 References

ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (US) Chile 13/13