# SAFETY DATA SHEET

#### **PPG AQUACOVER 200/400 HARDENER**



Date of issue 31 October 2024

Version 4.02

## 1. Product and company identification

Product name : PPG AQUACOVER 200/400 HARDENER

Product code : 000001103715
Other means of : 00220698; 00226419
identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Hardener.

Uses advised against : Not applicable.

Supplier's details : PPG PMC Japan Co., Ltd., 8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe

652-0803 Japan; Tel: +81-78-574-2777

**Emergency telephone** 

number

: 078 574 2777

## 2. Hazards identification

GHS Classification : SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 2

HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD -

Category 2

**GHS label elements** 

Hazard pictograms :





Signal word : Warning

**Hazard statements** : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear protective gloves. Wear eye or face protection. Avoid release to the

environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Japan Page: 1/12

Date of issue 31 October 2024

Version 4.02

Product name PPG AQUACOVER 200/400 HARDENER

### 2. Hazards identification

Response

: Collect spillage. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

: Not applicable.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not : None known.

result in classification

# 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS** number : Not applicable. **CSCL** number : Not available.

Ingredient name	%	CAS number	CSCL
bis-[4-(2,3-epoxipropoxi)phenyl]propane	50 - 100	1675-54-3	4-209; 7-1279; 7-1283
bisphenol F diglycidyl ether, isomer mixture oxirane, mono[(C12-14-alkyloxy)methyl] derivs	12.5 - <15 7 - <10	SUB140549 68609-97-2	Not available. 2-2426

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion

Over-exposure signs/symptoms

Japan Page: 2/12

Date of issue 31 October 2024 Version 4.02

**Product name PPG AQUACOVER 200/400 HARDENER** 

### 4. First aid measures

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

See toxicological information (Section 11)

## 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon oxides

halogenated compounds

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

Japan Page: 3/12

Date of issue 31 October 2024 Version 4.02

Product name PPG AQUACOVER 200/400 HARDENER

### 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

**Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## 8. Exposure controls/personal protection

**Control parameters** 

Occupational exposure limits

None.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

> Japan Page: 4/12

## 8. Exposure controls/personal protection

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye protection Skin protection

: Chemical splash goggles.

### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### Gloves

: butyl rubber

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# 9. Physical and chemical properties

### **Appearance**

Physical state : Liquid.

Color : Colorless.

Odor : Amine-like.

**pH** : 8

**Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

Relative density : 1.08

Solubility(ies) : Media Result

cold water Partially soluble

**Viscosity** : 60 - 100 s (ISO 6mm)

Japan Page: 5/12

Product code 000001103715 Date of issue 31 October 2024 Version 4.02

**Product name PPG AQUACOVER 200/400 HARDENER** 

## 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides halogenated compounds

# 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
bisphenol F diglycidyl ether, isomer mixture	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>2000 mg/kg	-
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs	LD50 Oral	Rat	17100 mg/kg	-

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane oxirane, mono[ (C12-14-alkyloxy)methyl] derivs	skin skin	Mouse Guinea pig	Sensitizing Sensitizing

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Japan Page: 6/12

Date of issue 31 October 2024 Version 4.02

**Product name PPG AQUACOVER 200/400 HARDENER** 

# 11. Toxicological information

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

# Information on the likely routes of exposure

: Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Japan Page: 7/12

# 11. Toxicological information

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PPG AQUACOVER 200/400 HARDENER	17369.8	17369.8	N/A	N/A	N/A
bis-[4-(2,3-epoxipropoxi)phenyl]propane	15000	23000	N/A	N/A	N/A
bisphenol F diglycidyl ether, isomer mixture	2500	2500	N/A	N/A	N/A
oxirane, mono[(C12-14-alkyloxy)methyl] derivs	17100	N/A	N/A	N/A	N/A

### Other information

None known.

# 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days
bisphenol F diglycidyl ether, isomer mixture	EC50 >1.8 mg/l	Algae	72 hours
	EC50 >1000 mg/l	Daphnia	48 hours
	LC50 2.54 mg/l	Fish	96 hours
	NOEC 0.3 mg/l	Daphnia	21 days
oxirane, mono[	LC50 >100 mg/l	Fish	96 hours
(C12-14-alkyloxy)methyl]			
derivs			

### Persistence/degradability

Product/ingredient name T	Test	Result	Dose	Inoculum
bisphenol F diglycidyl ether, isomer mixture		0 % - Not readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane bisphenol F diglycidyl ether,	-	-	Not readily  Not readily
isomer mixture			

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
bisphenol F diglycidyl ether, isomer mixture	3.6	-	Low
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs	3.77	-	Low

### **Mobility in soil**

	Japan	Page: 8/12
--	-------	------------

Date of issue 31 October 2024 Version 4.02

Product name PPG AQUACOVER 200/400 HARDENER

# 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

Other adverse effects : No known significant effects or critical hazards.

# 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# 14. Transport information

	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane, bisphenol F diglycidyl ether, isomer mixture)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane, bisphenol F diglycidyl ether, isomer mixture)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane, bisphenol F diglycidyl ether, isomer mixture)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

> Japan Page: 9/12

Date of issue 31 October 2024 Version 4.02

**Product name PPG AQUACOVER 200/400 HARDENER** 

# 14. Transport information

Transport in bulk according : Not applicable. to IMO instruments

# 15. Regulatory information

#### **Fire Service Law**

None of the components are listed.

### Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

### **Industrial Safety and Health Act**

### Ordinance on the Prevention of the Hazard due to Specified Chemical Substances

None of the components are listed.

### Substance(s) requiring labelling

None of the components are listed.

#### **Chemicals requiring notification**

None of the components are listed.

### Carcinogens based on Article 577-2 of the Ordinance on ISH

None of the components are listed.

### **Mutagen**

None of the components are listed.

**Corrosive liquid** : Not listed

**Occupational Safety and** 

**Health Law** 

: Not applicable.

Regulations on the

**Prevention of Tetraalkyl** 

**Lead Poisoning** 

: Not listed

: Not listed

: Not listed

**Harmful Substances** 

Harmful Substances,

**Subject to Obtaining** 

**Permission for** 

Manufacturing

**Prohibited for** 

**Manufacturing** 

Lead regulation : Not listed **Organic solvents** : Not applicable.

poisoning prevention

### Poisonous and Deleterious Substances

None of the components are listed.

### **Chemical Substances Control Law (CSCL)**

Page: 10/12 **Japan** 

Date of issue 31 October 2024 Version 4.02 Product code 000001103715

#### **Product name PPG AQUACOVER 200/400 HARDENER**

# 15. Regulatory information

Ingredient name	%	Status	Reference number
Polycondensate of 4,4'-isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	≥50 - ≤60	Priority assessment	87
4,4'-(Propane-2,2-diyl)diphenol	≤10	Priority assessment	75

**High Pressure Gas Control**: Not available.

Law

### **Explosives Control Law**

None of the components are listed.

Law concerning prevention : Marine pollutant: P of pollution of the ocean

#### **Maritime Safety Law**

### Notification Regulating Transportation of Dangerous Materials by Sea

None of the components are listed.

### **Container class**

None of the components are listed.

**JSOH Carcinogen** : Not listed List of Specially Controlled : Not listed

**Industrial Waste Japan inventory** 

: All components are listed or exempted.

**Road law** : Not available.

### 16. Other information

#### **History**

Date of issue/Date of

revision

: 31 October 2024

**Date of previous issue** : 10/9/2024 **Version** : 4.02 **Prepared by** : EHS

**Key to abbreviations** : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

**UN = United Nations** 

### ▼ Indicates information that has changed from previously issued version.

### **Notice to reader**

**Japan** Page: 11/12

Date of issue 31 October 2024

Version 4.02

**Product name PPG AQUACOVER 200/400 HARDENER** 

### 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Japan Page: 12/12