SAFETY DATA SHEET



Date of issue/Date of revision 5 November 2024 Version 1.02

Section 1. Identification		
Product name	: 2550 F WB URETHANE FLAT - A	
Product code	: 00462419	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	f the substance or mixture and uses advised against	
Product use	: Industrial applications, Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 888-977-4762	

Section 2. Hazards identification

Disposal		Not applicable. United States Page: 1/10
Storage		Not applicable.
Response		Not applicable.
Prevention	1	Not applicable.
Precautionary statements		
Hazard statements	1	No known significant effects or critical hazards.
Signal word	1	No signal word.
GHS label elements		
		Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 34.6% (oral), 34.6% (dermal), 35.8% (inhalation)
Classification of the substance or mixture	1	Not classified.
OSHA/HCS status		While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and availab for employees and other users of this product.

Product name 2550 F WB URETHANE FLAT - A

Section 2. Hazards identification

Supplemental label elements	: Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 2550 F WB URETHANE FLAT - A

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health e	effects		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/symptoms			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Indication of immediate	medical attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 		
Specific treatments	: No specific treatment.		

Product name 2550 F WB URETHANE FLAT - A

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures			
For non-emergency personnel	 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. 			
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).			
Methods and materials for co	ontainment and cleaning up			
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.			
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.			

United States Page: 3/10

United States

Page: 4/10

Product name 2550 F WB URETHANE FLAT - A

Section 6. Accidental release measures

Section 7. Handling and storage

Precautions for safe handling

Protective measures Special precautions	 Put on appropriate personal protective equipment (see Section 8). If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measured	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	:	Safety glasses with side shields.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Product name 2550 F WB URETHANE FLAT - A

Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

<u>Appearance</u>					
Physical state	1	Liquid.			
Color	1	White.			
Odor	:	Odorless.			
Odor threshold	1	Not available.			
рН	1	Not available.	Not available.		
Melting point	1	Not available.	Not available.		
Boiling point	1	>37.78°C (>100°F)			
Flash point	1	Closed cup: 121.11°C (25	0°F) [Product does not sustain combustion.]		
Auto-ignition temperature	1	Not available.			
Decomposition temperature	1	Not available.			
Flammability	1	Not available.			
Lower and upper explosive (flammable) limits	:	Not available.			
Evaporation rate	1	Not available.			
Vapor pressure	1	Not available.			
Vapor density	:	Not available.			
Relative density	:	1.05			
Density(lbs / gal)	1	8.76			
		Media	Result		
Solubility(ies)	:	cold water	Soluble		
Partition coefficient: n- octanol/water	:	Not applicable.			
Viscosity	:	Øynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)			
% Solid. (w/w)	1	37.135			

Date of issue 5 November 2024 Version 1.02

Product name 2550 F WB URETHANE FLAT - A

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.Chemical stability: The product is stable.Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.Conditions to avoid: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.Hazardous decomposition products: Depending on conditions, decomposition products may include the following materials: carbon oxides		
Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.Conditions to avoid: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.Hazardous decomposition: Depending on conditions, decomposition products may include the following materials:	Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
reactions Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. Hazardous decomposition : Depending on conditions, decomposition products may include the following materials:	Chemical stability	: The product is stable.
Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. Hazardous decomposition : Depending on conditions, decomposition products may include the following materials:	-	: Under normal conditions of storage and use, hazardous reactions will not occur.
oxidizing agents, strong alkalis, strong acids.Hazardous decomposition: Depending on conditions, decomposition products may include the following materials:	Conditions to avoid	
•	Incompatible materials	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Irritation/Corrosion			
Conclusion/Summary			
Skin	: There are no data available on the mixture itself.		
Eyes	: There are no data available on the mixture itself.		
Respiratory	: There are no data available on the mixture itself.		
<u>Sensitization</u>			
Conclusion/Summary			
Skin	: There are no data available on the mixture itself.		
Respiratory	: There are no data available on the mixture itself.		
<u>Mutagenicity</u>			
Conclusion/Summary	: There are no data available on the mixture itself.		
Carcinogenicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Reproductive toxicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Teratogenicity			
Conclusion/Summary	: There are no data available on the mixture itself.		
Specific target organ toxicity (single exposure)			
Not available.			
Specific target organ toxicity (repeated exposure)			

Not available.

Product name 2550 F WB URETHANE FLAT - A

Section 11. Toxicological information

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion Over-exposure signs/symptoms Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : No specific data.

Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	:	There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.		
<u>Short term exposure</u>				
Potential immediate effects	1	There are no data available on the mixture itself.		
Potential delayed effects	1	There are no data available on the mixture itself.		
<u>Long term exposure</u>				
Potential immediate effects	1	There are no data available on the mixture itself.		
Potential delayed effects	1	There are no data available on the mixture itself.		
Potential chronic health effects				
General	1	No known significant effects or critical hazards.		
Carcinogenicity	1	No known significant effects or critical hazards.		
Mutagenicity	:	No known significant effects or critical hazards.		
Reproductive toxicity	:	No known significant effects or critical hazards.		

Numerical measures of toxicity

Acute toxicity estimates

•			(gases)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
2550 F WB URETHANE FLAT - A	143403.1	143403.1	N/A	N/A	N/A

|--|

Product name 2550 F WB URETHANE FLAT - A

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and
	sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information				
	DOT	IMDG	ΙΑΤΑ	
UN number	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	
Transport hazard class (es)	-	-	-	
Packing group	-	-	-	
Environmental hazards	No.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	

United States	Page: 8/10
---------------	------------

Product name 2550 F WB URETHANE FLAT - A

14. Transport information

Additional information

- DOT : None identified. IMDG : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : At least one component is inactive.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

No products were found.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of previous issue	4	6/28/2023
Organization that prepared the SDS	:	EHS
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

United States Page: 9/10

Product name 2550 F WB URETHANE FLAT - A

Section 16. Other information

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.