SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 5 November 2024

Version 2.01

Date of issue 5 November 2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: 2550 F WB URETHANE FLAT CLEAR - A
Product code	: 00462425
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses of	f the substance or mixture and uses advised against
Product use	: Industrial applications, Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture	1	Not classified.
		Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 34.6% (oral), 34.6% (dermal), 35.8% (inhalation)
GHS label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 2: Hazards identification

Other hazards which do not : Emits toxic fumes when heated.

result in classification

See toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 2550 F WB URETHANE FLAT CLEAR - A
Other means of identification	: Not applicable.

Ingredient name	%	CAS number
Fropylidynetrimethanol, propoxylated	≥1.0 - ≤5.0	25723-16-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects			
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
Specific treatments	quantities have been ingested or inhaled.No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 5: Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protec	ive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
methous and materials for co	
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 7: Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8).
Special precautions	:	If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits
Fropylidynetrimethanol, propoxylated		None.	
C = Ceiling Limit STEI IPEL = Internal Permissible Exposure Limit TLV TWA TWA Consult local authorities for acceptable exposure limits.			 Short term exposure limit Threshold Limit Value Time Weighted Average
Recommended monitoring procedures			riate monitoring standards. Reference to hods for the determination of hazardous
Appropriate engineering controls	:	Good general ventilation should be so contaminants.	ufficient to control worker exposure to airborne
Environmental exposure controls			
Individual protection measure	<u>es</u>		
Hygiene measures		eating, smoking and using the lavato Appropriate techniques should be use	oughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. eusing. Ensure that eyewash stations and station location.
Eye/face protection Skin protection	:	Safety glasses with side shields.	

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 8: Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

<u>Appearance</u>		
Physical state	1	Liquid.
Color	:	Clear.
Odor	1	Odorless.
Odor threshold	:	Not available.
Molecular weight	1	Not applicable.
рН	÷	Not available.
Melting point	1	Not available.
Boiling point	1	>37.78°C (>100°F)
Flash point	1	Closed cup: 121.11°C (250°F) [Product does not sustain combustion.]
Auto-ignition temperature	1	Not available.
Decomposition temperature	:	Not available.
Flammability	4	Not available.
Lower and upper explosive (flammable) limits	1	Not available.
Evaporation rate	:	Not available.
Vapor pressure	1	Not available.
Vapor density	:	Not available.
Relative density	:	1.05
Density(lbs / gal)	:	8.76
Solubility(ies)		Media Result
oordonity(ies)	Ċ	cold water Soluble
Solubility in water	1	Not available.
Partition coefficient: n- octanol/water	:	Not applicable.
Viscosity	:	Øynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
% Solid. (w/w)	1	37.135

Date of issue 5 November 2024 Version 2.01

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 10: Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylidynetrimethanol, propoxylated	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2500 mg/kg	-
Conclusion/Summary	: There are no data availa	ble on the mixture i	tself.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data availa	ble on the mixture i	tself.	
Eyes	: There are no data availa	ble on the mixture i	tself.	
Respiratory	: There are no data availa	ble on the mixture i	tself.	
<u>Sensitization</u>				
Conclusion/Summary				
Skin	: There are no data availa	ble on the mixture i	tself.	
Respiratory	: There are no data availa	ble on the mixture i	tself.	
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data availa	ble on the mixture i	tself.	
Carcinogenicity				
Conclusion/Summary	: There are no data availa	ble on the mixture i	tself.	
Reproductive toxicity				
Conclusion/Summary	: There are no data availa	ble on the mixture i	tself.	
Teratogenicity				
Conclusion/Summary	: There are no data availa	ble on the mixture i	tself.	
Specific target organ toxici	ty (single exposure)			

Specific target organ toxicity (repeated exposure)

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 11: Toxicological information

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion **Over-exposure signs/symptoms** : No specific data. Eye contact Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data. Delayed and immediate effects and also chronic effects from short and long term exposure **Conclusion/Summary** : There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Short term exposure : There are no data available on the mixture itself. **Potential immediate** effects **Potential delayed effects** : There are no data available on the mixture itself. Long term exposure **Potential immediate** : There are no data available on the mixture itself. effects **Potential delayed effects** : There are no data available on the mixture itself. Potential chronic health effects General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. **Mutagenicity** : No known significant effects or critical hazards. **Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2550 F WB URETHANE FLAT CLEAR - A Propylidynetrimethanol, propoxylated	143403.1 2500		N/A N/A	N/A N/A

Mexico	Page: 7/10

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 12: Ecological information

<u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
Propylidynetrimethanol, propoxylated	Acute LC50 >100 mg/l	Fish	96 hours

Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
Propylidynetrimethanol, propoxylated	OECD 301A	84 % - Readily - 26	days	-	-
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
Propylidynetrimethanol, propoxylated	-		-		Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propylidynetrimethanol, propoxylated	0.01 to 1.5	-	Low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
	contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 14: Transport information

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

Mexico	: 1	None identified.
IMDG	: 1	None identified.
ΙΑΤΑ	: 1	None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

SECTION 15: Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

Product name 2550 F WB URETHANE FLAT CLEAR - A

SECTION 16: Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of previous issue Organization that prepared the SDS	- 1	6/28/2023 EHS
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.