# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 5 November 2024

Version 2.02

## **Section 1. Identification**

Product name : 2550 WB URETHANE GLOSS ASH WHITE - A

Product code : 00467405

Other means of : Not available.

identification

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Supplier : PPG Architectural Coatings Canada, Inc.

1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4

Canada

+1 450-655-3121

PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272

**Emergency telephone** 

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

### Section 2. Hazard identification

Classification of the substance or mixture

: CARCINOGENICITY - Category 2

Health Hazards Not Otherwise Classified - Category 1

This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).

**GHS label elements** 

Canada Page: 1/12

### Section 2. Hazard identification

**Hazard pictograms** 





Signal word : Danger

**Hazard statements** : Suspected of causing cancer.

Prolonged or repeated contact may dry skin and cause irritation.

**Precautionary statements** 

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eye or face protection.

: IF exposed or concerned: Get medical advice or attention. Response

: Store locked up. **Storage** 

**Disposal** : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental label

elements

: Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic

fumes when heated.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

39.3% (oral), 41.5% (dermal), 41.5% (inhalation)

## Section 3. Composition/information on ingredients

Substance/mixture

Mixture

2550 WB URETHANE GLOSS ASH WHITE - A **Product name** 

Other means of : Not available.

identification

### **CAS** number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
titanium dioxide	Titanium oxide; Titanium oxide (TiO2); CI 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate; glass flakes (CAS RN 65997-17-3): — of a thickness of 0,3 µm or more but not more than 10 µm, and — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282- 10-5); titanium dioxide, other than those of heading 3206 11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206 11 00	7 - 13*	13463-67-7
2,2',2"-nitrilotriethanol	Ethanol, 2,2',2"-nitrilotris-; TRIETHANOLAMINE; 2,2',2"- Trihydroxyethylamine; Tris(2-hydroxyethyl) amine; trolamine; Ethanol, 2,2',2"-nitrilotri-; ETHANOL, 2,2',2"-NITRILOTRIS-; TRIS	1 - 5*	102-71-6

Canada Page: 2/12

### Product name 2550 WB URETHANE GLOSS ASH WHITE - A

## Section 3. Composition/information on ingredients

(BETA-HYDROXYETHYL)AMINE;
NITRILOTRIETHANOL; 2,2',2"NITRILOTRIS(ETHANOL);
Trihydroxytriethylamine

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation dryness cracking

**Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

Canada Page: 3/12

### Product name 2550 WB URETHANE GLOSS ASH WHITE - A

### Section 4. First-aid measures

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides

nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Canada Page: 4/12

Date of issue 5 November 2024 Version 2.02

Product name 2550 WB URETHANE GLOSS ASH WHITE - A

### Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special precautions** 

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

**Control parameters** 

**Occupational exposure limits** 

Canada Page: 5/12

## Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Manium dioxide	CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 10 mg/m³. CA British Columbia Provincial (Canada, 8/2023) TWA 8 hours: 10 mg/m³. Form: Total dust. TWA 8 hours: 3 mg/m³. Form: respirable fraction. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 10 mg/m³. CA Quebec Provincial (Canada, 7/2023) TWAEV 8 hours: 10 mg/m³. Form: Total dust CA Saskatchewan Provincial (Canada, 7/2013) STEL 15 minutes: 20 mg/m³. TWA 8 hours: 10 mg/m³.
2,2',2"-nitrilotriethanol	CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 5 mg/m³. CA British Columbia Provincial (Canada, 8/2023) TWA 8 hours: 5 mg/m³. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 3.1 mg/m³. TWA 8 hours: 0.5 ppm. CA Quebec Provincial (Canada, 7/2023) Sensitizer. TWAEV 8 hours: 5 mg/m³. CA Saskatchewan Provincial (Canada, 7/2013) STEL 15 minutes: 10 mg/m³. TWA 8 hours: 5 mg/m³.

### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Canada Page: 6/12

Date of issue 5 November 2024 Version 2.02

Product name 2550 WB URETHANE GLOSS ASH WHITE - A

## Section 8. Exposure controls/personal protection

Eye/face protection Skin protection : Safety glasses with side shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

### **Appearance**

Physical state : Liquid.
Color : White. [Light]
Odor : Not available.
Odor threshold : Not available.
pH : Not applicable.
Melting point : Not available.
Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 121.11°C (250°F)

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Evaporation rate : Not available.

Vapor pressure : Not available.

Vapor density : Not available.

Polative density : 1.15

Relative density : 1.15 Density (lbs / gal) : 9.6

Solubility(ies) : Media

: Media Result cold water Not soluble

Partition coefficient: n-octanol/water

: Not applicable.

Canada Page: 7/12

Product code 00467405 Date of issue 5 November 2024 Version 2.02

Product name 2550 WB URETHANE GLOSS ASH WHITE - A

## Section 9. Physical and chemical properties

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

% Solid. (w/w) : 54.415

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

## **Section 11. Toxicological information**

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
2,2',2"-nitrilotriethanol	LD50 Oral	Rat	7.39 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

<u>Irritation/Corrosion</u>

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitization** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Classification** 

Canada Page: 8/12

Product code 00467405 Date of issue 5 November 2024 Version 2.02

### Product name 2550 WB URETHANE GLOSS ASH WHITE - A

## **Section 11. Toxicological information**

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
2,2',2"-nitrilotriethanol	-	3	-

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Name	•	Route of exposure	Target organs
2,2',2"-nitrilotriethanol	Category 3		Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which may cause damage to the following organs: lungs, liver,

upper respiratory tract, skin, eye, lens or cornea.

### **Aspiration hazard**

Not available.

### Information on the likely routes of exposure

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** : No known significant effects or critical hazards.

### **Over-exposure signs/symptoms**

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

Canada Page: 9/12

## Section 11. Toxicological information

### **Conclusion/Summary**

: There are no data available on the mixture itself. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### **Short term exposure**

Potential immediate

effects

: There are no data available on the mixture itself.

**Potential delayed effects** 

: There are no data available on the mixture itself.

**Long term exposure** 

**Potential immediate** 

effects

There are no data available on the mixture itself.

**Potential delayed effects**: There are no data available on the mixture itself.

### Potential chronic health effects

**General** 

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity

: Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity
Reproductive toxicity

No known significant effects or critical hazards.No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	(mg/kg)	Inhalation (gases) (ppm)	(vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2,2',2"-nitrilotriethanol	7390	N/A	N/A	N/A	N/A

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 11800 mg/l	Fish	96 hours

### Persistence and degradability

Canada	Page: 10/12
--------	-------------

Date of issue 5 November 2024 Version 2.02

### Product name 2550 WB URETHANE GLOSS ASH WHITE - A

## **Section 12. Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2',2"-nitrilotriethanol	-	-	Readily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2,2',2"-nitrilotriethanol	-1	3.89	Low

### **Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## **Section 14. Transport information**

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	<del>-</del>	-	-
Packing group	-	-	-
<b>Environmental hazards</b>	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

### **Additional information**

TDG : None identified.

IMDG : None identified.

Canada Page: 11/12

Date of issue 5 November 2024 Version 2.02

Product name 2550 WB URETHANE GLOSS ASH WHITE - A

## Section 14. Transport information

: None identified. **IATA** 

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# Section 15. Regulatory information

### **National Inventory List**

Canada inventory (DSL) : At least one component is not listed.

: EHS

### Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of issue/Date of

Key to abbreviations

5 November 2024

revision

Organization that prepared

the SDS

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

### Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> Canada Page: 12/12