# SAFETY DATA SHEET



#### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 5 November 2024 Date of issue 5 November 2024

Version 2.02

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : 2550 F WB URETHANE FLAT DARK GRAY - A

Product code : 00462420

Other means of : Not applicable.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Professional applications, Used by spraying.

Use of the substance/

mixture

Coating.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

**Emergency telephone** 

number

(514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

### **SECTION 2: Hazards identification**

Classification of the substance or mixture

: Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

34.5% (oral), 34.5% (dermal), 35.6% (inhalation)

**GHS label elements** 

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.

Mexico Page: 1/11

Product code 00462420 Date of issue 5 November 2024 Version 2.02

Product name 2550 F WB URETHANE FLAT DARK GRAY - A

### SECTION 2: Hazards identification

Other hazards which do not : Emits toxic fumes when heated.

result in classification

See toxicological information (Section 11)

## **SECTION 3: Composition/information on ingredients**

Substance/mixture

: Mixture

Product name

: 2550 F WB URETHANE FLAT DARK GRAY - A

Other means of identification

: Not applicable.

Ingredient name	%	CAS number
itanium dioxide	≥5.0 - ≤10	13463-67-7
propane-1,2-diol	≥1.0 - ≤5.0	57-55-6
Propylidynetrimethanol, propoxylated	≥1.0 - ≤5.0	25723-16-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Skin contact** 

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### **Over-exposure signs/symptoms**

See toxicological information (Section 11)

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

Mexico Page: 2/11

Date of issue 5 November 2024 Version 2.02

#### Product name 2550 F WB URETHANE FLAT DARK GRAY - A

### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Mexico Page: 3/11

Date of issue 5 November 2024 Version 2.02

Product name 2550 F WB URETHANE FLAT DARK GRAY - A

# SECTION 7: Handling and storage

#### **Precautions for safe handling**

**Protective measures Special precautions** 

- : Put on appropriate personal protective equipment (see Section 8).
- : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage,** including any incompatibilities

: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# SECTION 8: Exposure controls/personal protection

#### **Control parameters**

С

#### Occupational exposure limits

Ingredient name	Exposure limits
Manium dioxide	NOM-010-STPS-2014 (Mexico, 4/2016)
propane-1,2-diol	TWA 8 hours: 10 mg/m³.
Propylidynetrimethanol, propoxylated	TWA: 10 mg/m³. None.

#### Key to abbreviations

= Ceiling Limit IPFI = Internal Permissible Exposure Limit STEL = Short term exposure limit TLV = Threshold Limit Value = Time Weighted Average TWA

#### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

: Good general ventilation should be sufficient to control worker exposure to airborne

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Page: 4/11 Mexico

Date of issue 5 November 2024 Version 2.02

Product name 2550 F WB URETHANE FLAT DARK GRAY - A

### SECTION 8: Exposure controls/personal protection

**Eye/face protection** 

**Skin protection** 

**Hand protection** 

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates

this is necessary.

: For prolonged or repeated handling, use the following type of gloves: **Gloves** 

Recommended: nitrile rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

# SECTION 9: Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Dark grey.

Odor : Odorless. : Not available. **Odor threshold** : Not applicable. Molecular weight

: Not available. **Melting point** : Not available. **Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: 121.11°C (250°F) [Product does not sustain combustion.]

**Auto-ignition temperature** Not available. **Decomposition temperature** : Not available. **Flammability** : Not available. Lower and upper explosive : Not available.

(flammable) limits

: Not available. **Evaporation rate** Vapor pressure : Not available. Vapor density : Not available.

: 1.1 **Relative density** Density (lbs/gal) : 9.18

Media **Result** Solubility(ies)

cold water Soluble

Solubility in water Not available. Partition coefficient: n-: Not applicable.

octanol/water

**Mexico** Page: 5/11 Product code 00462420 Date of issue 5 November 2024 Version 2.02

Product name 2550 F WB URETHANE FLAT DARK GRAY - A

## **SECTION 9: Physical and chemical properties**

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

% Solid. (w/w) : ₩3.76

### **SECTION 10: Stability and reactivity**

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials:

carbon oxides metal oxide/oxides

# **SECTION 11: Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
Propylidynetrimethanol, propoxylated	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2500 mg/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Irritation/Corrosion** 

**Conclusion/Summary** 

Skin
 : There are no data available on the mixture itself.
 Eyes
 : There are no data available on the mixture itself.
 Respiratory
 : There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

Mexico Page: 6/11

Date of issue 5 November 2024 Version 2.02

### Product name 2550 F WB URETHANE FLAT DARK GRAY - A

### **SECTION 11: Toxicological information**

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
carbon black		2B	-

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

#### **Reproductive toxicity**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Target organs : Contains material which may cause damage to the following organs: blood, lungs,

upper respiratory tract, central nervous system (CNS).

#### **Aspiration hazard**

Not available.

### Information on the likely routes of exposure

### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Conclusion/Summary**

: There are no data available on the mixture itself. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Carbon black is utilized as a raw material in many liquid coating formulations. In this case, the carbon black particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of carbon black when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful

Mexico Page: 7/11

### Product name 2550 F WB URETHANE FLAT DARK GRAY - A

# SECTION 11: Toxicological information

depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Most carbon blacks contain trace quantities of polyaromatic hydrocarbons (PAH). PAHs are not expected to be released in biological fluids and are therefore not likely available for biological activity. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

**Potential delayed effects** 

Long term exposure

: There are no data available on the mixture itself.

**Potential immediate** 

effects **Potential delayed effects**  : There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Potential chronic health effects

**General**  No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2550 F WB URETHANE FLAT DARK GRAY - A propane-1,2-diol Propylidynetrimethanol, propoxylated	150998.9	150998.9	N/A	N/A	N/A
	20000	20800	N/A	N/A	N/A
	2500	2500	N/A	N/A	N/A

# **SECTION 12: Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide propane-1,2-diol Propylidynetrimethanol, propoxylated	Acute LC50 >100 mg/l Fresh water Acute LC50 40613 mg/l Acute LC50 >100 mg/l	Daphnia - <i>Daphnia magna</i> Fish Fish	48 hours 96 hours 96 hours

#### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Propylidynetrimethanol, propoxylated	OECD 301A	84 % - Readily - 26 days	-	-

Mexico Page: 8/11

Date of issue 5 November 2024 Version 2.02

Product name 2550 F WB URETHANE FLAT DARK GRAY - A

# **SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
propane-1,2-diol Propylidynetrimethanol, propoxylated	-	-	Readily Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
· · · · · · · · · · · · · · · · · · ·	-1.07 0.01 to 1.5	-	Low Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Mexico

Page: 9/11

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# **SECTION 14: Transport information**

	Mexico Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Date of issue 5 November 2024 Version 2.02

#### Product name 2550 F WB URETHANE FLAT DARK GRAY - A

### **SECTION 14: Transport information**

Marine	Not applicable.	Not applicable.	Not applicable.
pollutant			
substances			

#### **Additional information**

: None identified. Mexico **IMDG** : None identified. IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# **SECTION 15: Regulatory information**

#### **International regulations**

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### SECTION 16: Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

**Date of previous issue** 6/29/2023 Organization that prepared : EHS

the SDS

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not availableSGG = Segregation Group UN = United Nations

Mexico Page: 10/11

Date of issue 5 November 2024 Version 2.02

Product name 2550 F WB URETHANE FLAT DARK GRAY - A

### **SECTION 16: Other information**

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Mexico Page: 11/11