# **SAFETY DATA SHEET**

Date of issue/Date of revision

: 14 November 2024 Version



PPG

: 3.02

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PITT-CHAR XP HARDENER BLACK PF
Product code	: 000001104813
Other means of identifica	tion
00352602; 00354399	s of the substance or mixture and uses advised against
	s of the substance or mixture and uses advised against
1.2 Relevant identified use Product use	<ul> <li>s of the substance or mixture and uses advised against</li> <li>Professional applications, Used by spraying.</li> </ul>
1.2 Relevant identified use	· · · · · · · · · · · · · · · · · · ·

#### Sigma Paints Egypt Villa#8, street 279 New Maadi, Cairo Egypt Tel: 00202 516 223 797 Fax: 00202 516 38 04 e-mail address of person : PS.ACEMEA@ppg.com responsible for this SDS

1.4 Emergency telephone : +20 2 6840902 number

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



Code: 000001104813Date of issue/Date of revision: 14 November 2024

PITT-CHAR XP HARDENER BLACK PF

**SECTION 2: Hazards identification** 

SECTION 2. Hazalus	
Hazard statements	<ul> <li>Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.
Response	: Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> <li>P280, P273, P260, P391, P304 + P310, P501</li> </ul>
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: Causes digestive tract burns.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре	
Tatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	REACH #: 01-2119972320-44 EC: 500-191-5 CAS: 68082-29-1	≥25 - ≤50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]	
1,3,5-triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4		Carc. 2, H351 (oral) Repr. 2, H361f STOT RE 2, H373	-	[1]	
		English	(GB)	Egypt	2/15	

Code	: 000001104813	Date of issue/Date of revision	: 14 November 2024
PITT-CHAR X	(P HARDENER BLACK PF		

### **SECTION 3: Composition/information on ingredients**

•			0		
	CAS: 108-78-1 Index: 613-345-00-2		(urinary system)		
4,4'-lsopropylidenediphenol, ethoxylated	EC: polymer CAS: 32492-61-8 (EO> 4.5 moles)	≥5.0 - ≤10	Aquatic Chronic 3, H412	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 1716 mg/ kg ATE [Dermal] = 1465 mg/kg	[1] [2]
	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important syr	nptoms and effects, both acute and delayed
Potential acute health	<u>n effects</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.

English (GB)

Code: 000001104813Date of issue/Date of revision: 14 November 2024PITT-CHAR XP HARDENER BLACK PF

# **SECTION 4: First aid measures**

Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Corrosive to the digestive tract. Causes burns.
Over-exposure signs/	<u>symptoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

English (GB)	Egypt	4/15
--------------	-------	------

Code : 000001104813

Date of issue/Date of revision

: 14 November 2024

PITT-CHAR XP HARDENER BLACK PF

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	-	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	-	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Code : 000001104813 PITT-CHAR XP HARDENER BLACK PF Date of issue/Date of revision

: 14 November 2024

**SECTION 7: Handling and storage** 

7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
	handling of use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
głass, oxide, chemicals	ACGIH TLV (United States) TWA: 10 mg/m <sup>3</sup> . Form: Total dust. TWA: 3 mg/m <sup>3</sup> . Form: Respirable. TWA: 1. Form: Continuous filament glass fibres.
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	TWA: 5 mg/m <sup>3</sup> (Inhalable). Form: Continuous filament glass fibres. <b>ACGIH TLV (United States)</b> TWA: 10 mg/m <sup>3</sup> . Form: Total dust. TWA: 3 mg/m <sup>3</sup> . Form: Respirable.

No exposure indices known.

Recommended monitoring procedures	:	Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure controls		
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection measur	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	:	Chemical splash goggles and face shield.

Code : 000001104813	Date of issue/Date of revision	: 14 November 2024
PITT-CHAR XP HARDENER BLACK PF		

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: nitrile neoprene
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	:
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
OFOTION OF Develop	Land chamical preparties

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Appearance					
Physical state	:	Liquid.			
Colour	:	Black.			
Odour	:	Amine-like. [Strong]			
Odour threshold	:	Not available.			
Melting point/freezing point	:	Not determined.			
Initial boiling point and boiling range	:	>37.78°C			
Flammability	:	Not determined. There are no	o data availab	le on the mix	kture itself.
Upper/lower flammability or explosive limits	:	Not available.			
Flash point	1	Closed cup: 120°C			
Flash point Auto-ignition temperature	:	Closed cup: 120°C Ingredient name	°C	°F	Method
	:	•	° <b>C</b> 337.78	° <b>F</b> 640	Method
	:	Ingredient name	337.78	640	
Auto-ignition temperature	:	Ingredient name           3,6-diazaoctanethylenediamin	337.78 storage and h	640	
Auto-ignition temperature Decomposition temperature	:	Ingredient name 3,6-diazaoctanethylenediamin Stable under recommended s	337.78 storage and h ater. : Not availabl e): Not availabl	e.	
Auto-ignition temperature Decomposition temperature pH	:	Ingredient name 3,6-diazaoctanethylenediamin Stable under recommended s Not applicable. insoluble in wa Dynamic (room temperature) Kinematic (room temperature)	337.78 storage and h ater. : Not availabl e): Not availabl	e.	

 Code
 <th::000001104813</th>
 Date of issue/Date of revision
 : 14 November 2024

 PITT-CHAR XP HARDENER BLACK PF

### **SECTION 9: Physical and chemical properties**

Media	Result	Result						
cold water	Not soluble	Not soluble						
Partition coefficient: n-octa water	nol/ : Not applicable.							
Vapour pressure	:	Vapo	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
	2,4,6-tris (dimethylaminomethyl) phenol	0.056	0.0075	EU A.4				
Relative density	: 1.14			•				
Explosive properties	: The product itself is vapour or dust with			the formation	of an exp	olosible n	nixture of	

# **Oxidising properties** : Product does not present an oxidizing hazard.

# Particle characteristics Median particle size

# : Not applicable.

#### 9.2 Other information

No additional information.

### **SECTION 10: Stability and reactivity**

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

# **SECTION 11: Toxicological information**

11.1 Information on toxicological effects
<u>Acute toxicity</u>

Code : 000001104813

PITT-CHAR XP HARDENER BLACK PF

Date of issue/Date of revision

: 14 November 2024

**SECTION 11: Toxicological information** 

Product/ingredient name	Result	Species	Dose	Exposure
Fatty acids, C18-unsatd., dimers,	LD50 Dermal	Rat	>2000 mg/kg	-
oligomeric reaction products with tall-oil				
fatty acids and triethylenetetramine				
	LD50 Oral	Rat	>2000 mg/kg	-
1,3,5-triazine-2,4,6-triamine	LC50 Inhalation Dusts and	Rat	>5190 mg/m <sup>3</sup>	4 hours
	mists			
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan-1-amide)	mists			
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Irritant	Human	-	-	-

#### Conclusion/Summary

Skin : There are no data available on the mixture itself.

: There are no data available on the mixture itself.

#### Respiratory

Eyes

: There are no data available on the mixture itself.

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitising
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising

#### **Conclusion/Summary**

Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Teratogenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Specific target organ toxi	<u>city (single exposure)</u>
Not available.	

#### Specific target organ toxicity (repeated exposure)

Code	: 000001104813	Date of issue/Date of revision	: 14 November 2024
PITT-CHAR >	P HARDENER BLACK PF		

# CTION 11. Toxicological information

Product/ingr	edient name	Category	Route of exposure	Target organs
1,3,5-triazine-2,4,6-triamine		Category 2 -		urinary system
Aspiration hazard Not available.				
nformation on likely routes of exposure	: Not available.			
Potential acute health effect	<u>s</u>			
Inhalation	: No known significant effe	ects or critical haza	ards.	
Ingestion	: Corrosive to the digestive	e tract. Causes bu	irns.	
Skin contact	: Causes severe burns. N	lay cause an allerg	gic skin reaction.	
Eye contact	: Causes serious eye dam	age.		
Symptoms related to the phy	ysical, chemical and toxico	ological characte	<u>ristics</u>	
Inhalation Ingestion	<ul> <li>Adverse symptoms may reduced foetal weight increase in foetal deaths skeletal malformations</li> <li>Adverse symptoms may stomach pains reduced foetal weight increase in foetal deaths</li> </ul>			
Skin contact	skeletal malformations : Adverse symptoms may	include the follow:		
	pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations		.9.	
Eye contact	: Adverse symptoms may pain watering redness	include the followi	ng:	
Delayed and immediate effe	cts as well as chronic effec	cts from short an	d long-term exp	<u>oosure</u>
Short term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Long term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
<mark>Potential chronic health effe</mark> Not available.	ects			
Conclusion/Summary	: Not available.			
General	: May cause damage to or sensitized, a severe aller levels.			

Conforms to Reg 2020/878	gulation (EC) No. 1907/2006 (REACH	), Annex II, as amended by Commissio	n Regulation (EU)
Code : 0	00001104813	Date of issue/Date of revision	: 14 November 2024
PITT-CHAR XP I	HARDENER BLACK PF		
SECTION 1	1: Toxicological information	on	
Carcinogenic	ity : Suspected of causing	g cancer. Risk of cancer depends on dur	ation and level of

Carcinogenicity	exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility.
Other information	: Not available.

Causes digestive tract burns. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

#### 11.2 Information on other hazards

#### **11.2.1 Endocrine disrupting properties**

Not available.

#### **11.2.2 Other information**

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours
1,3,5-triazine-2,4,6-triamine	Acute EC50 200 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-	Acute EC50 29 to 43 mg/l	Algae -	72 hours
1-amide)	5	Pseudokirchneriella	
,		subcapitata	
	Acute EC50 94 mg/l	Daphnia - Daphnia magna	48 hours

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,4,6-tris (dimethylaminomethyl)phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	4 % - Not readily - 28 days	-	-
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days	-	-

#### **Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	-	-	Not readily
2,4,6-tris(dimethylaminomethyl)phenol N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	-	-	Not readily Readily
	English (GB)	Egypt	11/15

# **SECTION 12: Ecological information**

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	-1.22 0.219 -1.66 to -1.4 >6	3.8 - - -	Low Low Low High

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
European waste catalog	ue (EWC)
Waste code	Waste designation
<b>Ø</b> 8 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>
Type of packaging	European waste catalogue (EWC)
<b>C</b> ontainer	15 01 06 mixed packaging

English	(GB)
---------	------

Code

: 000001104813

Date of issue/Date of revision

: 14 November 2024

PITT-CHAR XP HARDENER BLACK PF

### **SECTION 13: Disposal considerations**

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	III	Ш	III
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Polyamide)	Not applicable.

#### **Additional information**

ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (E)
IMDG	: The marine pollutant mark is not required when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
14.6 Special pro user	ecautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

14.7 Transport in bulk	: Not applicable.
according to IMO	
instruments	

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u> <u>Annex XIV - List of substances subject to authorisation</u> <u>Annex XIV</u> None of the components are listed. <u>Substances of very high concern</u>

event of an accident or spillage.

Code<th::000001104813</th>Date of issue/Date of revision: 14 November 2024PITT-CHAR XP HARDENER BLACK PF

# **SECTION 15: Regulatory information**

-	-			
Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Substance of equivalent concern for human health	melamine	Candidate	D(2022) 9120-DC	1/17/2023
Substance of equivalent concern for environment	melamine	Candidate	D(2022) 9120-DC	1/17/2023

Not listed.

15.2 Chemical safety	: No Chemical Safety Assessment has been carried out.
assessment	

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Full text of abbreviated H	EUH statement = CLP- PNEC = Predicted No I RRN = REACH Registr : H302 Harmful if sw	ation Number		
statements	<ul> <li>H312 Harmful in co</li> <li>H314 Causes seve</li> <li>H315 Causes skin</li> <li>H317 May cause ar</li> <li>H318 Causes serio</li> <li>H351 Suspected of</li> <li>H361f Suspected of</li> <li>H373 May cause dat</li> <li>H411 Toxic to aquation</li> </ul>	ntact with skin. re skin burns and eye dam	prolonged or repeated ex	(posure.
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Carc. 2 Eye Dam. 1 Repr. 2 Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A Skin Sens. 1B STOT RE 2	ACUTE TOXICITY - ( LONG-TERM (CHRO LONG-TERM (CHRO CARCINOGENICITY SERIOUS EYE DAM/ REPRODUCTIVE TO SKIN CORROSION/II SKIN CORROSION/II SKIN SENSITISATIO SKIN SENSITISATIO SKIN SENSITISATIO SKIN SENSITISATIO	Category 4 NIC) AQUATIC HAZARI NIC) AQUATIC HAZARI - Category 2 AGE/EYE IRRITATION - XICITY - Category 2 RRITATION - Category 1 RRITATION - Category 2 N - Category 1 N - Category 1A	D - Category 3 Category 1 IB IC 2
	En	glish (GB)	Egypt	14/15

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)	
2020/878	

	NI 46: Other information		
PITT-CHAF	R XP HARDENER BLACK PF		
Code	: 000001104813	Date of issue/Date of revision	: 14 November 2024

### **SECTION 16: Other information**

EXPOSURE - Category 2

<u>History</u>	
Date of issue/ Date of revision	: 14 November 2024
Date of previous issue	: 30 July 2024
Prepared by	: EHS
Version	: 3.02

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB)	Egypt	15/15