

# SAFETY DATA SHEET

Date of issue/Date of revision

: 2 December 2024

Version

: 4



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMAGLIDE 2390 HARDENER

**Product code** : 000001194863

**Other means of identification**

00467225; 00470776

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** : Hardener.; Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

**Supplier**

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226

Acute Tox. 4, H332

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Muta. 2, H341

Repr. 1B, H360FD

STOT SE 2, H371

STOT SE 3, H335

STOT RE 2, H373

Aquatic Chronic 2, H411

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 2: Hazards identification

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### Hazard pictograms



#### Signal word

: Danger

#### Hazard statements

: Flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.  
Suspected of causing genetic defects.  
May damage fertility. May damage the unborn child.  
May cause damage to organs.  
May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

#### Precautionary statements

##### Prevention

: Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

##### Response

: Collect spillage.

##### Storage

: Store in a well-ventilated place. Keep container tightly closed.

##### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P280, P210, P273, P391, P403 + P233, P501

#### Supplemental label elements

: Not applicable.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Restricted to professional users.

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

Code : 000001194863 Date of issue/Date of revision : 2 December 2024  
SIGMAGLIDE 2390 HARDENER

## SECTION 2: Hazards identification

- Product meets the criteria for PBT or vPvB** : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.
- Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
tetraethyl silicate	REACH #: 01-2119496195-28 EC: 201-083-8 CAS: 78-10-4 Index: 014-005-00-0	≥25 - ≤48	Flam. Liq. 3, H226 Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H335	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
pentane-2,4-dione	REACH #: 01-2119458968-15 EC: 204-634-0 CAS: 123-54-6 Index: 606-029-00-0	≥25 - ≤27	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331	ATE [Oral] = 570 mg/kg ATE [Dermal] = 790 mg/kg ATE [Inhalation (vapours)] = 5.1 mg/l	[1] [2]
dibutylbis(pentane-2,4-dionato-O,O')tin	REACH #: 01-2119557817-24 EC: 245-152-0 CAS: 22673-19-4 Index: 650-056-00-0	≤1.9	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 (immune system) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1864 mg/kg M [Acute] = 1 M [Chronic] = 1	[1] [2]
decamethylcyclopentasiloxane	REACH #: 01-2119511367-43 EC: 208-764-9 CAS: 541-02-6	≤0.30	Not classified.	-	[3] [4]
dodecamethylcyclohexasiloxane	REACH #: 01-2119517435-42 EC: 208-762-8 CAS: 540-97-6	≤0.30	Not classified.	-	[3] [4]
octamethylcyclotetrasiloxane	REACH #: 01-2119529238-36 EC: 209-136-7 CAS: 556-67-2 Index: 014-018-00-1	≤0.30	Repr. 2, H361f Aquatic Chronic 1, H410  <b>See Section 16 for the full text of the H statements declared above.</b>	M [Chronic] = 10	[1] [2] [3] [4]

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

### SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
  - [2] Substance with a workplace exposure limit
  - [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
  - [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : May cause damage to organs following a single exposure if swallowed.

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
  - pain or irritation
  - watering
  - redness
- Inhalation** : Adverse symptoms may include the following:
  - respiratory tract irritation
  - coughing
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 7: Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
tetraethyl silicate	<b>EU OEL (Europe, 1/2022)</b> TWA 8 hours: 5 ppm. TWA 8 hours: 44 mg/m <sup>3</sup> .
pentane-2,4-dione	<b>ACGIH TLV (United States, 7/2023)</b> Absorbed through skin. TWA 8 hours: 25 ppm.
dibutylbis(pentane-2,4-dionato-O,O')tin	<b>ACGIH TLV (United States)</b> Absorbed through skin. STEL: 0.2 mg/m <sup>3</sup> . TWA: 0.1 mg/m <sup>3</sup> (as Sn).
octamethylcyclotetrasiloxane	<b>IPEL (-, 10/2017)</b> TWA: 10 ppm.

### Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs



Code : 000001194863

Date of issue/Date of revision

: 2 December 2024

SIGMAGLIDE 2390 HARDENER

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
tetraethyl silicate	DNEL	Long term Dermal	1.8 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	5.3 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	5.3 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	5.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	5.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	6.3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	44 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	44 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	44 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	44 mg/m <sup>3</sup>	Workers	Systemic
pentane-2,4-dione	DNEL	Long term Oral	7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	12 mg/kg bw/day	Workers	Systemic
dibutylbis(pentane-2,4-dionato-O,O')tin	DNEL	Long term Inhalation	84 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	0.002 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.003 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Oral	0.01 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.01 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	0.02 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	0.07 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	0.08 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	0.5 mg/kg bw/day	General population	Systemic
decamethylcyclopentasiloxane	DNEL	Short term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	4.3 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	17.3 mg/m <sup>3</sup>	General population	Systemic
dodecamethylcyclohexasiloxane	DNEL	Long term Inhalation	24.2 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	97.3 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.3 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	1.22 mg/m <sup>3</sup>	Workers	Local
octamethylcyclotetrasiloxane	DNEL	Short term Inhalation	1.5 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	6.1 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	3.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	13 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	13 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	73 mg/m <sup>3</sup>	Workers	Local
DNEL	Long term Inhalation	73 mg/m <sup>3</sup>	Workers	Systemic	

### PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
pentane-2,4-dione	-	Fresh water	0.026 mg/l	-
	-	Fresh water sediment	0.155 mg/kg dwt	-
	-	Marine water	0.0026 mg/l	-
	-	Marine water sediment	0.0155 mg/kg dwt	-
	-	Soil	0.01582 mg/kg dwt	-
	-	Sewage Treatment Plant	1.32 mg/l	-

### 8.2 Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.



Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 8: Exposure controls/personal protection

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapor (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Color** : Colorless.
- Odor** : Alcohol-like. [Slight]

Code : 000001194863 Date of issue/Date of revision : 2 December 2024  
SIGMAGLIDE 2390 HARDENER

## SECTION 9: Physical and chemical properties

- Melting point/freezing point** : Not determined.  
**Boiling point or initial boiling point and boiling range** : >37.78°C  
**Flammability** : Not determined. There are no data available on the mixture itself.  
**Lower and upper explosion limit** : Not available.  
**Flash point** : Closed cup: 26°C  
**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
pentane-2,4-dione	340	644	

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).  
**pH** : Not applicable. insoluble in water.  
**Viscosity** : Dynamic (room temperature): Not available.  
 Kinematic (room temperature): Not available.  
 Kinematic (40°C): >21 mm<sup>2</sup>/s  
**Viscosity** : 30 - <40 s (ISO 6mm)  
**Solubility** :

Media	Result
cold water	Not soluble

- Partition coefficient n-octanol/ water (log Pow)** : Not applicable.

**Vapor pressure** :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
pentane-2,4-dione	6.97557	0.93				

- Relative density** : 0.98

### Particle characteristics

- Median particle size** : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapor or dust with air is possible.

- Oxidizing properties** : Product does not present an oxidizing hazard.

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

- 10.2 Chemical stability** : The product is stable.

- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

Code : 000001194863 Date of issue/Date of revision : 2 December 2024  
SIGMAGLIDE 2390 HARDENER

## SECTION 10: Stability and reactivity

Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- Harmful if inhaled.
- Causes serious eye irritation.
- Causes skin irritation.
- May cause an allergic skin reaction.
- May damage fertility.
- May damage the unborn child.
- Suspected of causing genetic defects.
- May cause damage to organs.
- May cause respiratory irritation.
- May cause damage to organs through prolonged or repeated exposure.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<input checked="" type="checkbox"/> Tetraethyl silicate	LC50 Inhalation Dusts and mists	Rat	10 to 16 mg/l	4 hours
	LD50 Dermal	Rabbit	5.878 g/kg	-
	LD50 Oral	Rat	6270 mg/kg	-
pentane-2,4-dione	LC50 Inhalation Vapor	Rat	5.1 mg/l	4 hours
	LD50 Dermal	Rat	790 mg/kg	-
	LD50 Oral	Rat	570 mg/kg	-
dibutylbis(pentane-2,4-dionato-O,O')tin	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1864 mg/kg	-
decamethylcyclopentasiloxane	LC50 Inhalation Dusts and mists	Rat	8.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>15.3 g/kg	-
	LD50 Oral	Rat	>24134 mg/kg	-
dodecamethylcyclohexasiloxane	LD50 Oral	Rat	>50 g/kg	-
octamethylcyclotetrasiloxane	LC50 Inhalation Vapor	Rat	36 g/m <sup>3</sup>	4 hours
	LD50 Dermal	Rat	>2375 mg/kg	-
	LD50 Oral	Rat	>4800 mg/kg	-

### Acute toxicity estimates

Route	ATE value
<input checked="" type="checkbox"/> Oral	2221.45 mg/kg
Dermal	3144.44 mg/kg
Inhalation (vapors)	11.37 mg/l

**Conclusion/Summary** :  Harmful if inhaled.

### Irritation/Corrosion

**Conclusion/Summary**

- Skin** :  Causes skin irritation.
- Eyes** :  Causes serious eye irritation.

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 11: Toxicological information

**Respiratory** : Based on available data, the classification criteria are not met.

### Respiratory or skin sensitization

#### Conclusion/Summary

**Skin** : May cause an allergic skin reaction.

**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

Suspected of causing genetic defects.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

May damage fertility.  
May damage the unborn child.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
tetraethyl silicate	Category 3	-	Respiratory tract irritation
dibutylbis(pentane-2,4-dionato-O,O')tin	Category 1	-	-

**Conclusion/Summary** :

May cause damage to organs.  
May cause respiratory irritation.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
dibutylbis(pentane-2,4-dionato-O,O')tin	Category 1	-	immune system

**Conclusion/Summary** :

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

Based on available data, the classification criteria are not met.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : Harmful if inhaled. May cause respiratory irritation.

**Ingestion** : May cause damage to organs following a single exposure if swallowed.

**Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 11: Toxicological information

**Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

### Potential chronic health effects

**General** : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : Suspected of causing genetic defects.

**Reproductive toxicity** : May damage fertility. May damage the unborn child.

**Other information** : Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

### 11.2.2 Other information

Not available.

Code : 000001194863 Date of issue/Date of revision : 2 December 2024  
SIGMAGLIDE 2390 HARDENER

## SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
octamethylcyclotetrasiloxane	Chronic NOEC 100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
tetraethyl silicate	3.18	-	Low
pentane-2,4-dione	0.68	-	Low
decamethylcyclopentasiloxane	8.023	-	High
dodecamethylcyclohexasiloxane	8.87	1660	High
octamethylcyclotetrasiloxane	6.488	-	High

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
tetraethyl silicate	No	N/A	N/A	No	N/A	N/A	N/A
pentane-2,4-dione	No	N/A	N/A	No	N/A	N/A	N/A
decamethylcyclopentasiloxane	SVHC (Recommended)	Specified	Specified	Specified	SVHC (Recommended)	Specified	Specified
dodecamethylcyclohexasiloxane	SVHC (Recommended)	Specified	Specified	Specified	SVHC (Recommended)	Specified	Specified
octamethylcyclotetrasiloxane	SVHC (Recommended)	Specified	Specified	Specified	SVHC (Recommended)	Specified	Specified

### 12.6 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 000001194863 Date of issue/Date of revision : 2 December 2024  
SIGMAGLIDE 2390 HARDENER

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** :

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(dibutylbis(pentane-2,4-dionato-O,O')tin)	Not applicable.

### Additional information

English (US)	Europe	15/18
--------------	--------	-------



Code : 000001194863 Date of issue/Date of revision : 2 December 2024  
SIGMAGLIDE 2390 HARDENER

## SECTION 14: Transport information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Tunnel code** : (D/E)
- ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorization](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
☒ Toxic to reproduction	dibutylbis(pentane-2,4-dionato-O,O')tin	Candidate	D(2020) 4578-DC	6/25/2020
PBT	decamethylcyclopentasiloxane	Recommended	ED/71/2019	4/14/2021
	dodecamethylcyclohexasiloxane	Recommended	ED/71/2019	4/14/2021
	octamethylcyclotetrasiloxane	Recommended	ED/71/2019	4/14/2021
vPvB	decamethylcyclopentasiloxane	Recommended	ED/71/2019	4/14/2021
	dodecamethylcyclohexasiloxane	Recommended	ED/71/2019	4/14/2021
	octamethylcyclotetrasiloxane	Recommended	ED/71/2019	4/14/2021

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	Entry Number ( REACH )
☒ SIGMAGLIDE 2390 HARDENER	3
dibutylbis(pentane-2,4-dionato-O,O')tin	30
decamethylcyclopentasiloxane	20
octamethylcyclotetrasiloxane	30
	70
	70

**Labeling** : Restricted to professional users.

**Explosive precursors** : Not applicable.

[Ozone depleting substances \(1005/2009/EU\)](#)

Not listed.

[Seveso Directive](#)

Code : 000001194863  
SIGMAGLIDE 2390 HARDENER

Date of issue/Date of revision : 2 December 2024

## SECTION 15: Regulatory information

This product is controlled under the Seveso Directive.

### Danger criteria

#### Category

P5c  
E2

**15.2 Chemical Safety Assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

### Full text of abbreviated H statements

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

<b>Code</b> : 000001194863	<b>Date of issue/Date of revision</b> : 2 December 2024
<b>SIGMAGLIDE 2390 HARDENER</b>	

**SECTION 16: Other information**

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
STOT SE 2	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

**History**

<b>Date of issue/ Date of revision</b>	: 2 December 2024
<b>Date of previous issue</b>	: 29 July 2024
<b>Prepared by</b>	: EHS
<b>Version</b>	: 4

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*