# SAFETY DATA SHEET



#### **SIGMAGLIDE 790 HARDENER**



Date of issue 6 December 2024

Version 2.02

## 1. Product and company identification

Product name : SIGMAGLIDE 790 HARDENER

Product code : 000001198035 Other means of : 00472262 identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Hardener.

Uses advised against : Not applicable.

Supplier's details : PPG PMC Japan Co., Ltd., 8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe

652-0803 Japan; Tel: +81-78-574-2777

**Emergency telephone** 

number

: 078 574 2777

## 2. Hazards identification

GHS Classification : ACUTE TOXICITY (oral) - Category 3

SKIN CORROSION - Category 1
SERIOUS EYE DAMAGE - Category 1
TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2
HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 2

HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD -

Category 2

**GHS label elements** 

Hazard pictograms :









Signal word : Danger

**Hazard statements**: Toxic if swallowed.

Causes severe skin burns and eye damage. May damage fertility or the unborn child.

May cause damage to organs. (systemic toxicity) Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Japan Page: 1/12

### 2. Hazards identification

Response

: Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

**Storage** 

: Store locked up.

**Disposal** 

Dispose of contents and container in accordance with all local, regional, national and international regulations.

result in classification

Other hazards which do not : Causes respiratory tract burns.

# 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS** number : Not applicable. **CSCL** number Not available.

Ingredient name	%	CAS number	CSCL
Methylsilanetriyl triacetate oligomeric ethyl- and methylacetoxysilanes diacetoxydi-tert-butoxysilane	25 - <50 20 - <25 20 - <25 3 - <5	17689-77-9 4253-34-3 SUB142892 13170-23-5	9-1939 9-1939 Not available. 2-2062
dibutyltin di(acetate)	3 - <5	1067-33-0	2-2330

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

**Eye contact** : Causes serious eye damage.

> Japan Page: 2/12

Product code 000001198035 Date of issue 6 December 2024 Version 2.02

Product name SIGMAGLIDE 790 HARDENER

### 4. First aid measures

**Inhalation** : Corrosive to the respiratory system.

**Skin contact**: Causes severe burns. May cause damage to organs following a single exposure in

contact with skin.

Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach. May cause

damage to organs following a single exposure if swallowed.

#### **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

sewer or drain.

Japan Page: 3/12

Date of issue 6 December 2024 Version 2.02

Product name SIGMAGLIDE 790 HARDENER

## 5. Fire-fighting measures

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon oxides

metal oxide/oxides Formaldehyde.

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

**Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

> Japan Page: 4/12

## 7. Handling and storage

Conditions for safe storage: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

None.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye protection Skin protection**  : Chemical splash goggles and face shield.

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: nitrile neoprene

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

> Japan Page: 5/12

Product name SIGMAGLIDE 790 HARDENER

## 8. Exposure controls/personal protection

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Clear.

Odor : Hydrocarbon. [Strong]
Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 99°C (210.2°F)

Relative density : 1.16

Solubility(ies) : Media Result

cold water Not soluble

# 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides Formaldehyde. metal oxide/oxides

## 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ethyltriacetoxysilane	LD50 Oral	Rat	1.462 g/kg	-
Methylsilanetriyl triacetate	LD50 Oral	Rat	2060 mg/kg	-
dibutyltin di(acetate)	LD50 Dermal	Rabbit	2318 mg/kg	-

### **Irritation/Corrosion**

Not available.

### **Sensitization**

Japan Page: 6/12

Date of issue 6 December 2024 Version 2.02

Product name SIGMAGLIDE 790 HARDENER

## 11. Toxicological information

Not available.

#### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Name	,	Route of exposure	Target organs
ethyltriacetoxysilane Methylsilanetriyl triacetate	Category 2 Category 2		systemic toxicity systemic toxicity

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
dibutyltin di(acetate)	Category 2	-	liver

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : Corrosive to the respiratory system.

**Skin contact**: Causes severe burns. May cause damage to organs following a single exposure in

contact with skin.

Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach. May cause

damage to organs following a single exposure if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

Japan Page: 7/12

Product name SIGMAGLIDE 790 HARDENER

## 11. Toxicological information

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility or the unborn child.

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMAGLIDE 790 HARDENER	102.6	2440.0	N/A	N/A	N/A
ethyltriacetoxysilane	1462	N/A	N/A	N/A	N/A
Methylsilanetriyl triacetate	500	N/A	N/A	N/A	N/A
dibutyltin di(acetate)	5	2318	N/A	N/A	N/A

#### Other information

Causes respiratory tract burns. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F).

## 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
dibutyltin di(acetate)	Acute EC10 3.1 mg/l	Fish	72 hours
	Acute EC50 0.5 mg/l	Algae	72 hours

### Persistence/degradability

	Japan	Page: 8/12
--	-------	------------

Date of issue 6 December 2024 Version 2.02

Product name SIGMAGLIDE 790 HARDENER

## 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
dibutyltin di(acetate)	-	-	Not readily

#### **Bioaccumulative potential**

**Product code 000001198035** 

Not available.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

Other adverse effects : No known significant effects or critical hazards.

## 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# 14. Transport information

	UN	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(dibutyltin di(acetate))	Not applicable.

### **Additional information**

UN : None identified.

**IMDG**: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

Japan Page: 9/12

## 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# 15. Regulatory information

#### **Fire Service Law**

Category	Substance name/Type	Danger category	Signal word	Designated quantity
<b>⊘</b> ategory IV	Class III petroleums	III	Flammable - Keep Fire Away	2000 L

### Pollutant Release and Transfer Registers (PRTR)

Ingredient name			
Organic tin compounds (except for Bis(tributyltin) oxide)	3.2	Class 1	664

### **Industrial Safety and Health Act**

### Ordinance on the Prevention of the Hazard due to Specified Chemical Substances

None of the components are listed.

### Substance(s) requiring labelling

Ingredient name	%		Reference number
Tin and its compounds	≤10	Listed	322

### **Chemicals requiring notification**

Ingredient name	%	Status	Reference number
Tin and its compounds	≤10	Listed	322

### Carcinogens based on Article 577-2 of the Ordinance on ISH

None of the components are listed.

### **Mutagen**

Ingredient name	%	Status	Reference
			number
Dibutyltin di(acetate)	≤10	Listed	-

**Corrosive liquid** : Not listed **Occupational Safety and** 

**Health Law** 

: Not applicable.

Regulations on the **Prevention of Tetraalkyl**  : Not listed

**Lead Poisoning** 

Page: 10/12 **Japan** 

**Product code 000001198035** Date of issue 6 December 2024 Version 2.02

Product name SIGMAGLIDE 790 HARDENER

# 15. Regulatory information

**Harmful Substances** 

**Subject to Obtaining Permission for Manufacturing** 

Harmful Substances,

**Prohibited for** 

: Not listed

: Not listed

**Manufacturing** 

Lead regulation : Not listed **Organic solvents** : Not applicable.

poisoning prevention

#### Poisonous and Deleterious Substances

None of the components are listed.

### **Chemical Substances Control Law (CSCL)**

None of the components are listed.

**High Pressure Gas Control**: Not available.

Law

#### **Explosives Control Law**

None of the components are listed.

Law concerning prevention : Not available. of pollution of the ocean

# **Maritime Safety Law**

### Notification Regulating Transportation of Dangerous Materials by Sea

None of the components are listed.

### **Container class**

None of the components are listed.

: Not listed **JSOH Carcinogen List of Specially Controlled** : Not listed

**Industrial Waste** 

: All components are listed or exempted. Japan inventory

**Road law** : Not available.

## 16. Other information

#### **History**

Date of issue/Date of : 6 December 2024

revision

Date of previous issue : 10/9/2024 **Version** : 2.02 **Prepared by** : EHS

Page: 11/12 **Japan** 

Product code 000001198035 Date of issue 6 December 2024 Version 2.02

Product name SIGMAGLIDE 790 HARDENER

### 16. Other information

**Key to abbreviations** 

: ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

✓ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Japan Page: 12/12