

SAFETY DATA SHEET

Date of issue/Date of revision : 13 December 2024 Version : 8.01



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PPG VIKOTE 56 WHITE

Product code : 00154022

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.
PO Box 7509
Dammam 31472
Saudi Arabia
Tel: 00966 138 47 31 00
Fax: 00966 138 47 17 34

**e-mail address of person
responsible for this SDS** : ndpic@sfda.gov.sa

**1.4 Emergency telephone
number** : 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Lact., H362

STOT SE 3, H335

STOT SE 3, H336

Aquatic Acute 1, H400

Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 2: Hazards identification

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: Flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause harm to breast-fed children.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid contact during pregnancy and while nursing.

Response

: Collect spillage.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.
P210, P273, P263, P391, P403 + P233, P501

Supplemental label elements

: Contains 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene, n-butyl methacrylate and methyl methacrylate. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 3: Composition/information on ingredients

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|--|--|-------------|--|---|----------------|
| Hydrocarbons, C9, aromatics < 0.1% cumene | REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0 | ≥25 - ≤50 | Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 | EUH066: C ≥ 20% | [1] |
| xylene | REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 | ≥10 - ≤25 | Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 | ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| alkanes, C14-17, chloro | REACH #: 01-2119519269-33 EC: 287-477-0 CAS: 85535-85-9 Index: 602-095-00-X | ≥1.0 - ≤5.0 | Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH066 | M [Acute] = 100 M [Chronic] = 10 | [1] [3] [4] |
| ethylbenzene | REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4 | ≥1.0 - ≤5.0 | Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412 | ATE [Inhalation (vapours)] = 17.8 mg/l | [1] [2] |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | REACH #: 01-2119962189-26 CAS: 911674-82-3 Index: 616-198-00-2 | <1.0 | Skin Sens. 1, H317 Aquatic Chronic 4, H413 | - | [1] [2] |
| n-butyl methacrylate | REACH #: 01-2119486394-28 EC: 202-615-1 CAS: 97-88-1 Index: 607-033-00-5 | ≤0.30 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 | - | [1] [2] |
| methyl methacrylate | REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6 | ≤0.30 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 See Section 16 for the full text of the H statements declared above. | - | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 3: Composition/information on ingredients

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture contains $\geq 1\%$ of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 6: Accidental release measures

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid contact during pregnancy or while nursing. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 7: Handling and storage

containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Hydrocarbons, C9, aromatics < 0.1% cumene

Ministry of Labor (France, 9/2023) [hydrocarbures en C6-C12]

TWA 8 hours: 1000 mg/m³. Form: Vapour.

STEL 15 minutes: 1500 mg/m³. Form: Vapour.

xylene

Ministry of Labor (France, 9/2023) [xylènes, isomères mixtes, purs] Absorbed through skin.

STEL 15 minutes: 442 mg/m³.

STEL 15 minutes: 100 ppm.

TWA 8 hours: 221 mg/m³.

TWA 8 hours: 50 ppm.

ethylbenzene

Ministry of Labor (France, 9/2023) Absorbed through skin.

TWA 8 hours: 20 ppm.

TWA 8 hours: 88.4 mg/m³.

STEL 15 minutes: 442 mg/m³.

STEL 15 minutes: 100 ppm.

methyl methacrylate

Ministry of Labor (France, 9/2023)

TWA 8 hours: 50 ppm.

TWA 8 hours: 205 mg/m³.

STEL 15 minutes: 100 ppm.

STEL 15 minutes: 410 mg/m³.

| Product/ingredient name | Exposure limit values |
|-------------------------|--|
| Titanium dioxide | <p>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A4. TWA 8 hours: 10 mg/m³.</p> <p>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006) TWA 8 hours: 10 mg/m³.</p> <p>ACGIH TLV (United States, 7/2023) A3. TWA 8 hours: 2.5 mg/m³. Form: respirable fraction, finescale particles.</p> |
| xylene | <p>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [xylene (o, m & p isomers)] A4. STEL 15 minutes: 651 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 434 mg/m³. TWA 8 hours: 100 ppm.</p> <p>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006) [xylene (all isomers)] STEL 15 minutes: 150 ppm. TWA 8 hours: 434 mg/m³.</p> |

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

1,2,4-trimethylbenzene

STEL 15 minutes: 651 mg/m³.

TWA 8 hours: 100 ppm.

ACGIH TLV (United States, 7/2023) [p-xylene and mixtures containing p-xylene] A4. Ototoxicant.

TWA 8 hours: 20 ppm.

Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [trimethyl benzene (mixed isomers)]

TWA 8 hours: 123 mg/m³.

TWA 8 hours: 25 ppm.

ACGIH TLV (United States, 7/2023) A4.

TWA 8 hours: 10 ppm.

Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A3.

STEL 15 minutes: 543 mg/m³.

STEL 15 minutes: 125 ppm.

TWA 8 hours: 100 ppm.

TWA 8 hours: 434 mg/m³.

Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)

STEL 15 minutes: 125 ppm.

TWA 8 hours: 434 mg/m³.

STEL 15 minutes: 543 mg/m³.

TWA 8 hours: 100 ppm.

ACGIH TLV (United States, 7/2023) A3. Ototoxicant.

TWA 8 hours: 20 ppm.

ethylbenzene

mesitylene

Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [trimethyl benzene (mixed isomers)]

TWA 8 hours: 123 mg/m³.

TWA 8 hours: 25 ppm.

ACGIH TLV (United States, 7/2023) [trimethyl benzene, isomers]

TWA 8 hours: 10 ppm.

1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene

ACGIH TLV (United States)

TWA: 3 mg/m³ (Respirable fraction).

TWA: 10 mg/m³ (Total dust).

methyl methacrylate

Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A4. Sensitiser.

TWA 8 hours: 205 mg/m³.

TWA 8 hours: 50 ppm.

STEL 15 minutes: 410 mg/m³.

STEL 15 minutes: 100 ppm.

Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)

TWA 8 hours: 410 mg/m³.

TWA 8 hours: 100 ppm.

ACGIH TLV (United States, 7/2023) A4. Skin sensitiser.

TWA 8 hours: 50 ppm.

STEL 15 minutes: 100 ppm.

 xylene

DOL BEI (South Africa, 3/2021) [xylenes]

BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: end of shift.

ethylbenzene

DOL BEI (South Africa, 3/2021)

BEI: 0.15 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber

Recommended: polyvinyl alcohol (PVA), Viton®

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection :

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : White.
- Odour** : Aromatic.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not determined.
- Initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Upper/lower flammability or explosive limits** : Not available.
- Flash point** : Closed cup: 35°C
- Auto-ignition temperature** :

| Ingredient name | °C | °F | Method |
|---|------------|------------|--------|
| Hydrocarbons, C9, aromatics < 0.1% cumene | 280 to 470 | 536 to 878 | |

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s

Solubility(ies)

| Media | Result |
|------------|-------------|
| cold water | Not soluble |

- Partition coefficient: n-octanol/ water** : Not applicable.

Vapour pressure

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| Stylybenzene | 9.30076 | 1.2 | | | | |

- Relative density** : 1.08
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.
- Particle characteristics**
- Median particle size** : Not applicable.

9.2 Other information

No additional information.

Code : 00154022 Date of issue/Date of revision : 13 December 2024
PPG VIKOTE 56 WHITE

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|-----------------------|-------------------------|----------|
| Hydrocarbons, C9, aromatics < 0.1% cumene | LD50 Dermal | Rabbit - Male, Female | >2000 mg/kg | - |
| xylene | LD50 Oral | Rat | 8400 mg/kg | - |
| | LD50 Dermal | Rabbit | 1.7 g/kg | - |
| | LD50 Oral | Rat | 4.3 g/kg | - |
| alkanes, C14-17, chloro | LC50 Inhalation Vapour | Rat | >48.17 g/m ³ | 1 hours |
| | LD50 Oral | Rat | >5 g/kg | - |
| ethylbenzene | LC50 Inhalation Vapour | Rat | 17.8 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 17.8 g/kg | - |
| | LD50 Oral | Rat | 3.5 g/kg | - |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | LC50 Inhalation Dusts and mists | Rat | >5.08 mg/l | 4 hours |
| n-butyl methacrylate | LC50 Inhalation Gas. | Rat | 4910 ppm | 4 hours |
| | LC50 Inhalation Vapour | Rat | 29000 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 10.2 g/kg | - |
| | LD50 Oral | Rat | 16 g/kg | - |
| methyl methacrylate | LC50 Inhalation Vapour | Rat | 78000 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | 7872 mg/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| xylene | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 11: Toxicological information

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|---|------------|-------------------|------------------------------|
| Hydrocarbons, C9, aromatics < 0.1% cumene | Category 3 | - | Respiratory tract irritation |
| xylene | Category 3 | - | Narcotic effects |
| n-butyl methacrylate | Category 3 | - | Respiratory tract irritation |
| methyl methacrylate | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|----------------|
| ethylbenzene | Category 2 | - | hearing organs |

Aspiration hazard

| Product/ingredient name | Result |
|---|--------------------------------|
| Hydrocarbons, C9, aromatics < 0.1% cumene | ASPIRATION HAZARD - Category 1 |
| xylene | ASPIRATION HAZARD - Category 1 |
| ethylbenzene | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Ingestion : Can cause central nervous system (CNS) depression.

Skin contact : Causes skin irritation. Defatting to the skin.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 11: Toxicological information

Ingestion : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May cause harm to breast-fed children.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

| | |
|------------------------|--|
| Code : 00154022 | Date of issue/Date of revision : 13 December 2024 |
| PPG VIKOTE 56 WHITE | |

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|--|---|---|----------------------|
| Hydrocarbons, C9, aromatics < 0.1% cumene ethylbenzene | LC50 9.2 mg/l Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water | Fish Daphnia | 96 hours 48 hours |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | Acute LC50 >100 mg/l | Daphnia - <i>Ceriodaphnia dubia</i> Fish | - 96 hours |

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|--|------|--------------------------|------|----------|
| Hydrocarbons, C9, aromatics < 0.1% cumene ethylbenzene | - | 78 % - 28 days | - | - |
| | - | 79 % - Readily - 10 days | - | - |

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|-------------|-------------------------------|
| Hydrocarbons, C9, aromatics < 0.1% cumene xylene ethylbenzene | - - - | - - - | Readily Readily Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|---------------------------|-------------|
| Hydrocarbons, C9, aromatics < 0.1% cumene xylene | 3.7 to 4.5 3.12 | 10 to 2500 7.4 to 18.5 | High Low |
| alkanes, C14-17, chloro ethylbenzene | 4.7 to 8.3 3.6 | - 79.43 | High Low |
| n-butyl methacrylate | 2.99 | - | Low |
| methyl methacrylate | 1.38 | - | Low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|--|------------------|-----------|-----------|-----------|------------------|-----------|-----------|
| xylene | No | N/A | No | No | No | N/A | No |
| alkanes, C14-17, chloro ethylbenzene | SVHC (Candidate) | Specified | Specified | Specified | SVHC (Candidate) | Specified | Specified |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | No | N/A | No | Yes | No | N/A | No |
| | No | N/A | N/A | No | N/A | N/A | N/A |
| n-butyl methacrylate | No | N/A | N/A | No | N/A | N/A | N/A |
| methyl methacrylate | No | N/A | N/A | No | N/A | N/A | N/A |

12.6 Endocrine disrupting properties

Code : 00154022 **Date of issue/Date of revision** : 13 December 2024
PPG VIKOTE 56 WHITE

SECTION 12: Ecological information

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container | 15 01 06 mixed packaging |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA |
|---------------------------------|---------|--------|--|
| 14.1 UN number or ID number | UN1263 | UN1263 | UN1263 |
| 14.2 UN proper shipping name | PAINT | PAINT | PAINT |
| 14.3 Transport hazard class(es) | 3 | 3 | 3 |
| 14.4 Packing group | III | III | III |
| 14.5 Environmental hazards | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. |

Code : 00154022 Date of issue/Date of revision : 13 December 2024
PPG VIKOTE 56 WHITE

SECTION 14: Transport information

| | | | |
|-----------------------------|-----------------|---|-----------------|
| Marine pollutant substances | Not applicable. | (Solvent naphtha (petroleum), light aromatic) | Not applicable. |
|-----------------------------|-----------------|---|-----------------|

Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- Tunnel code** : (D/E)
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

| Intrinsic property | Ingredient name | Status | Reference number | Date of revision |
|--------------------|--|-----------|------------------|------------------|
| PBT | medium-chain chlorinated paraffins UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17 | Candidate | D(2021) 4569-DC | 7/8/2021 |
| vPvB | medium-chain chlorinated paraffins UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17 | Candidate | D(2021) 4569-DC | 7/8/2021 |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other national and international regulations.

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

Code : 00154022

Date of issue/Date of revision

: 13 December 2024

PPG VIKOTE 56 WHITE

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

Full text of abbreviated H statements

: H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H362 May cause harm to breast-fed children.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.
EUH066 Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

: Acute Tox. 4 ACUTE TOXICITY - Category 4
Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1 ASPIRATION HAZARD - Category 1
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3
Lact. REPRODUCTIVE TOXICITY - Effects on or via lactation
Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1 SKIN SENSITISATION - Category 1
STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 13 December 2024

Date of previous issue : 30 October 2024

Prepared by : EHS

Version : 8.01

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.