# **SAFETY DATA SHEET**



Date of issue/Date of revision 2 January 2025 Version 2

Section 1. Identification	
Product code	: 00476253
Product name	: SIGMASHIELD 905 BASE DARK GREY
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	Coating. Professional applications, Used by spraying.
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)

# Section 2. Hazards identification

Classification of the	KIN CORROSION/IRRITATION - Category 2
substance or mixture	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
	AQUATIC HAZARD (LONG-TERM) - Category 2

2

Hazard	pictograms
--------	------------



Signal word Hazard statements		Warning Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling.

Product name SIGMASHIELD 905 BASE DARK GREY

### Section 2. Hazards identification

Response	: Collect spillage. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Not applicable.
Other hazards which do not	: None known.

result in classification

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
-------------------	-----------

#### CAS number/other identifiers

EC number : Mixture.	CAS number EC number	: Not applicable. : Mixture.
----------------------	-------------------------	---------------------------------

Ingredient name	%	CAS number
bis-[4-(2,3-epoxipropoxi)phenyl]propane	25 - <50	1675-54-3
Talc , not containing asbestiform fibres	10 - <20	14807-96-6
1,6-bis(2,3-epoxypropoxy)hexane	5 - <10	16096-31-4
benzyl alcohol	5 - <10	100-51-6
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	0.3 - <1	123-26-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Singapore Englis	sh (US)
------------------	---------

Section 4. First ai	
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
ndication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Singapore	English (US)	Page: 3/12
-----------	--------------	------------

Product name SIGMASHIELD 905 BASE DARK GREY

### Section 5. Fire-fighting measures

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protectiv	ive equipment and emergency procedures
For non-emergency : personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders :	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions :	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

- : Put on appropriate personal protective equipment (see Section 8). Persons with a
- history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Section 7. Handling and storage

	•	•
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name			Exposure limits		
Falc , not containing asbestiform fibres         N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)			Workplace Safety and Health Act (Singapore, 2/2006) PEL (long term) 8 hours: 2 mg/m <sup>3</sup> . ACGIH TLV (United States) TWA: 10 mg/m <sup>3</sup> . Form: Total dust. TWA: 3 mg/m <sup>3</sup> . Form: Respirable.		
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.			
Appropriate engineering controls	:	Sood general ventilation should be su contaminants.	ufficient to control worker exposure to airborne		
Environmental exposure controls	:				
ndividual protection measur	es				
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should n	bughly after handling chemical products, before ry and at the end of the working period. ed to remove potentially contaminated clothing. ot be allowed out of the workplace. Wash . Ensure that eyewash stations and safety location.		
Eye/face protection Skin protection	:	Chemical splash goggles.			

Product code 00476253

Version 2

Product name SIGMASHIELD 905 BASE DARK GREY

# Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

<u>Appearance</u>
-------------------

: Liquid.	
: Characteristic.	
Not applicable.	
: >37.78°C (>100°F)	
: Closed cup: Not applicable.	
: Not available.	
: liquid	
: Not available.	
:	
: 1.29	
Media Result	
cold water Not soluble	
: Not available.	
<ul> <li>              ∫ynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): &gt;21 mm²/s (&gt;21 cSt)      </li> </ul>	
	Media       Result         cold water       Not soluble         Not available.       Not available.         Synamic (room temperature): Not available.       Kinematic (room temperature): Not available.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

# Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
is-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
-	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	LC50 Inhalation Dusts and mists	Rat	>5.11 mg/l	4 hours
,	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Singapore	English (US)	Page: 7/12
Singapore	English (US)	

# Section 11. Toxicological information

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing
Conclusion/Summary			
Skin	There are no data	available on the mixture itself.	
Respiratory	There are no data	available on the mixture itself.	
Mutagenicity			
Conclusion/Summary	: There are no data	a available on the mixture itself.	
<b>Carcinogenicity</b>			
Conclusion/Summary	: There are no data	a available on the mixture itself.	
Reproductive toxicity			
Conclusion/Summary	: There are no data	a available on the mixture itself.	
Teratogenicity			
Conclusion/Summary	: There are no data	a available on the mixture itself.	
Specific target organ toxic	ity (single exposur	<u>'e)</u>	

Name		Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effect	t <u>s</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: 📈 known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph Eye contact	ysical, chemical and toxicological characteristics : Adverse symptoms may include the following:
	pain or irritation watering redness
Inhalation	: No specific data.

Singapore	English (US)	Page: 8/12
-----------	--------------	------------

### Section 11. Toxicological information

		· · · · · · · · · · · · · · · · · · ·
Skin contact	irrit	lverse symptoms may include the following: tation dness
Ingestion	: No	o specific data.
Delayed and immediate effe	<u>ts an</u> c	d also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	: No	ot available.
Potential delayed effects	: No	ot available.
Long term exposure		
Potential immediate effects	: No	ot available.
Potential delayed effects	: No	ot available.
Potential chronic health eff	<u>cts</u>	
General		nce sensitized, a severe allergic reaction may occur when subsequently exposed very low levels.
Carcinogenicity	: No	hown significant effects or critical hazards.
Mutagenicity	: No	hown significant effects or critical hazards.
Reproductive toxicity	: No	hown significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Øral	9261.33 mg/kg

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

### Section 12. Ecological information

ż

#### **Toxicity**

# Section 12. Ecological information

Result	Species	Exposure
Acute LC50 1.8 mg/l Fresh water	Daphnia - <i>daphnia magna</i>	48 hours
Chronic NOEC 0.3 mg/l	Daphnia	21 days
Acute EC50 29 to 43 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
Acute EC50 94 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 1.8 mg/l Fresh water Chronic NOEC 0.3 mg/l Acute EC50 29 to 43 mg/l	Acute LC50 1.8 mg/l Fresh water       Daphnia - daphnia magna         Chronic NOEC 0.3 mg/l       Daphnia         Acute EC50 29 to 43 mg/l       Algae - Pseudokirchneriella         subcapitata       Subcapitata

#### Persistence/degradability

Product/ingredient name	Test	Result		Dose	Inoculum
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days		-	-
Conclusion/Summary	: Not available.	·			
Product/ingredient name	Aquatic half-life		Photolysi	S	Biodegradability
bis-[4-(2,3-epoxipropoxi)	-		-		Not readily

phenyl]propane benzyl alcohol	_	_	Readilv
N,N'-ethane-1,2-diylbis	-		Readily
(12-hydroxyoctadecan-			-
1-amide)			

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy) hexane	0.822	-	Low
benzyl alcohol N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	0.87 >6	-	Low High

#### Mobility in soil

Soil/water partition coefficient (Koc) : Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

Product name SIGMASHIELD 905 BASE DARK GREY

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

UN	:	This product is not regulated as a dangerous good when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
IMDG	:	This product is not regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
ΙΑΤΑ	:	This product is not regulated as a dangerous good when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	
Special precaution	ons	<b>for user</b> : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
Transport in bulk to IMO instrumen		• • • • • • • • • • • • • • • • • • • •	

Singapore	English (US)	Page: 11/12
-----------	--------------	-------------

# Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations Montreal Protocol Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 2 January 2025
Date of previous issue	: 7/17/2024
Version	: 2
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.