SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 3 January 2025 Version 1.02

Section 1. Identification		
Product name	: 🗖 QUATAPOXY A6 THICK GRAY - A	
Product code	: 00471360	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications, Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier	 PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121 	
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 888-977-4762	

Section 2. Hazard identification

Classification of the substance or mixture	 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B CARCINOGENICITY - Category 2 This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).
GHS label elements	protective equipment and/or engineering controls (see Section 8).

Canada Page: 1/13

Product name AQUATAPOXY A6 THICK GRAY - A

Section 2. Hazard identification

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.
Precautionary statements		
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	:	IF exposed or concerned: Get medical advice or attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	1	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Emits toxic fumes when heated.
		Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 9% (oral), 14% (dermal), 87.3% (inhalation)
Other hazards which do not result in classification	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 🗖 QUATAPOXY A6 THICK GRAY - A
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS numb	ber
bis-[4-(2,3-epoxipropoxi)phenyl] propane	2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)]bisoxirane; Oxirane, 2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)]bis-; Bisphenol A diglycidyl ether; Bisphenol A, diglycidyl ether; Bis-[4-(2,3-epoxypropoxy) phenyl]propane; 2,2-bis[4- (2,3-epoxypropoxy)phenyl]propane; Propane, 2,2-bis(p-(2,3-epoxypropoxy) phenyl)-; diglycidyl ether of bisphenol-A; 2,2-bis(4-hydroxyphenyl) propane bis (2,3-epoxypropyl) ether; Araldite;	60 - 80*	1675-54-3	
		(Canada F	Page: 2/1

Version 1.02

Product name AQUATAPOXY A6 THICK GRAY - A

Section 3. Composition/information on ingredients

	DIPHENYLOL PROPANE DIGLYCIDYL ETHER		
titanium dioxide	Titanium oxide; Titanium oxide (TiO2); Cl 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate; glass flakes (CAS RN 65997-17-3): — of a thickness of 0,3 µm or more but not more than 10 µm, and — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282- 10-5); titanium dioxide, other than those of heading 3206 11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206 11 00	7 - 13*	13463-67-7
Palygorskite	Attapulgite; CLAY, ATTAPULGITE; Permagel; PALYGORSKITE ((MG (AL0.5-1FE0-0.5))SI4(OH)O10.4H2O); ATTAPULGITE, ACTIVATED; magnesium aluminum silicate; Palygorskite ([Mg(Al0.5-1Fe0-0.5)]Si4(OH) O10.4H2O); Fibres-Natural Mineral Fibres, Attapulgite; Attapulgitee; Attaclay; Attagel	1 - 5*	12174-11-7

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Section 4. First-aid measures

Most important symptoms/effects, acute and delayed		
Potential acute health effects		
Eye contact Inhalation	 Causes serious eye irritation. No known significant effects or critical hazards. 	
Skin contact Ingestion	 Causes skin irritation. May cause an allergic skin reaction. No known significant effects or critical hazards. 	
Over-exposure signs/symp	<u>toms</u>	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Ingestion	: No specific data.	
Indication of immediate med	ical attention and special treatment needed, if necessary	
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	-
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	Wash hands thoroughly after handling.

Product name AQUATAPOXY A6 THICK GRAY - A

Section 7. Handling and storage

	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
is-[4-(2,3-epoxipropoxi)phenyl]propane titanium dioxide	None. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 10 mg/m ³ . CA British Columbia Provincial (Canada, 8/2023) TWA 8 hours: 10 mg/m ³ . Form: Total dust. TWA 8 hours: 3 mg/m ³ . Form: respirable fraction. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 10 mg/m ³ . CA Quebec Provincial (Canada, 7/2023) TWAEV 8 hours: 10 mg/m ³ . Form: Total dust CA Saskatchewan Provincial (Canada, 7/2013) STEL 15 minutes: 20 mg/m ³ . TWA 8 hours: 10 mg/m ³ .
Palygorskite	CA Quebec Provincial (Canada, 7/2023) [Attapulgite] TWAEV 8 hours: 1 fibers/cm ³ . Form: RESPIRABLE FIBRES (other than respirable asbestos fibres) : Objects, other than respirable asbestos fibres, longer than 5 μ m, having a diameter of less than 3 μ m and a ratio of length to diameter of more than 3 : 1

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
		Canada Page: 6/13

Product name AQUATAPOXY A6 THICK GRAY - A

Section 8. Exposure controls/personal protection

Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles.
Skin protection		
Hand protection	-	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Various
Odor	: Ammoniacal.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 185°C (365°F)
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability	: Not available.

Product name AQUATAPOXY A6 THICK GRAY - A

Section 9. Physical and chemical properties

Lower and upper explosive (flammable) limits	:	Not available.		
Evaporation rate	1	Not available.		
Vapor pressure	:	Not available.		
Vapor density	:	Not available.		
Relative density	:	1.3		
Density(lbs / gal)	:	10.85		
Solubility(ies)		Media	Result	
oolubility(les)		cold water	Soluble	
Partition coefficient: n- octanol/water	:	Not applicable.		
Viscosity	:	Kinematic (room te	nperature): Not available. mperature): Not available. 04°F)): >21 mm²/s (>21 cSt)	
% Solid. (w/w)	:	99.772		

Section 10. Stability and reactivity

	, , , , , , , , , , , , , , , , , , ,
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	 When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materi carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Product name AQUATAPOXY A6 THICK GRAY - A

Section 11. Toxicological information

Product/ingredient name	Resu	Result		Species	Species Sco		Exposure	Observation
bis-[4-(2,3-epoxipropoxi) E phenyl]propane		Eyes - Mild irritant		Rabbit	-		24 hours	-
		- Redness Inctivae	s of the	Rabbit	0.4		24 hours	-
		- Edema		Rabbit	0.5		4 hours	-
		- Erythema		Rabbit	0.8		4 hours	-
	Skin	- Mild irrita	nt	Rabbit	-		4 hours	-
Conclusion/Summary								
Skin				ole on the mixt				
Eyes	: There are no data a							
Respiratory	: The	ere are no o	data availat	ole on the mixt	ure itse	IT.		
<u>Sensitization</u>	1		i			ł		
Product/ingredient name	Route expos		•		Result			
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin		Mouse	Mouse		Sensitizing		
Skin	: The	ere are no o	data availat	ole on the mixt	ure itse	lf.		
Respiratory	: The	ere are no o	data availat	ole on the mixt	ure itse	lf.		
<u>Iutagenicity</u>								
Conclusion/Summary	: The	ere are no o	data availat	ole on the mixt	ure itse	lf.		
Carcinogenicity								
Conclusion/Summary	• The	ere are no i	data availał	ole on the mixt	ure itse	lf		
Classification	• • • • •							
Product/ingredient name		OSHA	IARC	NTP				
bis-[4-(2,3-epoxipropoxi)phe	nyl]	-	3	-				,
propane titanium dioxide			2B					
Palygorskite		-	3	-				
Carcinogen Classification	code:		-					
IARC: 1, 2A, 2B, 3, NTP: Known to be OSHA: + Not listed/not regu	4 e a human	ı carcinogen	; Reasonably	anticipated to be	a huma	n carcino	gen	
Reproductive toxicity								
Conclusion/Summary	: The	ere are no o	data availat	ole on the mixt	ure itse	lf.		
<u>Feratogenicity</u>								
Conclusion/Summary	: The	ere are no o	data availat	ole on the mixt	ure itse	lf.		
Specific target organ toxici					-			
Not available.	<u> </u>		#					
Specific target organ toxici	<u>ty (repe</u>	ated expo	<u>sure)</u>					

Not available.

Target organs

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract.

Section 11. Toxicological information

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	:	There are no data available on the mixture itself. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	ect	<u>8</u>
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Product name AQUATAPOXY A6 THICK GRAY - A

Section 11. Toxicological information

Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(mg/l)	Inhalation (dusts and mists) (mg/l)
bis-[4-(2,3-epoxipropoxi)phenyl]propane	15000	23000	N/A	N/A	N/A

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
titanium dioxide	Chronic NOEC 0.3 mg/l Acute LC50 >100 mg/l Fresh water	Daphnia Daphnia - <i>Daphnia magna</i>	21 days 48 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration landfill should only be considered when recycling is not feasible. This material ar its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty	Disposal methods	and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when
--	------------------	--

Canada Page: 11/13

Product name AQUATAPOXY A6 THICK GRAY - A

Section 13. Disposal considerations

material and runoff and contact with soil, waterways, drains and sewers. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class (es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information TDG : Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail. : This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, IMDG provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. : This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, ΙΑΤΑ provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. **Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Transport in bulk according : Not applicable. to IMO instruments **Proof of classification** : Product classified as per the following sections of the Transportation of Dangerous statement Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Section 15. Regulatory information

National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

Section 16. Other information

	s document for GHS hazard classifications. or determining the PPE code for this material.
Date of issue/Date of revision	3 January 2025
Organization that prepared the SDS	EHS
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
Indicates information that	a changed from providually issued version

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.