SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 3 January 2025

Version 1.01

Date of issue 3 January 2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: 🗛 QUATAPOXY A6 THICK GRAY - A
Product code	: 00471360
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Industrial applications, Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 9% (oral), 14% (dermal), 87.3% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements	

Mexico Page: 1/11

Product name AQUATAPOXY A6 THICK GRAY - A

SECTION 2: Hazards identification

Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P261 - Avoid breathing vapor. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace.
Response	 ▶302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : Emits toxic fumes when heated.

result in classification

See toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 🗚 WUATAPOXY A6 THICK GRAY - A
Other means of identification	: Not applicable.

Ingredient name	%	CAS number
	≥50 - ≤75 ≥10 - ≤20	1675-54-3 13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

: Causes serious eye irritation.

SECTION 4: First aid measures

Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medi	са	l attention and special treatment needed, if necessary
Notes to physician	1	Treat symptomatically. Contact poison treatment specialist immediately if large
		quantities have been ingested or inhaled.
Specific treatments	4	No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

SECTION 5: Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Product name AQUATAPOXY A6 THICK GRAY - A

SECTION 6: Accidental release measures

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

<u>Control parameters</u> <u>Occupational exposure limits</u>

Product name AQUATAPOXY A6 THICK GRAY - A

SECTION 8: Exposure controls/personal protection

Ingredient name				Exposure limits
b ís-[4-(2,3-epoxipropoxi)pheny titanium dioxide	yl]p	ropane		None. NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 10 mg/m ³ .
C = Ceiling Limit IPEL = Internal Permissible Expo	sur	e Limit T	TEL LV WA	 Short term exposure limit Threshold Limit Value Time Weighted Average
Consult local authorities for	· ac			5 5
Recommended monitoring procedures	:			riate monitoring standards. Reference to hods for the determination of hazardous
Appropriate engineering controls	:	Good general ventilation should b contaminants.	be st	ufficient to control worker exposure to airborne
Environmental exposure controls	:	they comply with the requirements	s of engi	ocess equipment should be checked to ensure environmental protection legislation. In some neering modifications to the process e emissions to acceptable levels.
Individual protection measure	<u>es</u>			
Hygiene measures	:	eating, smoking and using the law Appropriate techniques should be Contaminated work clothing shou	/ator e use ild ne sing	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. ot be allowed out of the workplace. Wash . Ensure that eyewash stations and safety location.
Eye/face protection Skin protection	:	Chemical splash goggles.		
Hand protection	:	be worn at all times when handlin this is necessary. Considering the check during use that the gloves a should be noted that the time to b different for different glove manuf	ig ch e pa are s oreal factu	s complying with an approved standard should nemical products if a risk assessment indicates arameters specified by the glove manufacturer, still retaining their protective properties. It kthrough for any glove material may be arers. In the case of mixtures, consisting of the of the gloves cannot be accurately
Gloves	:	butyl rubber		
Body protection	:			e body should be selected based on the task ad and should be approved by a specialist
Other skin protection	:		perf	nal skin protection measures should be formed and the risks involved and should be ing this product.
Respiratory protection	•	hazards of the product and the sa workers are exposed to concentra appropriate, certified respirators.	afe w atior Use	n known or anticipated exposure levels, the vorking limits of the selected respirator. If is above the exposure limit, they must use a properly fitted, air-purifying or air-fed d standard if a risk assessment indicates this is

SECTION 9: Physical and chemical properties

Appearance

Physical state	:	Liquid.	
Color	:	Various	
Odor	:	Ammoniacal.	
Odor threshold	:	Not available.	
Molecular weight	4	Not applicable.	
рН	4	Not available.	
Melting point	4	Not available.	
Boiling point	1	>37.78°C (>100°F)	
Flash point	1	Closed cup: 185°C (365°F)	
Auto-ignition temperature	:	Not available.	
Decomposition temperature	:	Not available.	
Flammability	4	Not available.	
Lower and upper explosive (flammable) limits	1	Not available.	
Evaporation rate	1	Not available.	
Vapor pressure	1	Not available.	
Vapor density	:	Not available.	
Relative density	:	1.3	
Density(lbs / gal)	:	10.85	
		Media Result	
Solubility(ies)	1	cold water Soluble	3
Solubility in water	:	Not available.	
Partition coefficient: n- octanol/water	;	Not applicable.	
Viscosity	1	Øynamic (room temperature): Not Kinematic (room temperature): No	t available.
% Solid. (w/w)	:	Kinematic (40°C (104°F)): >21 mn 99.772	n²/s (>21 cSt)

SECTION 10: Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Product name AQUATAPOXY A6 THICK GRAY - A

SECTION 10: Stability and reactivity

Hazardous decomposition : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ቓís-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
titanium dioxide	LD50 Oral LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral	Rat Rat Rabbit Rat	15000 mg/kg >6.82 mg/l >5000 mg/kg >5000 mg/kg	- 4 hours - -

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
s-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the conjunctivae	Rabbit	0.4	24 hours	-
	Skin - Edema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

- : There are no data available on the mixture itself.
 - There are no data available on the mixture itself.
 There are no data available on the mixture itself.

Respiratory Sensitization

Skin

Eyes

Product/ingredient name	Route of	Species	Result			
	exposure					
øís-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitizing			
Conclusion/Summary						
Skin	: There are no	o data available on the r	nixture itself.			
Respiratory	: There are no	: There are no data available on the mixture itself.				
Mutagenicity						
Conclusion/Summary	: There are no	o data available on the r	nixture itself.			
Carcinogenicity						
Conclusion/Summary	: There are no	o data available on the r	nixture itself.			
Classification						

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	3	-
titanium dioxide	-	2B	-

Carcinogen Classification code:

SECTION 11: Toxicological information

	•
OSHA: +	A, 2B, 3, 4 wn to be a human carcinogen; Reasonably anticipated to be a human carcinogen not regulated: -
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ to	oxicity (single exposure)
Not available.	
Specific target organ to Not available.	oxicity (repeated exposure)
Target organs	: Contains material which may cause damage to the following organs: lungs, upper respiratory tract.
Aspiration hazard	
Not available.	
Information on the likely	routos of oxposuro
-	
Potential acute health e	
Eye contact Inhalation	 Causes serious eye irritation. No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	No known significant effects or critical hazards.
Over-exposure signs/sy	-
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	 Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate	effects and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure	
Potential immediate effects	: There are no data available on the mixture itself.

SECTION 11: Toxicological information

Potential delayed effects	1	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	<u>cts</u>	
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name		(mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Insection of the section of the se	15000	23000	N/A	N/A	N/A

SECTION 12: Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
titanium dioxide	Chronic NOEC 0.3 mg/l Acute LC50 >100 mg/l Fresh water	Daphnia Daphnia - <i>Daphnia magna</i>	21 days 48 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ቓs-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

 Soil/water partition coefficient (Koc)
 : Not available.

 Other adverse effects
 : No known significant effects or critical hazards.

Product name AQUATAPOXY A6 THICK GRAY - A

SECTION 13: Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

	Mexico Classification	IMDG	IATA UN3082		
UN number	UN3082	UN3082			
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl] propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl] propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl] propane)		
Transport hazard class(es)	9	9	9		
Packing group		111			
Environmental hazards	Yes.	Yes.	Yes.		
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.		

Additional information

								Mexico	Page	o· 10/11
Transport in to IMO instru		•	: Not applic	able.						
Special preca	aution	s for user	upright an	t within user's d secure. Ensi of an accident	ure that pers	sons transp	•			
ΙΑΤΑ	:			lated as a dan s meet the ger						kg,
IMDG	:	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.								
Mexico	:	The enviror or ≤5 kg.	nmentally ha	zardous subst	ance mark i	is not require	ed when tr	ansported in	sizes o	of ≤5 L

SECTION 15: Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

SECTION 16: Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of previous issue Organization that prepared the SDS	: 3/22/2023 : EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.