# **SAFETY DATA SHEET**



Date of issue/Date of revision16 January 2025Version 2.05

Section 1. Identification		
Product code	: 000001198035	
Product name	: SIGMAGLIDE 790 C HARDENER	
Other means of identification 00472262	ion	
Product type	: Liquid.	
<u>Relevant identified uses of</u> Product use	<ul> <li>f the substance or mixture and uses advised against</li> <li>Hardener. Professional applications, Used by spraying.</li> </ul>	
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

## Section 2. Hazards identification

Classification of the	: SKIN CORROSION/IRRITATION - Category 1B
substance or mixture	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
	SKIN SENSITISATION - Category 1
	GERM CELL MUTAGENICITY - Category 2
	REPRODUCTIVE TOXICITY - Category 1B
	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2
	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

GHS label elements,	incluaing	precautionary	<u>/ statements</u>
Hazard nictograme		•	<b>A</b>



Product name SIGMAGLIDE 790 C HARDENER

### Section 2. Hazards identification

Hazard statements	:	Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility or the unborn child. May cause damage to organs. (thymus) May cause damage to organs through prolonged or repeated exposure. (immune system) Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.
Response	:	Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	1	Not applicable.
Disposal	:	Not applicable.
Other hazards which do not	:	Causes respiratory tract burns.

result in classification

### Section 3. Composition/information on ingredients

Substance/	mixture
------------	---------

: Mixture

#### **CAS** number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.

#### **Ingredient name** % **CAS number** triacetoxyethylsilane 25 - <50 17689-77-9 methylsilanetriyl triacetate 20 - <25 4253-34-3 oligomeric ethyl- and methylacetoxysilanes 20 - <25 SUB142892 diacetoxydi-tert-butoxysilane 3 - <5 13170-23-5 dibutyltin di(acetate) 3 - <5 1067-33-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Singapore	English (GB)	Page: 2/12
-----------	--------------	------------

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show the container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

Most important symptoms/ef	acute and delayed	
Potential acute health effect		
Eye contact	uses serious eye damage.	
Inhalation	rrosive to the respiratory system.	
Skin contact	uses severe burns. May cause damage to organs following a single expo ntact with skin. May cause an allergic skin reaction.	sure in
Ingestion	y cause burns to mouth, throat and stomach. May cause damage to orga owing a single exposure if swallowed.	ans
Over-exposure signs/sympt		
Eye contact	verse symptoms may include the following: in tering Iness	
Inhalation	verse symptoms may include the following: spiratory tract irritation ughing luced foetal weight rease in foetal deaths eletal malformations	
Skin contact	verse symptoms may include the following: in or irritation Iness stering may occur luced foetal weight rease in foetal deaths eletal malformations	
Ingestion	verse symptoms may include the following: mach pains luced foetal weight rease in foetal deaths eletal malformations	
Indication of immediate medi	ention and special treatment needed, if necessary	
Notes to physician	eat symptomatically. Contact poison treatment specialist immediately if la	rge

Singapore	English (GB)		Page: 3/
		quantities have been ingested or inhaled.	

### Section 4. First aid measures

Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Singapore	English (GB)	Page: 4/12
-----------	--------------	------------

### Section 6. Accidental release measures

#### Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Ingredient name		Exposure limits		
dibutyltin di(acetate)		Workplace Safety and Health Act (Singapore, 2/2006) [Tin, organic compounds] PEL (long term) 8 hours: 0.1 mg/m <sup>3</sup> (Sn). PEL (short term) 15 minutes: 0.2 mg/m <sup>3</sup> (Sn).		
Recommended monitoring procedures		nade to appropriate monitoring standards. Reference to ments for methods for the determination of hazardous required.		
Appropriate engineering controls	vapour or mist, use pro engineering controls to	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.		
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
ndividual protection measure	<u>es</u>			
Hygiene measures	eating, smoking and us Appropriate techniques Contaminated work clo	and face thoroughly after handling chemical products, before sing the lavatory and at the end of the working period. Is should be used to remove potentially contaminated clothing. thing should not be allowed out of the workplace. Wash before reusing. Ensure that eyewash stations and safety be workstation location.		
Eye/face protection	: Chemical splash goggl			
Skin protection				
Hand protection	be worn at all times wh this is necessary. Con check during use that t should be noted that th different for different gl	bervious gloves complying with an approved standard should en handling chemical products if a risk assessment indicates sidering the parameters specified by the glove manufacturer, he gloves are still retaining their protective properties. It e time to breakthrough for any glove material may be ove manufacturers. In the case of mixtures, consisting of e protection time of the gloves cannot be accurately		
Gloves	: nitrile neoprene			
Body protection		uipment for the body should be selected based on the task ne risks involved and should be approved by a specialist oduct.		
Other skin protection	selected based on the	nd any additional skin protection measures should be task being performed and the risks involved and should be at before handling this product.		

Product name SIGMAGLIDE 790 C HARDENER

### Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
------------------------	--

### Section 9. Physical and chemical properties

Appearance			
Physical state	Liquid.		
Colour	Clear.		
Odour	Hydrocarbon. [Strong]		
рН	insoluble in water.		
Boiling point	>37.78°C (>100°F)		
Flash point	Closed cup: 99°C (210.2°F)		
Evaporation rate	Not available.		
Flammability (solid, gas)	liquid		
Vapour pressure	Not available.		
Relative density	1.16		
Solubility(ies)	Media Result		
Solubility(les)	cold water Not soluble		
Auto-ignition temperature	Not available.		
Viscosity	Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)		

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides Formaldehyde. metal oxide/oxides

Singapore	English (GB)	Page: 7/12
-----------	--------------	------------

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
triacetoxyethylsilane	LD50 Oral	Rat	1.462 g/kg	-
methylsilanetriyl triacetate	LD50 Oral	Rat	2060 mg/kg	-
dibutyltin di(acetate)	LD50 Dermal	Rabbit	2318 mg/kg	-
Conclusion/Summary	There are no data available on the	e mixture itself.		
Irritation/Corrosion				
<b>Conclusion/Summary</b>				
Skin :	There are no data available on the	e mixture itself.		
Eyes :	There are no data available on the	e mixture itself.		
Respiratory :	There are no data available on the	e mixture itself.		
Sensitisation				
<b>Conclusion/Summary</b>				
Skin :	There are no data available on the	e mixture itself.		
Respiratory :	There are no data available on the	e mixture itself.		
Mutagenicity				
Conclusion/Summary	There are no data available on the	e mixture itself.		
Carcinogenicity				
Conclusion/Summary	There are no data available on the	e mixture itself.		
Reproductive toxicity				
Conclusion/Summary :	There are no data available on the	e mixture itself.		
<b>Teratogenicity</b>				
Conclusion/Summary :	There are no data available on the	e mixture itself.		
Specific target organ toxici	ty (single exposure)			

#### <u>Specific target organ toxicity (single exposure)</u>

Name		Route of exposure	Target organs
methylsilanetriyl triacetate	Category 3	-	Respiratory tract irritation
dibutyltin di(acetate)	Category 1	oral	thymus

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	-	immune system

#### **Aspiration hazard**

Not available.

#### Information on likely routes : Not available. of exposure

Potential acute health effects

Singapore E	nglish (GB)
-------------	-------------

Section 11. Toxicological information

Eye contact	: Causes serious eye damage.
Inhalation	: Corrosive to the respiratory system.
Skin contact	: Causes severe burns. May cause damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.
Ingestion	: May cause burns to mouth, throat and stomach. May cause damage to organs following a single exposure if swallowed.
Symptoms related to	the physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths

Delayed and immediate effects as well as chronic effects from short a	nd long-term exposure
Short term exposure	

skeletal malformations

<u>onort term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health effe	S	
General	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	No known significant effects or critical hazards.	

### Section 11. Toxicological information

**Mutagenicity** 

: Suspected of causing genetic defects.

**Reproductive toxicity** 

: May damage fertility or the unborn child.

#### Numerical measures of toxicity

#### **Acute toxicity estimates**

Route	ATE value
Oral	2279.64 mg/kg

#### **Other information**

Causes respiratory tract burns. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

### Section 12. Ecological information

t

Product/ingredient name	Result	Species	Exposure
dibutyltin di(acetate)	Acute EC10 3.1 mg/l	Fish	72 hours
	Acute EC50 0.5 mg/l	Algae	72 hours

#### Persistence/degradability

_			
Conc	lucion	/Summon	
CONC	เนรเบท	/Summary	/

: There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
dibutyltin di(acetate)	-	-	Not readily

#### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards. Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	I	II	I
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(dibutyltin di(acetate))	Not applicable.

#### Additional information

UN	: None identified.
IMDG	: The marine pollutant mark is not required when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg.
IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Singapore	English	(GB)
-----------	---------	------

### Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations Montreal Protocol Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

History

### Section 16. Other information

HISTORY	
Date of issue/Date of revision	: 16 January 2025
Date of previous issue	: 1/7/2025
Version	: 2.05
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.