SAFETY DATA SHEET

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Date of issue/Date of revision 20 January 2025

1 02 Vers

Version 1.02	
Section 1. Chemic	al product and company identification

Product code	: 000001189343
Product name	: SIGMAZINC 158/SIGMAGUARD 750 PIGMENT
Product name	: SIGMAZINC 158/SIGMAGUARD 750 PIGMENT
Other means of identification	: 00444811
Product type	: Powder.
Relevant identified uses of	of the substance or mixture and uses advised against
Product use	: Professional applications.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Supplier's details	: PPG Coatings (Kunshan) Co., Ltd 53 Jinyang Road, Lujia Town, 215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857
Emergency telephone number (with hours of operation)	: 00 86 532 83889090

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Emergency overview

Solid.

Various

Characteristic.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

See Section 12 for environmental precautions.

Classification of the	: AQUATIC HAZARD (ACUTE) - Category 1
substance or mixture	AQUATIC HAZARD (LONG-TERM) - Category 1

GHS label elements

China Page: 1/12 ŝ

Section 2. Hazards identification

Hazard pictograms

effects



		•
Signal word	:	Warning
Hazard statements	:	Very toxic to aquatic life.
		Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Avoid release to the environment.
Response	:	Collect spillage.
Suitable extinguishing	:	Use dry chemical powder.
media		
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	:	May form explosible dust-air mixture if dispersed.
Health hazards	:	No known significant effects or critical hazards.
Symptoms related to the phy	ysic	al, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following:
		irritation
		redness
Inhalation	1	Adverse symptoms may include the following: respiratory tract irritation
		coughing
Skin contact	:	No specific data.
Ingestion		No specific data.
-		
Delayed and immediate effect	<u>cts</u>	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate	:	Not available.
offecto		

Environmental hazards	: Very toxic to aquatic life	. Very toxic to aquatic life with long lasting effects.
		. Very toxic to aquatic file with long lasting chects.

Other hazards which do not	: May form explosible dust-air mixture if dispersed.
result in classification	

Potential delayed effects : Not available.

Section 3. Composition/information on ingredients

Substance/mixtur	e
Other means of	
identification	

: Mixture : 00444811

CAS number/other identifiers

CAS number : Not applicable.		
Ingredient name	%	CAS number
Źnc dust zinc oxide lead powder	70 - 100 0.1 - <1 <0.1	7440-66-6 1314-13-2 7439-92-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8. SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Eve contect	. Expedite to airborne concentrations above statutery or recommended expedit
Eye contact	 Exposure to airborne concentrations above statutory or recommended exposur limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposur limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs</u>	/symptoms
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

Date of issue 20 January 2025 Version 1.02

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Section 4. First aid measures

Indication of immediate med	ical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures **Extinguishing media** Suitable extinguishing : Use dry chemical powder. media Unsuitable extinguishing : Avoid high pressure media which could cause the formation of a potentially media explosible dust-air mixture. Specific hazards arising : May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must from the chemical be contained and prevented from being discharged to any waterway, sewer or drain. Hazardous thermal : Decomposition products may include the following materials: metal oxide/oxides decomposition products **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without for fire-fighters suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. **Special protective** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure equipment for fire-fighters mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Section 6. Accidental release measures

Small spill	equipment	tainers from spill area. Use spark-proof tools and explosion-proof t. Vacuum or sweep up material and place in a designated, labeled waste Dispose of via a licensed waste disposal contractor.
Large spill	equipment courses, b a designat wind dispe	tainers from spill area. Use spark-proof tools and explosion-proof t. Approach release from upwind. Prevent entry into sewers, water basements or confined areas. Vacuum or sweep up material and place in ted, labeled waste container. Avoid creating dusty conditions and prevent ersal. Dispose of via a licensed waste disposal contractor. Note: see for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Zínc oxide	GBZ 2.1 (China, 11/2022)
	PC-TWA 8 hours: 3 mg/m ³ .
	PC-STEL 15 minutes: 5 mg/m ³ .
lead powder	GBZ 2.1 (China, 11/2022)
	PC-TWA 8 hours: 0.05 mg/m ³ (as Pb).
	Form: dust.
	PC-TWA 8 hours: 0.03 mg/m ³ (as Pb).
	Form: fume.

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Section 8. Exposure controls/personal protection

-		· · ·
Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	:	Safety glasses with side shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state	1	Solid.	
		Powder.	
Color	4	Various	
Odor	1	Characteristic.	
Flash point	1	Closed cup: Not applicable	e.
Lower and upper explosive (flammable) limits	:	Not applicable.	
Relative density	1	7.14	
Solubility(ies)		Media	Result
Solubility(les)	1	cold water	Not soluble
Viscosity	:	Dynamic (room temperatu Kinematic (room temperat	

Section 10. Stability and reactivity				
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
Chemical stability	: The product is stable.			
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.			
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.			
Hazardous decomposition products	: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides			

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
zinc dust	LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Potential acute nealt	n effects
Eye contact	 Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	 Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to	the physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following:

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

coughing

Short term exposure	
Potential immediate	: Not available.
effects	

Date of issue 20 January 2025 Version 1.02

Section 11. Toxicological information

Potential delayed effects	1	Not available.
<u>Long term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
Potential chronic health eff	ect	<u>s</u>
General	:	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	() /	(vapors)	Inhalation (dusts and mists) (mg/l)
zinc oxide	N/A	2500	N/A	N/A	N/A

Other information

Sanding and grinding dusts may be harmful if inhaled.

Section 12. Ecological information

2

Toxicity

Product/ingredient name	Result	Species	Exposure
zinc dust	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 354 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Chronic EC10 6.3 µg/l	Daphnia - <i>Daphnia magna -</i> Neonate	21 days
	Chronic LC10 185 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	30 days
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - <i>Daphnia magna -</i> Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

Persistence/degradability

Not available.

Bioaccumulative potential

Not available.

Date of issue 20 January 2025 Version 1.02

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	UN3077	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	Environmentally hazardous substance, solid, n.o.s.
	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))
Transport hazard class(es)	9	9	9	9
Packing group	III	Ш	111	111
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(Zinc powder - zinc dust (stabilized))	Not applicable.

Additional information

CN	: None identified.
UN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Product code 000001189343

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Section 14. Transport information

Special precautions for user	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according	Not applicable.

to IMO instruments

Section 15. Regulatory information

China inventory (IECSC)	: All components are listed or exempted.
References	 Production Safety Law of the People's Republic of China Code of Occupational Disease Prevention of the People's Republic of China Environmental Protection Law of the People's Republic of China Fire Control Law of the People's Republic of China Regulations on the Control over Safety of Dangerous Chemicals Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1) General rule for classification and hazard communication of chemicals (GB13690) Safety data sheet for chemical products - Content and order of sections (GB/ T16483) Guidance on the compilation of safety data sheet for chemical products (GB/ T17519) General rule for preparation of precautionary label for chemicals (GB15258) Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 20 January 2025
Date of previous issue	: 9/29/2024
Version	: 1.02
	EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	UN = United Nations

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Section 16. Other information

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.