

SAFETY DATA SHEET

Date of issue/Date of revision

: 21 January 2025

Version

: 1.06



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMACOVER 350 HARDENER

Product code : 000001172489

Other means of identification

00220294; 00272755; 00480544

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Hardener.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

National advisory body/Poison Centre

National Poison Information Centre at Beaumont Hospital. Tel: +353 1 8092566, email: npicdublin@beaumont.ie

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Corr. 1C, H314

Eye Dam. 1, H318

Skin Sens. 1, H317

STOT SE 3, H335

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.
See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Flammable liquid and vapour. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. Toxic to aquatic life with long lasting effects.
<u>Precautionary statements</u>		
Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.
Response	:	Collect spillage.
Storage	:	Store in a well-ventilated place. Keep container tightly closed.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P210, P273, P391, P403 + P233, P501
Hazardous ingredients	:	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine; Amides, from C18-unsatd. fatty acid dimers, tall-oil fatty acids and triethylenetetramine, reaction products with bisphenol A-epichlorohydrin polymer; xylene; 2-methylpropan-1-ol; benzyl alcohol; 2,4,6-tris(dimethylaminomethyl)phenol and 3,6-diazaoctanethylenediamin
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

Code : 000001172489	Date of issue/Date of revision : 21 January 2025
SIGMACOVER 350 HARDENER	
SECTION 2: Hazards identification	

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	REACH #: 01-2119972320-44 EC: 500-191-5 CAS: 68082-29-1	≥25 - ≤50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
Amides, from C18-unsatd. fatty acid dimers, tall-oil fatty acids and triethylenetetramine, reaction products with bisphenol A-epichlorohydrin polymer	CAS: 68953-09-3	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≥10 - <20	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤25	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/kg ATE [Dermal] = 1280 mg/kg	[1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314	ATE [Oral] = 1716 mg/kg ATE [Dermal] = 1465	[1]

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 3: Composition/information on ingredients

			Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	mg/kg	
--	--	--	--	-------	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type
[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit
Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact : Causes serious eye damage.
- Inhalation : May cause respiratory irritation.
- Skin contact : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion : Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

- Eye contact : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 4: First aid measures

Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds

5.3 Advice for firefighters

Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
-----------------------------	--

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 6: Accidental release measures

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- 6.3 Methods and material for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)
See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters
Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	NAOSH (Ireland, 5/2021) [xylene] Absorbed through skin. OELV 8 hours: 50 ppm. OELV 8 hours: 221 mg/m³. OELV 15 minutes: 100 ppm. OELV 15 minutes: 442 mg/m³.
2-methylpropan-1-ol	NAOSH (Ireland, 5/2021) OELV 8 hours: 50 ppm. OELV 8 hours: 150 mg/m³. OELV 15 minutes: 75 ppm. OELV 15 minutes: 225 mg/m³.
ethylbenzene	NAOSH (Ireland, 5/2021) Absorbed through skin. OELV 8 hours: 100 ppm. OELV 8 hours: 442 mg/m³. OELV 15 minutes: 200 ppm. OELV 15 minutes: 884 mg/m³.

Biological exposure indices

Product/ingredient name	Exposure indices
xylene	NAOSH (Ireland, 1/2011) [Xylene] BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.
ethylbenzene	NAOSH (Ireland, 1/2011) BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air]. Sampling time: not critical. BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 8: Exposure controls/personal protection	
	should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	DNEL	Long term Oral	97.2 µg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	97.2 µg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.169 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0.272 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.952 mg/m³	Workers	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m³	Workers	Local
	DNEL	Long term Inhalation	221 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m³	General population	Local
	DNEL	Short term Inhalation	260 mg/m³	General population	Systemic
xylene	DNEL	Short term Inhalation	442 mg/m³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m³	Workers	Systemic
2-methylpropan-1-ol	DNEL	Long term Inhalation	55 mg/m³	General population	Local
	DNEL	Long term Inhalation	310 mg/m³	Workers	Local
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5.4 mg/m³	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	22 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m³	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m³	Workers	Systemic
2,4,6-tris (dimethylaminomethyl)phenol	DNEL	Long term Oral	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.13 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	0.13 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 8: Exposure controls/personal protection

ethylbenzene	DNEL	Long term Inhalation	0.53 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	0.6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	2.1 mg/m³	Workers	Systemic
	DMEL	Long term Inhalation	442 mg/m³	Workers	Local
	DMEL	Short term Inhalation	884 mg/m³	Workers	Systemic
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
3,6-diazaoctanethylenediamin	DNEL	Long term Inhalation	15 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	293 mg/m³	Workers	Local
	DNEL	Long term Dermal	28 µg/cm²	Workers	Local
	DNEL	Long term Dermal	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.29 mg/m³	General population	Systemic
	DNEL	Long term Oral	0.41 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.43 mg/cm²	General population	Local
	DNEL	Long term Dermal	0.57 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	1 mg/cm²	General population	Local
	DNEL	Long term Inhalation	1 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	8 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1600 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	5380 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	-	Fresh water	0.043 mg/l	Assessment Factors
	-	Marine water	0 mg/l	Assessment Factors
	-	Sewage Treatment Plant	3.84 mg/l	Assessment Factors
	-	Fresh water sediment	434.02 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	43.4 mg/kg dwt	Equilibrium Partitioning
	-	Soil	86.78 mg/kg dwt	Equilibrium Partitioning
	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
xylene	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
	-	Fresh water	0.4 mg/l	Assessment Factors
	-	Marine water	0.04 mg/l	Assessment Factors
	-	Sewage Treatment Plant	10 mg/l	Assessment Factors
2-methylpropan-1-ol	-	Fresh water sediment	1.56 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.156 mg/kg dwt	-
	-	Soil	0.076 mg/kg dwt	Equilibrium Partitioning
	-	Fresh water	0.1 mg/l	Assessment Factors
	-	Marine water	0.01 mg/l	Assessment Factors
ethylbenzene	-	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	-	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	-	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
	-	Secondary Poisoning	20 mg/kg	-

8.2 Exposure controls

Code : 000001172489
SIGMACOVER 350 HARDENER

Date of issue/Date of revision

: 21 January 2025

SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles and face shield. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : nitrile neoprene
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation.

Product/ingredient name	Result	Species	Dose	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
xylene	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
2-methylpropan-1-ol	LC50 Inhalation Vapour	Rat	24.6 mg/l	4 hours
	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
ethylbenzene	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
	LD50 Dermal	Rabbit	1465 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Oral	Rat	1716 mg/kg	-

Route	ATE value
Oral	5970.26 mg/kg
Dermal	7198.1 mg/kg
Inhalation (vapours)	69.76 mg/l

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 11: Toxicological information

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
xylene	Skin - Irritant	Human	-	-	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : Causes severe burns.

Eyes : Causes serious eye damage.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitising
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin : May cause an allergic skin reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects

Conclusion/Summary : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Code : 000001172489	Date of issue/Date of revision : 21 January 2025
SIGMACOVER 350 HARDENER	

SECTION 11: Toxicological information

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation	: May cause respiratory irritation.
Ingestion	: Corrosive to the digestive tract. Causes burns.
Skin contact	: Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.
Eye contact	: Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.

Long term exposure

Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.

Potential chronic health effects

General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 11: Toxicological information

visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours
2-methylpropan-1-ol	Acute EC50 1100 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Ceriodaphnia dubia	-

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,4,6-tris(dimethylaminomethyl)phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	4 % - Not readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	-	-	Not readily
xylene	-	-	Readily
benzyl alcohol	-	-	Readily
2,4,6-tris(dimethylaminomethyl)phenol	-	-	Not readily
ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
2-methylpropan-1-ol	1	-	Low
benzyl alcohol	0.87	-	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low
ethylbenzene	3.6	79.43	Low
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste :

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 13: Disposal considerations

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
---------------------	---

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3469	UN3469	UN3469	UN3469
14.2 UN proper shipping name	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE
14.3 Transport hazard class(es)	3 (8)	3 (8)	3 (8)	3 (8)
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Polyamide)	Not applicable.

Additional information

ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (D/E)
ADN	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user	: Transport within user’s premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
-----------------------------------	---

14.7 Maritime transport in bulk according to IMO instruments	: Not applicable.
--	-------------------

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
SIGMACOVER 350 HARDENER	3

Labelling : Not applicable.

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E2

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- IMDG = International Maritime Dangerous Goods
- IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225 H226 H302 H304 H312 H314 H315 H317 H318 H319 H332 H335 H336 H373 H411 H412	Highly flammable liquid and vapour. Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
--	---

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A Skin Sens. 1B STOT RE 2 STOT SE 3	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
--	--

History

Date of issue/ Date of revision	: 21 January 2025
Date of previous issue	: 7 November 2024
Prepared by	: EHS
Version	: 1.06

Disclaimer

Code	: 000001172489	Date of issue/Date of revision	: 21 January 2025
SIGMACOVER 350 HARDENER			

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.