

# SAFETY DATA SHEET

Date of issue/Date of revision

: 24 January 2025

Version

: 15



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMASHIELD 880 BASE GREY 5177

**Product code** : 00323078

**Other means of identification**

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person  
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Numéro de téléphone d'appel d'urgence : 01 45 42 59 59 (Association ORFILA, organisme agréé prévu au 4ème alinéa de l'article L231-7 du code du travail)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Muta. 2, H341

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 2: Hazards identification

2.2 Label elements

|                                                                                                                                    |   |                                                                                                                                                                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms                                                                                                                  | : |                                                                                                                                                                                                   |
| Signal word                                                                                                                        | : | Warning                                                                                                                                                                                                                                                                            |
| Hazard statements                                                                                                                  | : | Flammable liquid and vapour.<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>Suspected of causing genetic defects.<br>Harmful to aquatic life with long lasting effects.                                                   |
| <u>Precautionary statements</u>                                                                                                    |   |                                                                                                                                                                                                                                                                                    |
| Prevention                                                                                                                         | : | Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. |
| Response                                                                                                                           | : | IF exposed or concerned: Get medical advice or attention.                                                                                                                                                                                                                          |
| Storage                                                                                                                            | : | Not applicable.                                                                                                                                                                                                                                                                    |
| Disposal                                                                                                                           | : | Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P202, P280, P210, P273, P308 + P313, P501                                                                                                                     |
| Hazardous ingredients                                                                                                              | : | <input checked="" type="checkbox"/> Bis-[4-(2,3-epoxipropoxy)phenyl]propane; Epoxy Resin (700<MW<=1100); Phenol, methylstyrenated; 2,3-epoxypropyl neodecanoate and 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene                                                           |
| Supplemental label elements                                                                                                        | : | <input checked="" type="checkbox"/> Contains epoxy constituents. May produce an allergic reaction.                                                                                                                                                                                 |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable.                                                                                                                                                                                                                                                                    |
| <u>Special packaging requirements</u>                                                                                              |   |                                                                                                                                                                                                                                                                                    |
| Containers to be fitted with child-resistant fastenings                                                                            | : | Not applicable.                                                                                                                                                                                                                                                                    |
| Tactile warning of danger                                                                                                          | : | Not applicable.                                                                                                                                                                                                                                                                    |

2.3 Other hazards

|                                                     |   |                                                                                                                                     |
|-----------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------|
| Product meets the criteria for PBT or vPvB          | : | <input checked="" type="checkbox"/> This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2. |
| Other hazards which do not result in classification | : | Prolonged or repeated contact may dry skin and cause irritation.                                                                    |

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                              | Identifiers                                                                            | % by weight  | Classification                                                                                                                                                                 | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|------------------------------------------------------|----------------------------------------------------------------------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------|
| Bis-[4-(2,3-epoxipropoxy)phenyl]propane              | REACH #:<br>01-2119456619-26<br>EC: 216-823-5<br>CAS: 1675-54-3<br>Index: 603-073-00-2 | ≥10 - ≤22    | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                                                                                     | Skin Irrit. 2, H315: C ≥ 5%<br>Eye Irrit. 2, H319: C ≥ 5%         | [1]     |
| xylene                                               | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7                        | ≥5.0 - ≤10   | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | ATE [Dermal] = 1700 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| Epoxy Resin (700<MW ≤1100)                           | CAS: 25036-25-3                                                                        | ≥1.0 - ≤5.0  | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317                                                                                                                | -                                                                 | [1]     |
| Phenol, methylstyrenated                             | REACH #:<br>01-2119555274-38<br>EC: 270-966-8<br>CAS: 68512-30-1                       | ≥1.0 - ≤5.0  | Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412                                                                                                           | -                                                                 | [1] [3] |
| 2-methylpropan-1-ol                                  | REACH #:<br>01-2119484609-23<br>EC: 201-148-0<br>CAS: 78-83-1<br>Index: 603-108-00-1   | ≥1.0 - <3.0  | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336                                                                            | -                                                                 | [1] [2] |
| 2,3-epoxypropyl neodecanoate                         | REACH #:<br>01-2119431597-33<br>EC: 247-979-2<br>CAS: 26761-45-5                       | ≥0.10 - ≤2.1 | Skin Sens. 1, H317<br>Muta. 2, H341<br>Aquatic Chronic 2, H411                                                                                                                 | -                                                                 | [1]     |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | REACH #:<br>01-2119962189-26<br>CAS: 911674-82-3<br>Index: 616-198-00-2                | <1.0         | Skin Sens. 1, H317<br>Aquatic Chronic 4, H413<br><br>See Section 16 for the full text of the H statements declared above.                                                      | -                                                                 | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard  
[2] Substance with a workplace exposure limit  
[3] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  
Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Code : 00323078

Date of issue/Date of revision

: 24 January 2025

SIGMASHIELD 880 BASE GREY 5177

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : ☒ Decomposition products may include the following materials:  
carbon oxides  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

**SECTION 6: Accidental release measures**

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Large spill                     | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information.<br>See Section 8 for information on appropriate personal protective equipment.<br>See Section 13 for additional waste treatment information.                                                                                                                                                                                                                                                                                                                                                                                                                                      |

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective measures                    | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

**7.2 Conditions for safe storage, including any incompatibilities**

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**7.3 Specific end use(s)**

See Section 1.2 for Identified uses.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name                                                                | Exposure limit values                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  ylene | <b>Ministry of Labor (France, 9/2023) [xylènes, isomères mixtes, purs]</b> Absorbed through skin.<br>STEL 15 minutes: 442 mg/m³.<br>STEL 15 minutes: 100 ppm.<br>TWA 8 hours: 221 mg/m³.<br>TWA 8 hours: 50 ppm. |
| 2-methylpropan-1-ol                                                                    | <b>Ministry of Labor (France, 9/2023)</b><br>TWA 8 hours: 50 ppm.<br>TWA 8 hours: 150 mg/m³.                                                                                                                     |

**Recommended monitoring procedures** :  Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

| Product/ingredient name                                                                                                   | Type | Exposure              | Value              | Population                     | Effects  |
|---------------------------------------------------------------------------------------------------------------------------|------|-----------------------|--------------------|--------------------------------|----------|
|  is-[4-(2,3-epoxipropoxy)phenyl]propane | DNEL | Long term Inhalation  | 12.25 mg/m³        | Workers                        | Systemic |
|                                                                                                                           | DNEL | Short term Inhalation | 12.25 mg/m³        | Workers                        | Systemic |
|                                                                                                                           | DNEL | Long term Dermal      | 8.33 mg/kg bw/day  | Workers                        | Systemic |
|                                                                                                                           | DNEL | Short term Dermal     | 8.33 mg/kg bw/day  | Workers                        | Systemic |
|                                                                                                                           | DNEL | Long term Dermal      | 3.571 mg/kg bw/day | General population [Consumers] | Systemic |
|                                                                                                                           | DNEL | Short term Dermal     | 3.571 mg/kg bw/day | General population [Consumers] | Systemic |
|                                                                                                                           | DNEL | Long term Oral        | 0.75 mg/kg bw/day  | General population [Consumers] | Systemic |
|                                                                                                                           | DNEL | Short term Oral       | 0.75 mg/kg bw/day  | General population [Consumers] | Systemic |
|                                                                                                                           | DNEL | Long term Dermal      | 89.3 µg/kg bw/day  | General population             | Systemic |
|                                                                                                                           | DNEL | Long term Oral        | 0.5 mg/kg bw/day   | General population             | Systemic |
|                                                                                                                           | DNEL | Long term Dermal      | 0.75 mg/kg bw/day  | Workers                        | Systemic |
|                                                                                                                           | DNEL | Long term Inhalation  | 0.87 mg/m³         | General population             | Systemic |
|                                                                                                                           | DNEL | Long term Inhalation  | 4.93 mg/m³         | Workers                        | Systemic |
|                                                                                                                           | DNEL | Long term Oral        | 5 mg/kg bw/day     | General population             | Systemic |
|                                                                                                                           | DNEL | Long term Inhalation  | 65.3 mg/m³         | General population             | Local    |
|                                                                                                                           | DNEL | Long term Inhalation  | 65.3 mg/m³         | General population             | Systemic |
|                                                                                                                           | DNEL | Long term Dermal      | 125 mg/kg bw/day   | General population             | Systemic |
|                                                                                                                           | DNEL | Long term Dermal      | 212 mg/kg bw/day   | Workers                        | Systemic |
|                                                                                                                           | DNEL | Long term Inhalation  | 221 mg/m³          | Workers                        | Local    |
| ylene                                                                                                                     |      |                       |                    |                                |          |

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 8: Exposure controls/personal protection

|                              |      |                       |                   |                    |          |
|------------------------------|------|-----------------------|-------------------|--------------------|----------|
| Phenol, methylstyrenated     | DNEL | Long term Inhalation  | 221 mg/m³         | Workers            | Systemic |
|                              | DNEL | Short term Inhalation | 260 mg/m³         | General population | Local    |
|                              | DNEL | Short term Inhalation | 260 mg/m³         | General population | Systemic |
|                              | DNEL | Short term Inhalation | 442 mg/m³         | Workers            | Local    |
|                              | DNEL | Short term Inhalation | 442 mg/m³         | Workers            | Systemic |
|                              | DNEL | Long term Oral        | 0.2 mg/kg bw/day  | General population | Systemic |
|                              | DNEL | Long term Inhalation  | 0.348 mg/m³       | General population | Systemic |
|                              | DNEL | Long term Inhalation  | 1.41 mg/m³        | Workers            | Systemic |
|                              | DNEL | Long term Dermal      | 1.67 mg/kg bw/day | General population | Systemic |
|                              | DNEL | Long term Dermal      | 3.5 mg/kg bw/day  | Workers            | Systemic |
| 2-methylpropan-1-ol          | DNEL | Long term Inhalation  | 55 mg/m³          | General population | Local    |
|                              | DNEL | Long term Inhalation  | 310 mg/m³         | Workers            | Local    |
| 2,3-epoxypropyl neodecanoate | DNEL | Long term Dermal      | 2.5 mg/kg bw/day  | General population | Systemic |
|                              | DNEL | Long term Inhalation  | 4 mg/m³           | General population | Systemic |
|                              | DNEL | Long term Dermal      | 4.2 mg/kg bw/day  | Workers            | Systemic |
|                              | DNEL | Long term Inhalation  | 5.88 mg/m³        | Workers            | Systemic |
|                              | DNEL | Long term Oral        | 2.5 mg/kg bw/day  | General population | Systemic |

PNECs

| Product/ingredient name                  | Type | Compartment Detail     | Value           | Method Detail            |
|------------------------------------------|------|------------------------|-----------------|--------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl] propane | -    | Fresh water            | 0.006 mg/l      | Assessment Factors       |
|                                          | -    | Marine water           | 0.001 mg/l      | Assessment Factors       |
|                                          | -    | Fresh water sediment   | 0.996 mg/kg dwt | Equilibrium Partitioning |
|                                          | -    | Marine water sediment  | 0.1 mg/kg dwt   | Equilibrium Partitioning |
|                                          | -    | Soil                   | 0.196 mg/kg dwt | Equilibrium Partitioning |
|                                          | -    | Sewage Treatment Plant | 10 mg/l         | Assessment Factors       |
|                                          | -    | Secondary Poisoning    | 11 mg/kg        | Assessment Factors       |
|                                          | -    | Fresh water            | 0.327 mg/l      | -                        |
|                                          | -    | Marine water           | 0.327 mg/l      | -                        |
|                                          | -    | Sewage Treatment Plant | 6.58 mg/l       | -                        |
| xylene                                   | -    | Fresh water            | 12.46 mg/kg dwt | -                        |
|                                          | -    | Marine water sediment  | 12.46 mg/kg dwt | -                        |
|                                          | -    | Soil                   | 2.31 mg/kg      | -                        |
|                                          | -    | Fresh water            | 0.4 mg/l        | Assessment Factors       |
|                                          | -    | Marine water           | 0.04 mg/l       | Assessment Factors       |
|                                          | -    | Sewage Treatment Plant | 10 mg/l         | Assessment Factors       |
|                                          | -    | Fresh water sediment   | 1.56 mg/kg dwt  | Equilibrium Partitioning |
|                                          | -    | Marine water sediment  | 0.156 mg/kg dwt | -                        |
|                                          | -    | Soil                   | 0.076 mg/kg dwt | Equilibrium Partitioning |
|                                          | -    |                        |                 |                          |
| 2-methylpropan-1-ol                      | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |
|                                          | -    |                        |                 |                          |

8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 8: Exposure controls/personal protection

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye/face protection             | : Chemical splash goggles. Use eye protection according to EN 166.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Skin protection                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Hand protection                 | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |
| Gloves                          | : butyl rubber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Body protection                 | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Other skin protection           | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Respiratory protection          | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

|                                                          |                                                                      |
|----------------------------------------------------------|----------------------------------------------------------------------|
| Appearance                                               |                                                                      |
| Physical state                                           | : Liquid.                                                            |
| Colour                                                   | : Various                                                            |
| Odour                                                    | : Aromatic.                                                          |
| Melting point/freezing point                             | : Not determined.                                                    |
| Boiling point or initial boiling point and boiling range | : >37.78°C                                                           |
| Flammability                                             | : Not determined. There are no data available on the mixture itself. |
| Lower and upper explosion limit                          | : Not available.                                                     |

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 9: Physical and chemical properties

Flash point

Auto-ignition temperature

Decomposition temperature

pH

Viscosity

Viscosity

Solubility

Partition coefficient n-octanol/ water (log Pow)

Vapour pressure

Relative density

Particle characteristics

Median particle size

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties

Oxidising properties

No additional information.

: Closed cup: 37°C

:

| Ingredient name              | °C  | °F    | Method |
|------------------------------|-----|-------|--------|
| 2,3-epoxypropyl neodecanoate | 276 | 528.8 |        |

: Stable under recommended storage and handling conditions (see Section 7).

: Not applicable. insoluble in water.

: 

Dynamic (room temperature): Not available.

Kinematic (room temperature): >400 mm²/s

Kinematic (40°C): >21 mm²/s

: 60 - 100 s (ISO 6mm)

:

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

: Not applicable.

: 

| Ingredient name     | Vapour Pressure at 20°C |      |                | Vapour pressure at 50°C |     |        |
|---------------------|-------------------------|------|----------------|-------------------------|-----|--------|
|                     | mm Hg                   | kPa  | Method         | mm Hg                   | kPa | Method |
| 2-methylpropan-1-ol | <12.00102               | <1.6 | DIN EN 13016-2 |                         |     |        |

: 1.7

: Not applicable.

<

SECTION 10: Stability and reactivity

|                                         |                                                                                                                                                                              |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.                                                                                 |
| 10.2 Chemical stability                 | : The product is stable.                                                                                                                                                     |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                                                                                            |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8.                                |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions:<br>oxidising agents, strong alkalis, strong acids.                                          |
| 10.6 Hazardous decomposition products   | : <input checked="" type="checkbox"/> Depending on conditions, decomposition products may include the following materials:<br>carbon oxides sulfur oxides metal oxide/oxides |

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- ☒ Causes serious eye irritation.
- ☐ Causes skin irritation.
- ☐ May cause an allergic skin reaction.
- ☐ Suspected of causing genetic defects.

Acute toxicity

| Product/ingredient name                                                     | Result                          | Species | Dose        | Exposure |
|-----------------------------------------------------------------------------|---------------------------------|---------|-------------|----------|
| <input checked="" type="checkbox"/> Bis-[4-(2,3-epoxipropoxi)phenyl]propane | LD50 Dermal                     | Rabbit  | 23000 mg/kg | -        |
|                                                                             | LD50 Oral                       | Rat     | 15000 mg/kg | -        |
| xylene                                                                      | LD50 Dermal                     | Rabbit  | 1.7 g/kg    | -        |
|                                                                             | LD50 Oral                       | Rat     | 4.3 g/kg    | -        |
| Epoxy Resin (700<MW<=1100)                                                  | LD50 Dermal                     | Rat     | >2000 mg/kg | -        |
|                                                                             | LD50 Oral                       | Rat     | >2000 mg/kg | -        |
| Phenol, methylstyrenated                                                    | LD50 Dermal                     | Rabbit  | >2000 mg/kg | -        |
|                                                                             | LD50 Oral                       | Rat     | >2000 mg/kg | -        |
| 2-methylpropan-1-ol                                                         | LC50 Inhalation Vapour          | Rat     | 24.6 mg/l   | 4 hours  |
|                                                                             | LD50 Dermal                     | Rabbit  | 2460 mg/kg  | -        |
| 2,3-epoxypropyl neodecanoate                                                | LD50 Oral                       | Rat     | 2830 mg/kg  | -        |
|                                                                             | LD50 Dermal                     | Rat     | 3800 mg/kg  | -        |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene                        | LD50 Oral                       | Rat     | 9.6 g/kg    | -        |
|                                                                             | LC50 Inhalation Dusts and mists | Rat     | >5.08 mg/l  | 4 hours  |

Acute toxicity estimates

| Route                                      | ATE value      |
|--------------------------------------------|----------------|
| <input checked="" type="checkbox"/> Dermal | 31673.58 mg/kg |
| Inhalation (vapours)                       | 204.95 mg/l    |

Conclusion/Summary : ☒ Based on available data, the classification criteria are not met.

Irritation/Corrosion

| Product/ingredient name                                                     | Result                             | Species | Score | Exposure        | Observation |
|-----------------------------------------------------------------------------|------------------------------------|---------|-------|-----------------|-------------|
| <input checked="" type="checkbox"/> Bis-[4-(2,3-epoxipropoxi)phenyl]propane | Eyes - Mild irritant               | Rabbit  | -     | 24 hours        | -           |
|                                                                             | Eyes - Redness of the conjunctivae | Rabbit  | 0.4   | 24 hours        | -           |
| xylene                                                                      | Skin - Oedema                      | Rabbit  | 0.5   | 4 hours         | -           |
|                                                                             | Skin - Erythema/Eschar             | Rabbit  | 0.8   | 4 hours         | -           |
|                                                                             | Skin - Mild irritant               | Rabbit  | -     | 4 hours         | -           |
|                                                                             | Skin - Moderate irritant           | Rabbit  | -     | 24 hours 500 mg | -           |

Conclusion/Summary

- Skin** : ☒ Causes skin irritation.
- Eyes** : ☒ Causes serious eye irritation.
- Respiratory** : ☒ Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

| Product/ingredient name                                                     | Route of exposure | Species | Result      |
|-----------------------------------------------------------------------------|-------------------|---------|-------------|
| <input checked="" type="checkbox"/> Bis-[4-(2,3-epoxipropoxi)phenyl]propane | skin              | Mouse   | Sensitising |

Conclusion/Summary

- Skin** : ☒ May cause an allergic skin reaction.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 11: Toxicological information

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| xylene                  | Category 3 | -                 | Respiratory tract irritation |
| 2-methylpropan-1-ol     | Category 3 | -                 | Respiratory tract irritation |
|                         | Category 3 |                   | Narcotic effects             |

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

Eye contact : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 11: Toxicological information

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

| Product/ingredient name                              | Result                          | Species                           | Exposure |
|------------------------------------------------------|---------------------------------|-----------------------------------|----------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane              | Acute LC50 1.8 mg/l Fresh water | Daphnia - <i>daphnia magna</i>    | 48 hours |
|                                                      | Chronic NOEC 0.3 mg/l           | Daphnia                           | 21 days  |
|                                                      | Acute EC50 1100 mg/l            | Daphnia                           | 48 hours |
|                                                      | Acute EC50 3.5 mg/l             | Algae                             | 96 hours |
|                                                      | Acute EC50 4.8 mg/l             | Daphnia - <i>Daphnia magna</i>    | 48 hours |
| 2-methylpropan-1-ol                                  | Acute LC50 9.6 mg/l             | Fish - <i>Oncorhynchus mykiss</i> | 96 hours |
| 2,3-epoxypropyl neodecanoate                         | Acute LC50 >100 mg/l            | Fish                              | 96 hours |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene |                                 |                                   |          |

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Based on available data, the classification criteria are not met.

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 12: Ecological information

| Product/ingredient name                 | Aquatic half-life | Photolysis | Biodegradability |
|-----------------------------------------|-------------------|------------|------------------|
| Bis-[4-(2,3-epoxipropoxy)phenyl]propane | -                 | -          | Not readily      |
| xylene                                  | -                 | -          | Readily          |
| 2,3-epoxypropyl neodecanoate            | -                 | -          | Not readily      |

12.3 Bioaccumulative potential

| Product/ingredient name      | LogP <sub>ow</sub> | BCF         | Potential |
|------------------------------|--------------------|-------------|-----------|
| Xylene                       | 3.12               | 7.4 to 18.5 | Low       |
| Phenol, methylstyrenated     | 3.627              | -           | Low       |
| 2-methylpropan-1-ol          | 1                  | -           | Low       |
| 2,3-epoxypropyl neodecanoate | 4.4                | -           | High      |

12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

| Product/ingredient name                              | PBT | P   | B   | T  | vPvB             | vP        | vB        |
|------------------------------------------------------|-----|-----|-----|----|------------------|-----------|-----------|
| Bis-[4-(2,3-epoxipropoxy)phenyl]propane              | No  | N/A | N/A | No | N/A              | N/A       | N/A       |
| xylene                                               | No  | N/A | No  | No | No               | N/A       | No        |
| Epoxy Resin (700<MW<=1100)                           | No  | N/A | N/A | No | N/A              | N/A       | N/A       |
| Phenol, methylstyrenated                             | No  | N/A | N/A | No | SVHC (Candidate) | Specified | Specified |
| 2-methylpropan-1-ol                                  | No  | N/A | N/A | No | N/A              | N/A       | N/A       |
| 2,3-epoxypropyl neodecanoate                         | No  | N/A | N/A | No | N/A              | N/A       | N/A       |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | No  | N/A | N/A | No | N/A              | N/A       | N/A       |

12.6 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 13: Disposal considerations

|                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods of disposal                            | : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste                                | :                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <a href="#">European waste catalogue (EWC)</a> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Waste code                                     | Waste designation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 08 01 11*                                      | waste paint and varnish containing organic solvents or other hazardous substances                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                     |                                                                                                                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging           |                                                                                                                                                                                                    |
| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
| Type of packaging   | European waste catalogue (EWC)                                                                                                                                                                     |
| Container           | 15 01 06 mixed packaging                                                                                                                                                                           |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SECTION 14: Transport information

|                                 |                 |                 |                 |                 |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               | 3               |
| 14.4 Packing group              | III             | III             | III             | III             |
| 14.5 Environmental hazards      | No.             | Yes.            | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

|                        |                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional information |                                                                                                                                                                                                                          |
| ADR/RID                | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.                                                                                                           |
| Tunnel code            | : (D/E)                                                                                                                                                                                                                  |
| ADN                    | : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1. |

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 14: Transport information

|      |                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------|
| IMDG | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5. |
| IATA | : None identified.                                                                                         |

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)  
[Annex XIV](#)

None of the components are listed.  
[Substances of very high concern](#)

| Intrinsic property                      | Ingredient name                                                                | Status    | Reference number | Date of revision |
|-----------------------------------------|--------------------------------------------------------------------------------|-----------|------------------|------------------|
| <input checked="" type="checkbox"/> PvB | Oligomerisation and alkylation reaction products of 2-phenylpropene and phenol | Candidate | D(2023) 8585-DC  | 1/23/2024        |

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

| Product/ingredient name                                            | Entry Number ( REACH ) |
|--------------------------------------------------------------------|------------------------|
| <input checked="" type="checkbox"/> SIGMASHIELD 880 BASE GREY 5177 | 3                      |

Labelling : Not applicable.  
Explosive precursors : ☒Not applicable.  
[Ozone depleting substances \(1005/2009/EU\)](#)  
Not listed.

[Seveso Directive](#)  
This product is controlled under the Seveso Directive.  
[Danger criteria](#)

| Category |
|----------|
| P5c      |

[National regulations](#)

|                                                   |                                                                                                                                              |                                           |
|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| Social Security Code, Articles L 461-1 to L 461-7 | : <input checked="" type="checkbox"/> bis-[4-(2,3-epoxipropoxy)phenyl]propane<br>xylene<br>Epoxy Resin (700<MW<=1100)<br>2-methylpropan-1-ol | RG 51<br>RG 4bis, RG 84<br>RG 51<br>RG 84 |
| Reinforced medical surveillance                   | : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable                      |                                           |

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 15: Regulatory information

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| References | : Reinforced medical surveillance ; Decree no. 2001-97 of 1 February 2001 establishing specific rules for the prevention of risks from carcinogens, mutagens and reprotoxics and amending the Labour code ; Decree no. 2003-1254 of 23 December 2003 relating to prevention of chemical risks and amending the Labour code ; Decree no. 2004-187 of 26 February 2004 on the placing on the market of biocidal products ; Decree no. 88-1231 of 29/12/1988 relating to poisonous preparations and substances. ; Decree no. 95-517 of 15 May 1997, relating to the classification of dangerous waste. ; Labour code article: R231-53 ; Labour code: Occupational air (ventilation, air purification): Art. R 232-5 to R 232-5-14 ; Labour code: Prevention of chemical risk: Art.R231-51 and R 231-54 to R 231-54-9 ; Labour code: Prevention of fires: Art.R232-12-13 to R 232-12-29 and R 233-30 ; Labour code: provisions applicable to women: Art. L 234-3 to L 236-6 ; Labour code: provisions applicable to young workers: Art. L 234-3 to L 236-6; Art: R234-16 ; Labour code: Sanitary installations: Art. R 232-2 à R 232-2-7 ; Law 76-663 of 19 July 1976 amending and implementing decree of 21 September 1977 relating to classified installations for the protection of the environment ; Tables of anticipated professional diseases according to article R461-3 of the labour code |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                 |                                                       |
|---------------------------------|-------------------------------------------------------|
| 15.2 Chemical safety assessment | : No Chemical Safety Assessment has been carried out. |
|---------------------------------|-------------------------------------------------------|

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
PBT = Persistent, Bioaccumulative and Toxic  
vPvB = Very Persistent and Very Bioaccumulative  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
IMDG = International Maritime Dangerous Goods  
IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification                                                                                                                    | Justification                                                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Muta. 2, H341<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

Full text of abbreviated H statements

|                                |            |                                |                   |
|--------------------------------|------------|--------------------------------|-------------------|
| Code                           | : 00323078 | Date of issue/Date of revision | : 24 January 2025 |
| SIGMASHIELD 880 BASE GREY 5177 |            |                                |                   |

SECTION 16: Other information

|      |                                                         |
|------|---------------------------------------------------------|
| H226 | Flammable liquid and vapour.                            |
| H304 | May be fatal if swallowed and enters airways.           |
| H312 | Harmful in contact with skin.                           |
| H315 | Causes skin irritation.                                 |
| H317 | May cause an allergic skin reaction.                    |
| H318 | Causes serious eye damage.                              |
| H319 | Causes serious eye irritation.                          |
| H332 | Harmful if inhaled.                                     |
| H335 | May cause respiratory irritation.                       |
| H336 | May cause drowsiness or dizziness.                      |
| H341 | Suspected of causing genetic defects.                   |
| H411 | Toxic to aquatic life with long lasting effects.        |
| H412 | Harmful to aquatic life with long lasting effects.      |
| H413 | May cause long lasting harmful effects to aquatic life. |

Full text of classifications [CLP/GHS]

|                   |                                                               |
|-------------------|---------------------------------------------------------------|
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                   |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2               |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3               |
| Aquatic Chronic 4 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4               |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                |
| Muta. 2           | GERM CELL MUTAGENICITY - Category 2                           |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                        |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                               |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

History

|                                 |                    |
|---------------------------------|--------------------|
| Date of issue/ Date of revision | : 24 January 2025  |
| Date of previous issue          | : 15 November 2022 |
| Prepared by                     | : EHS              |
| Version                         | : 15               |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.