# SAFETY DATA SHEET



#### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 17 February 2025 Date of issue 17 February 2025

**Version 7** 

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : PSX 700 NEW HP RED TINT RESIN

Product code : PX700T4C/05

Other means of : Not applicable.

identification Product type

: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

**Manufacturer** : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone

number

(514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

### **SECTION 2: Hazards identification**

Classification of the : ACUTE TOXICITY (dermal) - Category 5
substance or mixture : SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

60.5% (oral), 63.5% (dermal), 83.4% (inhalation)

**GHS** label elements

Hazard pictograms :





Signal word : Warning

**Hazard statements** : H313 - May be harmful in contact with skin.

H317 - May cause an allergic skin reaction.

H361 - Suspected of damaging fertility or the unborn child.

**Precautionary statements** 

Mexico Page: 1/12

Date of issue 17 February 2025 Version 7

### Product code PX700T4C/05

Product name PSX 700 NEW HP RED TINT RESIN

### SECTION 2: Hazards identification

**Prevention** : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P261 - Avoid breathing vapor.

P272 - Contaminated work clothing should not be allowed out of the workplace.

: P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P302 + P312, P352 - IF ON SKIN: Call a POISON CENTER or doctor if you feel

unwell. Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

: P405 - Store locked up. Storage

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

result in classification

Other hazards which do not : Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may

be harmful or fatal or cause blindness. Emits toxic fumes when heated.

See toxicological information (Section 11)

### **SECTION 3: Composition/information on ingredients**

Substance/mixture : Mixture

: PSX 700 NEW HP RED TINT RESIN **Product name** 

Other means of identification

Response

: Not applicable.

| Ingredient name                                                      | %            | CAS number     |
|----------------------------------------------------------------------|--------------|----------------|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with | ≥20 - ≤50    | 30583-72-3     |
| 1-chloro-2,3-epoxypropane                                            |              |                |
| barium sulfate                                                       | ≥20 - ≤43    | 7727-43-7      |
| titanium dioxide                                                     | ≥5.0 - ≤10   | 13463-67-7     |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate                      | ≥1.0 - ≤5.0  | 41556-26-7     |
| Polyamide                                                            | ≥0.10 - ≤2.6 | Not available. |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate                    | <1.0         | 82919-37-7     |
| toluene                                                              | <1.0         | 108-88-3       |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

> Mexico Page: 2/12

Product code PX700T4C/05 Date of issue 17 February 2025 Version 7

Product name PSX 700 NEW HP RED TINT RESIN

### SECTION 4: First aid measures

Ingestion If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Inhalation

**Skin contact** : May be harmful in contact with skin. May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion

#### Over-exposure signs/symptoms

See toxicological information (Section 11)

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

### **SECTION 5: Firefighting measures**

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical **Hazardous thermal** decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon oxides

nitrogen oxides sulfur oxides

halogenated compounds metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

Mexico Page: 3/12

Product name PSX 700 NEW HP RED TINT RESIN

### **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

### For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### **SECTION 7: Handling and storage**

#### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### **Special precautions**

: Ingestion of product or cured coating may be harmful. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Mexico Page: 4/12

**Product name PSX 700 NEW HP RED TINT RESIN** 

### **SECTION 7: Handling and storage**

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

### **Occupational exposure limits**

| Ingredient name                                   | Exposure limits                                            |
|---------------------------------------------------|------------------------------------------------------------|
|                                                   | None.                                                      |
| barium sulfate                                    | NOM-010-STPS-2014 (Mexico, 4/2016)                         |
|                                                   | TWA 8 hours: 10 mg/m³.                                     |
| titanium dioxide                                  | NOM-010-STPS-2014 (Mexico, 4/2016)                         |
|                                                   | TWA 8 hours: 10 mg/m³.                                     |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   | None.                                                      |
| Polyamide                                         | None.                                                      |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | None.                                                      |
| toluene                                           | NOM-010-STPS-2014 (Mexico, 4/2016)<br>TWA 8 hours: 20 ppm. |

#### Key to abbreviations

C = Ceiling Limit

= Internal Permissible Exposure Limit **IPEL** 

STEL = Short term exposure limit TLV = Threshold Limit Value TWA = Time Weighted Average

#### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection Skin protection** 

: Safety glasses with side shields.

Mexico Page: 5/12

### **SECTION 8: Exposure controls/personal protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

### **SECTION 9: Physical and chemical properties**

**Appearance** 

Physical state : Liquid.
Color : Various
Odor : Aromatic.
Odor threshold : Not available.
Molecular weight : Not applicable.
pH : Not applicable.
Melting point : Not available.

**Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability : Not available.

Lower and upper explosive

(flammable) limits

Evaporation rate : Not available.

Vapor pressure : Not available.

Vapor density : Not available.

Relative density : 1.44

Density ( lbs / gal ) : 12.02

Solubility(ies) : Media Result

cold water Not soluble

: Not available.

Solubility in water : Not available.

Partition coefficient: n- : Not applicable.

octanol/water

Mexico Page: 6/12

Product code PX700T4C/05 Date of issue 17 February 2025 Version 7

**Product name PSX 700 NEW HP RED TINT RESIN** 

### **SECTION 9: Physical and chemical properties**

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

% Solid. (w/w) : 98.269

## **SECTION 10: Stability and reactivity**

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

### **SECTION 11: Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

| Product/ingredient name      | Result                          | Species | Dose        | Exposure |
|------------------------------|---------------------------------|---------|-------------|----------|
| <mark></mark> øarium sulfate | LD50 Dermal                     | Rat     | >2000 mg/kg | -        |
|                              | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| titanium dioxide             | LC50 Inhalation Dusts and mists | Rat     | >6.82 mg/l  | 4 hours  |
|                              | LD50 Dermal                     | Rabbit  | >5000 mg/kg | -        |
|                              | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| bis(1,2,2,6,6-pentamethyl-   | LD50 Oral                       | Rat     | 3.125 g/kg  | -        |
| 4-piperidyl) sebacate        |                                 |         |             |          |
| Polyamide                    | LC50 Inhalation Dusts and mists | Rat     | >6.3 mg/l   | 4 hours  |
|                              | LD50 Dermal                     | Rat     | >2000 mg/kg | -        |
|                              | LD50 Oral                       | Rat     | >2000 mg/kg | -        |
| methyl                       | LD50 Oral                       | Rat     | 3.125 g/kg  | -        |
| 1,2,2,6,6-pentamethyl-       |                                 |         |             |          |
| 4-piperidyl sebacate         |                                 |         |             |          |
| toluene                      | LC50 Inhalation Vapor           | Rat     | 49 g/m³     | 4 hours  |
|                              | LD50 Dermal                     | Rabbit  | 8.39 g/kg   | -        |
|                              | LD50 Oral                       | Rat     | 5580 mg/kg  | -        |

**Conclusion/Summary** 

: There are no data available on the mixture itself.

Irritation/Corrosion
Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mexico Page: 7/12

**Product name PSX 700 NEW HP RED TINT RESIN** 

### **SECTION 11: Toxicological information**

### **Sensitization**

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Classification** 

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| titanium dioxide        | -    | 2B   | -   |
| toluene                 | -    | 3    | -   |

### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### **Reproductive toxicity**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name    | 3 3 3      | Route of exposure | Target organs    |
|---------|------------|-------------------|------------------|
| toluene | Category 3 | -                 | Narcotic effects |

### Specific target organ toxicity (repeated exposure)

| Name    | 3.5        | Route of exposure | Target organs |
|---------|------------|-------------------|---------------|
| toluene | Category 2 | -                 | -             |

#### **Target organs**

: Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes.

Contains material which may cause damage to the following organs: lungs.

### **Aspiration hazard**

| Name    | Result                         |
|---------|--------------------------------|
| toluene | ASPIRATION HAZARD - Category 1 |

### Information on the likely routes of exposure

### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May be harmful in contact with skin. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact** : No specific data.

Mexico Page: 8/12

Product code PX700T4C/05 Date of issue 17 February 2025 Version 7

### **Product name PSX 700 NEW HP RED TINT RESIN**

### **SECTION 11: Toxicological information**

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary** 

: There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

**Potential immediate** 

Potential delayed effects

effects

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : Suspected of damaging fertility or the unborn child.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

Mexico Page: 9/12

**Product name PSX 700 NEW HP RED TINT RESIN** 

### **SECTION 11: Toxicological information**

| Product/ingredient name                           | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | (gases) | Inhalation<br>(vapors)<br>(mg/l) | Inhalation<br>(dusts<br>and mists)<br>(mg/l) |
|---------------------------------------------------|------------------|-------------------|---------|----------------------------------|----------------------------------------------|
| SX 700 NEW HP RED TINT RESIN                      | 39684.9          | 4019.4            | N/A     | N/A                              | N/A                                          |
| barium sulfate                                    | N/A              | 2500              | N/A     | N/A                              | N/A                                          |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   | 3125             | N/A               | N/A     | N/A                              | N/A                                          |
| Polyamide                                         | 2500             | 2500              | N/A     | N/A                              | N/A                                          |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 3125             | N/A               | N/A     | N/A                              | N/A                                          |
| toluene                                           | 5580             | 8390              | N/A     | 49                               | N/A                                          |

### **SECTION 12: Ecological information**

#### **Toxicity**

| Product/ingredient name                                                                   | Result                           | Species                 | Exposure |
|-------------------------------------------------------------------------------------------|----------------------------------|-------------------------|----------|
| Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | LC50 11.5 mg/l                   | Fish                    | 96 hours |
| titanium dioxide                                                                          | Acute LC50 >100 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |

### Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| luene                   | -                 | -          | Readily          |

### **Bioaccumulative potential**

| Product/ingredient name | LogPow | BCF  | Potential |
|-------------------------|--------|------|-----------|
| voluene                 | 2.73   | 8.32 | Low       |

### **Mobility in soil**

Soil/Water partition coefficient

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled

Mexico Page: 10/12

**Product name PSX 700 NEW HP RED TINT RESIN** 

### **SECTION 13: Disposal considerations**

material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### **SECTION 14: Transport information**

|                                   | Mexico Classification | IMDG            | IATA            |
|-----------------------------------|-----------------------|-----------------|-----------------|
| UN number                         | Not regulated.        | Not regulated.  | Not regulated.  |
| UN proper shipping name           | -                     | -               | -               |
| Transport hazard class(es)        | -                     | -               | -               |
| Packing group                     | -                     | -               | -               |
| Environmental hazards             | No.                   | No.             | No.             |
| Marine<br>pollutant<br>substances | Not applicable.       | Not applicable. | Not applicable. |

#### **Additional information**

Mexico : None identified. **IMDG** : None identified. IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

### **SECTION 15: Regulatory information**

### **International regulations**

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

Mexico Page: 11/12 Product code PX700T4C/05 Date of issue 17 February 2025 Version 7

**Product name PSX 700 NEW HP RED TINT RESIN** 

### **SECTION 15: Regulatory information**

### SECTION 16: Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of previous issue 2/7/2025 Organization that prepared

the SDS

: EHS

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships.

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> Mexico Page: 12/12