

# SAFETY DATA SHEET

Date of issue/Date of revision

: 14 March 2025

Version

: 11.02



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMARINE 40 BASE L

**Product code** : 00249742

**Other means of identification**

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person  
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Poison Information Centre; emergency telephone, public + 45 82 12 12 12 (health sector +45 35 31 55 55)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226  
Carc. 1B, H350  
Repr. 1B, H360D  
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Flammable liquid and vapour.  
May cause drowsiness or dizziness.  
May cause cancer.  
May damage the unborn child.

### Precautionary statements

Prevention

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

: IF exposed or concerned: Get medical advice or attention.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P202, P280, P210, P308 + P313, P403 + P233, P501

Hazardous ingredients

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics; calcium bis (2-ethylhexanoate) and butanone oxime

Supplemental label elements

: Repeated exposure may cause skin dryness or cracking.  
Contains butanone oxime and neodecanoic acid, cobalt salt. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Restricted to professional users.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	EUH066: C ≥ 20%	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9	≥1.0 - ≤5.0	Asp. Tox. 1, H304 EUH066	EUH066: C ≥ 20%	[1]
calcium bis (2-ethylhexanoate)	REACH #: 01-2119978297-19 EC: 205-249-0 CAS: 136-51-6 Index: 607-230-00-6	<1.0	Eye Dam. 1, H318 Repr. 1B, H360D	-	[1]
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 Index: 607-230-00-6	≤1.0	Repr. 1B, H360D	-	[1] [2]
butanone oxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	<1.0	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 1, H370 (upper respiratory tract) STOT SE 3, H336 STOT RE 2, H373 (blood system)	ATE [Oral] = 100 mg/kg ATE [Dermal] = 1100 mg/kg	[1]
2-ethylhexanoic acid	REACH #: 01-2119488942-23 EC: 205-743-6 CAS: 149-57-5 Index: 607-230-00-6	<0.30	Repr. 1B, H360D	-	[1]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0.30	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 (gastrointestinal tract) (oral) Aquatic Chronic 3, H412	ATE [Oral] = 1098 mg/kg	[1] [2]

English (GB)

Denmark

3/21

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

### SECTION 3: Composition/information on ingredients

propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.30	Repr. 2, H361fd	-	[1]
See Section 16 for the full text of the H statements declared above.					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

- Eye contact** : No specific data.

Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 4: First aid measures

Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising from the substance or mixture	
Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 7: Handling and storage

- Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities


: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)  
See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters  
Occupational exposure limits

Product/ingredient name	Exposure limit values
 1-methoxy-2-propanol	<b>Working Environment Authority (Denmark, 3/2024) [1-methoxy-2-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 185 mg/m³. STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm.
2-ethylhexanoic acid, zirconium salt	<b>Working Environment Authority (Denmark, 3/2024) [zirconiumforbindelser]</b> TWA 8 hours: 5 mg/m³ (calculated as Zr). STEL 15 minutes: 10 mg/m³ (calculated as Zr).
neodecanoic acid, cobalt salt	<b>Working Environment Authority (Denmark, 3/2024) [uorganiske cobaltforbindelser] K.</b> TWA 8 hours: 0.01 mg/m³ (calculated as Co).

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs



Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	DNEL - Workers - Long term - Dermal <i>Effects: Systemic</i>	208 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	871 mg/m <sup>3</sup>
	DNEL - General population - Consumers - Long term - Dermal <i>Effects: Systemic</i>	125 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Inhalation <i>Effects: Systemic</i>	185 mg/m <sup>3</sup>
	DNEL - General population - Consumers - Long term - Oral <i>Effects: Systemic</i>	125 mg/kg bw/day
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	33 mg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Systemic</i>	43.9 mg/m <sup>3</sup>
	DNEL - General population - Long term - Dermal <i>Effects: Systemic</i>	78 mg/kg bw/day
	DNEL - Workers - Long term - Dermal <i>Effects: Systemic</i>	183 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	369 mg/m <sup>3</sup>
1-methoxy-2-propanol	DNEL - Workers - Short term - Inhalation <i>Effects: Local</i>	553.5 mg/m <sup>3</sup>
	DNEL - Workers - Short term - Inhalation <i>Effects: Systemic</i>	553.5 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	0.167 mg/kg bw/day
	DNEL - General population - Long term - Dermal <i>Effects: Systemic</i>	0.167 mg/kg bw/day
	DNEL - Workers - Long term - Dermal <i>Effects: Systemic</i>	0.333 mg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Systemic</i>	0.58 mg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	2.351 mg/m <sup>3</sup>
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	0.66 mg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Local</i>	2.66 mg/m <sup>3</sup>
	DNEL - General population - Long term - Inhalation <i>Effects: Systemic</i>	0.58 mg/m <sup>3</sup>
calcium bis (2-ethylhexanoate)	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	2.351 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	0.167 mg/kg bw/day
	DNEL - General population - Long term - Dermal <i>Effects: Systemic</i>	0.167 mg/kg bw/day
	DNEL - Workers - Long term - Dermal <i>Effects: Systemic</i>	0.333 mg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	0.7 mg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Local</i>	2.82 mg/m <sup>3</sup>
	DMEL - General population - Long term - Oral <i>Effects: Systemic</i>	1.6 µg/kg bw/day
	DMEL - Workers - Long term - Dermal <i>Effects: Systemic</i>	4 µg/kg bw/day
	DMEL - General population - Long term - Inhalation <i>Effects: Systemic</i>	4.82 µg/m <sup>3</sup>
	DMEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	28 µg/m <sup>3</sup>
2-ethylhexanoic acid, zirconium salt	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	0.43 mg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Local</i>	0.9 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	1 mg/kg bw/day
	DNEL - General population - Long term - Dermal <i>Effects: Systemic</i>	1 mg/kg bw/day
	DNEL - Workers - Long term - Dermal <i>Effects: Systemic</i>	2 mg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Systemic</i>	3.5 mg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
butanone oxime	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
2-ethylhexanoic acid	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
neodecanoic acid, cobalt salt	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>
	DNEL - General population - Long term - Oral <i>Effects: Systemic</i>	32 µg/kg bw/day
	DNEL - General population - Long term - Inhalation <i>Effects: Local</i>	43 µg/m <sup>3</sup>
	DNEL - Workers - Long term - Inhalation <i>Effects: Systemic</i>	14 mg/m <sup>3</sup>



Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 8: Exposure controls/personal protection

propylidynetrimethanol	Inhalation		
	DNEL - Workers - Long term - Inhalation	Effects: Local	273.2 µg/m³
	DNEL - General population - Long term - Oral	Effects: Systemic	0.34 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic	0.34 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic	0.58 mg/m³
	DNEL - Workers - Long term - Dermal	Effects: Systemic	0.94 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	3.3 mg/m³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
4-methoxy-2-propanol	Fresh water - Assessment Factors	10 mg/l
	Marine water - Assessment Factors	1 mg/l
	Sewage Treatment Plant - Assessment Factors	100 mg/l
	Fresh water sediment - Equilibrium Partitioning	41.6 mg/kg
	Marine water sediment - Equilibrium Partitioning	4.17 mg/kg
butanone oxime	Soil - Equilibrium Partitioning	2.47 mg/kg
	Fresh water - Assessment Factors	0.256 mg/l
	Sewage Treatment Plant - Assessment Factors	177 mg/l
neodecanoic acid, cobalt salt	Fresh water - Sensitivity Distribution	0.6 µg/l
	Marine water - Sensitivity Distribution	2.36 µg/l
	Sewage Treatment Plant - Assessment Factors	0.37 mg/l
	Fresh water sediment - Sensitivity Distribution	9.5 mg/kg dwt
	Marine water sediment - Sensitivity Distribution	9.5 mg/kg dwt
	Soil - Sensitivity Distribution	10.9 mg/kg dwt

8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 8: Exposure controls/personal protection

Gloves	: For prolonged or repeated handling, use the following type of gloves:  Recommended: nitrile rubber, butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance											
Physical state	: Liquid.										
Colour	: Various										
Odour	: Aromatic.										
Melting point/freezing point	: Not determined.										
Boiling point or initial boiling point and boiling range	: >37.78°C										
Flammability	: Not determined. There are no data available on the mixture itself.										
Lower and upper explosion limit	: Not available.										
Flash point	: Closed cup: 42°C										
Auto-ignition temperature	:										
<table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</td><td>&gt;230</td><td>&gt;446</td><td></td></tr></table>				Ingredient name	°C	°F	Method	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>230	>446	
Ingredient name	°C	°F	Method								
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>230	>446									
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).										
pH	: Not applicable. insoluble in water.										
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): >21 mm²/s										
Solubility	:										



Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 11: Toxicological information

Product/ingredient name	Result	Dose / Exposure
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rat - Oral - LD50	>5000 mg/kg
1-methoxy-2-propanol	Rat - Dermal - LD50 Rabbit - Dermal - LD50 Rat - Oral - LD50 Rat - Inhalation - LC50 Vapour	>5000 mg/kg 13 g/kg 5.2 g/kg >7000 ppm [6 hours]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rat - Oral - LD50	>6 g/kg
2-ethylhexanoic acid, zirconium salt	Rabbit - Dermal - LD50 Rabbit - Dermal - LD50 Rat - Oral - LD50	>5000 mg/kg >5 g/kg >5 g/kg
butanone oxime	<i>Toxic effects:</i> Behavioral - Somnolence (general depressed activity) Rabbit - Dermal - LD50 Rat - Oral - LD50	1100 mg/kg 100 mg/kg
2-ethylhexanoic acid	Rat - Oral - LD50 Rat - Dermal - LD50	3640 mg/kg >2000 mg/kg
neodecanoic acid, cobalt salt	Rat - Female - Oral - LD50	1098 mg/kg
propylidynetrimethanol	Rat - Oral - LD50 Rabbit - Dermal - LD50	14000 mg/kg 10 g/kg

Acute toxicity estimates

Route	ATE value
Oral	19880.2 mg/kg

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Test	Result
Neodecanoic acid, cobalt salt	Mouse - skin OECD 429	Result: Sensitising

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity (single exposure)

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	-	Narcotic effects
1-methoxy-2-propanol	Category 3	-	Narcotic effects
butanone oxime	Category 1	-	upper respiratory tract
-	Category 3	-	Narcotic effects

**Conclusion/Summary :**

May cause drowsiness or dizziness.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
butanone oxime	Category 2	-	blood system
neodecanoic acid, cobalt salt	Category 1	oral	gastrointestinal tract

**Conclusion/Summary :**

Based on available data, the classification criteria are not met.

### Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1

**Conclusion/Summary :**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure :** Not available.

### Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Ingestion** : Can cause central nervous system (CNS) depression.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Eye contact** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
  - nausea or vomiting
  - headache
  - drowsiness/fatigue
  - dizziness/vertigo
  - unconsciousness
  - reduced foetal weight
  - increase in foetal deaths
  - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
  - reduced foetal weight
  - increase in foetal deaths
  - skeletal malformations

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 11: Toxicological information

**Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

**Eye contact** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

### Potential chronic health effects

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : May damage the unborn child.

**Other information** : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

### 12.1 Toxicity



Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 12: Ecological information

Product/ingredient name	Result	Species	Dose / Exposure
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LC50	Algae	>1000 mg/l [72 hours]
1-methoxy-2-propanol	Acute - LC50 - Fresh water	Fish - Goldfish	>4500 mg/l [96 hours]
2-ethylhexanoic acid, zirconium salt	Acute - LC50	Daphnia - Daphnia	23300 mg/l [48 hours]
propylidynetrimethanol	Acute - LC50	Fish	>100 mg/l [96 hours]
	Acute - LC50	Fish	>1000 mg/l [96 hours]

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	80% [28 days] - Readily	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	10 to 2500	High
1-methoxy-2-propanol	<1	-	Low
butanone oxime	0.63	5.01	Low
2-ethylhexanoic acid	2.7	-	Low
propylidynetrimethanol	-0.47	-	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
1-methoxy-2-propanol	1.02	10.447
calcium bis(2-ethylhexanoate)	1.82	66.4852
butanone oxime	1.43	27.1042
2-ethylhexanoic acid	1.82	66.4852
propylidynetrimethanol	1.22	16.5101

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 12: Ecological information

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	
European waste catalogue (EWC)	
Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances


Packaging	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information


	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
English (GB)		Denmark		16/21

Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 14: Transport information

14.5 Environmental hazards Marine pollutant substances	No.  Not applicable.	 No.  Not applicable.	No.  Not applicable.	No.  Not applicable.
--	----------------------------	--	----------------------------	----------------------------

Additional information

ADR/RID	: None identified.
Tunnel code	: (D/E)
ADN	:  None identified.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)


[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	Entry Number ( REACH )
 SIGMARINE 40 BASE L	3
	28
	30
calcium bis(2-ethylhexanoate)	30
2-ethylhexanoic acid, zirconium salt	30
butanone oxime	28

Labelling : Restricted to professional users.

Explosive precursors : Not applicable.

[Ozone depleting substances \(EU 2024/590\)](#)

Not listed.

[Seveso Directive](#)

This product is controlled under the Seveso Directive.

[Danger criteria](#)

Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 15: Regulatory information

Category
P5c

National regulations

Product registration number : PR-1864004

Fire class : F+1

Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Butanone oxime neodecanoic acid, cobalt salt	Listed Listed	Carc. 1B, H350 -

MAL-code : 2-1

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/ protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 2-1  
**Application:** When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Gas filter mask must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied half mask, arm protectors and eye protection must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied half mask, eye protection, coveralls and hood must be worn.

Code : 00249742

Date of issue/Date of revision

: 14 March 2025

SIGMARINE 40 BASE L

## SECTION 15: Regulatory information

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

<b>Code</b> : 00249742	<b>Date of issue/Date of revision</b> : 14 March 2025
<b>SIGMARINE 40 BASE L</b>	

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226 Carc. 1B, H350 Repr. 1B, H360D STOT SE 3, H336	On basis of test data Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H226 H301 H302 H304 H312 H315 H317 H318 H336 H350 H360D H361fd  H370 H372 H373  H412 EUH066	Flammable liquid and vapour. Toxic if swallowed. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness. May cause cancer. May damage the unborn child. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
---	--

Full text of classifications [CLP/GHS]

Acute Tox. 3 Acute Tox. 4 Aquatic Chronic 3 Asp. Tox. 1 Carc. 1B Eye Dam. 1 Flam. Liq. 3 Repr. 1B Repr. 2 Skin Irrit. 2 Skin Sens. 1 STOT RE 1  STOT RE 2  STOT SE 1  STOT SE 3	ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 FLAMMABLE LIQUIDS - Category 3 REPRODUCTIVE TOXICITY - Category 1B REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
--	--

History

<b>Date of issue/ Date of revision</b>	: 14 March 2025
<b>Date of previous issue</b>	: 25 October 2023
<b>Prepared by</b>	: EHS
<b>Version</b>	: 11.02

Disclaimer



Code	: 00249742	Date of issue/Date of revision	: 14 March 2025
SIGMARINE 40 BASE L			

SECTION 16: Other information

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*