# **SAFETY DATA SHEET**



Date of issue 4/20/2025 (month/day/year)

Version 1

# Section 1. Chemical product and company identification

A. Product name : SIGMASHIELD 905 HARDENER

**Product code** : 000010025240

Other means of identification

00481356; 00482488

B. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

**Email Address** 

: PPG SSC

(680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

**Emergency telephone** 

number:

: +82-52-210-8331

### Section 2. Hazards identification

A. Hazard classification : CORROSIVE TO METALS - Category 1

ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 3
ACUTE TOXICITY (inhalation) - Category 3

SKIN CORROSION - Category 1
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 2

This product is classified in accordance with the Industrial Safety and Health Act and

the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :





Signal word : Danger

Korea (GHS) Page: 1/13

Product code 000010025240 Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

### Section 2. Hazards identification

**Hazard statements**: H290 - May be corrosive to metals.

H302 - Harmful if swallowed.

H311 + H331 - Toxic in contact with skin or if inhaled.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H361 - Suspected of damaging fertility or the unborn child.

#### **Precautionary statements**

**Prevention** 

: P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P234 - Keep only in original packaging.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

**Response**: P390 - Absorb spillage to prevent material damage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention. P304 + P340, P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or doctor.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

P363 - Wash contaminated clothing before reuse.

P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

P321 - Specific treatment (see the label).

Storage: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

C. Other hazards which do

not result in classification

: None known.

# Section 3. Composition/information on ingredients

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

Chemical name	Common name	Identifiers	%
POLYOXYPROPYLENE POLYAMINE	polyoxy propylene triamine	CAS: 39423-51-3	50 -
		EC: 500-105-6	<60
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	Isophorone diamine	CAS: 2855-13-2	20 - <30
		EC: 220-666-8	
Benzyl alcohol	BENZYL ALCOHOL	CAS: 100-51-6 EC: 202-859-9	10 -<20
2,4,6-tris[(dimethylamino)methyl]phenol	2,4,6-tris(dimethylaminomethyl)phenol	CAS: 90-72-2	1 - <5

Korea (GHS) Page: 2/13

Product code 000010025240	Date of issue	4/20/2025 (month/day/year)	Version 1	
Product name SIGMASHIELD 905 HARDENER				
Section 3. Composition	n/information on inc	gredients		
SALICYLIC ACID	Salicylic acid	EC: 202-013-9 CAS: 69-72-7 EC: 200-712-3	1 - <5	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

A. Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running
	water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

B. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

D. Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

: Use an extinguishing agent suitable for the surrounding fire.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### A. Extinguishing media

Suitable extinguishing

media

extinguishing media

Unsuitable : None known.

B. Specific hazards arising

from the chemical

**Hazardous thermal** decomposition products

carbon oxides nitrogen oxides

halogenated compounds

: Decomposition products may include the following materials:

: In a fire or if heated, a pressure increase will occur and the container may burst.

Korea (GHS)

Page: 3/13

Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

# Section 5. Fire-fighting measures

C. Special equipment for fire-fighting

Product code 000010025240

- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- **Fire-fighting procedures**
- 10 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Section 6. Accidental release measures

- A. Personal precautions. protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- **B. Environmental** precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- C. Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Absorb spillage to prevent material damage. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Absorb spillage to prevent material damage. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

- A. Precautions for safe handling
- Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.

Korea (GHS) Page: 4/13 Date of issue 4/20/2025 (month/day/year)

Product code 000010025240

**Product name SIGMASHIELD 905 HARDENER** 

Version 1

# Section 7. Handling and storage

- B. Conditions for safe storage, including any incompatibilities
- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a corrosion resistant container with a resistant inner liner. Store locked up. Keep away from metals. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### A. Occupational exposure limits

None.

Recommended monitoring procedures

- Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- controls
- B. Appropriate engineering: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental** exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### C. Personal protective equipment

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Eye protection Hand protection** 

- Chemical splash goggles and face shield.
- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: butyl rubber

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

> Korea (GHS) Page: 5/13

Date of issue 4/20/2025 (month/day/year)

**Version 1** 

**Product name SIGMASHIELD 905 HARDENER** 

**Product code 000010025240** 

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

**Physical state** : Liquid.

Color : Not available. B. Odor Characteristic. : Not available. C. Odor threshold D. pH : Not applicable. E. Melting/freezing point : Not available. F. Boiling point/boiling : >37.78°C (>100°F)

range

G. Flash point : Closed cup: 195°C (383°F)

H. Evaporation rate : Not available. Flammability (solid, gas) : Not available. : Not available. J. Lower and upper

explosive (flammable) limits

K. Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Propylidynetrimethanol, propoxylated, reaction products with ammonia	5.12	0.68	EU A.4			

Media Result L. Solubility(ies)

> cold water Not soluble

Solubility in water : Not available. Vapor density Not available.

**Relative density** 0.98

Partition coefficient: n-

octanol/water

: Not applicable.

D	Auto-ignition	:
Γ.	temperature	

Ingredient name	°C	°F	Method
Propylidynetrimethanol, propoxylated, reaction products with ammonia	320	608	EU A.15

**Decomposition** temperature

: Not available.

: Dynamic (room temperature): Not available. **Viscosity** R.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Flow time (ISO 2431) : Not available. Molecular weight : Not applicable.

Korea (GHS) Page: 6/13 Product code 000010025240 Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

# Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

D. Hazardous Depending on conditions, decomposition products may include the following decomposition products

materials: carbon oxides nitrogen oxides halogenated compounds

# **Section 11. Toxicological information**

A. Information on the likely : Not available. routes of exposure

Potential acute health effects

Inhalation : Toxic if inhaled. : Harmful if swallowed. Ingestion

**Skin contact** : Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.

: Causes serious eye damage. **Eye contact** 

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Eye contact** : Adverse symptoms may include the following:

> pain watering redness

B. Health hazards **Acute toxicity** 

Korea (GHS) Page: 7/13 Product code 000010025240 Date of issue 4/20/2025 (month/day/year) Version 1
Product name SIGMASHIELD 905 HARDENER

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
POLYOXYPROPYLENE POLYAMINE	LD50 Dermal	Rabbit	0.4 g/kg	-
	LD50 Oral	Rat	0.22 g/kg	-
3-aminomethyl-	LC50 Inhalation Dusts and	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine	mists			
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
Benzyl alcohol	LC50 Inhalation Dusts and	Rat	>5 mg/l	4 hours
	mists			
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
2,4,6-tris[(dimethylamino)methyl]phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
SALICYLIC ACID	LD50 Oral	Rat	0.891 g/kg	-

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Irritation/Corrosion**

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.
Eyes : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitizing

#### **Conclusion/Summary**

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Specific target organ toxicity (single exposure)**

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Korea (GHS) Page: 8/13

Product code 000010025240 Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

# **Section 11. Toxicological information**

#### **Aspiration hazard**

Not available.

#### Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : Suspected of damaging fertility or the unborn child.

#### **Additional information**

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

Chemical name	Identifiers	GHS Classification
POLYOXYPROPYLENE POLYAMINE	CAS: 39423-51-3 EC: 500-105-6	CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	CAS: 2855-13-2	CORROSIVE TO METALS - Category 1
	EC: 220-666-8	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1A
Benzyl alcohol	CAS: 100-51-6 EC: 202-859-9	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 3 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
2,4,6-tris[(dimethylamino)methyl]phenol	CAS: 90-72-2 EC: 202-013-9	CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1
SALICYLIC ACID	CAS: 69-72-7 EC: 200-712-3	ACUTE TOXICITY (oral) - Category 4 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2

Korea (GHS) Page: 9/13

Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

Product code 000010025240

# **Section 12. Ecological information**

#### A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
2,4,6-tris[(dimethylamino) methyl]phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
SALICYLIC ACID		Daphnia - <i>Daphnia longispina</i> - Neonate	48 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

#### B. Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
2,4,6-tris[(dimethylamino) methyl]phenol	OECD Ready Biodegradability - Closed Bottle Test	4 % - Not ı	readily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	gradability
Benzyl alcohol 2,4,6-tris[(dimethylamino)	-		-		Readily Not rea	

#### C. Bioaccumulative potential

methyl]phenol

Product/ingredient name	LogPow	BCF	Potential
POLYOXYPROPYLENE POLYAMINE	-1.13	-	Low
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	0.99	-	Low
Benzyl alcohol	0.87	-	Low
2,4,6-tris[(dimethylamino) methyl]phenol	0.219	-	Low
SALICYLIC ACID	2.21 to 2.26	-	Low

#### D. Mobility in soil

Soil/Water partition

coefficient

: Not available.

**E.** Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Korea (GHS) Page: 10/13

Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

### Section 13. Disposal considerations

#### **B.** Disposal precautions

Product code 000010025240

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
A. UN number	UN3066	UN3066	UN3066
B. UN proper shipping name	PAINT	PAINT	PAINT
C. Transport hazard class(es)	8	8	8
D. Packing group	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
E. Marine pollutant substances	Not applicable.	(Polyoxy propylene diamine)	Not applicable.

#### **Additional information**

UN : None identified.

**IMDG**: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

# F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

# Section 15. Regulatory information

#### A. Regulation according to ISHA

ISHA article 117 (Harmful substances prohibited from manufacture) : None of the components are listed.

ISHA article 118 (Harmful substances requiring permission) : None of the components are listed.

Korea (GHS) Page: 11/13

Product code 000010025240 Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

### Section 15. Regulatory information

Article 2 of Youth Protection Act on Substances Hazardous : It is not allowed to sell to persons under the age of 19.

to Youth

#### **Exposure Limits of Chemical Substances and Physical Factors**

None of the components have an OEL.

**ISHA Enforcement Regs**: None of the components are listed.

**Annex 19 (Exposure** standards established

for harmful factors) **ISHA Enforcement Regs** 

Annex 11-5 (Harmful factors subject to Work

**Environment Measurement)** 

**ISHA Enforcement Regs**: None of the components are listed.

**Annex 22 (Harmful Factors Subject to Special Health Check-**

up)

Standard of Industrial

Safety and Health **Annex 12 (Hazardous** substances subject to

: None of the components are listed.

: None of the components are listed.

control)

#### B. Regulation according to Chemicals Control Act

Article 11 (TRI) : None of the components are listed. : None of the components are listed.

: Not applicable

Article 18 Prohibited (K-

Reach Article 27)

**Article 19 Subject to** authorization (K-Reach

Article 25)

: None of the components are listed.

**Article 20 Restricted (K-**

Reach Article 27)

: None of the components are listed.

**Article 20 Toxic** 

**Chemicals (K-Reach** 

Article 20) **Korea inventory** 

: All components are listed or exempted.

**Article 39 (Accident Precaution Chemicals**)

: None of the components are listed.

C. Dangerous Materials **Safety Management Act**  : Class: Class 4 - Flammable Liquid

Item: 5. Class 3 petroleums - Water-insoluble liquid

Threshold: 2000 L Danger category: III

Signal word: Contact with sources of ignition prohibited

D. Wastes regulation Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### E. Regulation according to other foreign laws

Korea (GHS) Page: 12/13 Product code 000010025240 Date of issue 4/20/2025 (month/day/year) Version 1

**Product name SIGMASHIELD 905 HARDENER** 

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

### Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

**NIER Notice** 

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. First issue date : 4/20/2025
 C. Date of issue/Date of : 4/20/2025

revision

D. Version : 1
Prepared by : EHS

E. Other

▼ Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 13/13