

SAFETY DATA SHEET

Date of issue/Date of revision

: 1 May 2025

Version

: 2.01



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Product code : 000001189343

Other means of identification

00444811

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Protective and Marine Coatings Pty Ltd
7 Arnold Street,
Alrode, Alberton, Gauteng
South Africa
Tel: 0027 11 389 4800

**e-mail address of person
responsible for this SDS** : PS.ACEMEA@ppg.com

**1.4 Emergency telephone
number** : +27 (0)861 555 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Acute 1, H400
Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

:



: Warning

Hazard statements : Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Avoid release to the environment.

| | | | |
|--------------------------------------|-----------------------|---------------------------------------|---------------------|
| Code | : 000001189343 | Date of issue/Date of revision | : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | | | |

SECTION 2: Hazards identification

| | |
|---|---|
| Response | : Collect spillage. |
| Storage | : Not applicable. |
| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. P273, P391, P501 |
| Supplemental label elements | : Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. |
| <u>Special packaging requirements</u> | |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |

2.3 Other hazards

| | |
|--|--|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|------------------------------------|--|--------|---|--|---------|
| zinc powder zinc dust (stabilised) | REACH #: 01-2119467174-37 EC: 231-175-3 CAS: 7440-66-6 Index: 030-001-01-9 | ≥90 | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M [Acute] = 1 M [Chronic] = 1 | [1] |
| zinc oxide | REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7 | ≤1.0 | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M [Acute] = 1 M [Chronic] = 1 | [1] [2] |
| lead powder | EC: 231-100-4 CAS: 7439-92-1 Index: 082-013-00-1 | <0.010 | Repr. 1A, H360FD Lact., H362 STOT RE 1, H372 (blood, central nervous system (CNS), kidneys) (oral, inhalation) Aquatic Acute 1, H400 | Repr. 1A, H360D: C ≥ 0.03% STOT RE 1, H372: C ≥ 0.5% M [Acute] = 10 M [Chronic] = 100 | [1] [2] |
| English (GB) South Africa 2/13 | | | | | |

Code : 000001189343

Date of issue/Date of revision

: 1 May 2025

SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|--|--|--|--|--|
| | | | Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above. | | |
|--|--|--|--|--|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

| | |
|--------------------------------------|--|
| Code : 000001189343 | Date of issue/Date of revision : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | |

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Use dry chemical powder. |
| Unsuitable extinguishing media | : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--|---|
| Hazards from the substance or mixture | : May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products | : Decomposition products may include the following materials: metal oxide/oxides |

5.3 Advice for firefighters

- | | |
|---|---|
| Special precautions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- | | |
|------------------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |

6.2 Environmental precautions

- | |
|--|
| : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. |
|--|

6.3 Methods and material for containment and cleaning up

- | | |
|--------------------|--|
| Small spill | : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. |

6.4 Reference to other sections

- | |
|---|
| : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |
|---|

Code : 000001189343

Date of issue/Date of revision

: 1 May 2025

SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Code : 000001189343 **Date of issue/Date of revision** : 1 May 2025
SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : nitrile rubber, butyl rubber, PVC, Viton®

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection :

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid.
Product type : Powder.
Colour : Various
Odour : Characteristic.

| | | | |
|--------------------------------------|----------------|--------------------------------|--------------|
| Code | : 000001189343 | Date of issue/Date of revision | : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | | | |

SECTION 9: Physical and chemical properties

| | |
|--|---|
| Odour threshold | : Not available. |
| Melting point/freezing point | : Not determined. |
| Initial boiling point and boiling range | : Not available. |
| Flammability | : Not determined. There are no data available on the mixture itself. |
| Upper/lower flammability or explosive limits | : Not applicable. |
| Minimum explosive concentration (MEC) | : 10 g/m ³ |
| Flash point | : Closed cup: Not applicable. |
| Auto-ignition temperature | : Not applicable. |
| Decomposition temperature | : Stable under recommended storage and handling conditions (see Section 7). |
| pH | : Not applicable. insoluble in water. |
| Viscosity | : Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): Not applicable. |
| Solubility(ies) | : |
| Media | Result |
| cold water | Not soluble |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Vapour pressure | : Not available. |
| Relative density | : 7.14 |
| Explosive properties | : Not available. |
| Oxidising properties | : Product does not present an oxidizing hazard. |
| Particle characteristics | |
| Median particle size | : 10 - 100 µm |
| 9.2 Other information | |
| Explosive properties | : Not available. |
| Oxidising properties | : Product does not present an oxidizing hazard. |
| No additional information. | |

SECTION 10: Stability and reactivity

| | |
|---|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |

Code : 000001189343 **Date of issue/Date of revision** : 1 May 2025
SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Based on available data, the classification criteria are not met.

Acute toxicity

| Product/ingredient name | Result | Dose / Exposure |
|------------------------------------|---|-----------------------------------|
| zinc powder zinc dust (stabilised) | Rat - Oral - LD50 | >2000 mg/kg |
| zinc oxide | Rat - Inhalation - LC50 Dusts and mists | >5.4 mg/l [4 hours] |
| | Rat - Oral - LD50 | >5000 mg/kg |
| | Rat - Dermal - LD50 | >2000 mg/kg |
| | Rat - Inhalation - LC50 Dusts and mists | >5700 mg/m ³ [4 hours] |

Acute toxicity estimates

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|--|
| Lead powder | Category 1 | oral, inhalation | blood, central nervous system (CNS), kidneys |

Conclusion/Summary (Product) :

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

| | | | |
|--------------------------------------|----------------|--------------------------------|--------------|
| Code | : 000001189343 | Date of issue/Date of revision | : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | | | |

- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Ingestion** : No specific data.
- Skin contact** : No specific data.
- Eye contact** : Adverse symptoms may include the following:
irritation
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

Potential chronic health effects

- General** : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.
- Other information** : Not available.
Sanding and grinding dusts may be harmful if inhaled.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Dose / Exposure |
|------------------------------------|------------------------------|--|-----------------------|
| Zinc powder zinc dust (stabilised) | Acute - EC50 - Fresh water | Algae - <i>Pseudokirchneriella subcapitata</i> | 0.106 mg/l [72 hours] |
| | Chronic - EC10 | Daphnia - Water flea - <i>Daphnia magna</i> - Neonate | 6.3 µg/l [21 days] |
| | Acute - EC50 - Fresh water | Daphnia - Water flea - <i>Daphnia magna</i> | 354 µg/l [48 hours] |
| | Chronic - LC10 - Fresh water | Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i> - Juvenile (Fledgling, Hatchling, | 185 µg/l [30 days] |

| | | | |
|--------------------------------------|----------------|--------------------------------|--------------|
| Code | : 000001189343 | Date of issue/Date of revision | : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | | | |

SECTION 12: Ecological information

| | | | |
|-------------|------------------------------|---|-----------------------|
| zinc oxide | Chronic - EC10 - Fresh water | Weanling) Algae - Green algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase | 27.3 µg/l [72 hours] |
| | Acute - EC50 - Fresh water | Daphnia - Water flea - <i>Daphnia magna</i> - Neonate | 0.481 mg/l [48 hours] |
| | Acute - EC50 | Algae | 0.17 mg/l [72 hours] |
| | Chronic - NOEC - Fresh water | Algae | 0.017 mg/l [72 hours] |
| lead powder | Acute - LC50 - Fresh water | Daphnia - Water flea - <i>Daphnia magna</i> | 0.594 mg/l [48 hours] |
| | Acute - EC50 - Fresh water | Algae - Green algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase | 20.5 µg/l [72 hours] |
| | Chronic - EC10 - Fresh water | Algae - Green algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase | 3.9 µg/l [72 hours] |

Conclusion/Summary : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Based on available data, the classification criteria are not met.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient

Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 000001189343 **Date of issue/Date of revision** : 1 May 2025
SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|-----------------------|
| 08 02 01 | waste coating powders |

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container | 15 01 06 mixed packaging |

- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA |
|--|--|--|--|
| 14.1 UN number or ID number | UN3077 | UN3077 | UN3077 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized)) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. | Environmentally hazardous substance, solid, n.o.s. |
| 14.3 Transport hazard class(es) | 9 | 9 | 9 |
| 14.4 Packing group | III | III | III |
| 14.5 Environmental hazards | Yes. | Yes. | Yes. |
| Marine pollutant substances | Not applicable. | (Zinc powder - zinc dust (stabilized)) | Not applicable. |

Additional information

- ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

| | | | |
|--------------------------------------|----------------|--------------------------------|--------------|
| Code | : 000001189343 | Date of issue/Date of revision | : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | | | |

SECTION 14: Transport information

| | |
|---|---|
| Tunnel code | : (-) |
| IMDG | : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis. |
| IATA | : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. |
| 14.6 Special precautions for user | : Transport within user’s premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
| 14.7 Transport in bulk according to IMO instruments | : Not applicable. |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

| Intrinsic property | Ingredient name | Status | Reference number | Date of revision |
|-----------------------|-----------------|-------------|------------------|------------------|
| Toxic to reproduction | lead powder | Recommended | D(2021) 4569-DC | 4/12/2023 |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other national and international regulations.

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

| | |
|--|---|
| Indicates information that has changed from previously issued version. | |
| Abbreviations and acronyms | : ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number |
| Full text of abbreviated H statements | |

| | | | |
|--------------------------------------|----------------|--------------------------------|--------------|
| Code | : 000001189343 | Date of issue/Date of revision | : 1 May 2025 |
| SIGMAZINC 158/SIGMAGUARD 750 PIGMENT | | | |

SECTION 16: Other information

| | | | |
|---|--|---|--|
| Full text of classifications [CLP/GHS] | : H360FD May damage fertility. May damage the unborn child. | | |
| | H362 May cause harm to breast-fed children. | | |
| | H372 Causes damage to organs through prolonged or repeated exposure. | | |
| | H400 Very toxic to aquatic life. | | |
| | H410 Very toxic to aquatic life with long lasting effects. | | |
| | Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 | |
| | Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 | |
| | Lact. | REPRODUCTIVE TOXICITY - Effects on or via lactation | |
| | Repr. 1A | REPRODUCTIVE TOXICITY - Category 1A | |
| | STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED | |
| | | EXPOSURE - Category 1 | |

History

| | |
|---------------------------------|-------------------|
| Date of issue/ Date of revision | : 1 May 2025 |
| Date of previous issue | : 20 January 2025 |
| Prepared by | : EHS |
| Version | : 2.01 |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.