# SAFETY DATA SHEET

The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7



Date of issue/Date of revision 9 May 2025

Version 1.03

## Section 1. Identification

**Product code** : 000001021716

Product name : PPG AQUACOVER 400 BASE (TINTED)

Product type : Liquid.

Other means of identification

**№**0226417; 00226420; 00226423; 00226427; 00226568; 00226569; 00440560; 00440561; 00440932; 00440934

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating

Professional applications, Used by spraying, Application by non spray methods...

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

Company/undertaking

identification

: PPG Industries Sales, Inc. and PPG Coatings (Philippines), Inc.

3rd Floor First Life Center 174 Salcedo St., Legaspi Village Makati City 1229, Philippines

Tel # 00632- 752-6773/ Fax # 00632-752-6771

**Emergency telephone** 

number

: CHEMTREC +(63) 2-395-3308 (CCN 17704)

## Section 2. Hazards identification

Classification of the substance or mixture

: SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1

AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 30.7%

**GHS label elements** 

Hazard pictograms





Signal word : Danger

**Hazard statements** : May cause an allergic skin reaction.

Causes serious eye damage.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

Prevention: Wear protective gloves. Wear eye or face protection. Avoid release to the

environment. Avoid breathing vapor. Wash hands thoroughly after handling. Do not touch eyes. Contaminated work clothing should not be allowed out of the workplace.

Philippines Page: 1/12

**Product name** PPG AQUACOVER 400 BASE (TINTED)

## Section 2. Hazards identification

: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical Response

help. Take off contaminated clothing and wash it before reuse. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical help.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not : None known.

result in classification

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Ingredient name	%	CAS number
Decanedioic acid, compds. with 1,3-benzenedimethanamine-bisphenol A-bisphenol A diglycidyl ether-diethylenetriamine glycidyl Ph ether reaction product-epichlorohydrin-formaldehyde-propylene oxide-	10 - <20	260549-92-6
triethylenetetramine polymer		
Talc , not containing asbestiform fibres	5 - <10	14807-96-6
aluminium dihydrogen triphosphate	3 - <5	13939-25-8
zinc oxide	1 - <3	1314-13-2
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	0.1 - <0.3	68082-29-1
ammonia, anhydrous	0.1 - < 0.3	7664-41-7
maleic anhydride	<0.1	108-31-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

## **Description of necessary first aid measures**

**Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed - get medical attention if pain, irritation or blistering occurs after contact.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Page: 2/12 **Philippines** 

Product name PPG AQUACOVER 400 BASE (TINTED)

## Section 4. First aid measures

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Philippines Page: 3/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Philippines Page: 4/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Exposure limits
ACGIH TLV (United States, 1/2024)
TWA 8 hours: 2 mg/m³. Form: Respirable
fraction.
TLV (Philippines, 4/2016)
TLV 8 hours: 20 mppcf. Form: Dust.
TLV (Philippines, 4/2016)
TLV 8 hours: 15 mg/m <sup>3</sup> .
TLV (Philippines, 4/2016)
TLV 8 hours: 1 mg/m³. Form: Fume.
TLV (Philippines, 4/2016) [Ammonia]
TLV 8 hours: 30 mg/m³.
TLV 8 hours: 50 ppm.
TLV (Philippines, 4/2016)
TLV 8 hours: 1 mg/m³.
TLV 8 hours: 0.25 ppm.

# Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

## Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### **Gloves**

: polyethylene butyl rubber

Philippines Page: 5/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## Section 8. Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a

respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.
Color : Various
Odor : Amine-like.
Odor threshold : Not available.
Melting point/freezing point : Not available.
Boiling point or initial : >37.78°C (>100°F)

boiling point and boiling

range

Flammability : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Flash point : Closed cup: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

**pH** : 8

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm<sup>2</sup>/s

Solubility(ies) : Media Result

cold water Partially soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Vapor pressure

:		Vapoi	Vapor Pressure at 20°C			Vapor pressure at 50°C	
	Ingredient name	mm Hg	kPa		mm Hg	kPa	Method
	water	17.5	2.3				

Relative density : 1.38

Relative vapor density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

Evaporation rate : Not available.

Philippines Page: 6/12

**Product name** PPG AQUACOVER 400 BASE (TINTED)

## Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** products

: Depending on conditions, decomposition products may include the following

materials: metal oxide/oxides

**Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not

occur.

## Section 11. Toxicological information

## Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
atuminium dihydrogen triphosphate	LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	_
ammonia, anhydrous	LC50 Inhalation Gas. LC50 Inhalation Gas. LC50 Inhalation Vapor	Rat Rat Rat	9500 ppm 2000 ppm 4673 mg/m³	1 hours 4 hours 4 hours
maleic anhydride	LD50 Oral LD50 Dermal LD50 Oral	Rat Rabbit Rat	0.35 g/kg 2620 mg/kg 400 mg/kg	- - -

## **Conclusion/Summary Irritation/Corrosion**

: There are no data available on the mixture itself.

Product/ingredient name	Result	Species	Score	Exposure	Observation
Patty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Irritant	Human	_	_	_

## **Conclusion/Summary**

Skin : There are no data available on the mixture itself.

: There are no data available on the mixture itself. **Eyes** 

> **Philippines** Page: 7/12

**Product name** PPG AQUACOVER 400 BASE (TINTED)

## **Section 11. Toxicological information**

**Respiratory**: There are no data available on the mixture itself.

**Sensitization** 

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitizing

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
ralc , not containing asbestiform fibres	Category 3		Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
maleic anhydride	Category 1	inhalation	respiratory system

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Philippines Page: 8/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## **Section 11. Toxicological information**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

### **Short term exposure**

**Potential immediate** 

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

## **Acute toxicity estimates**

Route	ATE value
Øral	60623.54 mg/kg
Dermal	125063.04 mg/kg

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.

Philippines Page: 9/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## **Section 12. Ecological information**

## **Toxicity**

Product/ingredient name	Result	Species	Exposure
<b>z</b> nc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - <i>Daphnia magna</i> - Neonate	72 hours 48 hours
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Chronic NOEC 0.017 mg/l Fresh water EC10 1.78 mg/l	Algae Algae	72 hours 72 hours

### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	-	-	Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
maleic anhydride	-2.78	-	Low

### **Mobility in soil**

Soil/Water partition coefficient

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Philippines Page: 10/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## **Section 14. Transport information**

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

UN : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user :Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

## Section 15. Regulatory information

### International regulations

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

## Section 16. Other information

#### **History**

Date of issue/Date of

: 9 May 2025

revision

Date of previous issue

: 1/23/2025

**Version** 

1.03 : EHS

**Prepared by** 

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

**Philippines** Page: 11/12

**Product name PPG AQUACOVER 400 BASE (TINTED)** 

## Section 16. Other information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

## Procedure used to derive the classification

Classification	Justification
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1	Calculation method Calculation method
AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method Calculation method

<sup>▼</sup> Indicates information that has changed from previously issued version.

### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Philippines Page: 12/12