

# SAFETY DATA SHEET



Date of issue/Date of revision

: 9 May 2025

Version

: 1.09

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMA FLUORESCENT PAINT  
**Product code** : 000001039107  
**Product type** : Liquid.  
**Other means of identification** : 00906734; 00906735 ; 00906738 ; 00907724 ; 00907725 ; 00907728 ; 00907729 ; 00907730

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.  
**Use of the substance/mixture** : Coating.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

**Supplier**  
+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture  
**Classification according to UK CLP/GHS**  
Flam. Liq. 3, H226  
Carc. 1B, H350  
STOT SE 3, H336  
STOT RE 1, H372  
Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.  
See Section 16 for the full text of the H statements declared above.  
See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

|                                                                                                                                    |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Code : 000001039107                                                                                                                |                                                                                      | Date of issue/Date of revision : 9 May 2025                                                                                                                                                                                       |                                                                                                                                                                                        |         |
| SIGMA FLUORESCENT PAINT                                                                                                            |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
| SECTION 2: Hazards identification                                                                                                  |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
| Hazard statements                                                                                                                  |                                                                                      | : Flammable liquid and vapour.<br>May cause drowsiness or dizziness.<br>May cause cancer.<br>Causes damage to organs through prolonged or repeated exposure.<br>Toxic to aquatic life with long lasting effects.                  |                                                                                                                                                                                        |         |
| Precautionary statements                                                                                                           |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
| Prevention                                                                                                                         |                                                                                      | : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour. |                                                                                                                                                                                        |         |
| Response                                                                                                                           |                                                                                      | : Collect spillage.                                                                                                                                                                                                               |                                                                                                                                                                                        |         |
| Storage                                                                                                                            |                                                                                      | : Not applicable.                                                                                                                                                                                                                 |                                                                                                                                                                                        |         |
| Disposal                                                                                                                           |                                                                                      | : Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P280, P210, P273, P260, P391, P501                                                                         |                                                                                                                                                                                        |         |
| Supplemental label elements                                                                                                        |                                                                                      | : Repeated exposure may cause skin dryness or cracking.<br>Contains isobutyl methacrylate and butanone oxime. May produce an allergic reaction.                                                                                   |                                                                                                                                                                                        |         |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles |                                                                                      | : Restricted to professional users.                                                                                                                                                                                               |                                                                                                                                                                                        |         |
| Special packaging requirements                                                                                                     |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
| Containers to be fitted with child-resistant fastenings                                                                            |                                                                                      | : Not applicable.                                                                                                                                                                                                                 |                                                                                                                                                                                        |         |
| Tactile warning of danger                                                                                                          |                                                                                      | : Not applicable.                                                                                                                                                                                                                 |                                                                                                                                                                                        |         |
| 2.3 Other hazards                                                                                                                  |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII                                  |                                                                                      | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.                                                                                                                                           |                                                                                                                                                                                        |         |
| Other hazards which do not result in classification                                                                                |                                                                                      | : Prolonged or repeated contact may dry skin and cause irritation.                                                                                                                                                                |                                                                                                                                                                                        |         |
| SECTION 3: Composition/information on ingredients                                                                                  |                                                                                      |                                                                                                                                                                                                                                   |                                                                                                                                                                                        |         |
| 3.2 Mixtures                                                                                                                       |                                                                                      | : Mixture                                                                                                                                                                                                                         |                                                                                                                                                                                        |         |
| Product/ingredient name                                                                                                            | Identifiers                                                                          | %                                                                                                                                                                                                                                 | Classification                                                                                                                                                                         | Type    |
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene                                              | REACH #:<br>01-2119458049-33<br>EC: 919-446-0<br>CAS: 64742-82-1                     | ≥25 - ≤50                                                                                                                                                                                                                         | Flam. Liq. 3, H226<br>Carc. 1B, H350<br>STOT SE 3, H336<br>STOT RE 1, H372<br>(central nervous system (CNS))<br>(inhalation)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066 | [1] [2] |
| isobutyl methacrylate                                                                                                              | REACH #:<br>01-2119488331-38<br>EC: 202-613-0<br>CAS: 97-86-9<br>Index: 607-113-00-X | <1.0                                                                                                                                                                                                                              | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Skin Sens. 1B, H317<br>STOT SE 3, H335                                                                                                    | [1]     |
| butanone oxime                                                                                                                     | REACH #:<br>01-2119539477-28                                                         | ≤0.30                                                                                                                                                                                                                             | Acute Tox. 3, H301<br>Acute Tox. 4, H312                                                                                                                                               | [1]     |
| English (GB)                                                                                                                       |                                                                                      | United Kingdom (UK)                                                                                                                                                                                                               |                                                                                                                                                                                        | 2/14    |

**Code** : 000001039107 **Date of issue/Date of revision** : 9 May 2025  
**SIGMA FLUORESCENT PAINT**

### SECTION 3: Composition/information on ingredients

|  |                                                      |  |                                                                                                                                                                                                                                                                                    |  |
|--|------------------------------------------------------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|  | EC: 202-496-6<br>CAS: 96-29-7<br>Index: 616-014-00-0 |  | Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Carc. 1B, H350<br>STOT SE 1, H370<br>(upper respiratory tract)<br>STOT SE 3, H336<br>STOT RE 2, H373<br>(blood system)<br><b>See Section 16 for<br/>the full text of the H<br/>statements declared<br/>above.</b> |  |
|--|------------------------------------------------------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| <b>Code</b> : 000001039107     | <b>Date of issue/Date of revision</b> : 9 May 2025 |
| <b>SIGMA FLUORESCENT PAINT</b> |                                                    |

## SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

**Code** : 000001039107  
**SIGMA FLUORESCENT PAINT**

**Date of issue/Date of revision** : 9 May 2025

## SECTION 6: Accidental release measures

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| <b>Code</b> : 000001039107     | <b>Date of issue/Date of revision</b> : 9 May 2025 |
| <b>SIGMA FLUORESCENT PAINT</b> |                                                    |

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**Occupational exposure limits**

| Product/ingredient name                                                               | Exposure limit values                                                                                             |
|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | <b>IPEL (Europe)</b><br>TWA: 52 ppm (hydrocarbons). Form: Vapour.<br>TWA: 300 mg/m³ (hydrocarbons). Form: Vapour. |

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name                                                               | Type | Exposure              | Value            | Population         | Effects  |
|---------------------------------------------------------------------------------------|------|-----------------------|------------------|--------------------|----------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | DNEL | Long term Inhalation  | 330 mg/m³        | Workers            | Systemic |
|                                                                                       | DNEL | Long term Dermal      | 21 mg/kg bw/day  | Workers            | Systemic |
|                                                                                       | DNEL | Long term Inhalation  | 71 mg/m³         | General population | Systemic |
|                                                                                       | DNEL | Long term Dermal      | 12 mg/kg bw/day  | General population | Systemic |
|                                                                                       | DNEL | Long term Oral        | 21 mg/kg bw/day  | General population | Systemic |
| isobutyl methacrylate                                                                 | DNEL | Short term Inhalation | 570 mg/m³        | Workers            | Systemic |
|                                                                                       | DNEL | Short term Inhalation | 570 mg/m³        | General population | Systemic |
|                                                                                       | DNEL | Long term Dermal      | 3 mg/kg bw/day   | General population | Systemic |
|                                                                                       | DNEL | Long term Dermal      | 5 mg/kg bw/day   | Workers            | Systemic |
|                                                                                       | DNEL | Long term Inhalation  | 66.5 mg/m³       | General population | Systemic |
| butanone oxime                                                                        | DNEL | Long term Inhalation  | 366.4 mg/m³      | General population | Local    |
|                                                                                       | DNEL | Long term Inhalation  | 409 mg/m³        | Workers            | Local    |
|                                                                                       | DNEL | Long term Inhalation  | 415.9 mg/m³      | Workers            | Systemic |
|                                                                                       | DMEL | Long term Oral        | 1.6 µg/kg bw/day | General population | Systemic |
|                                                                                       | DMEL | Long term Dermal      | 4 µg/kg bw/day   | Workers            | Systemic |
|                                                                                       | DMEL | Long term Inhalation  | 4.82 µg/m³       | General population | Systemic |
|                                                                                       | DMEL | Long term Inhalation  | 28 µg/m³         | Workers            | Systemic |
|                                                                                       | DNEL | Long term Inhalation  | 0.43 mg/m³       | General population | Local    |
|                                                                                       | DNEL | Long term Inhalation  | 0.9 mg/m³        | Workers            | Local    |
|                                                                                       | DNEL | Long term Inhalation  | 0.9 mg/m³        | Workers            | Local    |

**PNECs**

| Product/ingredient name | Compartment Detail     | Value      | Method Detail      |
|-------------------------|------------------------|------------|--------------------|
| butanone oxime          | Fresh water            | 0.256 mg/l | Assessment Factors |
|                         | Sewage Treatment Plant | 177 mg/l   | Assessment Factors |

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures**



**Code** : 000001039107  
**SIGMA FLUORESCENT PAINT**

**Date of issue/Date of revision** : 9 May 2025

## SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:  
  
Recommended: nitrile rubber, neoprene
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** :
- Initial boiling point and boiling range** : >37.78°C (>100°F)
- Flammability (solid, gas)** : liquid





|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| <b>Code</b> : 000001039107     | <b>Date of issue/Date of revision</b> : 9 May 2025 |
| <b>SIGMA FLUORESCENT PAINT</b> |                                                    |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name                                                               | Result      | Species | Dose         | Exposure |
|---------------------------------------------------------------------------------------|-------------|---------|--------------|----------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | LD50 Oral   | Rat     | >15000 mg/kg | -        |
| isobutyl methacrylate                                                                 | LD50 Oral   | Rat     | 6.4 g/kg     | -        |
| butanone oxime                                                                        | LD50 Dermal | Rabbit  | 1100 mg/kg   | -        |
|                                                                                       | LD50 Oral   | Rat     | 100 mg/kg    | -        |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| SIGMA FLUORESCENT PAINT | 50000        | N/A            | N/A                      | N/A                         | N/A                                 |
| isobutyl methacrylate   | 6400         | N/A            | N/A                      | N/A                         | N/A                                 |
| butanone oxime          | 100          | 1100           | N/A                      | N/A                         | N/A                                 |

Irritation/Corrosion

Conclusion/Summary : Not available.

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name                                                               | Category   | Route of exposure | Target organs                |
|---------------------------------------------------------------------------------------|------------|-------------------|------------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | Category 3 | -                 | Narcotic effects             |
| isobutyl methacrylate                                                                 | Category 3 | -                 | Respiratory tract irritation |
| butanone oxime                                                                        | Category 1 | -                 | upper respiratory tract      |
| -                                                                                     | Category 3 | -                 | Narcotic effects             |

Specific target organ toxicity (repeated exposure)

**Code** : 000001039107 **Date of issue/Date of revision** : 9 May 2025  
**SIGMA FLUORESCENT PAINT**

**SECTION 11: Toxicological information**

| Product/ingredient name                                                               | Category   | Route of exposure | Target organs                |
|---------------------------------------------------------------------------------------|------------|-------------------|------------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | Category 1 | inhalation        | central nervous system (CNS) |
| butanone oxime                                                                        | Category 2 | -                 | blood system                 |

**Aspiration hazard**

| Product/ingredient name                                                               | Result                         |
|---------------------------------------------------------------------------------------|--------------------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

**Potential acute health effects**

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.  
**Skin contact** : Defatting to the skin. May cause skin dryness and irritation.  
**Ingestion** : Can cause central nervous system (CNS) depression.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact** : No specific data.  
**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking  
**Ingestion** : No specific data.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure**

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

**Long term exposure**

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

**Potential chronic health effects**

Not available.

**Conclusion/Summary** : Not available.  
**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.  
**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

|                         |                |                                |              |
|-------------------------|----------------|--------------------------------|--------------|
| Code                    | : 000001039107 | Date of issue/Date of revision | : 9 May 2025 |
| SIGMA FLUORESCENT PAINT |                |                                |              |

SECTION 11: Toxicological information

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name                                                               | Result                              | Species           | Exposure |
|---------------------------------------------------------------------------------------|-------------------------------------|-------------------|----------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | Chronic NOEC 0.097 mg/l Fresh water | Daphnia - Daphnia | 21 days  |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

| Product/ingredient name                                                               | Test                                                             | Result                   | Dose | Inoculum |
|---------------------------------------------------------------------------------------|------------------------------------------------------------------|--------------------------|------|----------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | OECD 301 F Ready Biodegradability - Manometric Respirometry Test | 75 % - Readily - 28 days | -    | -        |

Conclusion/Summary : Not available.

| Product/ingredient name                                                               | Aquatic half-life | Photolysis | Biodegradability |
|---------------------------------------------------------------------------------------|-------------------|------------|------------------|
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF  | Potential |
|-------------------------|--------------------|------|-----------|
| isobutyl methacrylate   | 2.95               | -    | Low       |
| butanone oxime          | 0.63               | 5.01 | Low       |

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

**Code** : 000001039107 **Date of issue/Date of revision** : 9 May 2025  
**SIGMA FLUORESCENT PAINT**

## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

### Hazardous waste

#### Waste catalogue

| Waste code | Waste designation                                                                 |
|------------|-----------------------------------------------------------------------------------|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue          |
|-------------------|--------------------------|
| Container         | 15 01 06 mixed packaging |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                        | ADR/RID         | ADN             | IMDG                                           | IATA                                                               |
|----------------------------------------|-----------------|-----------------|------------------------------------------------|--------------------------------------------------------------------|
| <b>14.1 UN number</b>                  | UN1263          | UN1263          | UN1263                                         | UN1263                                                             |
| <b>14.2 UN proper shipping name</b>    | PAINT           | PAINT           | PAINT                                          | PAINT                                                              |
| <b>14.3 Transport hazard class(es)</b> | 3               | 3               | 3                                              | 3                                                                  |
| <b>14.4 Packing group</b>              | III             | III             | III                                            | III                                                                |
| <b>14.5 Environmental hazards</b>      | Yes.            | Yes.            | Yes.                                           | Yes. The environmentally hazardous substance mark is not required. |
| <b>Marine pollutant substances</b>     | Not applicable. | Not applicable. | (Naphtha (petroleum), hydrodesulfurized heavy) | Not applicable.                                                    |

### Additional information

**ADR/RID** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.

**Tunnel code** : (D/E)

**ADN** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.

**IMDG** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.

|                         |                |                                |              |
|-------------------------|----------------|--------------------------------|--------------|
| Code                    | : 000001039107 | Date of issue/Date of revision | : 9 May 2025 |
| SIGMA FLUORESCENT PAINT |                |                                |              |

SECTION 14: Transport information

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Explosive precursors** : Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name                                                               | Entry Number (REACH) |
|---------------------------------------------------------------------------------------|----------------------|
| SIGMA FLUORESCENT PAINT                                                               | 3                    |
|                                                                                       | 28                   |
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) > 0.1% cumene | 28                   |
| butanone oxime                                                                        | 28                   |

**Labelling** : Restricted to professional users.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|----------|
| P5c      |
| E2       |

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate  
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = GB CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| <b>Code</b> : 000001039107     | <b>Date of issue/Date of revision</b> : 9 May 2025 |
| <b>SIGMA FLUORESCENT PAINT</b> |                                                    |

**SECTION 16: Other information**

Procedure used to derive the classification

| Classification                                                                                        | Justification                                                                                                 |
|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Carc. 1B, H350<br>STOT SE 3, H336<br>STOT RE 1, H372<br>Aquatic Chronic 2, H411 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

Full text of abbreviated H statements

|        |                                                                    |
|--------|--------------------------------------------------------------------|
| H226   | Flammable liquid and vapour.                                       |
| H301   | Toxic if swallowed.                                                |
| H304   | May be fatal if swallowed and enters airways.                      |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.                                            |
| H317   | May cause an allergic skin reaction.                               |
| H318   | Causes serious eye damage.                                         |
| H335   | May cause respiratory irritation.                                  |
| H336   | May cause drowsiness or dizziness.                                 |
| H350   | May cause cancer.                                                  |
| H370   | Causes damage to organs.                                           |
| H372   | Causes damage to organs through prolonged or repeated exposure.    |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H411   | Toxic to aquatic life with long lasting effects.                   |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |

Full text of classifications

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Carc. 1B          | CARCINOGENICITY - Category 1B                                   |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| Skin Sens. 1B     | SKIN SENSITISATION - Category 1B                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 1         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1   |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

History

|                                        |              |
|----------------------------------------|--------------|
| <b>Date of issue/ Date of revision</b> | : 9 May 2025 |
| <b>Date of previous issue</b>          | : 7 May 2025 |
| <b>Prepared by</b>                     | : EHS        |
| <b>Version</b>                         | : 1.09       |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.