

# SAFETY DATA SHEET



Date of issue/Date of revision 19 May 2025

Version 1.01

## Section 1. Identification

**Product code** : 000010023093  
**Product name** : SIGMACOVER 256S BASE N9.5 WHITE  
**Other means of identification** : 00316033  
**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Coating.  
Professional applications, Used by spraying.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

**Supplier's details** : PT PPG Coatings Indonesia  
Jl. Rawagelam III No.1  
13930 Jakarta  
Indonesia  
Tel +62 21 4605710  
PMC.Safety@PPG.com

**Emergency telephone number** : CHEMTREC 001-803-017-9114 (CCN 17704)

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
AQUATIC HAZARD (LONG-TERM) - Category 2  
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 39.6%

### GHS label elements, including precautionary statements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : Flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

## Section 2. Hazards identification

### Precautionary statements

- Prevention** : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Avoid release to the environment. Do not breathe vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
- Response** : Collect spillage. Get medical advice or attention if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

### CAS number/other identifiers

**CAS number** : Not applicable.

**EC number** : Mixture.

| Ingredient name                                     | %       | CAS number |
|-----------------------------------------------------|---------|------------|
| Epoxy Resin                                         | 20- <25 | SUB110652  |
| crystalline silica, respirable powder (<10 microns) | 5- <10  | 14808-60-7 |
| xylene                                              | 5- <10  | 1330-20-7  |
| trizinc bis(orthophosphate)                         | 5- <10  | 7779-90-0  |
| Talc , not containing asbestiform fibres            | 5- <10  | 14807-96-6 |
| Epoxy resin (MW ≤ 700)                              | 5- <10  | 25068-38-6 |
| Solvent naphtha (petroleum), light aromatic         | 3- <5   | 64742-95-6 |
| 1,2,4-trimethylbenzene                              | 1- <3   | 95-63-6    |
| ethylbenzene                                        | 1- <3   | 100-41-4   |
| 1-methoxy-2-propanol                                | 1- <3   | 107-98-2   |

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
phosphorus oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

xylene

#### **Ministry of Employment and Labor (Indonesia, 2/1997)**

STEL 15 minutes: 651 mg/m<sup>3</sup>.

STEL 15 minutes: 150 ppm.

#### **Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018) [xilen]**

TWA 8 hours: 434 mg/m<sup>3</sup>.

TWA 8 hours: 100 ppm.

## Section 8. Exposure controls/personal protection

Talc , not containing asbestiform fibres

STEL 15 minutes: 651 mg/m<sup>3</sup>.

STEL 15 minutes: 150 ppm.

**Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018)**

TWA 8 hours: 2 mg/m<sup>3</sup>. Form: respirable particles.

**Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018)**  
**[trimetilbenzen]**

TWA 8 hours: 123 mg/m<sup>3</sup>.

TWA 8 hours: 25 ppm.

**Ministry of Employment and Labor (Indonesia, 2/1997)**

STEL 15 minutes: 543 mg/m<sup>3</sup>.

STEL 15 minutes: 125 ppm.

**Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018)**

TWA 8 hours: 20 ppm.

**Ministry of Employment and Labor (Indonesia, 2/1997)**

STEL 15 minutes: 553 mg/m<sup>3</sup>.

STEL 15 minutes: 150 ppm.

**Minister of Labor of the Republic of Indonesia (Indonesia, 4/2018)**

TWA 8 hours: 100 ppm.

STEL 15 minutes: 150 ppm.

1,2,4-trimethylbenzene

ethylbenzene

1-methoxy-2-propanol

### Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Chemical splash goggles.

#### Skin protection

## Section 8. Exposure controls/personal protection

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hand protection        | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Gloves                 | : butyl rubber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Body protection        | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.                                                                                                                                                                                    |
| Other skin protection  | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.                                                                                                                                                                                                                                                                                                                                                                                  |
| Respiratory protection | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.                                                                                                                                                               |

## Section 9. Physical and chemical properties

### Appearance

|                                                  |                           |
|--------------------------------------------------|---------------------------|
| Physical state                                   | : Liquid.                 |
| Color                                            | : White.                  |
| Odor                                             | : Aromatic.               |
| Odor threshold                                   | : Not available.          |
| pH                                               | : Not applicable.         |
| Melting point                                    | : Not available.          |
| Boiling point                                    | : >37.78°C (>100°F)       |
| Flash point                                      | : Closed cup: 30°C (86°F) |
| Evaporation rate                                 | : Not available.          |
| Flammability/Combustible properties (solid, gas) | : Not available.          |
| Lower and upper explosive (flammable) limits     | : Not available.          |
| Vapor pressure                                   | : Not available.          |
| Vapor density                                    | : Not available.          |
| Relative density                                 | : 1.51                    |

|                 |              |               |
|-----------------|--------------|---------------|
| Solubility(ies) | <b>Media</b> | <b>Result</b> |
|                 | cold water   | Not soluble   |

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature : Not available.

## Section 9. Physical and chemical properties

**Decomposition temperature** : Not available.

**Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm<sup>2</sup>/s

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                     | Result                          | Species | Dose                    | Exposure |
|---------------------------------------------|---------------------------------|---------|-------------------------|----------|
| xylene                                      | LD50 Dermal                     | Rabbit  | 1.7 g/kg                | -        |
|                                             | LD50 Oral                       | Rat     | 4.3 g/kg                | -        |
| trizinc bis(orthophosphate)                 | LC50 Inhalation Dusts and mists | Rat     | >5.7 mg/l               | 4 hours  |
|                                             | LD50 Oral                       | Rat     | >5000 mg/kg             | -        |
| Epoxy resin (MW ≤ 700)                      | LD50 Dermal                     | Rabbit  | >2 g/kg                 | -        |
|                                             | LD50 Oral                       | Rat     | >2 g/kg                 | -        |
| Solvent naphtha (petroleum), light aromatic | LD50 Dermal                     | Rabbit  | 3.48 g/kg               | -        |
|                                             | LD50 Oral                       | Rat     | 8400 mg/kg              | -        |
| 1,2,4-trimethylbenzene                      | LC50 Inhalation Vapor           | Rat     | 18000 mg/m <sup>3</sup> | 4 hours  |
|                                             | LD50 Oral                       | Rat     | 5 g/kg                  | -        |
| ethylbenzene                                | LC50 Inhalation Vapor           | Rat     | 17.8 mg/l               | 4 hours  |
|                                             | LD50 Dermal                     | Rabbit  | 17.8 g/kg               | -        |
|                                             | LD50 Oral                       | Rat     | 3.5 g/kg                | -        |
| 1-methoxy-2-propanol                        | LC50 Inhalation Vapor           | Rat     | >7000 ppm               | 6 hours  |
|                                             | LD50 Dermal                     | Rabbit  | 13 g/kg                 | -        |
|                                             | LD50 Oral                       | Rat     | 5.2 g/kg                | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

## Section 11. Toxicological information

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| xylene                  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| Epoxy resin (MW ≤ 700)  | Eyes - Mild irritant     | Rabbit  | -     | -               | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | -               | -           |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

| Product/ingredient name | Route of exposure | Species | Result      |
|-------------------------|-------------------|---------|-------------|
| Epoxy resin (MW ≤ 700)  | skin              | Mouse   | Sensitizing |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name                                        | Category   | Route of exposure | Target organs                |
|---------------------------------------------|------------|-------------------|------------------------------|
| xylene                                      | Category 3 | -                 | Respiratory tract irritation |
| Talc , not containing asbestiform fibres    | Category 3 | -                 | Respiratory tract irritation |
| Solvent naphtha (petroleum), light aromatic | Category 3 | -                 | Narcotic effects             |
| 1,2,4-trimethylbenzene                      | Category 3 | -                 | Respiratory tract irritation |
| 1-methoxy-2-propanol                        | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Name                                                | Category   | Route of exposure | Target organs  |
|-----------------------------------------------------|------------|-------------------|----------------|
| crystalline silica, respirable powder (<10 microns) | Category 1 | inhalation        | -              |
| ethylbenzene                                        | Category 2 | -                 | hearing organs |

### Aspiration hazard

| Name                                        | Result                         |
|---------------------------------------------|--------------------------------|
| xylene                                      | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), light aromatic | ASPIRATION HAZARD - Category 1 |
| ethylbenzene                                | ASPIRATION HAZARD - Category 1 |

## Section 11. Toxicological information

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : There are no data available on the mixture itself.  
**Potential delayed effects** : There are no data available on the mixture itself.

#### Long term exposure

**Potential immediate effects** : There are no data available on the mixture itself.  
**Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

**General** : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route                        | ATE value      |
|------------------------------|----------------|
| Dermal                       | 10274.94 mg/kg |
| Inhalation (vapors)          | 49.67 mg/l     |
| Inhalation (dusts and mists) | 5.89 mg/l      |

## Section 11. Toxicological information

### Other information :

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

## Section 12. Ecological information

### Toxicity

| Product/ingredient name                                  | Result                                                                                                                           | Species                                                           | Exposure                              |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------|
| trizinc bis(orthophosphate)                              | Acute LC50 0.112 mg/l<br>Chronic NOEC 0.026 mg/l                                                                                 | Fish<br>Fish                                                      | 96 hours<br>30 days                   |
| Epoxy resin (MW ≤ 700)                                   | Acute LC50 1.8 mg/l<br>Chronic NOEC 0.3 mg/l                                                                                     | Daphnia<br>Daphnia                                                | 48 hours<br>21 days                   |
| Solvent naphtha (petroleum), light aromatic ethylbenzene | Acute LC50 8.2 mg/l                                                                                                              | Fish                                                              | 96 hours                              |
| 1-methoxy-2-propanol                                     | Acute EC50 1.8 mg/l Fresh water<br>Chronic NOEC 1 mg/l Fresh water<br>Acute LC50 23300 mg/l<br>Acute LC50 >4500 mg/l Fresh water | Daphnia<br>Daphnia - <i>Ceriodaphnia dubia</i><br>Daphnia<br>Fish | 48 hours<br>-<br>48 hours<br>96 hours |

### Persistence/degradability

Not available.

| Product/ingredient name | Test      | Result                   | Dose | Inoculum |
|-------------------------|-----------|--------------------------|------|----------|
| Epoxy resin (MW ≤ 700)  | OECD 301F | 5 % - 28 days            | -    | -        |
| ethylbenzene            | -         | 79 % - Readily - 10 days | -    | -        |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |
| Epoxy resin (MW ≤ 700)  | -                 | -          | Not readily      |
| ethylbenzene            | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| xylene                  | 3.12               | 7.4 to 18.5 | Low       |
| Epoxy resin (MW ≤ 700)  | 3                  | 31          | Low       |
| 1,2,4-trimethylbenzene  | 3.63               | 120.23      | Low       |
| ethylbenzene            | 3.6                | 79.43       | Low       |
| 1-methoxy-2-propanol    | <1                 | -           | Low       |

### Mobility in soil

**Soil/Water partition coefficient** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                    | UN                                                                 | IMDG                          | IATA                                                               |
|------------------------------------|--------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------|
| <b>UN number</b>                   | UN1263                                                             | UN1263                        | UN1263                                                             |
| <b>UN proper shipping name</b>     | PAINT                                                              | PAINT                         | PAINT                                                              |
| <b>Transport hazard class(es)</b>  | 3                                                                  | 3                             | 3                                                                  |
| <b>Packing group</b>               | III                                                                | III                           | III                                                                |
| <b>Environmental hazards</b>       | Yes. The environmentally hazardous substance mark is not required. | Yes.                          | Yes. The environmentally hazardous substance mark is not required. |
| <b>Marine pollutant substances</b> | Not applicable.                                                    | (trizinc bis(orthophosphate)) | Not applicable.                                                    |

### Additional information

**UN** : None identified.

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

|                                                     |                                  |                     |
|-----------------------------------------------------|----------------------------------|---------------------|
| <b>Product code</b> 000010023093                    | <b>Date of issue</b> 19 May 2025 | <b>Version</b> 1.01 |
| <b>Product name</b> SIGMACOVER 256S BASE N9.5 WHITE |                                  |                     |

## Section 15. Regulatory information

**Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

### Law No. 74/2001 - Banned

None of the components are listed.

### Law No. 74/2001 - Restricted

None of the components are listed.

**Law No. 74/2001 - Chemicals that may be used** : Not determined

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Section 16. Other information

### History

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Date of issue/Date of revision</b> | : 19 May 2025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Date of previous issue</b>         | : 4/20/2025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Version</b>                        | : 1.01                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Prepared by</b>                    | : EHS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Key to abbreviations</b>           | : <ul style="list-style-type: none"> <li>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway</li> <li>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</li> <li>IATA = International Air Transport Association</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>UN = United Nations</li> </ul> |

Indicates information that has changed from previously issued version.

### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.