

SAFETY DATA SHEET

Date of issue/Date of revision

: 5 June 2025

Version

: 8.02



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMASHIELD 220/420/460/880/880GF HARDENER

Product code : 00190962

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : ☒ Coating.; Hardener.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

National advisory body/Poison Centre

National Poison Information Centre at Beaumont Hospital. Tel: +353 1 8092566, email: npicdublin@beaumont.ie

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Corr. 1C, H314
Eye Dam. 1, H318
Skin Sens. 1, H317
Repr. 1B, H360F
STOT SE 3, H335
Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.
See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Flammable liquid and vapour. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May damage fertility. Very toxic to aquatic life with long lasting effects.
<u>Precautionary statements</u>		
Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.
Response	:	Collect spillage.
Storage	:	Store in a well-ventilated place. Keep container tightly closed.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P210, P273, P391, P403 + P233, P501
Hazardous ingredients	:	Epoxy Amine Resin; xylene; Propylidynetrimethanol, propoxylated, reaction products with ammonia; benzyl alcohol; 2-methylpropan-1-ol; 4,4'-isopropylidenediphenol; m-phenylenebis(methylamine) and 2,4,6-tris(dimethylaminomethyl)phenol
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
---	---	---

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 2: Hazards identification

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

May cause endocrine disruption.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Epoxy Amine Resin	CAS: SUB123903	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	-	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Propylidynetrimethanol, propoxylated, reaction products with ammonia	REACH #: 01-2119556886-20 EC: 500-105-6 CAS: 39423-51-3	≥10 - ≤16	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥5.0 - ≤10	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg	[1]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≥5.0 - ≤10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
4,4'-isopropylidenediphenol	REACH #: 01-2119457856-23 EC: 201-245-8 CAS: 80-05-7 Index: 604-030-00-0	≥1.0 - ≤5.0	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 10	[1] [2] [3]
m-phenylenebis (methylamine)	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	≥1.0 - ≤4.3	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 EUH071	ATE [Oral] = 930 mg/kg ATE [Inhalation (gases)] = 4500 ppm	[1] [2]
ethylbenzene	REACH #:	≥1.0 - ≤5.0	Flam. Liq. 2, H225	ATE [Inhalation	[1] [2]

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 3: Composition/information on ingredients

	01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4		Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	(vapours)] = 17.8 mg/l	
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2	≥0.30 - ≤2.6	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern - Endocrine disrupting properties

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact : Causes serious eye damage.
- Inhalation : May cause respiratory irritation.
- Skin contact : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion : No known significant effects or critical hazards.

Code : 00190962

Date of issue/Date of revision

: 5 June 2025

SIGMASHIELD 220/420/460/880/880GF HARDENER

SECTION 4: First aid measures

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides

5.3 Advice for firefighters

Code : 00190962 Date of issue/Date of revision : 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER

SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 7: Handling and storage

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Xylene	NAOSH (Ireland, 4/2024) [xylene] Absorbed through skin. OELV 8 hours: 50 ppm. OELV 8 hours: 221 mg/m³. OELV 15 minutes: 100 ppm. OELV 15 minutes: 442 mg/m³.
2-methylpropan-1-ol	NAOSH (Ireland, 4/2024) OELV 8 hours: 150 ppm. OELV 8 hours: 700 mg/m³.
4,4'-isopropylidenediphenol	NAOSH (Ireland, 4/2024) Repr 1B. Sensitiser. OELV 8 hours: 2 mg/m³. Form: Inhalable fraction.
m-phenylenebis(methylamine)	NAOSH (Ireland, 4/2024) OELV 8 hours: 0.1 mg/m³.
ethylbenzene	NAOSH (Ireland, 4/2024) Absorbed through skin.

English (GB)	Ireland	7/21
--------------	---------	------

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 8: Exposure controls/personal protection

OELV 8 hours: 100 ppm.
OELV 8 hours: 442 mg/m³.
OELV 15 minutes: 200 ppm.
OELV 15 minutes: 884 mg/m³.

Biological exposure indices

Product/ingredient name	Exposure indices
Xylene	NAOSH (Ireland, 1/2011) [Xylene] BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.
ethylbenzene	NAOSH (Ireland, 1/2011) BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air]. Sampling time: not critical. BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
Xylene	DNEL - General population - Long term - Oral	<i>Effects: Systemic</i> 5 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	<i>Effects: Local</i> 65.3 mg/m³
	DNEL - General population - Long term - Inhalation	<i>Effects: Systemic</i> 65.3 mg/m³
	DNEL - General population - Long term - Dermal	<i>Effects: Systemic</i> 125 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i> 212 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	<i>Effects: Local</i> 221 mg/m³
	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i> 221 mg/m³
	DNEL - General population - Short term - Inhalation	<i>Effects: Local</i> 260 mg/m³
	DNEL - General population - Short term - Inhalation	<i>Effects: Systemic</i> 260 mg/m³
	DNEL - Workers - Short term - Inhalation	<i>Effects: Local</i> 442 mg/m³
	DNEL - Workers - Short term - Inhalation	<i>Effects: Systemic</i> 442 mg/m³

Code : 00190962

Date of issue/Date of revision

: 5 June 2025

SIGMASHIELD 220/420/460/880/880GF HARDENER

SECTION 8: Exposure controls/personal protection

Propylidynetrimethanol, propoxylated, reaction products with ammonia	DNEL - Workers - Long term - Dermal	Effects: Systemic	1.6 mg/kg bw/day
benzyl alcohol	DNEL - Workers - Long term - Inhalation	Effects: Systemic	14.1 mg/m ³
	DNEL - General population - Long term - Oral	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic	5.4 mg/m ³
	DNEL - Workers - Long term - Dermal	Effects: Systemic	8 mg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic	20 mg/kg bw/day
	DNEL - General population - Short term - Dermal	Effects: Systemic	20 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	22 mg/m ³
	DNEL - General population - Short term - Inhalation	Effects: Systemic	27 mg/m ³
2-methylpropan-1-ol	DNEL - Workers - Short term - Dermal	Effects: Systemic	40 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	Effects: Systemic	110 mg/m ³
	DNEL - General population - Long term - Inhalation	Effects: Local	55 mg/m ³
4,4'-isopropylidenediphenol	DNEL - Workers - Long term - Inhalation	Effects: Local	310 mg/m ³
	DNEL - General population - Short term - Dermal	Effects: Systemic	24 µg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic	24 µg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic	53 µg/kg bw/day
	DNEL - General population - Long term - Oral	Effects: Systemic	53 µg/kg bw/day
	DNEL - Workers - Short term - Dermal	Effects: Systemic	66 µg/kg bw/day
	DNEL - Workers - Long term - Dermal	Effects: Systemic	66 µg/kg bw/day
	DNEL - General population - Short term - Inhalation	Effects: Local	1 mg/m ³
	DNEL - General population - Long term - Inhalation	Effects: Local	1 mg/m ³
	DNEL - General population - Short term - Inhalation	Effects: Systemic	1 mg/m ³
	DNEL - General population - Long term - Inhalation	Effects: Systemic	1 mg/m ³
	DNEL - Workers - Short term - Inhalation	Effects: Local	2 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Local	2 mg/m ³
	DNEL - Workers - Short term - Inhalation	Effects: Systemic	2 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	2 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Local	0.2 mg/m ³
m-phenylenebis (methylamine)	DNEL - Workers - Long term - Dermal	Effects: Systemic	0.33 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	1.2 mg/m ³
ethylbenzene	DMEL - Workers - Long term - Inhalation	Effects: Local	442 mg/m ³
	DMEL - Workers - Short term - Inhalation	Effects: Systemic	884 mg/m ³
	DNEL - General population - Long term - Oral	Effects: Systemic	1.6 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic	15 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	77 mg/m ³
	DNEL - Workers - Long term - Dermal	Effects: Systemic	180 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	Effects: Local	293 mg/m ³
	DNEL - General population - Long term - Oral	Effects: Systemic	0.075 mg/kg bw/day
2,4,6-tris (dimethylaminomethyl) phenol	DNEL - General population - Short term - Dermal	Effects: Systemic	0.075 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic	0.075 mg/kg bw/day
	DNEL - General population - Short term - Inhalation	Effects: Systemic	0.13 mg/m ³
	DNEL - General population - Long term - Inhalation	Effects: Systemic	0.13 mg/m ³

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 8: Exposure controls/personal protection

	Inhalation		
	DNEL - Workers - Long term - Dermal	Effects: Systemic	0.15 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	0.53 mg/m³
	DNEL - Workers - Short term - Dermal	Effects: Systemic	0.6 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	Effects: Systemic	2.1 mg/m³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage Treatment Plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dwt
	Marine water sediment	12.46 mg/kg dwt
	Soil	2.31 mg/kg
2-methylpropan-1-ol	Fresh water - Assessment Factors	0.4 mg/l
	Marine water - Assessment Factors	0.04 mg/l
	Sewage Treatment Plant - Assessment Factors	10 mg/l
	Fresh water sediment - Equilibrium Partitioning	1.56 mg/kg dwt
	Marine water sediment	0.156 mg/kg dwt
	Soil - Equilibrium Partitioning	0.076 mg/kg dwt
4,4'-isopropylidenediphenol	Fresh water - Sensitivity Distribution	0.018 mg/l
	Marine water - Sensitivity Distribution	0.018 mg/l
	Sewage Treatment Plant - Assessment Factors	320 mg/l
	Fresh water sediment - Assessment Factors	1.2 mg/kg dwt
	Marine water sediment - Assessment Factors	0.24 mg/kg dwt
	Soil - Assessment Factors	3.7 mg/kg dwt
ethylbenzene	Fresh water - Assessment Factors	0.1 mg/l
	Marine water - Assessment Factors	0.01 mg/l
	Sewage Treatment Plant - Assessment Factors	9.6 mg/l
	Fresh water sediment - Equilibrium Partitioning	13.7 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	1.37 mg/kg dwt
	Soil - Equilibrium Partitioning	2.68 mg/kg dwt
	Secondary Poisoning	20 mg/kg

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield. Use eye protection according to EN 166.

Skin protection

Hand protection :

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 8: Exposure controls/personal protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves	: nitrile neoprene
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	:  Various [Light]
Odour	: Amine-like.
Melting point/freezing point	: Not determined.
Boiling point or initial boiling point and boiling range	: >37.78°C
Flammability	: Not determined. There are no data available on the mixture itself.
Lower and upper explosion limit	: Not available.
Flash point	: Closed cup: 36°C
Auto-ignition temperature	: 305°C (581°F)

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- Causes severe skin burns and eye damage.
- May cause an allergic skin reaction.
- May damage fertility.
- May cause respiratory irritation.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
Xylene	Rat - Oral - LD50	4.3 g/kg
	Rabbit - Dermal - LD50	1.7 g/kg
	Rat - Oral - LD50	0.22 g/kg
Propylidynetrimethanol, propoxylated, reaction products with ammonia		
benzyl alcohol	Rabbit - Dermal - LD50	0.4 g/kg
	Rabbit - Dermal - LD50	>2000 mg/kg
	Rat - Oral - LD50	1200 mg/kg
2-methylpropan-1-ol	Rat - Inhalation - LC50 Dusts and mists	>5 mg/l [4 hours]
	Rat - Oral - LD50	2830 mg/kg
	Rabbit - Dermal - LD50	2460 mg/kg
4,4'-isopropylidenediphenol	Rat - Inhalation - LC50 Vapour	24.6 mg/l [4 hours]
	Rat - Oral - LD50	3.25 g/kg
	Toxic effects: Lung, Thorax, or Respiration - DyspneaLung, Thorax, or Respiration - Cyanosis	
	Rabbit - Dermal - LD50	3600 mg/kg
	Toxic effects: Behavioral - Somnolence (general depressed activity)Cardiac - Other changesLung, Thorax, or Respiration - Changes in pulmonary vascular resistance	
m-phenylenebis(methylamine)	Rat - Oral - LD50	930 mg/kg
	Rat - Male, Female - Dermal - LD50	>3100 mg/kg
	Rat - Inhalation - LC50 Gas.	700 ppm [1 hours]
	Toxic effects: Eye - Lacrimation Lung, Thorax, or Respiration - Respiratory depression	
ethylbenzene	Rat - Oral - LD50	3.5 g/kg
	Rabbit - Dermal - LD50	17.8 g/kg
	Rat - Inhalation - LC50 Vapour	17.8 mg/l [4 hours]
2,4,6-tris(dimethylaminomethyl) phenol	Rat - Dermal - LD50	1280 mg/kg
	Rat - Oral - LD50	1200 mg/kg
	Toxic effects: Peripheral Nerve and Sensation - Flaccid paralysis without anesthesia (usually neuromuscular blockage) Lung, Thorax, or Respiration - Dyspnea	

Acute toxicity estimates

Route	ATE value
Oral	2115 mg/kg
Dermal	3589.26 mg/kg
Inhalation (gases)	108958.84 ppm
Inhalation (vapours)	51.63 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 11: Toxicological information

Product/ingredient name	Result
☒ xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours
m-phenylenebis(methylamine)	Rat - Skin - Severe irritant Duration of treatment/exposure: 4 hours Observation period: 4 hours

Conclusion/Summary

Skin : ☒ Causes severe burns.

Eyes : ☒ Causes serious eye damage.

Respiratory : ☒ Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Test	Result
☒ m-phenylenebis(methylamine)	Mouse - skin OECD 429	Result: Sensitising

Conclusion/Summary

Skin : ☒ May cause an allergic skin reaction.

Respiratory : ☒ Based on available data, the classification criteria are not met.

Mutagenicity
☒ Based on available data, the classification criteria are not met.

Carcinogenicity
☒ Based on available data, the classification criteria are not met.

Reproductive toxicity
☒ May damage fertility.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
☒ xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
4,4'-isopropylidenediphenol	Category 3	-	Respiratory tract irritation

Conclusion/Summary :

☒ May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
☒ ethylbenzene	Category 2	-	hearing organs

Conclusion/Summary :

☒ Based on available data, the classification criteria are not met.

Aspiration hazard

Product/ingredient name	Result
☒ xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Conclusion/Summary :

☒ Based on available data, the classification criteria are not met.

Code : 00190962	Date of issue/Date of revision : 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER	

SECTION 11: Toxicological information

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : May cause respiratory irritation.

Ingestion : No known significant effects or critical hazards.

Skin contact : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility.

Other information :

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 11: Toxicological information

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

May cause endocrine disruption.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
2-methylpropan-1-ol 4,4'-isopropylidenediphenol	Acute - EC50	Daphnia	1100 mg/l [48 hours]
	Acute - LC50 - Fresh water	Fish	4.6 mg/l [96 hours]
	Acute - LC50 - Fresh water	Crustaceans	0.885 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Fish	0.000174 mg/l [5 months]
ethylbenzene	Acute - EC50	Algae - Green algae - <i>Raphidocelis subcapitata</i>	1.32 mg/l [72 hours]
	Chronic - EC10	Algae - Green algae - <i>Raphidocelis subcapitata</i>	1189 µg/l [72 hours]
	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	1 mg/l
2,4,6-tris (dimethylaminomethyl)phenol	Acute - LC50	Daphnia	>100 mg/l [48 hours]
	Acute - LC50	Fish	>100 mg/l [96 hours]

Conclusion/Summary : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
ethylbenzene 2,4,6-tris (dimethylaminomethyl)phenol	- OECD [Ready Biodegradability - Closed Bottle Test]	79% [10 days] - Readily 4% [28 days] - Not readily	

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Xylene	-	-	Readily
benzyl alcohol	-	-	Readily
4,4'-isopropylidenediphenol	-	-	Readily
ethylbenzene	-	-	Readily
2,4,6-tris(dimethylaminomethyl)phenol	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	3.12	7.4 to 18.5	Low
Propylidynetrimethanol, propoxylated, reaction products with ammonia	-1.13	-	Low
benzyl alcohol	0.87	-	Low
2-methylpropan-1-ol	1	-	Low
4,4'-isopropylidenediphenol	3.4	43.65	Low
m-phenylenebis(methylamine)	0.18	2.69	Low
ethylbenzene	3.6	79.43	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
benzyl alcohol	1.1	12.6442
2-methylpropan-1-ol	1.08	12.0246
4,4'-isopropylidenediphenol	3.16	1436.23
m-phenylenebis(methylamine)	1.67	46.5812
ethylbenzene	2.23	170.406
2,4,6-tris(dimethylaminomethyl)phenol	2.72	525.589

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

May cause endocrine disruption.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 13: Disposal considerations

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:
European waste catalogue (EWC)	
Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
---------------------	---

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3469	UN3469	UN3469	UN3469
14.2 UN proper shipping name	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE	PAINT, FLAMMABLE, CORROSIVE
14.3 Transport hazard class(es)	3 (8)	3 (8)	3 (8)	3 (8)
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Polyoxy propylene diamine)	Not applicable.

Additional information	
ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (D/E)
ADN	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 14: Transport information

IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)
[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)
None of the components are listed.
[Substances of very high concern](#)

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
 Toxic to reproduction Endocrine disrupting properties for human health Endocrine disrupting properties for environment	bisphenol A	Recommended	ED/01/2018	10/1/2019
	bisphenol A	Recommended	ED/01/2018	10/1/2019
	bisphenol A	Recommended	ED/01/2018	10/1/2019

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	Entry Number (REACH)
 SIGMASHIELD 220/420/460/880/880GF HARDENER	3
4,4'-isopropylidenediphenol	30
	30
	66

Labelling : Restricted to professional users.

Explosive precursors : Not applicable.

[Ozone depleting substances \(EU 2024/590\)](#)
Not listed.

[Seveso Directive](#)
This product is controlled under the Seveso Directive.
[Danger criteria](#)

Category
 P501 E1

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 15: Regulatory information

Product/ingredient name	List name	Not available.	Classification	Notes
4,4'-isopropylidenediphenol	NAOSH	-	Repr 1B	EU derived Occupational Exposure Limit Values

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- IMDG = International Maritime Dangerous Goods
- IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F STOT SE 3, H335 Aquatic Chronic 1, H410	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225 H226 H302 H304 H312 H314 H315 H317 H318 H319 H332 H335 H336 H360F H373 H400 H410	Highly flammable liquid and vapour. Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May damage fertility. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
---	--

Code	: 00190962	Date of issue/Date of revision	: 5 June 2025
SIGMASHIELD 220/420/460/880/880GF HARDENER			

SECTION 16: Other information

H411 H412 EUH071	Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Corrosive to the respiratory tract.
------------------------	---

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Repr. 1B Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1B STOT RE 2 STOT SE 3	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 REPRODUCTIVE TOXICITY - Category 1B SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
---	--

History

Date of issue/ Date of revision	: 5 June 2025
Date of previous issue	: 24 April 2025
Prepared by	: EHS
Version	: 8.02

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.