

SAFETY DATA SHEET

Date of issue/Date of revision

: 12 June 2025

Version

: 1.05



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMAGUARD 730 BASE CREAM

Product code : 000001099376

Other means of identification

00469661

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Numéro de téléphone d'appel d'urgence : 01 45 42 59 59 (Association ORFILA, organisme agréé prévu au 4ème alinéa de l'article L231-7 du code du travail)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT RE 2, H373

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms



Signal word

: Warning

Hazard statements

: Flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.

Response

: Collect spillage.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.
P280, P210, P273, P260, P391, P501

Hazardous ingredients

: bis-[4-(2,3-epoxipropoxy)phenyl]propane; Epoxy Resin (700<MW<=1100); Phenol, styrenated; Quartz (SiO₂) and Phenol, polymer with formaldehyde, glycidyl ether (MW <=700)

Supplemental label elements

: Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
1,4-bis-[4-(2,3-epoxipropoxy)phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥5.0 - ≤10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Epoxy Resin (700<MW ≤1100)	CAS: 25036-25-3	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
Phenol, styrenated	EC: 262-975-0 CAS: 61788-44-1	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≥1.0 - <3.0	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
crystalline silica, respirable powder (<10 microns)	EC: 238-878-4 CAS: 14808-60-7	≥1.0 - ≤5.0	STOT RE 1, H372 (inhalation)	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
Phenol, polymer with formaldehyde, glycidyl ether (MW≤700)	CAS: 28064-14-4	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	REACH #: 01-0000017900-73 EC: 432-840-2 CAS: 220926-97-6 Index: 616-201-00-7	≥1.0 - ≤5.0	Acute Tox. 4, H332 STOT RE 2, H373 (lungs) (inhalation) Aquatic Chronic 4, H413	ATE [Inhalation (dusts and mists)] = 3.56 mg/l	[1]
Hydrocarbons, C9, aromatics < 0.1% cumene	REACH #: 01-2119455851-35	≤1.6	Flam. Liq. 3, H226 STOT SE 3, H335	-	[1] [2]

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 3: Composition/information on ingredients

	EC: 918-668-5 CAS: 128601-23-0		STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 See Section 16 for the full text of the H statements declared above.	
--	-----------------------------------	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Code : 000001099376 Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM

SECTION 4: First aid measures

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	Ministry of Labor (France, 6/2024) [xylènes, isomères mixtes, purs] Absorbed through skin. STEL 15 minutes: 442 mg/m ³ . STEL 15 minutes: 100 ppm. TWA 8 hours: 221 mg/m ³ . TWA 8 hours: 50 ppm.
2-methylpropan-1-ol	Ministry of Labor (France, 6/2024) TWA 8 hours: 50 ppm. TWA 8 hours: 150 mg/m ³ .
crystalline silica, respirable powder (<10 microns)	Ministry of Labor (France, 6/2024) TWA 8 hours: 0.1 mg/m ³ . Form: Respirable fraction.
ethylbenzene	Ministry of Labor (France, 6/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 88.4 mg/m ³ . STEL 15 minutes: 442 mg/m ³ . STEL 15 minutes: 100 ppm.
Hydrocarbons, C9, aromatics < 0.1% cumene	Ministry of Labor (France, 9/2023) [hydrocarbures en C6-C12] TWA 8 hours: 1000 mg/m ³ . Form: Vapour. STEL 15 minutes: 1500 mg/m ³ . Form: Vapour.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i> 12.25 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Effects: Systemic</i> 12.25 mg/m ³
	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i> 8.33 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	<i>Effects: Systemic</i> 8.33 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Dermal	<i>Effects: Systemic</i> 3.571 mg/kg bw/day
	DNEL - General population - Consumers - Short term - Dermal	<i>Effects: Systemic</i> 3.571 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Oral	<i>Effects: Systemic</i> 0.75 mg/kg bw/day
	DNEL - General population - Consumers - Short term - Oral	<i>Effects: Systemic</i> 0.75 mg/kg bw/day
	DNEL - General population - Long term - Dermal	<i>Effects: Systemic</i> 89.3 µg/kg bw/day
	DNEL - General population - Long term - Oral	<i>Effects: Systemic</i> 0.5 mg/kg bw/day

English (GB)

France

7/21

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 8: Exposure controls/personal protection

xylene	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i>	0.75 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	<i>Effects: Systemic</i>	0.87 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i>	4.93 mg/m ³
	DNEL - General population - Long term - Oral	<i>Effects: Systemic</i>	5 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	<i>Effects: Local</i>	65.3 mg/m ³
	DNEL - General population - Long term - Inhalation	<i>Effects: Systemic</i>	65.3 mg/m ³
	DNEL - General population - Long term - Dermal	<i>Effects: Systemic</i>	125 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i>	212 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	<i>Effects: Local</i>	221 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i>	221 mg/m ³
Phenol, styrenated	DNEL - General population - Short term - Inhalation	<i>Effects: Local</i>	260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Effects: Systemic</i>	260 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Effects: Local</i>	442 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Effects: Systemic</i>	442 mg/m ³
	DNEL - General population - Long term - Oral	<i>Effects: Systemic</i>	0.75 mg/kg bw/day
	DNEL - General population - Long term - Dermal	<i>Effects: Systemic</i>	0.75 mg/kg bw/day
2-methylpropan-1-ol	DNEL - General population - Long term - Inhalation	<i>Effects: Systemic</i>	1.31 mg/m ³
	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i>	2.1 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i>	7.4 mg/m ³
ethylbenzene	DNEL - General population - Long term - Inhalation	<i>Effects: Local</i>	55 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Effects: Local</i>	310 mg/m ³
	DMEL - Workers - Long term - Inhalation	<i>Effects: Local</i>	442 mg/m ³
	DMEL - Workers - Short term - Inhalation	<i>Effects: Systemic</i>	884 mg/m ³
	DNEL - General population - Long term - Oral	<i>Effects: Systemic</i>	1.6 mg/kg bw/day
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	DNEL - General population - Long term - Inhalation	<i>Effects: Systemic</i>	15 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i>	77 mg/m ³
	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i>	180 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	<i>Effects: Local</i>	293 mg/m ³
	DNEL - General population - Long term - Inhalation	<i>Effects: Local</i>	82.5 µg/m ³
Hydrocarbons, C9, aromatics < 0.1% cumene	DNEL - Workers - Long term - Inhalation	<i>Effects: Local</i>	332 µg/m ³
	DNEL - General population - Short term - Inhalation	<i>Effects: Local</i>	25.7 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Effects: Local</i>	51.3 mg/m ³
	DNEL - Workers - Long term - Dermal	<i>Effects: Systemic</i>	25 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	<i>Effects: Systemic</i>	150 mg/m ³
	DNEL - General population - Long term - Dermal	<i>Effects: Systemic</i>	11 mg/kg
	DNEL - General population - Long term - Oral	<i>Effects: Systemic</i>	11 mg/kg
	DNEL - General population - Long term - Inhalation	<i>Effects: Systemic</i>	32 mg/m ³

PNECs

Code : 000001099376 Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail - Method	Value
1,4-bis-[4-(2,3-epoxipropoxy)phenyl]propane	Fresh water - Assessment Factors	0.006 mg/l
	Marine water - Assessment Factors	0.001 mg/l
xylene	Fresh water sediment - Equilibrium Partitioning	0.996 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.1 mg/kg dwt
	Soil - Equilibrium Partitioning	0.196 mg/kg dwt
	Sewage Treatment Plant - Assessment Factors	10 mg/l
	Secondary Poisoning - Assessment Factors	11 mg/kg
	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage Treatment Plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dwt
	Marine water sediment	12.46 mg/kg dwt
2-methylpropan-1-ol	Soil	2.31 mg/kg
	Fresh water - Assessment Factors	0.4 mg/l
	Marine water - Assessment Factors	0.04 mg/l
	Sewage Treatment Plant - Assessment Factors	10 mg/l
	Fresh water sediment - Equilibrium Partitioning	1.56 mg/kg dwt
	Marine water sediment	0.156 mg/kg dwt
ethylbenzene	Soil - Equilibrium Partitioning	0.076 mg/kg dwt
	Fresh water - Assessment Factors	0.1 mg/l
	Marine water - Assessment Factors	0.01 mg/l
	Sewage Treatment Plant - Assessment Factors	9.6 mg/l
	Fresh water sediment - Equilibrium Partitioning	13.7 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	1.37 mg/kg dwt
	Soil - Equilibrium Partitioning	2.68 mg/kg dwt
	Secondary Poisoning	20 mg/kg

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 8: Exposure controls/personal protection

(breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Beige.
- Odour** : Aromatic. [Slight]
- Melting point/freezing point** : Not determined.
- Boiling point or initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: 35°C
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Hydrocarbons, C9, aromatics < 0.1% cumene	280 to 470	536 to 878	

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- pH** : Not applicable. insoluble in water.
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): >400 mm²/s
Kinematic (40°C): >21 mm²/s

Code : 000001099376 Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM

SECTION 9: Physical and chemical properties

Viscosity : > 100 s (ISO 6mm)

Solubility :

Media	Result
cold water	Not soluble

Partition coefficient n-octanol/
water (log Pow) : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-methylpropan-1-ol	<12.00102	<1.6	DIN EN 13016-2			

Relative density : 1.56

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Acute toxicity

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 11: Toxicological information

Product/ingredient name	Result	Dose / Exposure
Diis-[4-(2,3-epoxipropoxy)phenyl] propane	Rabbit - Dermal - LD50	23000 mg/kg
xylene	Rat - Oral - LD50	15000 mg/kg
Epoxy Resin (700<MW<=1100)	Rat - Oral - LD50	4.3 g/kg
Phenol, styrenated	Rabbit - Dermal - LD50	1.7 g/kg
	Rat - Oral - LD50	>2000 mg/kg
	Rat - Dermal - LD50	>2000 mg/kg
	Rabbit - Dermal - LD50	>5010 mg/kg
	<u>Toxic effects:</u> Gastrointestinal - Gastritis Liver - Other changes Kidney, Ureter, and Bladder - Other changes	
	Rat - Oral - LD50	3550 mg/kg
	<u>Toxic effects:</u> Behavioral - Food intake (animal) Gastrointestinal - Gastritis Liver - Other changes	
2-methylpropan-1-ol	Rat - Oral - LD50	2830 mg/kg
	Rabbit - Dermal - LD50	2460 mg/kg
ethylbenzene	Rat - Inhalation - LC50 Vapour	24.6 mg/l [4 hours]
	Rat - Oral - LD50	3.5 g/kg
	Rabbit - Dermal - LD50	17.8 g/kg
	Rat - Inhalation - LC50 Vapour	17.8 mg/l [4 hours]
	Rat - Oral - LD50	>2000 mg/kg
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine		
	Rat - Dermal - LD50	>2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	3.56 mg/l [4 hours]
Hydrocarbons, C9, aromatics < 0.1% cumene	Rat - Oral - LD50	8400 mg/kg
	<u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Lung, Thorax, or Respiration - Other changes	
	Rabbit - Male, Female - Dermal - LD50	>2000 mg/kg

Acute toxicity estimates

Route	ATE value
Dermal	19339.13 mg/kg
Inhalation (vapours)	112.77 mg/l
Inhalation (dusts and mists)	348 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
Diis-[4-(2,3-epoxipropoxy)phenyl] propane	Rabbit - Eyes - Redness of the conjunctivae Duration of treatment/exposure: 24 hours Irritation score: 0.4
-	Rabbit - Eyes - Mild irritant Duration of treatment/exposure: 24 hours Fully reversible in 7 days or less
-	Rabbit - Skin - Erythema/Eschar Duration of treatment/exposure: 4 hours Irritation score: 0.8
-	Rabbit - Skin - Oedema

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 11: Toxicological information

-	Duration of treatment/exposure: 4 hours Irritation score: 0.5
xylene	<u>Rabbit - Skin - Mild irritant</u> Duration of treatment/exposure: 4 hours <u>Rabbit - Skin - Moderate irritant</u> Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

Skin : Causes skin irritation.

Eyes : Causes serious eye irritation.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Test	Result
bis-[4-(2,3-epoxipropoxy)phenyl] propane	Mouse - skin	Result: Sensitising
Phenol, styrenated	Mouse - skin OECD 429	Result: Sensitising

Conclusion/Summary

Skin : May cause an allergic skin reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
Hydrocarbons, C9, aromatics < 0.1% cumene	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects

Conclusion/Summary

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-
ethylbenzene	Category 2	-	hearing organs
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Category 2	inhalation	lungs

Conclusion/Summary

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Code : 000001099376 Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM

SECTION 11: Toxicological information

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9, aromatics < 0.1% cumene	ASPIRATION HAZARD - Category 1

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : No specific data.
Ingestion : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

- General** : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.
Other information :

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 11: Toxicological information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
Is-[4-(2,3-epoxypropoxy)phenyl]propane	Chronic - NOEC	Daphnia	0.3 mg/l [21 days]
Phenol, styrenated 2-methylpropan-1-ol ethylbenzene	Acute - LC50 - Fresh water	Daphnia - <i>daphnia magna</i>	1.8 mg/l [48 hours]
	Acute - EC50	Daphnia	3.8 mg/l [48 hours]
	Acute - EC50	Daphnia	1100 mg/l [48 hours]
	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	1 mg/l
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Acute - LC50	Fish - <i>Oncorhynchus mykiss</i> (rainbow trout)	>100 mg/l [96 hours]
	Acute - EC50	Daphnia - <i>Daphnia magna</i> (Water flea)	>100 mg/l [48 hours]
	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i> (microalgae)	>100 mg/l [72 hours]
	Chronic - NOEC	Daphnia - <i>Daphnia magna</i> (Water flea)	≥50 mg/l [21 days]
Hydrocarbons, C9, aromatics < 0.1% cumene	Chronic - NOEC	Algae - <i>Pseudokirchneriella subcapitata</i>	100 mg/l [72 hours]
	LC50	Fish	9.2 mg/l [96 hours]

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 12: Ecological information

Product/ingredient name	Test	Result	Dose / Inoculum
Phenol, styrenated ethylbenzene 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine Hydrocarbons, C9, aromatics < 0.1% cumene	OECD 301F - OECD [Ready Biodegradability - Closed Bottle Test] -	7% [28 days] - Not readily 79% [10 days] - Readily 9% [29 days] - Not readily 78% [28 days]	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	-	Not readily
xylene	-	-	Readily
Phenol, styrenated ethylbenzene	-	-	Not readily
Hydrocarbons, C9, aromatics < 0.1% cumene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
2-methylpropan-1-ol	1	-	Low
ethylbenzene	3.6	79.43	Low
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	>6	-	High
Hydrocarbons, C9, aromatics < 0.1% cumene	3.7 to 4.5	10 to 2500	High

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
Bis-[4-(2,3-epoxipropoxy)phenyl]propane	4.02	10465.7
2-methylpropan-1-ol	1.08	12.0246
ethylbenzene	2.23	170.406

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 000001099376 Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste :

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(bis-[4-(2,3-epoxipropoxy)phenyl]propane)	Not applicable.

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 14: Transport information

Additional information

- ADR/RID** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.
- Tunnel code** : (D/E)
- ADN** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.
- IMDG** : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
SIGMAGUARD 730 BASE CREAM	3

Labelling : Not applicable.

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E2

National regulations

Code : 000001099376 Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM

SECTION 15: Regulatory information

Social Security Code, Articles L 461-1 to L 461-7	: Bis-[4-(2,3-epoxipropoxy)phenyl]propane xylene Epoxy Resin (700<MW<=1100) 2-methylpropan-1-ol Quartz (SiO ₂) ethylbenzene Phenol, polymer with formaldehyde, glycidyl ether (MW <=700) Hydrocarbons, C9, aromatics < 0.1% cumene	RG 84 RG 4bis, RG 84 RG 51 RG 84 RG 25 RG 84 RG 51 RG 4Bis, RG 84
Reinforced medical surveillance	: Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable	
References	: Reinforced medical surveillance ; Decree no. 2001-97 of 1 February 2001 establishing specific rules for the prevention of risks from carcinogens, mutagens and reprotoxics and amending the Labour code ; Decree no. 2003-1254 of 23 December 2003 relating to prevention of chemical risks and amending the Labour code ; Decree no. 2004-187 of 26 February 2004 on the placing on the market of biocidal products ; Decree no. 88-1231 of 29/12/1988 relating to poisonous preparations and substances. ; Decree no. 95-517 of 15 May 1997, relating to the classification of dangerous waste. ; Labour code article: R231-53 ; Labour code: Occupational air (ventilation, air purification): Art. R 232-5 to R 232-5-14 ; Labour code: Prevention of chemical risk: Art.R231-51 and R 231-54 to R 231-54-9 ; Labour code: Prevention of fires: Art.R232-12-13 to R 232-12-29 and R 233-30 ; Labour code: provisions applicable to women: Art. L 234-3 to L 236-6 ; Labour code: provisions applicable to young workers: Art. L 234-3 to L 236-6; Art: R234-16 ; Labour code: Sanitary installations: Art. R 232-2 à R 232-2-7 ; Law 76-663 of 19 July 1976 amending and implementing decree of 21 September 1977 relating to classified installations for the protection of the environment ; Tables of anticipated professional diseases according to article R461-3 of the labour code	

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Code : 000001099376	Date of issue/Date of revision : 12 June 2025
SIGMAGUARD 730 BASE CREAM	

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225 H226 H304 H312 H315 H317 H318 H319 H332 H335 H336 H372 H373	Highly flammable liquid and vapour. Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure.
H411 H412 H413 EUH066	Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life. Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Aquatic Chronic 4 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1B STOT RE 1	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 12 June 2025

Date of previous issue : 28 April 2025

Prepared by : EHS

Version : 1.05

Disclaimer

English (GB)	France	20/21
---------------------	---------------	--------------

Code : 000001099376

Date of issue/Date of revision

: 12 June 2025

SIGMAGUARD 730 BASE CREAM

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.