

# SAFETY DATA SHEET

Date of issue/Date of revision

: 16 June 2025

Version

: 6.01



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMASHIELD 880 BASE YELLOW BS 10E53

**Product code** : 00317914

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person  
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Poison Information Centre; emergency telephone, public + 45 82 12 12 12 (health sector +45 35 31 55 55)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Muta. 2, H341

STOT RE 2, H373

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms : 

- Signal word : Warning
- Hazard statements : Flammable liquid and vapour.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of causing genetic defects.  
May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

Precautionary statements

- Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour.
- Response : Collect spillage.
- Storage : Not applicable.
- Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P280, P210, P273, P260, P391, P501

Hazardous ingredients : bis-[4-(2,3-epoxipropoxy)phenyl]propane; Epoxy Resin (700<MW<=1100); Phenol, methylstyrenated; 2,3-epoxypropyl neodecanoate; Quartz (SiO2) and 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

- Containers to be fitted with child-resistant fastenings : Not applicable.
- Tactile warning of danger : Not applicable.

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.
- Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                              | Identifiers                                                                            | % by weight | Classification                                                                                                                                                                 | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|------------------------------------------------------|----------------------------------------------------------------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane              | REACH #:<br>01-2119456619-26<br>EC: 216-823-5<br>CAS: 1675-54-3<br>Index: 603-073-00-2 | ≥10 - ≤25   | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                                                                                     | Skin Irrit. 2, H315: C ≥ 5%<br>Eye Irrit. 2, H319: C ≥ 5%         | [1]     |
| xylene                                               | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7                        | ≥5.0 - ≤10  | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | ATE [Dermal] = 1700 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| Epoxy Resin (700<MW ≤1100)                           | CAS: 25036-25-3                                                                        | ≥1.0 - ≤5.0 | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317                                                                                                                | -                                                                 | [1]     |
| Phenol, methylstyrenated                             | REACH #:<br>01-2119555274-38<br>EC: 270-966-8<br>CAS: 68512-30-1                       | ≥1.0 - ≤5.0 | Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412                                                                                                           | -                                                                 | [1] [3] |
| 2-methylpropan-1-ol                                  | REACH #:<br>01-2119484609-23<br>EC: 201-148-0<br>CAS: 78-83-1<br>Index: 603-108-00-1   | ≥1.0 - <3.0 | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336                                                                            | -                                                                 | [1] [2] |
| 2,3-epoxypropyl neodecanoate                         | REACH #:<br>01-2119431597-33<br>EC: 247-979-2<br>CAS: 26761-45-5                       | ≥1.0 - ≤5.0 | Skin Sens. 1, H317<br>Muta. 2, H341<br>Aquatic Chronic 2, H411                                                                                                                 | -                                                                 | [1]     |
| crystalline silica, respirable powder (<10 microns)  | EC: 238-878-4<br>CAS: 14808-60-7                                                       | ≥1.0 - ≤5.0 | STOT RE 1, H372 (inhalation)                                                                                                                                                   | -                                                                 | [1] [2] |
| ethylbenzene                                         | REACH #:<br>01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4  | ≥1.0 - ≤5.0 | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373 (hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412                                                   | ATE [Inhalation (vapours)] = 17.8 mg/l                            | [1] [2] |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | REACH #:<br>01-2119962189-26<br>CAS: 911674-82-3<br>Index: 616-198-00-2                | <1.0        | Skin Sens. 1, H317<br>Aquatic Chronic 4, H413                                                                                                                                  | -                                                                 | [1]     |

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 3: Composition/information on ingredients

|                             |                                                                                        |       |                                                                                                                              |                                  |     |
|-----------------------------|----------------------------------------------------------------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-----|
| trizinc bis(orthophosphate) | REACH #:<br>01-2119485044-40<br>EC: 231-944-3<br>CAS: 7779-90-0<br>Index: 030-011-00-6 | ≤0.30 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br><br>See Section 16 for the full text of the H statements declared above. | M [Acute] = 1<br>M [Chronic] = 1 | [1] |
|-----------------------------|----------------------------------------------------------------------------------------|-------|------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-----|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

- [1] Substance classified with a health or environmental hazard
  - [2] Substance with a workplace exposure limit
  - [3] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.

|                                      |                                                      |
|--------------------------------------|------------------------------------------------------|
| <b>Code</b> : 00317914               | <b>Date of issue/Date of revision</b> : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |                                                      |

## SECTION 4: First aid measures

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Code : 00317914

Date of issue/Date of revision

: 16 June 2025

SIGMASHIELD 880 BASE YELLOW BS 10E53

## SECTION 6: Accidental release measures

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

#### Small spill

- : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

- : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

#### Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 7: Handling and storage

Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name                             | Exposure limit values                                                                                                                                                                                                                                         |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| xylene                                              | <b>Working Environment Authority (Denmark, 3/2024) [xylen, alle isomere]</b> Absorbed through skin.<br>TWA 8 hours: 25 ppm.<br>TWA 8 hours: 109 mg/m³.<br>STEL 15 minutes: 442 mg/m³.<br>STEL 15 minutes: 100 ppm.                                            |
| 2-methylpropan-1-ol                                 | <b>Working Environment Authority (Denmark, 3/2024) [butanol, alle isomere]</b> Absorbed through skin.<br>CEIL: 50 ppm.<br>CEIL: 150 mg/m³.                                                                                                                    |
| crystalline silica, respirable powder (<10 microns) | <b>Working Environment Authority (Denmark, 3/2024) K.</b><br>TWA 8 hours: 0.1 mg/m³. Form: Respirable fraction.<br>TWA 8 hours: 0.3 mg/m³. Form: total.<br>STEL 15 minutes: 0.6 mg/m³. Form: total.<br>STEL 15 minutes: 0.2 mg/m³. Form: Respirable fraction. |
| ethylbenzene                                        | <b>Working Environment Authority (Denmark, 3/2024) K.</b> Absorbed through skin.<br>TWA 8 hours: 50 ppm.<br>TWA 8 hours: 217 mg/m³.<br>STEL 15 minutes: 434 mg/m³.<br>STEL 15 minutes: 100 ppm.                                                               |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Code : 00317914

Date of issue/Date of revision

: 16 June 2025

SIGMASHIELD 880 BASE YELLOW BS 10E53

## SECTION 8: Exposure controls/personal protection

| Product/ingredient name                 | Exposure                                                    | Value                                            |
|-----------------------------------------|-------------------------------------------------------------|--------------------------------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Systemic</i> 12.25 mg/m <sup>3</sup> |
|                                         | DNEL - Workers - Short term - Inhalation                    | <i>Effects: Systemic</i> 12.25 mg/m <sup>3</sup> |
|                                         | DNEL - Workers - Long term - Dermal                         | <i>Effects: Systemic</i> 8.33 mg/kg bw/day       |
|                                         | DNEL - Workers - Short term - Dermal                        | <i>Effects: Systemic</i> 8.33 mg/kg bw/day       |
|                                         | DNEL - General population - Consumers - Long term - Dermal  | <i>Effects: Systemic</i> 3.571 mg/kg bw/day      |
|                                         | DNEL - General population - Consumers - Short term - Dermal | <i>Effects: Systemic</i> 3.571 mg/kg bw/day      |
|                                         | DNEL - General population - Consumers - Long term - Oral    | <i>Effects: Systemic</i> 0.75 mg/kg bw/day       |
|                                         | DNEL - General population - Consumers - Short term - Oral   | <i>Effects: Systemic</i> 0.75 mg/kg bw/day       |
|                                         | DNEL - General population - Long term - Dermal              | <i>Effects: Systemic</i> 89.3 µg/kg bw/day       |
|                                         | DNEL - General population - Long term - Oral                | <i>Effects: Systemic</i> 0.5 mg/kg bw/day        |
|                                         | DNEL - Workers - Long term - Dermal                         | <i>Effects: Systemic</i> 0.75 mg/kg bw/day       |
|                                         | DNEL - General population - Long term - Inhalation          | <i>Effects: Systemic</i> 0.87 mg/m <sup>3</sup>  |
|                                         | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Systemic</i> 4.93 mg/m <sup>3</sup>  |
|                                         | DNEL - General population - Long term - Oral                | <i>Effects: Systemic</i> 5 mg/kg bw/day          |
| xylene                                  | DNEL - General population - Long term - Inhalation          | <i>Effects: Local</i> 65.3 mg/m <sup>3</sup>     |
|                                         | DNEL - General population - Long term - Inhalation          | <i>Effects: Systemic</i> 65.3 mg/m <sup>3</sup>  |
|                                         | DNEL - General population - Long term - Dermal              | <i>Effects: Systemic</i> 125 mg/kg bw/day        |
|                                         | DNEL - Workers - Long term - Dermal                         | <i>Effects: Systemic</i> 212 mg/kg bw/day        |
| Phenol, methylstyrenated                | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Local</i> 221 mg/m <sup>3</sup>      |
|                                         | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Systemic</i> 221 mg/m <sup>3</sup>   |
|                                         | DNEL - General population - Short term - Inhalation         | <i>Effects: Local</i> 260 mg/m <sup>3</sup>      |
|                                         | DNEL - General population - Short term - Inhalation         | <i>Effects: Systemic</i> 260 mg/m <sup>3</sup>   |
|                                         | DNEL - Workers - Short term - Inhalation                    | <i>Effects: Local</i> 442 mg/m <sup>3</sup>      |
|                                         | DNEL - Workers - Short term - Inhalation                    | <i>Effects: Systemic</i> 442 mg/m <sup>3</sup>   |
|                                         | DNEL - General population - Long term - Oral                | <i>Effects: Systemic</i> 0.2 mg/kg bw/day        |
|                                         | DNEL - General population - Long term - Inhalation          | <i>Effects: Systemic</i> 0.348 mg/m <sup>3</sup> |
|                                         | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Systemic</i> 1.41 mg/m <sup>3</sup>  |
|                                         | DNEL - General population - Long term - Dermal              | <i>Effects: Systemic</i> 1.67 mg/kg bw/day       |
| 2-methylpropan-1-ol                     | DNEL - Workers - Long term - Dermal                         | <i>Effects: Systemic</i> 3.5 mg/kg bw/day        |
|                                         | DNEL - General population - Long term - Inhalation          | <i>Effects: Local</i> 55 mg/m <sup>3</sup>       |
| 2,3-epoxypropyl neodecanoate            | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Local</i> 310 mg/m <sup>3</sup>      |
|                                         | DNEL - General population - Long term - Dermal              | <i>Effects: Systemic</i> 2.5 mg/kg bw/day        |
| ethylbenzene                            | DNEL - General population - Long term - Inhalation          | <i>Effects: Systemic</i> 4 mg/m <sup>3</sup>     |
|                                         | DNEL - Workers - Long term - Dermal                         | <i>Effects: Systemic</i> 4.2 mg/kg bw/day        |
|                                         | DNEL - Workers - Long term - Inhalation                     | <i>Effects: Systemic</i> 5.88 mg/m <sup>3</sup>  |
|                                         | DNEL - General population - Long term - Oral                | <i>Effects: Systemic</i> 2.5 mg/kg bw/day        |
|                                         | DMEL - Workers - Long term - Inhalation                     | <i>Effects: Local</i> 442 mg/m <sup>3</sup>      |
|                                         | DMEL - Workers - Short term - Inhalation                    | <i>Effects: Systemic</i> 884 mg/m <sup>3</sup>   |
|                                         | DNEL - General population - Long term - Oral                | <i>Effects: Systemic</i> 1.6 mg/kg bw/day        |

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 8: Exposure controls/personal protection

|  |                                                    |                   |                  |
|--|----------------------------------------------------|-------------------|------------------|
|  | DNEL - General population - Long term - Inhalation | Effects: Systemic | 15 mg/m³         |
|  | DNEL - Workers - Long term - Inhalation            | Effects: Systemic | 77 mg/m³         |
|  | DNEL - Workers - Long term - Dermal                | Effects: Systemic | 180 mg/kg bw/day |
|  | DNEL - Workers - Short term - Inhalation           | Effects: Local    | 293 mg/m³        |

PNECs

| Product/ingredient name                  | Compartment Detail - Method                      | Value           |
|------------------------------------------|--------------------------------------------------|-----------------|
| bis-[4-(2,3-epoxipropoxy)phenyl] propane | Fresh water - Assessment Factors                 | 0.006 mg/l      |
|                                          | Marine water - Assessment Factors                | 0.001 mg/l      |
|                                          | Fresh water sediment - Equilibrium Partitioning  | 0.996 mg/kg dwt |
|                                          | Marine water sediment - Equilibrium Partitioning | 0.1 mg/kg dwt   |
|                                          | Soil - Equilibrium Partitioning                  | 0.196 mg/kg dwt |
|                                          | Sewage Treatment Plant - Assessment Factors      | 10 mg/l         |
| xylene                                   | Secondary Poisoning - Assessment Factors         | 11 mg/kg        |
|                                          | Fresh water                                      | 0.327 mg/l      |
|                                          | Marine water                                     | 0.327 mg/l      |
|                                          | Sewage Treatment Plant                           | 6.58 mg/l       |
|                                          | Fresh water sediment                             | 12.46 mg/kg dwt |
|                                          | Marine water sediment                            | 12.46 mg/kg dwt |
| 2-methylpropan-1-ol                      | Soil                                             | 2.31 mg/kg      |
|                                          | Fresh water - Assessment Factors                 | 0.4 mg/l        |
|                                          | Marine water - Assessment Factors                | 0.04 mg/l       |
|                                          | Sewage Treatment Plant - Assessment Factors      | 10 mg/l         |
|                                          | Fresh water sediment - Equilibrium Partitioning  | 1.56 mg/kg dwt  |
|                                          | Marine water sediment                            | 0.156 mg/kg dwt |
| ethylbenzene                             | Soil - Equilibrium Partitioning                  | 0.076 mg/kg dwt |
|                                          | Fresh water - Assessment Factors                 | 0.1 mg/l        |
|                                          | Marine water - Assessment Factors                | 0.01 mg/l       |
|                                          | Sewage Treatment Plant - Assessment Factors      | 9.6 mg/l        |
|                                          | Fresh water sediment - Equilibrium Partitioning  | 13.7 mg/kg dwt  |
|                                          | Marine water sediment - Equilibrium Partitioning | 1.37 mg/kg dwt  |
| trizinc bis(orthophosphate)              | Soil - Equilibrium Partitioning                  | 2.68 mg/kg dwt  |
|                                          | Secondary Poisoning                              | 20 mg/kg        |
|                                          | Fresh water - Sensitivity Distribution           | 20.6 µg/l       |
|                                          | Marine water - Sensitivity Distribution          | 6.1 µg/l        |
|                                          | Sewage Treatment Plant - Assessment Factors      | 100 µg/l        |
|                                          | Fresh water sediment - Sensitivity Distribution  | 117.8 mg/kg dwt |
|                                          | Marine water sediment - Equilibrium Partitioning | 56.5 mg/kg dwt  |
|                                          | Soil - Sensitivity Distribution                  | 35.6 mg/kg dwt  |

8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Code : 00317914

Date of issue/Date of revision

: 16 June 2025

SIGMASHIELD 880 BASE YELLOW BS 10E53

## SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Yellow.
- Odour** : Aromatic.
- Melting point/freezing point** : Not determined.
- Boiling point or initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Lower and upper explosion limit** : Not available.



|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- Causes serious eye irritation.
- Causes skin irritation.
- May cause an allergic skin reaction.
- Suspected of causing genetic defects.
- May cause damage to organs through prolonged or repeated exposure.

Acute toxicity

| Product/ingredient name                              | Result                                  | Dose / Exposure      |
|------------------------------------------------------|-----------------------------------------|----------------------|
| bis-[4-(2,3-epoxipropoxi)phenyl] propane             | Rabbit - Dermal - LD50                  | 23000 mg/kg          |
| xylene                                               | Rat - Oral - LD50                       | 15000 mg/kg          |
| Epoxy Resin (700<MW<=1100)                           | Rat - Oral - LD50                       | 4.3 g/kg             |
| Phenol, methylstyrenated                             | Rabbit - Dermal - LD50                  | 1.7 g/kg             |
| 2-methylpropan-1-ol                                  | Rat - Oral - LD50                       | >2000 mg/kg          |
| 2,3-epoxypropyl neodecanoate                         | Rat - Dermal - LD50                     | >2000 mg/kg          |
| ethylbenzene                                         | Rat - Oral - LD50                       | >2000 mg/kg          |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | Rabbit - Dermal - LD50                  | >2000 mg/kg          |
| trizinc bis(orthophosphate)                          | Rat - Oral - LD50                       | 2830 mg/kg           |
|                                                      | Rabbit - Dermal - LD50                  | 2460 mg/kg           |
|                                                      | Rat - Inhalation - LC50 Vapour          | 24.6 mg/l [4 hours]  |
|                                                      | Rat - Oral - LD50                       | 9.6 g/kg             |
|                                                      | Rat - Dermal - LD50                     | 3800 mg/kg           |
|                                                      | Rat - Oral - LD50                       | 3.5 g/kg             |
|                                                      | Rabbit - Dermal - LD50                  | 17.8 g/kg            |
|                                                      | Rat - Inhalation - LC50 Vapour          | 17.8 mg/l [4 hours]  |
|                                                      | Rat - Inhalation - LC50 Dusts and mists | >5.08 mg/l [4 hours] |
|                                                      | Rat - Oral - LD50                       | >5000 mg/kg          |
|                                                      | Rat - Inhalation - LC50 Dusts and mists | >5.7 mg/l [4 hours]  |

Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Dermal               | 29799.76 mg/kg |
| Inhalation (vapours) | 173.65 mg/l    |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

| Product/ingredient name                  | Result                                                                                                           |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| bis-[4-(2,3-epoxipropoxi)phenyl] propane | Rabbit - Eyes - Redness of the conjunctivae<br>Duration of treatment/exposure: 24 hours<br>Irritation score: 0.4 |
| -                                        | Rabbit - Eyes - Mild irritant<br>Duration of treatment/exposure: 24 hours<br>Fully reversible in 7 days or less  |
| -                                        | Rabbit - Skin - Erythema/Eschar<br>Duration of treatment/exposure: 4 hours<br>Irritation score: 0.8              |
| -                                        | Rabbit - Skin - Oedema<br>Duration of treatment/exposure: 4 hours<br>Irritation score: 0.5                       |

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 11: Toxicological information

|        |                                                                                                                       |
|--------|-----------------------------------------------------------------------------------------------------------------------|
| -      | Rabbit - Skin - Mild irritant<br>Duration of treatment/exposure: 4 hours                                              |
| xylene | Rabbit - Skin - Moderate irritant<br>Amount/concentration applied: 500 mg<br>Duration of treatment/exposure: 24 hours |

Conclusion/Summary

**Skin** : Causes skin irritation.  
**Eyes** : Causes serious eye irritation.  
**Respiratory** : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

| Product/ingredient name                     | Test         | Result              |
|---------------------------------------------|--------------|---------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]<br>propane | Mouse - skin | Result: Sensitising |

Conclusion/Summary

**Skin** : May cause an allergic skin reaction.  
**Respiratory** : Based on available data, the classification criteria are not met.

Mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| xylene                  | Category 3 | -                 | Respiratory tract irritation |
| 2-methylpropan-1-ol     | Category 3 | -                 | Respiratory tract irritation |
| -                       | Category 3 | -                 | Narcotic effects             |

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name                             | Category   | Route of exposure | Target organs  |
|-----------------------------------------------------|------------|-------------------|----------------|
| crystalline silica, respirable powder (<10 microns) | Category 1 | inhalation        | -              |
| ethylbenzene                                        | Category 2 | -                 | hearing organs |

Conclusion/Summary :

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

Conclusion/Summary :

Based on available data, the classification criteria are not met.

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 11: Toxicological information

Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.
- Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation : No specific data.
- Ingestion : No specific data.
- Skin contact : Adverse symptoms may include the following:
  - irritation
  - redness
  - dryness
  - cracking
- Eye contact : Adverse symptoms may include the following:
  - pain or irritation
  - watering
  - redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects : No known significant effects or critical hazards.
- Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects : No known significant effects or critical hazards.
- Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

- General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity : No known significant effects or critical hazards.
- Mutagenicity : Suspected of causing genetic defects.
- Reproductive toxicity : No known significant effects or critical hazards.
- Other information : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 11: Toxicological information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

| Product/ingredient name                              | Result                       | Species                             | Dose / Exposure       |
|------------------------------------------------------|------------------------------|-------------------------------------|-----------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane              | Chronic - NOEC               | Daphnia                             | 0.3 mg/l [21 days]    |
| 2-methylpropan-1-ol                                  | Acute - LC50 - Fresh water   | Daphnia - <i>daphnia magna</i>      | 1.8 mg/l [48 hours]   |
| 2,3-epoxypropyl neodecanoate                         | Acute - EC50                 | Daphnia                             | 1100 mg/l [48 hours]  |
|                                                      | Acute - LC50                 | Fish - <i>Oncorhynchus mykiss</i>   | 9.6 mg/l [96 hours]   |
|                                                      | Acute - EC50                 | Daphnia - <i>Daphnia magna</i>      | 4.8 mg/l [48 hours]   |
| ethylbenzene                                         | Acute - EC50                 | Algae                               | 3.5 mg/l [96 hours]   |
|                                                      | Acute - EC50 - Fresh water   | Daphnia                             | 1.8 mg/l [48 hours]   |
|                                                      | Chronic - NOEC - Fresh water | Daphnia - <i>Ceriodaphnia dubia</i> | 1 mg/l                |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | Acute - LC50                 | Fish                                | >100 mg/l [96 hours]  |
| trizinc bis(orthophosphate)                          | Acute - LC50                 | Fish                                | 0.112 mg/l [96 hours] |
|                                                      | Chronic - NOEC               | Fish                                | 0.026 mg/l [30 days]  |

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result                  | Dose / Inoculum |
|-------------------------|------|-------------------------|-----------------|
| ethylbenzene            | -    | 79% [10 days] - Readily |                 |

| Product/ingredient name                 | Aquatic half-life | Photolysis | Biodegradability |
|-----------------------------------------|-------------------|------------|------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | -                 | -          | Not readily      |
| xylene                                  | -                 | -          | Readily          |
| 2,3-epoxypropyl neodecanoate            | -                 | -          | Not readily      |
| ethylbenzene                            | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name      | LogP <sub>ow</sub> | BCF         | Potential |
|------------------------------|--------------------|-------------|-----------|
| xylene                       | 3.12               | 7.4 to 18.5 | Low       |
| Phenol, methylstyrenated     | 3.627              | -           | Low       |
| 2-methylpropan-1-ol          | 1                  | -           | Low       |
| 2,3-epoxypropyl neodecanoate | 4.4                | -           | High      |
| ethylbenzene                 | 3.6                | 79.43       | Low       |

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient

| Product/ingredient name                 | logKoc | Koc     |
|-----------------------------------------|--------|---------|
| bis-[4-(2,3-epoxipropoxi)phenyl]propane | 4.02   | 10465.7 |
| 2-methylpropan-1-ol                     | 1.08   | 12.0246 |
| ethylbenzene                            | 2.23   | 170.406 |

12.5 Results of PBT and vPvB assessment

| Product/ingredient name                              | PBT | P   | B   | T   | vPvB             | vP        | vB        |
|------------------------------------------------------|-----|-----|-----|-----|------------------|-----------|-----------|
| bis-[4-(2,3-epoxipropoxi)phenyl]propane              | No  | N/A | N/A | No  | N/A              | N/A       | N/A       |
| xylene                                               | No  | N/A | No  | No  | No               | N/A       | No        |
| Epoxy Resin (700<MW<=1100)                           | No  | N/A | N/A | No  | N/A              | N/A       | N/A       |
| Phenol, methylstyrenated                             | No  | N/A | N/A | No  | SVHC (Candidate) | Specified | Specified |
| 2-methylpropan-1-ol                                  | No  | N/A | N/A | No  | N/A              | N/A       | N/A       |
| 2,3-epoxypropyl neodecanoate                         | No  | N/A | N/A | No  | N/A              | N/A       | N/A       |
| ethylbenzene                                         | No  | N/A | No  | Yes | No               | N/A       | No        |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | No  | N/A | N/A | No  | N/A              | N/A       | N/A       |

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Methods of disposal            | : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste                | :                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| European waste catalogue (EWC) |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Waste code                     | Waste designation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 08 01 11*                      | waste paint and varnish containing organic solvents or other hazardous substances                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 13: Disposal considerations

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.                                                                                                                                                                                                                                                                                                                                          |
| Type of packaging   | European waste catalogue (EWC)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Container           | 15 01 06 mixed packaging                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

|                                 |                 |                 |                                           |                                                                    |
|---------------------------------|-----------------|-----------------|-------------------------------------------|--------------------------------------------------------------------|
|                                 | ADR/RID         | ADN             | IMDG                                      | IATA                                                               |
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263                                    | UN1263                                                             |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT                                     | PAINT                                                              |
| 14.3 Transport hazard class(es) | 3               | 3               | 3                                         | 3                                                                  |
| 14.4 Packing group              | III             | III             | III                                       | III                                                                |
| 14.5 Environmental hazards      | Yes.            | Yes.            | Yes.                                      | Yes. The environmentally hazardous substance mark is not required. |
| Marine pollutant substances     | Not applicable. | Not applicable. | (bis-[4-(2,3-epoxipropoxy)phenyl]propane) | Not applicable.                                                    |

Additional information

|             |                                                                                                                                                                                                                                                     |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ADR/RID     | : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2. |
| Tunnel code | : (D/E)                                                                                                                                                                                                                                             |
| ADN         | : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2. |
| IMDG        | : This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.     |
| IATA        | : The environmentally hazardous substance mark may appear if required by other transportation regulations.                                                                                                                                          |

|                                   |                                                                                                                                                                                                                     |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 14.6 Special precautions for user | : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)  
Annex XIV - List of substances subject to authorisation  
Annex XIV

None of the components are listed.  
Substances of very high concern

| Intrinsic property | Ingredient name          | Status    | Reference number | Date of revision |
|--------------------|--------------------------|-----------|------------------|------------------|
| vPvB               | Phenol, methylstyrenated | Candidate | D(2023) 8585-DC  | 1/23/2024        |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name              | Entry Number ( REACH ) |
|--------------------------------------|------------------------|
| SIGMASHIELD 880 BASE YELLOW BS 10E53 | 3                      |

Labelling : Not applicable.  
Explosive precursors : Not applicable.  
Ozone depleting substances (EU 2024/590)  
Not listed.

Seveso Directive  
This product is controlled under the Seveso Directive.  
Danger criteria

| Category  |
|-----------|
| P5c<br>E2 |

National regulations  
Product registration number : PR-2361505  
Fire class : II-1  
Executive Order No. 1795/2015

| Ingredient name                              | Annex I Section A | Annex I Section B  |
|----------------------------------------------|-------------------|--------------------|
| ethylbenzene<br>2,3-epoxypropyl neodecanoate | Listed<br>-       | -<br>Muta. 2, H341 |

MAL-code : 3-5

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 15: Regulatory information

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/ protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 3-5  
**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask, protective clothing and eye protection must be worn.

When spraying in new\* booths if the operator is outside the spray zone.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone. During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 15: Regulatory information

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Restrictions on use : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances : Listed
- Carcinogenic waste : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
PBT = Persistent, Bioaccumulative and Toxic  
vPvB = Very Persistent and Very Bioaccumulative  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
IMDG = International Maritime Dangerous Goods  
IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification                                                                                                                                       | Justification                                                                                                                                             |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Muta. 2, H341<br>STOT RE 2, H373<br>Aquatic Chronic 2, H411 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

Full text of abbreviated H statements

|                                      |            |                                |                |
|--------------------------------------|------------|--------------------------------|----------------|
| Code                                 | : 00317914 | Date of issue/Date of revision | : 16 June 2025 |
| SIGMASHIELD 880 BASE YELLOW BS 10E53 |            |                                |                |

SECTION 16: Other information

|      |                                                                    |
|------|--------------------------------------------------------------------|
| H225 | Highly flammable liquid and vapour.                                |
| H226 | Flammable liquid and vapour.                                       |
| H304 | May be fatal if swallowed and enters airways.                      |
| H312 | Harmful in contact with skin.                                      |
| H315 | Causes skin irritation.                                            |
| H317 | May cause an allergic skin reaction.                               |
| H318 | Causes serious eye damage.                                         |
| H319 | Causes serious eye irritation.                                     |
| H332 | Harmful if inhaled.                                                |
| H335 | May cause respiratory irritation.                                  |
| H336 | May cause drowsiness or dizziness.                                 |
| H341 | Suspected of causing genetic defects.                              |
| H372 | Causes damage to organs through prolonged or repeated exposure.    |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life.                                        |
| H410 | Very toxic to aquatic life with long lasting effects.              |
| H411 | Toxic to aquatic life with long lasting effects.                   |
| H412 | Harmful to aquatic life with long lasting effects.                 |
| H413 | May cause long lasting harmful effects to aquatic life.            |

Full text of classifications [CLP/GHS]

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Aquatic Chronic 4 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Muta. 2           | GERM CELL MUTAGENICITY - Category 2                             |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

History

|                                 |                |
|---------------------------------|----------------|
| Date of issue/ Date of revision | : 16 June 2025 |
| Date of previous issue          | : 3 March 2025 |
| Prepared by                     | : EHS          |
| Version                         | : 6.01         |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.