# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2023.

Date of issue/Date of revision 23 June 2025

Version 4.02

### Section 1. Identification

Product name : 2550 WB URETHANE GLOSS CATALYST - B

Product code : 00462418

Other means of : Not available.

identification

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Professional applications, Used by spraying.

Use of the substance/

mixture

: Hardener.

Uses advised against : Not applicable.

Supplier : PPG Canada Inc.

5676 Timberlea Blvd Mississauga ON L4W 4M6

Canada

+1 905-629-7999

PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272

**Emergency telephone** 

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

### Section 2. Hazard identification

Classification of the substance or mixture

: ACUTE TOXICITY (inhalation) - Category 4

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

RESPIRATORY SENSITIZATION - Category 1A

SKIN SENSITIZATION - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

**GHS label elements** 

Hazard pictograms :





Canada Page: 1/14

### Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 2. Hazard identification

Signal word

: Danger

**Hazard statements** 

: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause respiratory irritation.

#### **Precautionary statements**

**Prevention** 

: Wear protective gloves. Wear eye or face protection. Wear respiratory protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage Disposal**  : Store locked up. Store in a well-ventilated place. Keep container tightly closed.

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Moisture-sensitive material. Skin contact to isocyanate monomer may lead to allergic lung reaction. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Emits toxic fumes when heated. Percentage of the mixture consisting of ingredient(s) of unknown acute dermal

toxicity: 18.6%

Other hazards which do not : None known. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

**Product name** 

: 2550 WB URETHANE GLOSS CATALYST - B

Other means of identification

: Not available.

**CAS** number/other identifiers

Canada Page: 2/14

# Section 3. Composition/information on ingredients

Ingredient name	Synonyms	% (w/w)	CAS number
Mexamethylene diisocyanate, oligomers (Iminooxadiazindione type)	Hexane, 1,6-diisocyanato-, homopolymer; Hexamethylene diisocyanate, homopolymer; Hexamethylene diisocyanate polymer; Isocyanic acid, hexamethylene ester; Hexamethylene diisocyanate (HDI) homopolymer; Poly (hexamethylene diisocyanate); Polymer of 1,6-diisocyanatohexane; Trimer of isocyanate monomer (including crude tolylene diisocyanate, polymethylene polyphenyl polyisocyanate), and polymer thereof (i.e. isocyanurate-containing isocyanate).; Polymer (i.e.urethodione group bearing isocyanate) of isocyanate monomer; Condensate (i.e.carbodiimide group-bearing isocyanate) or isocyanate monomer; 1,6-Diisocyanatohexane homopolymer	65 - 85*	28182-81-2
Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino) -1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	N,N-dimethylcyclohexanamine, compounds with 3-cyclohexylamino- 1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer; N, N-Dimethylcyclohexanamine compds. with 3-(cyclohexylamino) -1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	10 - 30*	666723-27-9
cyclohexyldimethylamine	Cyclohexanamine, N,N-dimethyl-; N,N'-Dimethylcyclohexylamine; N, N-Dimethylcyclohexylamine; Cyclohexylamine, N,N-dimethyl-; DIMETHYLCYCLOHEXYLAMINE; CYCLOHEXANAMINE, N,N-DIMETHYL; n,n-dimethylcyclohexylamine; N,N-Dimethylcyclohexylamine (8CA); N,N-Dimethylcyclohexanamine; N,N-Dimethylaminocyclohexane; N-Alkyl (C1-4)-N-alkyl (C1-4) cyclohexylamine	0.5 - 1.5*	98-94-2
hexamethylene-di-isocyanate	hexamethylene diisocyanate; Hexane, 1,6-diisocyanato-; 1,6-Hexamethylene diisocyanate; Hexamethylene-1,6-diisocyanate; 1,6-Diisocyanatohexane; HMDI; HDI; isocyanic acid, diester with 1,6-hexanediol; 1,6-hexanediol diisocyanate; 1,6-Diisocyantohexane; HEXAMETHYLENE-DIISOCYANATE	0.1 - 1*	822-06-0

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

Canada Page: 3/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

trained personner.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

Canada Page: 4/14

### Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 4. First-aid measures

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal** decomposition products

: Decomposition products may include the following materials:

carbon oxides nitrogen oxides sulfur oxides

Cyanate and isocyanate. hydrogen cyanide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways. drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Canada Page: 5/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 6. Accidental release measures

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

#### **Special provisions**

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

# Section 7. Handling and storage

#### Precautions for safe handling

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Special precautions**

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

# Advice on general occupational hygiene

Wash hands thoroughly after handling.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Canada Page: 6/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Precautions should be taken to minimize exposure to atmospheric humidity or water. CO<sub>2</sub> will be formed, which, in closed containers, could result in pressurization.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
Fexamethylene diisocyanate, oligomers (Iminooxadiazindione type)	CA Quebec Provincial (Canada, 2/2024) [Isocyanate oligomers] Sensitizer.
Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)	CA Quebec Provincial (Canada, 2/2024)
-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	[Isocyanate oligomers] Sensitizer.
cyclohexyldimethylamine	CA Ontario Provincial (Canada, 6/2019) STEL 15 minutes: 26 mg/m³. STEL 15 minutes: 5 ppm.
hexamethylene-di-isocyanate	CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 0.005 ppm. OEL 8 hours: 0.03 mg/m³.
	CA British Columbia Provincial (Canada,
	4/2024) Inhalation sensitizer.
	TWA 8 hours: 0.005 ppm.
	C: 0.01 ppm.
	CA Ontario Provincial (Canada, 6/2019)
	[Isocyanates, organic compounds]
	Ceiling Limit: 0.02 ppm.
	TWA 8 hours: 0.005 ppm.
	CA Quebec Provincial (Canada, 2/2024)
	Sensitizer.
	TWAEV 8 hours: 0.005 ppm.
	TWAEV 8 hours: 0.034 mg/m³.
	CA Saskatchewan Provincial (Canada,
	4/2021)
	STEL 15 minutes: 0.015 ppm. TWA 8 hours: 0.005 ppm.
	1 VVA o Hours. 0.003 ppm.

#### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Canada Page: 7/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

# Section 8. Exposure controls/personal protection

### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection Hand protection** 

: Chemical splash goggles.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

: butyl rubber **Gloves** 

: Personal protective equipment for the body should be selected based on the task **Body protection** being performed and the risks involved and should be approved by a specialist

before handling this product.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: Use an air-fed respirator unless a site-specific assessment determines that an air-**Respiratory protection** 

fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits

of the selected respirator.

Restrictions on use Persons with a history of asthma, allergies or chronic or recurrent respiratory

disease should not be employed in any process in which this product is used.

# Section 9. Physical and chemical properties

#### **Appearance**

**Physical state** : Liquid.

Color : Yellow. [Light] : Characteristic. Odor : Not applicable. **Melting point** : Not available. **Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: 185°C (365°F)

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available. **Flammability** : Not available.

Canada Page: 8/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 9. Physical and chemical properties

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 1.15 Density ( lbs / gal ) : 9.6

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

% Solid. (w/w) : 100

**Particle characteristics** 

**Median particle size** : Not applicable.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : In a fire, hazardous decomposition products may be produced.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols,

water. Uncontrolled exothermic reactions occur with amines and alcohols.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following materials: Cyanate and isocyanate. carbon oxides nitrogen oxides sulfur oxides hydrogen

cyanide

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Dose
Fexamethylene diisocyanate, oligomers (Iminooxadiazindione type)	Rat - Male, Female - Oral - LD50	>5000 mg/kg
	Rat - Dermal - LD50	>2000 mg/kg
Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	Rat - Oral - LD50	>5000 mg/kg
cyclohexyldimethylamine	Rat - Dermal - LD50	370 mg/kg

Canada Page: 9/14

### Product name 2550 WB URETHANE GLOSS CATALYST - B

### **Section 11. Toxicological information**

<del>_</del>		
	Rat - Oral - LD50	0.272 g/kg
	Rat - Inhalation - LC50 Vapor	9 mg/l [1 hours]
hexamethylene-di-isocyanate	Rat - Oral - LD50	0.71 g/kg
	Rabbit - Dermal - LD50	0.57 g/kg
	Rat - Inhalation - LC50 Vapor	151 mg/m³ [4 hours]
	Rat - Inhalation - LC50 Dusts and	124 mg/m³ [4 hours]
	mists	

Product Conclusion : There are no data available on the mixture itself.

**Skin corrosion/irritation** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Serious eye damage/eye irritation

**Conclusion/Summary**: There are no data available on the mixture itself.

Respiratory corrosion/irritation

**Conclusion/Summary**: There are no data available on the mixture itself.

Sensitization Skin

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory

**Conclusion/Summary**: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Hexamethylene diisocyanate, oligomers (Iminooxadiazindione type) Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
homopolymer hexamethylene-di-isocyanate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

<u>Target organs</u>: Contains material which may cause damage to the following organs: upper respiratory tract, skin, central nervous system (CNS).

### Information on the likely routes of exposure

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### **Over-exposure signs/symptoms**

Canada	Page: 10/14
--------	-------------

### Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 11. Toxicological information

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. Skin contact

There are no data available on the mixture itself. Skin contact to isocyanate monomer may lead to allergic lung reaction. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Repeated exposure may lead to permanent respiratory disability. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and

immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

effects

: There are no data available on the mixture itself.

**Potential delayed effects**: There are no data available on the mixture itself.

Potential chronic health effects

Conclusion/Summary : There are no data available on the mixture itself.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

Canada Page: 11/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

# **Section 11. Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2550 WB URETHANE GLOSS CATALYST - B Hexamethylene diisocyanate, oligomers (Iminooxadiazindione type)	27200.0 N/A	2345.6 2500		52.3 N/A	1.9 1.5
Cyclohexanamine, N,N-dimethyl-, compds. with 3- (cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	N/A	N/A	N/A	11	N/A
cyclohexyldimethylamine hexamethylene-di-isocyanate	272 710	370 570		4.5 0.151	N/A 0.124

# Section 12. Ecological information

**Toxicity** 

Product/ingredient name	Result	Species
Mexamethylene diisocyanate, oligomers (Iminooxadiazindione type)	Acute - LC50 >100 mg/l [96 hours]	Fish - Danio rerio (zebra fish)
, ,	Acute - EC50 >100 mg/l [48 hours]	Daphnia - daphnia magna
	Acute - EC50 >1000 mg/l [72 hours]	Algae - scenedesmus subspicatus
Cyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	Acute - LC50 35.2 mg/l [96 hours]	Fish - zebra fish
• •	Acute - EC50 >100 mg/l [48 hours]	Daphnia - <i>Daphnia magna</i>
	Acute - IC50 72 mg/l [72 hours]	Aquatic plants - Desmodesmus subspicatus

**Conclusion/Summary** : Not available.

### Persistence and degradability

Product/ingredient name	Result
Vyclohexanamine, N,N-dimethyl-, compds. with 3-(cyclohexylamino)-1-propanesulfonic acid-blocked 1,6-diisocyanatohexane homopolymer	0% [28 days]

**Conclusion/Summary** : Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
<b>⊮</b> examethylene diisocyanate,	5.54	3.2	Low
oligomers			
(Iminooxadiazindione type)			
cyclohexyldimethylamine	2.01	-	Low
hexamethylene-di-isocyanate	0.02	-	Low

Canada Page: 12/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 12. Ecological information

**Mobility in soil** 

Soil/Water partition

coefficient

: Not available.

# Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# **Section 14. Transport information**

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

: None identified. **TDG IMDG** : None identified. IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Canada Page: 13/14

Product name 2550 WB URETHANE GLOSS CATALYST - B

### Section 15. Regulatory information

**National Inventory List** 

Canada inventory ( DSL ) : All components are listed or exempted.

### Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

Date of issue/Date of

23 June 2025

revision

Organization that prepared

: EHS

the SDS

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Canada Page: 14/14