

SAFETY DATA SHEET

Date of issue/Date of revision

: 24 June 2025

Version

: 2.01



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PPG AQUACOVER ONE 645 REDBROWN

Product code : 000001191195

Other means of identification

00454100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying, Application by non spray methods..

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Poison Information Centre; emergency telephone, public + 45 82 12 12 12 (health sector +45 35 31 55 55)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 2: Hazards identification

Hazard statements	: Harmful to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
Prevention	: Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations. P273, P501
Supplemental label elements	: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
<u>Special packaging requirements</u>	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≥1.0 - ≤5.0	Eye Irrit. 2, H319	-	[1] [2]
ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≤0.30	Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Inhalation (vapours)] = 11 mg/l STOT SE 3, H335: C ≥ 5% M [Acute] = 1	[1] [2]
3-iodo-2-propynyl	EC: 259-627-5	<0.10	Acute Tox. 4, H302	ATE [Oral] = 1470 mg/	[1]

Code : 000001191195		Date of issue/Date of revision		: 24 June 2025	
PPG AQUACOVER ONE 645 REDBROWN					
SECTION 3: Composition/information on ingredients					
butylcarbamate	CAS: 55406-53-6 Index: 616-212-00-7		Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	CAS: SUB141402	<0.10	Acute Tox. 1, H330 STOT RE 2, H373 (liver) Aquatic Chronic 1, H410	ATE [Inhalation (dusts and mists)] = 0.047 mg/l M [Chronic] = 10	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	<0.010	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 221 mg/kg ATE [Inhalation (dusts and mists)] = 0.14 mg/l M [Acute] = 1000 M [Chronic] = 10	[1]
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Skin Irrit. 2, H315: 0.06% ≤ C < 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit
Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Code : 000001191195

Date of issue/Date of revision

: 24 June 2025

PPG AQUACOVER ONE 645 REDBROWN

SECTION 5: Firefighting measures

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures
- : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	Working Environment Authority (Denmark, 3/2024) TWA 8 hours: 68 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. STEL 15 minutes: 101 mg/m³.
ammonia	Working Environment Authority (Denmark, 3/2024) [ammoniak] TWA 8 hours: 20 ppm. TWA 8 hours: 14 mg/m³. STEL 15 minutes: 36 mg/m³. STEL 15 minutes: 50 ppm.

- Recommended monitoring procedures
- : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 8: Exposure controls/personal protection

of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
2-(2-butoxyethoxy) ethanol	DNEL - General population - Long term - Oral	Effects: Systemic 6.25 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Effects: Local 67.5 mg/m³
3-iodo-2-propynyl butylcarbamate	DNEL - Workers - Short term - Inhalation	Effects: Local 101.2 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic 0.023 mg/m³
1,2-benzisothiazol-3 (2H)-one	DNEL - Workers - Short term - Inhalation	Effects: Systemic 0.07 mg/m³
	DNEL - Workers - Short term - Inhalation	Effects: Local 1.16 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Local 1.16 mg/m³
	DNEL - Workers - Long term - Dermal	Effects: Systemic 2 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic 0.345 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Effects: Systemic 0.966 mg/kg bw/day
pyrithione zinc reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	DNEL - General population - Long term - Inhalation	Effects: Systemic 1.2 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic 6.81 mg/m³
	DNEL - Workers - Long term - Dermal	Effects: Systemic 0.01 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Local 0.02 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Local 0.02 mg/m³
	DNEL - General population - Short term - Inhalation	Effects: Local 0.04 mg/m³
	DNEL - Workers - Short term - Inhalation	Effects: Local 0.04 mg/m³
	DNEL - General population - Long term - Oral	Effects: Systemic 0.09 mg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic 0.11 mg/kg bw/day

PNECs

Product/ingredient name	Compartment Detail - Method	Value
2-(2-butoxyethoxy)ethanol	Fresh water - Assessment Factors	1.1 mg/l
	Marine water - Assessment Factors	0.11 mg/l
	Sewage Treatment Plant - Assessment Factors	200 mg/l
	Fresh water sediment - Equilibrium Partitioning	4.4 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.44 mg/kg dwt
	Soil - Equilibrium Partitioning	0.32 mg/kg dwt

8.2 Exposure controls

- Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Individual protection measures
- Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection : Safety glasses with side shields. Use eye protection according to EN 166.
- Skin protection

Code : 000001191195

Date of issue/Date of revision

: 24 June 2025

PPG AQUACOVER ONE 645 REDBROWN

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Brownish-red.
- Odour** : Characteristic.
- Melting point/freezing point** : Not determined.
- Boiling point or initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: Not applicable.
- Auto-ignition temperature** :

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794

Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
pH	: 8.5
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): >21 mm²/s
Viscosity	: > 100 s (ISO 6mm)
Solubility	:

Media	Result
cold water	Partially soluble

Partition coefficient n-octanol/ water (log Pow)	: Not applicable.																				
Vapour pressure	: <table><tr><th rowspan="2">Ingredient name</th><th colspan="3">Vapour Pressure at 20°C</th><th colspan="3">Vapour pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>water</td><td>17.5</td><td>2.3</td><td></td><td></td><td></td><td></td></tr></table>	Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	water	17.5	2.3				
Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C																	
	mm Hg	kPa	Method	mm Hg	kPa	Method															
water	17.5	2.3																			

Relative density	: 1.07
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information	
9.2.1 Information with regard to physical hazard classes	
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
No additional information.	

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Based on available data, the classification criteria are not met.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
2-(2-butoxyethoxy)ethanol	Rat - Oral - LD50	4500 mg/kg
ammonia	<u>Toxic effects:</u> Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes	
	Rabbit - Dermal - LD50	2700 mg/kg
3-iodo-2-propynyl butylcarbamate	Rat - Oral - LD50	350 mg/kg
	<u>Toxic effects:</u> Gastrointestinal - Other changes	
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	Liver - Other changes Kidney, Ureter, and Bladder - Other changes	
	Rabbit - Dermal - LD50	>2 g/kg
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50	1470 mg/kg
	<u>Toxic effects:</u> Behavioral - Ataxia Liver - Other changes Kidney, Ureter, and Bladder - Other changes	
pyrithione zinc	Rat - Inhalation - LC50 Dusts and mists	0.67 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists	0.047 mg/l [4 hours]
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Rat - Oral - LD50	450 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	0.21 mg/l [4 hours]
	Rat - Oral - LD50	177 mg/kg
	Rabbit - Dermal - LD50	>2 g/kg
	Rat - Inhalation - LC50 Dusts and mists	0.14 mg/l [4 hours]
	Rat - Oral - LD50	53 mg/kg
	<u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression	

Acute toxicity estimates

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
3-iodo-2-propynyl butylcarbamate	<u>Rabbit - Eyes - Severe irritant</u>
pyrithione zinc	<u>Rabbit - Eyes - Cornea opacity</u> Duration of treatment/exposure: 24 hours Observation period: 24 hours Irritation score: 4

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 11: Toxicological information

Product/ingredient name	Test	Result
1,2-benzisothiazol-3(2H)-one	Guinea pig - skin OECD 406	Result: Sensitising

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ammonia	Category 3	-	Respiratory tract irritation

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-iodo-2-propynyl butylcarbamate	Category 1	-	larynx
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	Category 2	-	liver
pyrithione zinc	Category 1	-	-

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

Ingestion : No specific data.

Skin contact : No specific data.

Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 11: Toxicological information

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Sanding and grinding dusts may be harmful if inhaled. Contains isothiazolinones. May cause allergic reaction.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
3-iodo-2-propynyl butylcarbamate	Acute - LC50	Fish - Trout	0.067 mg/l [96 hours]
	Chronic - NOEC	Fish - Trout	0.049 mg/l [96 hours]
	Acute - EC50 - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	0.186 mg/l [48 hours]
	Chronic - EC10	Algae - Green algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase	0.025 mg/l [72 hours]
1,2-benzisothiazol-3(2H)-one	Acute - EC50	Algae - Green algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase	0.039 mg/l [72 hours]
	Acute - EC50	Algae	0.11 mg/l [72 hours]
	Chronic - NOEC	Algae - Trout	0.0403 mg/l [72 hours]
	Acute - EC50	Daphnia	2.9 mg/l [48 hours]
pyrithione zinc	Acute - LC50	Fish	2.15 mg/l [96 hours]
	Acute - LC50	Daphnia	0.0082 mg/l [48 hours]
	Chronic - NOEC	Daphnia	0.0027 mg/l [21 days]
	Acute - EC50 - Marine water	Algae - Diatom - <i>Nitzschia pungens</i>	5.513 µg/l [96 hours]
	Chronic - NOEC - Marine water	Algae - Diatom - <i>Nitzschia pungens</i>	1.889 µg/l [96 hours]

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 12: Ecological information

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
3-iodo-2-propynyl butylcarbamate pyrithione zinc	-	25% [28 days] - Inherent	
	-	39% [28 days]	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl butylcarbamate	-	-	Inherent
1,2-benzisothiazol-3(2H)-one	-	-	Not readily
pyrithione zinc	-	50%; <28 day(s)	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
1,2-benzisothiazol-3(2H)-one	0.7	-	Low
pyrithione zinc	0.9	0.9	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
2-(2-butoxyethoxy)ethanol	1.56	36.5981
3-iodo-2-propynyl butylcarbamate	1.13	13.4558
1,2-benzisothiazol-3(2H)-one	1.86	73.142

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 13: Disposal considerations

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:
European waste catalogue (EWC)	
Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information	
ADR/RID	: None identified.
ADN	: The product is only regulated as a dangerous good when transported in tank vessels.
IMDG	: None identified.
IATA	: None identified.
	:

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 14: Transport information

14.6 Special precautions for user	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Maritime transport in bulk according to IMO instruments	: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
PPG AQUACOVER ONE 645 REDBROWN 2-(2-butoxyethoxy)ethanol	3 55 [Consumer paint]

Labelling : Not applicable.

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

Biocidal products regulation : Contains a biocidal product; C(M)IT/MIT (3:1)

National regulations	
MAL-code	: 0-3
Protection based on MAL	: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:
	General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/ protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.
	In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 15: Regulatory information

MAL-code: 0-3

Application: During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Coveralls must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Arm protectors and apron must be worn.

During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Gas filter mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use	: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
List of undesirable substances	: Not listed
Carcinogenic waste	: Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

15.2 Chemical safety assessment	: No Chemical Safety Assessment has been carried out.
---------------------------------	---

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 1	ACUTE TOXICITY - Category 1
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C

Code	: 000001191195	Date of issue/Date of revision	: 24 June 2025
PPG AQUACOVER ONE 645 REDBROWN			

SECTION 16: Other information

Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision	: 24 June 2025
Date of previous issue	: 24 June 2025
Prepared by	: EHS
Version	: 2.01

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.