SAFETY DATA SHEET



Date of issue

24 June 2025

Version 4

Section 1. Product and company identification

Product name : MEGASEAL HSPC Comp B

Product code : 00333469
Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:

Supplier : PPG Industries Uruguay SA

Av. Italia 5846 esg. Ancona - Montevideo

Uruguay

Tel. +598 26000514 Fax. +598 26003032

Email address: : HazComLatam@ppg.com

Emergency telephone number

Hospital de Clinicas- CIAT- 1722

Section 2. Hazards identification

Classification of the substance or mixture

: MCUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 5
SKIN CORROSION - Category 1
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

Target organs: Contains material which causes damage to the following organs: blood, liver, heart,

brain, skin.

Contains material which may cause damage to the following organs: kidneys, the reproductive system, gastrointestinal tract, upper respiratory tract, central nervous

system (CNS), eye, lens or cornea, muscle tissue, ovary, testes.

Product name MEGASEAL HSPC Comp B

Section 2. Hazards identification

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 16.7%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 35.5%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 28.4%

GHS label elements

Hazard pictograms









Signal word : Danger

Hazard statements: Harmful if swallowed.

May be harmful in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. (kidneys)

Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapor. Wash thoroughly after handling.

Response

: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification

 Zauses digestive tract burns. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F).

Section 3. Composition/information on ingredients

Substance/mixture
Other means of

identification

: Not available.

: Mixture

CAS number/other identifiers

CAS number : Not applicable.

English (US) Uruguay 2/14

Code 00333469 Date of issue 24 June 2025 Version **Product name MEGASEAL HSPC Comp B**

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
	20 - <30	84852-15-3
Polyaminoamide	15 - <20	68082-29-1
Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-	12.5 - <15	9046-10-0 (n = 2-6)
(2-aminomethylethoxy)-		
benzyl alcohol	10 - <12.5	100-51-6
Formaldehyde, polymer with benzenamine, hydrogenated	10 - <12.5	135108-88-2
4-tert-butylphenol	3 - <5	98-54-4
m-phenylenebis(methylamine)	3 - <5	1477-55-0
trimethylhexane-1,6-diamine	3 - <5	25620-58-0
Phenol, 2-nonyl-, branched	2 - <3	91672-41-2
2,4,6-tris(dimethylaminomethyl)phenol	2 - <3	90-72-2
3,6-diazaoctanethylenediamin	1 - <2	112-24-3
salicylic acid	1 - <2	69-72-7
4,4'-methylenebis(cyclohexylamine)	1 - <2	1761-71-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Description of necess	ary mist allu measures
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician **Specific treatments** : The exposed person may need to be kept under medical surveillance for 48 hours.

No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

: Causes severe burns. May be harmful in contact with skin. May cause an allergic **Skin contact**

skin reaction.

: Harmful if swallowed. Corrosive to the digestive tract. Causes burns. Ingestion

English (US) **Uruguay** 3/14

Product name MEGASEAL HSPC Comp B

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon oxides nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Formaldehyde.

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

English (US) Uruguay 4/14

Product name MEGASEAL HSPC Comp B

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
m-phenylenebis(methylamine)	ACGIH TLV (United States, 1/2024) Absorbed through skin. C: 0.018 ppm.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Wuser operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

English (US) Uruguay 5/14

Product name MEGASEAL HSPC Comp B

Section 8. Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection
Skin protection
Hand protection

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Not available.

Odor : Characteristic.

pH : Not applicable.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 93.33°C (200°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

English (US) Uruguay 6/14

Code Date of issue 24 June 2025 Version 00333469

Product name MEGASEAL HSPC Comp B

Section 9. Physical and chemical properties

: Not available. Vapor pressure Vapor density Not available.

Relative density : 0.98

Media Result Solubility(ies)

cold water Not soluble

Water Solubility at room

temperature

: 0.1 g/l

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature Decomposition temperature

: Not available. : Not available.

Viscosity

: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
₄ -nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
Poly[oxy(methyl-	LD50 Dermal	Rat	2980 mg/kg	-
1,2-ethanediyl)], α-				
(2-aminomethylethyl)-ω-				
(2-aminomethylethoxy)-				
	LD50 Oral	Rat	2885 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
Formaldehyde, polymer with	LD50 Oral	Rat	300 mg/kg	-

English (US) **Uruguay** 7/14

Code 00333469 Date of issue 24 June 2025 Version **Product name MEGASEAL HSPC Comp B**

Section 11. Toxicological information

benzenamine, hydrogenated				
4-tert-butylphenol	LD50 Dermal	Rabbit	2.29 g/kg	-
	LD50 Oral	Rat	2.95 g/kg	-
m-phenylenebis	LC50 Inhalation Gas.	Rat	700 ppm	1 hours
(methylamine)				
	LD50 Dermal	Rat - Male,	>3100 mg/kg	-
		Female		
	LD50 Oral	Rat	930 mg/kg	-
2,4,6-tris	LD50 Dermal	Rat	1280 mg/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
salicylic acid	LD50 Oral	Rat	0.891 g/kg	-
4,4'-methylenebis	LD50 Dermal	Rabbit	2.11 g/kg	-
(cyclohexylamine)				
	LD50 Oral	Rat	0.625 g/kg	-
			59	

Conclusion/Summary Irritation/Corrosion

: There are no data available on the mixture itself.

Product/ingredient name	Result	Species	Score	Exposure	Observation
 ✓-nonylphenol, branched m-phenylenebis (methylamine)	Skin - Erythema/Eschar Skin - Severe irritant	Rabbit Rat	4	- 4 hours	- 4 hours

Conclusion/Summary

: There are no data available on the mixture itself. Skin : There are no data available on the mixture itself. **Eyes** : There are no data available on the mixture itself. Respiratory

Sensitization

• • • • • • • • • • • • • • • • • • • •	Route of exposure	Species	Result
m-phenylenebis (methylamine)	skin	Mouse	Sensitizing
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitizing

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Not available.

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

English (US) **Uruguay** 8/14

Product name MEGASEAL HSPC Comp B

Section 11. Toxicological information

Teratogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	, , , , , , , , , , , , , , , , , , ,	Route of exposure	Target organs
Formaldehyde, polymer with benzenamine, hydrogenated 4,4'-methylenebis(cyclohexylamine)	3-17 -	oral oral	kidneys -

Target organs

: Contains material which causes damage to the following organs: blood, liver, heart,

brain, skin.

Contains material which may cause damage to the following organs: kidneys, the reproductive system, gastrointestinal tract, upper respiratory tract, central nervous system (CNS), eye, lens or cornea, muscle tissue, ovary, testes.

Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact :

✓ auses severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

English (US) Uruguay 9/14

Product name MEGASEAL HSPC Comp B

Section 11. Toxicological information

Ingestion: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Can form nitrosamines in the presence of certain organic materials and if heated. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and longterm exposure by oral, inhalation and dermal routes of exposure and eye contact. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

Short term exposure

Potential immediate

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

Potential immediate

: There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

English (US) Uruguay 10/14

Code 00333469 Date of issue 24 June 2025 Version 4
Product name MEGASEAL HSPC Comp B

Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
MEGASEAL HSPC Comp B	868.5	2312.0	20022.9	N/A	N/A
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
Poly[oxy(methyl-1,2-ethanediyl)], α-	2885	2980	N/A	N/A	N/A
(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-					
benzyl alcohol	1200	2500	N/A	N/A	N/A
Formaldehyde, polymer with benzenamine, hydrogenated	300	N/A	N/A	N/A	N/A
4-tert-butylphenol	2950	2290	N/A	N/A	N/A
m-phenylenebis(methylamine)	930	2500	4500	N/A	N/A
trimethylhexane-1,6-diamine	500	N/A	N/A	N/A	N/A
Phenol, 2-nonyl-, branched	500	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
3,6-diazaoctanethylenediamin	1716	1465	N/A	N/A	N/A
salicylic acid	891	N/A	N/A	N/A	N/A
4,4'-methylenebis(cyclohexylamine)	625	2110	N/A	N/A	N/A

Other information : Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
≰ -nonylphenol, branched	Acute EC50 0.04 mg/l	Algae - Raphidocelis subcapitata	72 hours
• •	Acute EC50 0.044 mg/l	Crustaceans - Moina macrocopa	
	Acute LC50 0.221 mg/l	Fish	96 hours
Poly[oxy(methyl-	EC50 15 mg/l	Algae	72 hours
1,2-ethanediyl)], α-			
(2-aminomethylethyl)-ω-			
(2-aminomethylethoxy)-			
Formaldehyde, polymer with	Acute EC50 43.94 mg/l	Algae	72 hours
benzenamine, hydrogenated			
	Acute EC50 15.4 mg/l	Daphnia	48 hours
	Acute LC50 63 mg/l	Fish	96 hours
4-tert-butylphenol	Acute EC50 16.91 mg/l Fresh water	Algae - Selenastrum	72 hours
		capricornutum - Exponential	
		growth phase	
Phenol, 2-nonyl-, branched	Acute LC50 0.017 mg/l	Fish - <i>Pleuronectes americanus</i>	96 hours
2,4,6-tris	Acute LC50 >100 mg/l	Daphnia	48 hours
(dimethylaminomethyl)phenol			
	Acute LC50 >100 mg/l	Fish	96 hours
salicylic acid	Acute EC50 1147.57 mg/l Fresh water	Daphnia - <i>Daphnia longispina</i> - Neonate	48 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

Persistence/degradability

Code 00333469 Date of issue 24 June 2025 Version 4
Product name MEGASEAL HSPC Comp B

Section 12. Ecological information

Product/ingredient name	Test	Result	Dose	Inoculum
Formaldehyde, polymer with benzenamine, hydrogenated		0 % - Not readily - 28 days	-	-
2,4,6-tris (dimethylaminomethyl)phenol	OECD Ready Biodegradability - Closed Bottle Test	4 % - Not readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Poly[oxy(methyl-	-	-	Not readily
1,2-ethanediyl)], α-			,
(2-aminomethylethyl)-ω-			
(2-aminomethylethoxy)-			
benzyl alcohol	-	-	Readily
Formaldehyde, polymer with	-	-	Not readily
benzenamine, hydrogenated			,
2,4,6-tris	-	-	Not readily
(dimethylaminomethyl)phenol			,

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
♣-nonylphenol, branched	5.4	251.19	Low
benzyl alcohol	0.87	-	Low
Formaldehyde, polymer with	2.68	209 to 219	Low
benzenamine, hydrogenated			
4-tert-butylphenol	3	67.61	Low
m-phenylenebis	0.18	2.69	Low
(methylamine)			
2,4,6-tris	0.219	-	Low
(dimethylaminomethyl)phenol			
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	Low
salicylic acid	2.21 to 2.26	-	Low
4,4'-methylenebis	2.03	-	Low
(cyclohexylamine)			

Mobility in soil

Soil/Water partition coefficient

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when

English (US) Uruguay 12/14

Product name MEGASEAL HSPC Comp B

Section 13. Disposal considerations

handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	IATA
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group	II	II	II	II
Environmental hazards Marine pollutant substances	Yes. The environmentally hazardous substance mark is not required. Not applicable.	Yes. The environmentally hazardous substance mark is not required. Not applicable.	Yes. (4-nonylphenol, branched)	Yes. The environmentally hazardous substance mark is not required. Not applicable.

Additional information

UN : None identified.Brazil : None identified.

Risk number : 80

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

English (US) Uruguay 13/14

Product name MEGASEAL HSPC Comp B

Section 16. Other information

History

Date of previous issue : 10/5/2021

Version : 4

EHS

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References: ABNT NBR 14725-4: 2014

ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (US) Uruguay 14/14