

SAFETY DATA SHEET



Date of issue/Date of revision

: 24 June 2025

Version

: 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : MEGASEAL SL Comp B
Product code : 00333461
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Acute Tox. 4, H302
Skin Corr. 1A, H314
Eye Dam. 1, H318
Skin Sens. 1, H317
Repr. 2, H361fd
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Code : 00333461

Date of issue/Date of revision

: 24 June 2025

MEGASEAL SL Comp B

SECTION 3: Composition/information on ingredients

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	REACH #: 01-2119560598-25 EC: 247-063-2 CAS: 25513-64-8	≥5.0 - ≤10	(M=10) Aquatic Chronic 1, H410 (M=10) Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	[1]
Nonylphenols	EC: 294-048-1 CAS: 91672-41-2	≥1.0 - <3.0	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10) EUH071 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

☒ Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayedPotential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : ☒ No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness

Code : 00333461
MEGASEAL SL Comp B

Date of issue/Date of revision : 24 June 2025

SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 stomach pains
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
 carbon oxides
 nitrogen oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Code : 00333461
MEGASEAL SL Comp B

Date of issue/Date of revision : 24 June 2025

SECTION 6: Accidental release measures

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections : See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Code : 00333461		Date of issue/Date of revision		: 24 June 2025																																																																																																																																																																																
MEGASEAL SL Comp B																																																																																																																																																																																				
SECTION 7: Handling and storage																																																																																																																																																																																				
7.3 Specific end use(s)																																																																																																																																																																																				
See Section 1.2 for Identified uses.																																																																																																																																																																																				
SECTION 8: Exposure controls/personal protection																																																																																																																																																																																				
8.1 Control parameters																																																																																																																																																																																				
The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).																																																																																																																																																																																				
Occupational exposure limits																																																																																																																																																																																				
No exposure limit value known.																																																																																																																																																																																				
No exposure indices known.																																																																																																																																																																																				
Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.																																																																																																																																																																																				
DNELs/DMELs																																																																																																																																																																																				
<table><tr><th>Product/ingredient name</th><th>Type</th><th>Exposure</th><th>Value</th><th>Population</th><th>Effects</th></tr><tr><td rowspan="11">benzyl alcohol</td><td>DNEL</td><td>Long term Oral</td><td>4 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Dermal</td><td>4 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Inhalation</td><td>5.4 mg/m³</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Dermal</td><td>8 mg/kg bw/day</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Oral</td><td>20 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Dermal</td><td>20 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Inhalation</td><td>22 mg/m³</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>27 mg/m³</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Dermal</td><td>40 mg/kg bw/day</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>110 mg/m³</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>0.073 mg/m³</td><td>Workers</td><td>Local</td></tr><tr><td rowspan="4">3-aminomethyl-3,5,5-trimethylcyclohexylamine</td><td>DNEL</td><td>Long term Inhalation</td><td>0.073 mg/m³</td><td>Workers</td><td>Local</td></tr><tr><td>DNEL</td><td>Long term Oral</td><td>0.3 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Oral</td><td>0.3 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Oral</td><td>0.33 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td rowspan="11">Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer</td><td>DNEL</td><td>Long term Inhalation</td><td>0.58 mg/m³</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Dermal</td><td>0.67 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Oral</td><td>0.99 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>1.74 mg/m³</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Dermal</td><td>1.87 mg/kg bw/day</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Inhalation</td><td>3.29 mg/m³</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>9.87 mg/m³</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Oral</td><td>0.4 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>0.8 mg/m³</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Dermal</td><td>7.6 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Oral</td><td>0.08 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td rowspan="7">4-nonylphenol, branched</td><td>DNEL</td><td>Long term Inhalation</td><td>0.4 mg/m³</td><td>General population</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Inhalation</td><td>0.5 mg/m³</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Short term Inhalation</td><td>1 mg/m³</td><td>Workers</td><td>Systemic</td></tr><tr><td>DNEL</td><td>Long term Dermal</td><td>3.8 mg/kg bw/day</td><td>General population</td><td>Systemic</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>						Product/ingredient name	Type	Exposure	Value	Population	Effects	benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic	DNEL	Long term Inhalation	5.4 mg/m³	General population	Systemic	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic	DNEL	Long term Inhalation	22 mg/m³	Workers	Systemic	DNEL	Short term Inhalation	27 mg/m³	General population	Systemic	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic	DNEL	Short term Inhalation	110 mg/m³	Workers	Systemic	DNEL	Short term Inhalation	0.073 mg/m³	Workers	Local	3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL	Long term Inhalation	0.073 mg/m³	Workers	Local	DNEL	Long term Oral	0.3 mg/kg bw/day	General population	Systemic	DNEL	Short term Oral	0.3 mg/kg bw/day	General population	Systemic	DNEL	Long term Oral	0.33 mg/kg bw/day	General population	Systemic	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer	DNEL	Long term Inhalation	0.58 mg/m³	General population	Systemic	DNEL	Long term Dermal	0.67 mg/kg bw/day	General population	Systemic	DNEL	Short term Oral	0.99 mg/kg bw/day	General population	Systemic	DNEL	Short term Inhalation	1.74 mg/m³	General population	Systemic	DNEL	Long term Dermal	1.87 mg/kg bw/day	Workers	Systemic	DNEL	Long term Inhalation	3.29 mg/m³	Workers	Systemic	DNEL	Short term Inhalation	9.87 mg/m³	Workers	Systemic	DNEL	Short term Oral	0.4 mg/kg bw/day	General population	Systemic	DNEL	Short term Inhalation	0.8 mg/m³	General population	Systemic	DNEL	Short term Dermal	7.6 mg/kg bw/day	General population	Systemic	DNEL	Long term Oral	0.08 mg/kg bw/day	General population	Systemic	4-nonylphenol, branched	DNEL	Long term Inhalation	0.4 mg/m³	General population	Systemic	DNEL	Long term Inhalation	0.5 mg/m³	Workers	Systemic	DNEL	Short term Inhalation	1 mg/m³	Workers	Systemic	DNEL	Long term Dermal	3.8 mg/kg bw/day	General population	Systemic															
Product/ingredient name	Type	Exposure	Value	Population	Effects																																																																																																																																																																															
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Inhalation	5.4 mg/m³	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Inhalation	22 mg/m³	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	27 mg/m³	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	110 mg/m³	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	0.073 mg/m³	Workers	Local																																																																																																																																																																															
3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL	Long term Inhalation	0.073 mg/m³	Workers	Local																																																																																																																																																																															
	DNEL	Long term Oral	0.3 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Oral	0.3 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Oral	0.33 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer	DNEL	Long term Inhalation	0.58 mg/m³	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Dermal	0.67 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Oral	0.99 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	1.74 mg/m³	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Dermal	1.87 mg/kg bw/day	Workers	Systemic																																																																																																																																																																															
	DNEL	Long term Inhalation	3.29 mg/m³	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	9.87 mg/m³	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Oral	0.4 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	0.8 mg/m³	General population	Systemic																																																																																																																																																																															
	DNEL	Short term Dermal	7.6 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Oral	0.08 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
4-nonylphenol, branched	DNEL	Long term Inhalation	0.4 mg/m³	General population	Systemic																																																																																																																																																																															
	DNEL	Long term Inhalation	0.5 mg/m³	Workers	Systemic																																																																																																																																																																															
	DNEL	Short term Inhalation	1 mg/m³	Workers	Systemic																																																																																																																																																																															
	DNEL	Long term Dermal	3.8 mg/kg bw/day	General population	Systemic																																																																																																																																																																															
English (GB)		United Kingdom (UK)		6/15																																																																																																																																																																																

Code : 00333461
MEGASEAL SL Comp B

Date of issue/Date of revision : 24 June 2025

SECTION 8: Exposure controls/personal protection

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	DNEL DNEL DNEL	Long term Dermal Short term Dermal Long term Oral	7.5 mg/kg bw/day 15 mg/kg bw/day 0.05 mg/kg bw/day	Workers Workers General population	Systemic Systemic Systemic
---	----------------------	---	--	--	----------------------------------

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	Fresh water	0.102 mg/l	-
	Marine water	0.0102 mg/l	-
	Fresh water sediment	0.62 mg/kg dwt	-
	Marine water sediment	0.062 mg/kg dwt	-
	Soil	10 mg/kg dwt	-
	Sewage Treatment Plant	72 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
nitrile neoprene

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code	: 00333461	Date of issue/Date of revision	: 24 June 2025
MEGASEAL SL Comp B			

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state : Liquid.
- Colour : Not available.
- Odour : Characteristic.
- Odour threshold : Not available.
- Melting point/freezing point :
- Initial boiling point and boiling range : >37.78°C (>100°F)
- Flammability (solid, gas) : liquid
- Upper/lower flammability or explosive limits : Not available.
- Flash point : Closed cup: 93.33°C (200°F)
- Auto-ignition temperature :

Ingredient name	°C	°F	Method
Phenylphenol, branched	372	701.6	ASTM E 659

- pH : Not applicable.
- Viscosity : Not applicable. insoluble in water.
- Dynamic (room temperature): Not available.
- Kinematic (room temperature): Not available.
- Kinematic (40°C): >21 mm²/s

Solubility(ies) :

Media	Result
cold water	Not soluble

- Solubility in water : 6.4 g/l
- Miscible with water : No.
- Partition coefficient: n-octanol/ water : Not applicable.
- Vapour pressure : 1.8 kPa (13.3 mm Hg)
- Relative density : 1
- Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties : Product does not present an oxidizing hazard.
- Particle characteristics
- Median particle size : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

Code : 00333461	Date of issue/Date of revision : 24 June 2025
MEGASEAL SL Comp B	

SECTION 10: Stability and reactivity

- 10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
3-aminomethyl-3,5,5-trimethylcyclohexylamine	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.01 mg/l	4 hours
4-nonylphenol, branched	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
	LD50 Dermal	Rabbit	2.14 g/kg	-
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	LD50 Oral	Rat	1300 mg/kg	-
	LD50 Oral	Rat	910 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
MEGASEAL SL Comp B	1332.2	N/A	N/A	N/A	N/A
benzyl alcohol	1200	N/A	N/A	N/A	N/A
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	N/A	N/A	N/A	N/A
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	910	N/A	N/A	N/A	N/A
Nonylphenols	500	N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4-nonylphenol, branched 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	Skin - Erythema/Eschar	Rabbit	4	-	-
	Skin - Primary dermal irritation index (PDII)	Rabbit	8	-	-

- Conclusion/Summary : Not available.
- Skin : There are no data available on the mixture itself.
- Eyes : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl-3,5,5-trimethylcyclohexylamine 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	skin	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising

- Conclusion/Summary
- Skin : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.

Code : 00333461
MEGASEAL SL Comp B

Date of issue/Date of revision : 24 June 2025

SECTION 11: Toxicological information

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 pain
 watering
 redness
- Inhalation** : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 stomach pains
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Code : 00333461	Date of issue/Date of revision : 24 June 2025
MEGASEAL SL Comp B	

SECTION 11: Toxicological information

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effects	Not available.
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility. Suspected of damaging the unborn child.
Other information	: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
4-nonylphenol, branched	Acute EC50 0.04 mg/l	Algae - Green algae - <i>Raphidocelis subcapitata</i>	72 hours
	Acute EC50 0.044 mg/l	Crustaceans - Water flea - <i>Moina macrocopa</i>	48 hours
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	Acute LC50 0.221 mg/l	Fish	96 hours
	NOEC 16 mg/l	Algae - <i>pseudokirchneriella subcapitata</i>	72 hours
Nonylphenols	Acute EC50 29.5 mg/l	Algae - <i>Scenedesmus subspicatus</i>	72 hours
	Acute LC50 0.017 mg/l	Fish - <i>Pleuronectes americanus</i>	96 hours

Conclusion/Summary	: Not available.
---------------------------	------------------

12.2 Persistence and degradability

Conclusion/Summary		: Not available.	
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol 2,2,4(or 2,4,4)- trimethylhexane-1,6-diamine	-	-	Readily
	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.87	-	Low
	0.99	-	Low
4-nonylphenol, branched 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	5.4	251.19	Low
	-0.3	-	Low

12.4 Mobility in soil

Soil/water partition coefficient	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

Code : 00333461	Date of issue/Date of revision : 24 June 2025
MEGASEAL SL Comp B	

SECTION 12: Ecological information

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	
Waste catalogue	

Waste code	Waste designation
08 01 99	wastes not otherwise specified

Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
----------------------------	---

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3066	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8	8
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	 (4-nonylphenol, branched)	Not applicable.

Additional information	
ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Code	: 00333461	Date of issue/Date of revision	: 24 June 2025
MEGASEAL SL Comp B			

SECTION 14: Transport information

ADN	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
 Substance of equivalent concern for environment	4-nonylphenol, branched and linear substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof	Candidate	-	12/19/2012

Explosive precursors :  Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
 MEGASEAL SL Comp B	3
4-nonylphenol, branched	46
Nonylphenols	46

Labelling : Not applicable.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
 1

Code : 00333461	Date of issue/Date of revision : 24 June 2025
MEGASEAL SL Comp B	

SECTION 16: Other information

 Indicates information that has changed from previously issued version.	
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
 Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361fd Aquatic Acute 1, H400 Aquatic Chronic 1, H410	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

 H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

 Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

History

Date of issue/ Date of revision	: 24 June 2025
Date of previous issue	: 9 November 2022
Prepared by	: EHS
Version	: 1.01

Disclaimer

Code	: 00333461	Date of issue/Date of revision	: 24 June 2025
MEGASEAL SL Comp B			

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.