

SAFETY DATA SHEET

Date of issue/Date of revision

: 30 June 2025

Version

: 7.02



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : AMERCOAT 138G DK GRAY TYPE I/II/IV KIT

Product code : 00333924

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Repr. 1B, H360F

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility. Harmful to aquatic life with long lasting effects.
<u>Precautionary statements</u>		
Prevention	:	Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.
Response	:	IF exposed or concerned: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P202, P280, P210, P273, P308 + P313, P501
Hazardous ingredients	:	bis-[4-(2,3-epoxipropoxy)phenyl]propane; oxirane, mono[(C12-14-alkyloxy)methyl] derivs. ; benzyl alcohol; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) and 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine
Supplemental label elements	:	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
 2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

Code : 00333924

Date of issue/Date of revision

: 30 June 2025

AMERCOAT 138G DK GRAY TYPE I/II/IV KIT

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
bis-[4-(2,3-epoxipropoxy)phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Hydrocarbons, C9, aromatics > 0.1% cumene	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	≥5.0 - <10	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	Carc. 1B, H350: C ≥ 10%	[1] [2]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Repr. 1B, H360F	-	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥1.0 - ≤3.3	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	<1.0	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg	[1]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	<1.0	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	≤0.30	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1] [2]
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	REACH #: 01-2119560598-25 EC: 247-063-2 CAS: 25513-64-8	≤0.30	Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 910 mg/kg	[1]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	≤0.30	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation]	[1] [2]

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 3: Composition/information on ingredients

				(vapours)] = 3 mg/l STOT SE 1, H370: C ≥ 10% STOT SE 2, H371: 3% ≤ C < 10%	
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
 - [2] Substance with a workplace exposure limit
- Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact : Causes serious eye irritation.
- Inhalation : No known significant effects or critical hazards.
- Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 4: First aid measures

Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising from the substance or mixture	
Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Hydrocarbons, C9, aromatics > 0.1% cumene	EU OEL (Europe) TWA: 19 ppm. TWA: 100 mg/m³.
n-butyl acetate	EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm.
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	ACGIH TLV (United States) TWA: 10 mg/m³. Form: Total dust. TWA: 3 mg/m³. Form: Respirable.
methanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 200 ppm. TWA 8 hours: 260 mg/m³.

Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
-----------------------------------	---

DNELs/DMELs

Code : 00333924

Date of issue/Date of revision

: 30 June 2025

AMERCOAT 138G DK GRAY TYPE I/II/IV KIT

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	DNEL - Workers - Long term - Inhalation	Effects: Systemic 12.25 mg/m ³
	DNEL - Workers - Short term - Inhalation	Effects: Systemic 12.25 mg/m ³
	DNEL - Workers - Long term - Dermal	Effects: Systemic 8.33 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	Effects: Systemic 8.33 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Dermal	Effects: Systemic 3.571 mg/kg bw/day
	DNEL - General population - Consumers - Short term - Dermal	Effects: Systemic 3.571 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Oral	Effects: Systemic 0.75 mg/kg bw/day
	DNEL - General population - Consumers - Short term - Oral	Effects: Systemic 0.75 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic 89.3 µg/kg bw/day
	DNEL - General population - Long term - Oral	Effects: Systemic 0.5 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Effects: Systemic 0.75 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic 0.87 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic 4.93 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic 150 mg/m ³
Hydrocarbons, C9, aromatics > 0.1% cumene	DNEL - Workers - Long term - Dermal	Effects: Systemic 25 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic 32 mg/m ³
	DNEL - General population - Long term - Dermal	Effects: Systemic 11 mg/kg bw/day
	DNEL - General population - Long term - Oral	Effects: Systemic 11 mg/kg bw/day
	DNEL - General population - Long term - Oral	Effects: Systemic 0.5 mg/kg bw/day
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	DNEL - General population - Long term - Dermal	Effects: Systemic 0.5 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic 0.87 mg/m ³
	DNEL - Workers - Long term - Dermal	Effects: Systemic 1 mg/kg bw/day
n-butyl acetate	DNEL - Workers - Long term - Inhalation	Effects: Systemic 3.6 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic 300 mg/m ³
	DNEL - Workers - Long term - Dermal	Effects: Systemic 11 mg/m ³
	DNEL - General population - Long term - Oral	Effects: Systemic 2 mg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic 2 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic 3.4 mg/kg bw/day
	DNEL - General population - Short term - Dermal	Effects: Systemic 6 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Effects: Systemic 7 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	Effects: Systemic 11 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic 12 mg/m ³
	DNEL - General population - Long term - Inhalation	Effects: Local 35.7 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic 48 mg/m ³
	DNEL - General population - Short term - Inhalation	Effects: Local 300 mg/m ³
	DNEL - General population - Short term - Inhalation	Effects: Systemic 300 mg/m ³
	DNEL - Workers - Long term - Inhalation	Effects: Local 300 mg/m ³

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 8: Exposure controls/personal protection

benzyl alcohol	DNEL - Workers - Short term - Inhalation	Effects: Local	600 mg/m³
	DNEL - Workers - Short term - Inhalation	Effects: Systemic	600 mg/m³
	DNEL - General population - Long term - Oral	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Effects: Systemic	5.4 mg/m³
	DNEL - Workers - Long term - Dermal	Effects: Systemic	8 mg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic	20 mg/kg bw/day
	DNEL - General population - Short term - Dermal	Effects: Systemic	20 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	22 mg/m³
	DNEL - General population - Short term - Inhalation	Effects: Systemic	27 mg/m³
3-aminomethyl-3,5,5-trimethylcyclohexylamine	DNEL - Workers - Short term - Dermal	Effects: Systemic	40 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	Effects: Systemic	110 mg/m³
	DNEL - Workers - Short term - Inhalation	Effects: Local	0.073 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Local	0.073 mg/m³
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	DNEL - General population - Long term - Oral	Effects: Systemic	0.3 mg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic	0.3 mg/kg bw/day
	DNEL - General population - Long term - Oral	Effects: Systemic	0.05 mg/kg bw/day
	DNEL - General population - Short term - Oral	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Long term - Oral	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Short term - Dermal	Effects: Systemic	4 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Effects: Systemic	4 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	Effects: Systemic	20 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Effects: Systemic	20 mg/kg bw/day
	DNEL - General population - Short term - Inhalation	Effects: Local	26 mg/m³
methanol	DNEL - General population - Long term - Inhalation	Effects: Local	26 mg/m³
	DNEL - General population - Short term - Inhalation	Effects: Systemic	26 mg/m³
	DNEL - General population - Long term - Inhalation	Effects: Systemic	26 mg/m³
	DNEL - Workers - Short term - Inhalation	Effects: Local	130 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Local	130 mg/m³
	DNEL - Workers - Short term - Inhalation	Effects: Systemic	130 mg/m³
	DNEL - Workers - Long term - Inhalation	Effects: Systemic	130 mg/m³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
bis-[4-(2,3-epoxipropoxi)phenyl] propane	Fresh water - Assessment Factors	0.006 mg/l
	Marine water - Assessment Factors	0.001 mg/l
	Fresh water sediment - Equilibrium Partitioning	0.996 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.1 mg/kg dwt
	Soil - Equilibrium Partitioning	0.196 mg/kg dwt
n-butyl acetate	Sewage Treatment Plant - Assessment Factors	10 mg/l
	Secondary Poisoning - Assessment Factors	11 mg/kg
	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine water sediment	0.0981 mg/kg
	Sewage Treatment Plant	35.6 mg/l
	Soil	0.0903 mg/kg

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine methanol	Fresh water	0.102 mg/l
	Marine water	0.0102 mg/l
	Fresh water sediment	0.62 mg/kg dwt
	Marine water sediment	0.062 mg/kg dwt
	Soil	10 mg/kg dwt
	Sewage Treatment Plant	72 mg/l
	Fresh water - Assessment Factors	20.8 mg/l
	Marine water - Assessment Factors	2.08 mg/l
	Sewage Treatment Plant - Assessment Factors	100 mg/l
	Fresh water sediment - Equilibrium Partitioning	77 mg/kg
	Marine water sediment - Equilibrium Partitioning	7.7 mg/kg
	Soil - Assessment Factors	100 mg/kg

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Skin protection

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 8: Exposure controls/personal protection

- Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state

: Liquid.
- Colour

: Grey.
- Odour

: Characteristic.
- Melting point/freezing point

: Not determined.
- Boiling point or initial boiling point and boiling range

: >37.78°C
- Flammability

: Not determined. There are no data available on the mixture itself.
- Lower and upper explosion limit

: Not available.
- Flash point

: Closed cup: 40°C
- Auto-ignition temperature

:

Ingredient name	°C	°F	Method
n-butyl acetate	415	779	EU A.15

- Decomposition temperature

: Stable under recommended storage and handling conditions (see Section 7).
- pH

: Not applicable. insoluble in water.
- Viscosity

: Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s

- Solubility

:

Media	Result
cold water	Not soluble

- Solubility in water

: 0.2 g/l
- Partition coefficient n-octanol/ water (log Pow)

: Not applicable.
- Vapour pressure

: 1.7 kPa (12.5 mm Hg)
- Relative density

: 1.95

Particle characteristics

- Median particle size

: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 9: Physical and chemical properties

Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
9.2.2 Other safety characteristics	
Evaporation rate	: 0.41 (butyl acetate = 1)
No additional information.	

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May damage fertility.

Acute toxicity		
Product/ingredient name	Result	Dose / Exposure
bis-[4-(2,3-epoxipropoxy)phenyl] propane	Rabbit - Dermal - LD50	23000 mg/kg
Hydrocarbons, C9, aromatics > 0.1% cumene	Rat - Oral - LD50	15000 mg/kg
	Rat - Female - Oral - LD50	3492 mg/kg
oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	Rabbit - Dermal - LD50	>3160 mg/kg
	Rat - Oral - LD50	17100 mg/kg
n-butyl acetate	Rabbit - Dermal - LD50	>4000 mg/kg
	Rabbit - Dermal - LD50	>17600 mg/kg
	Rat - Oral - LD50	10.768 g/kg
	Rat - Inhalation - LC50 Vapour	2000 ppm [4 hours]
	Rat - Inhalation - LC50 Vapour	>21.1 mg/l [4 hours]
benzyl alcohol	Rabbit - Dermal - LD50	>2000 mg/kg
	Rat - Oral - LD50	1200 mg/kg
3-aminomethyl-	Rat - Inhalation - LC50 Dusts and mists	>5 mg/l [4 hours]
	Rat - Oral - LD50	1030 mg/kg
English (GB)		Europe
		12/21

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 11: Toxicological information

3,5,5-trimethylcyclohexylamine	Rat - Dermal - LD50	>2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5.01 mg/l [4 hours]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	Rat - Oral - LD50	>2000 mg/kg
	Rat - Dermal - LD50	>2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5.11 mg/l [4 hours]
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	Rat - Oral - LD50	910 mg/kg
methanol	Rabbit - Dermal - LD50	15800 mg/kg
	<u>Toxic effects</u> : Eye - Visual field changes	
	Rat - Oral - LD50	5600 mg/kg
	Rat - Inhalation - LC50 Vapour	64000 ppm [4 hours]

Acute toxicity estimates

Route	ATE value
Oral	82468.18 mg/kg
Dermal	247404.55 mg/kg
Inhalation (vapours)	2474.05 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
bis-[4-(2,3-epoxipropoxy)phenyl] propane	<u>Rabbit - Eyes - Redness of the conjunctivae</u> Duration of treatment/exposure: 24 hours Irritation score: 0.4
-	<u>Rabbit - Eyes - Mild irritant</u> Duration of treatment/exposure: 24 hours Fully reversible in 7 days or less
-	<u>Rabbit - Skin - Erythema/Eschar</u> Duration of treatment/exposure: 4 hours Irritation score: 0.8
-	<u>Rabbit - Skin - Oedema</u> Duration of treatment/exposure: 4 hours Irritation score: 0.5
-	<u>Rabbit - Skin - Mild irritant</u> Duration of treatment/exposure: 4 hours
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	<u>Rabbit - Skin - Primary dermal irritation index (PDII)</u> Irritation score: 8

Conclusion/Summary

Skin : Causes skin irritation.
Eyes : Causes serious eye irritation.
Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 11: Toxicological information

Product/ingredient name	Test	Result
bis-[4-(2,3-epoxipropoxy)phenyl] propane	Mouse - skin	Result: Sensitising
3-aminomethyl-3,5,5-trimethylcyclohexylamine	Guinea pig - skin OECD 406	Result: Sensitising
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	Guinea pig - skin	Result: Sensitising

Conclusion/Summary

Skin : May cause an allergic skin reaction.
Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
n-butyl acetate	Category 3	-	Narcotic effects
methanol	Category 1	-	-

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics > 0.1% cumene	ASPIRATION HAZARD - Category 1

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 11: Toxicological information

- Ingestion : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects : No known significant effects or critical hazards.
- Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects : No known significant effects or critical hazards.
- Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

- General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity : No known significant effects or critical hazards.
- Mutagenicity : No known significant effects or critical hazards.
- Reproductive toxicity : May damage fertility.
- Other information : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Chronic - NOEC	Daphnia	0.3 mg/l [21 days]
Hydrocarbons, C9, aromatics > 0.1% cumene	Acute - LC50 - Fresh water	Daphnia - <i>daphnia magna</i>	1.8 mg/l [48 hours]
	EC50	Daphnia	3.2 mg/l [48 hours]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LC50	Fish	9.2 mg/l [96 hours]
	LC50	Fish	>1.8 mg/l [96 hours]
n-butyl acetate N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	EC50	Daphnia	7.2 mg/l [48 hours]
	EC50	Algae	844 mg/l [72 hours]
	Acute - LC50	Fish	18 mg/l [96 hours]
	Acute - EC50	Daphnia - <i>Daphnia magna</i>	94 mg/l [48 hours]
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i>	29 to 43 mg/l [72 hours]
	Acute - EC50	Algae - <i>Scenedesmus subspicatus</i>	29.5 mg/l [72 hours]
	NOEC	Algae - <i>pseudokirchneriella subcapitata</i>	16 mg/l [72 hours]
methanol	Acute - LC50 - Fresh water	Fish - Trout	13 mg/l [96 hours]

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
Hydrocarbons, C9, aromatics > 0.1% cumene	-	75% [28 days] - Readily	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	OECD [Ready Biodegradability - Manometric Respirometry Test]	87% [28 days] - Readily	
n-butyl acetate N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	TEPA and OECD 301D	83% [28 days] - Readily	
	-	63% [28 days]	

Code : 00333924

Date of issue/Date of revision

: 30 June 2025

AMERCOAT 138G DK GRAY TYPE I/II/IV KIT

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxy)phenyl]propane	-	-	Not readily
Hydrocarbons, C9, aromatics	-	-	Readily
> 0.1% cumene	-	-	Readily
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	-	Readily
n-butyl acetate	-	-	Readily
benzyl alcohol	-	-	Readily
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	-	-	Readily
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	Low
n-butyl acetate	2.3	-	Low
benzyl alcohol	0.87	-	Low
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	-	Low
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	>6	-	High
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	-0.3	-	Low
methanol	-0.77	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
bis-[4-(2,3-epoxipropoxy)phenyl]propane	4.02	10465.7
n-butyl acetate	1.52	33.2139
benzyl alcohol	1.1	12.6442
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1.99	98.3852
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	4.31	20542.3
methanol	0.44	2.75443

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:

European waste catalogue (EWC)

Waste code	Waste designation
08 01 99	wastes not otherwise specified

Packaging

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
---------------------	---

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

English (GB)	Europe	18/21
--------------	--------	-------

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 14: Transport information

ADR/RID	: None identified.
Tunnel code	: (D/E)
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)
[Annex XIV - List of substances subject to authorisation](#)

Annex XIV	
None of the components are listed.	
Substances of very high concern	
None of the components are listed.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	
Product/ingredient name	Entry Number (REACH)
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT	3
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	30
methanol	30
	69

Labelling : Restricted to professional users.

Explosive precursors : Not applicable.

[Ozone depleting substances \(EU 2024/590\)](#)
Not listed.

[Seveso Directive](#)
This product is controlled under the Seveso Directive.

Danger criteria
Category
P5c

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H360F	May damage fertility.
H370	Causes damage to organs.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -

Code	: 00333924	Date of issue/Date of revision	: 30 June 2025
AMERCOAT 138G DK GRAY TYPE I/II/IV KIT			

SECTION 16: Other information

STOT SE 3	Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
-----------	--

History

Date of issue/ Date of revision : 30 June 2025
Date of previous issue : 24 June 2025
Prepared by : EHS
Version : 7.02

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.