

Audit - EU DK MAL Code

PPG VIKOTE 56 GREY 5177

	Product as is	Ready-for-use mixture
MAL Code	5-3	☒ Not applicable.
MAL Protection	According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/ apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 5-3 Application: When spraying in new* booths if the operator is outside the spray zone. During non-atomizing spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin. - Air-supplied full mask must be worn. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone. During downtimes, cleaning and repair of closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. - Air-supplied full mask and coveralls must be worn. When spraying in existing* spray booths, if the operator is outside the spray zone. - Air-supplied full mask, arm protectors and apron must be worn. During all spraying where atomization occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth. - Air-supplied full mask, coveralls and hood must be worn.	☒ Not applicable.

 Not applicable.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Not applicable.

 Not applicable.

Low Boiling
Liquid
MAL Number
Audit (Textual)

 3348.1

Not applicable.

 3

 Not applicable.

Figure-before-dash (from MAL Number) = 5
3200 < MAL Number [3348.1]
MAL Number = density * $\Sigma[\text{Conc}(i) * \text{MAL Factor}(i)] = 1.018 * 3288.9 = 3348.1$
Density (from Density (g/m³) data entry) = 1.018
 $\Sigma[\text{Conc}(i) * \text{MAL Factor}(i)] = 3288.9$
[Hydrocarbons, C9, aromatics] Conc * MAL Factor = 33.37% * 58 = 1935.6
MAL Factor entered against range: '0 to 100' = 58
[XYLENES] Conc * MAL Factor = 15.19% * 46 = 698.9
MAL Factor entered against range: '0 to 100' = 46
[SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC] Conc * MAL Factor = 7.959% * 58 = 461.6
MAL Factor entered against range: '0 to 100' = 58
[ETHYLBENZENE] Conc * MAL Factor = 3.466% * 46 = 159.4
MAL Factor entered against range: '0 to 100' = 46
[cyclohexanone] Conc * MAL Factor = 0.3972% * 70 = 27.80
MAL Factor entered against range: '0 to 100' = 70
[ETHYL ALCOHOL] Conc * MAL Factor = 0.3326% * 7 = 2.328
MAL Factor entered against range: '0 to 100' = 7
[1-METHOXY-2-PROPYL ACETATE] Conc * MAL Factor = 0.03802% * 19 = 0.7223
MAL Factor entered against range: '0 to 100' = 19
[N-BUTYL ACETATE] Conc * MAL Factor = 0.03551% * 14 = 0.4972
MAL Factor entered against range: '0 to 100' = 14
[METHYL ALCOHOL] Conc * MAL Factor = 0.01750% * 54 = 0.9452
MAL Factor entered against range: '0 to 100' = 54
[CUMENE] Conc * MAL Factor = 0.0009029% * 1000 = 0.9029
MAL Factor entered against range: '0 to 100' = 1000
[toluene] Conc * MAL Factor = 0.0007494% * 74 = 0.05545
MAL Factor entered against range: '0 to 100' = 74
[2-METHOXY-1-PROPYL ACETATE] Conc * MAL Factor = 0.0002980% * 181 = 0.05393
MAL Factor entered against range: '0 to 100' = 181
[1-BUTANOL] Conc * MAL Factor = 0.0002980% * 67 = 0.01996
MAL Factor entered against range: '0 to 100' = 67
[BENZENE] Conc * MAL Factor = 0.000009029% * 880 = 0.007945
MAL Factor entered against range: '0 to 100' = 880
[ACETIC ACID] Conc * MAL Factor = 0.000005251% * 400 = 0.0002100
MAL Factor entered against range: '0 to 100' = 400
[ACETONE] Conc * MAL Factor = 0.000005251% * 23 = 0.00001208
MAL Factor entered against range: '0 to 100' = 23
Ingredients with MAL factor of 0 [did not contribute] {Denmark MAL Code}
ACRYLIC RESIN (26.53%)
MAL Factor entered against range: '0 to 100' = 0
TITANIUM DIOXIDE (6.701%)
MAL Factor entered against range: '0 to 100' = 0
PARAFFIN WAXES AND HYDROCARBON WAXES; CHLORINATED (3.8%)
MAL Factor entered against range: '0 to 100' = 0
QUATERN.AM.CPS,BIS(HYDROGEN.TALLOW ALKYL)DIMET.-,BENTONITE (0.9218%)

MAL Factor entered against range: '0 to 100' = 0
 N,N-1,6-HEXANEDIYLBIS (12-HYDROXY-OCTADECANEIMIDE) (0.55%)
 MAL Factor entered against range: '0 to 100' = 0
 ALUMINUM HYDROXIDE (0.252%)
 MAL Factor entered against range: '0 to 100' = 0
 modified polyurethane (0.1354%)
 Default assumption [non-volatile] = 0
 TRIMETHYLOLPROPANE (0.072%)
 MAL Factor entered against range: '0 to 100' = 0
 TITANIUM DIOXIDE (<10 microns) (0.06715%)
 MAL Factor entered against range: '0 to 100' = 0
 SILICA (0.0504%)
 MAL Factor entered against range: '0 to 100' = 0
 WATER (0.03601%)
 MAL Factor entered against range: '0 to 100' = 0
 ZIRCONIUM OXIDE (0.0216%)
 MAL Factor entered against range: '0 to 100' = 0
 QUARTZ (>10 microns) (0.01900%)
 MAL Factor entered against range: '0 to 100' = 0
 CARBON BLACK (0.0137%)
 MAL Factor entered against range: '0 to 100' = 0
 QUARTZ (<10 microns) (0.009407%)
 MAL Factor entered against range: '0 to 100' = 0
 IRON HYDROXIDE OXIDE (0.0062%)
 MAL Factor entered against range: '0 to 100' = 0
 Siloxanes and Silicones, methyl 3,3,3-trifluoropropyl (0.002800%)
 Default assumption [non-volatile] = 0
 dibutyltin dilaurate (0.00002709%)
 MAL Factor entered against range: '0 to 100' = 0
 organotin compound (0.00002709%)
 From US (ACGIH) OELs: Product is assumed to be non-volatile, due to an OEL in mg/m³ being available, and no ppm OEL being available] = 0
 Available value in mg/m³ = 0.1
 DENATONIUM BENZOATE (0.00003326%)
 Default assumption [non-volatile] = 0
 OCTAMETHYLCYCLOTETRAILOXANE (0.0000004%)
 MAL Factor entered against range: '0 to 100' = 0

Figure-after-dash (Ingredient(s) above the cut-off on their own) = 3

Ingredients above the Figure-after-dash 3 concentration limit on their own {Denmark MAL Code}

XYLENES (15.19%)

Ingredient concentration is above the limit [10%]

Stricter figure-after-dash numbers that are not available because $\Sigma [\text{ing conc} / \text{ing limit}] < 1$

Figure-after-dash 6 calculated ratio: $\Sigma [\text{ing conc} / \text{ing limit}] = 0.0039709848$

METHYL ALCOHOL: $\text{Ing conc} / \text{Ing limit} = 0.01750 / 20 = 0.0008752$

Minimum value of concentration limit associated with figure-after-dash 6 = 20

CARBON BLACK: $\text{Ing conc} / \text{Ing limit} = 0.0137 / 25 = 0.000548$

Minimum value of concentration limit associated with figure-after-dash 6 = 25

QUARTZ (<10 microns): $\text{Ing conc} / \text{Ing limit} = 0.009407 / 10 = 0.0009407$

Minimum value of concentration limit associated with figure-after-dash 6 = 10

2-METHOXY-1-PROPYL ACETATE: $\text{Ing conc} / \text{Ing limit} = 0.0002980 / 0.2 = 0.001490$

Minimum value of concentration limit associated with figure-after-dash 6 = 0.2

dibutyltin dilaurate: $\text{Ing conc} / \text{Ing limit} = 0.00002709 / 1 = 0.00002709$

Minimum value of concentration limit associated with figure-after-dash 6 = 1

BENZENE: $\text{Ing conc} / \text{Ing limit} = 0.000009029 / 0.1 = 0.00009029$

Minimum value of concentration limit associated with figure-after-dash 6 = 0.1

Figure-after-dash 4 calculated ratio: $\Sigma [\text{ing conc} / \text{ing limit}] = 0.000000210048$

ACETIC ACID: $\text{Ing conc} / \text{Ing limit} = 0.0000005251 / 25 = 0.0000002100$

Minimum value of concentration limit associated with figure-after-dash 4 = 25