

SAFETY DATA SHEET



Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Date of issue/Date of revision 8 August 2025

Version 1.03

Section 1. Chemical product and company identification

Product code : 000010023257
Product name : SIGMASHIELD 1200 BASE RAL 3020
Product name : SIGMASHIELD 1200 BASE RAL 3020
Other means of identification : 00370506
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Not applicable.

Supplier's details : PPG Coatings (Kunshan) Co., Ltd
53 Jinyang Road, Lujia Town,
215331 Kunshan City, Jiangsu Province, P.R. China
Tel: 86 512 57678859 Fax: 86 512 57678857

Emergency telephone number (with hours of operation) : 00 86 532 83889090

Section 2. Hazards identification

Classification of the substance or mixture according to GB 30000.1-2024 and GB 30000-2013

Emergency overview

Liquid.
Red.

Characteristic.

May be harmful if swallowed or in contact with skin.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice or attention. If eye irritation persists: Get medical advice or attention.

See Section 12 for environmental precautions.

Section 2. Hazards identification

Classification of the substance or mixture

- : ACUTE TOXICITY (oral) - Category 5
ACUTE TOXICITY (dermal) - Category 5
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
AQUATIC HAZARD (ACUTE) - Category 2
AQUATIC HAZARD (LONG-TERM) - Category 2
- Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 12.2%
- Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 47.1%
- Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 16.4%

GHS label elements

Hazard pictograms



Signal word

- : Warning

Hazard statements

- : May be harmful if swallowed or in contact with skin.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

- : Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

- : Collect spillage. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Suitable extinguishing media

- : Use an extinguishing agent suitable for the surrounding fire.

Storage

- : Not applicable.

Disposal

- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Physical and chemical hazards

- : No known significant effects or critical hazards.

Health hazards

- : May be harmful if swallowed or in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Section 2. Hazards identification

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Environmental hazards : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : 00370506

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
bisphenol F diglycidyl ether, isomer mixture	40 - <70	SUB140549
benzyl alcohol	1 - <10	100-51-6
Phenol, polymer with formaldehyde, glycidyl ether	1 - <10	28064-14-4
Talc , not containing asbestiform fibres	1 - <10	14807-96-6
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	0.1 - <1	100545-48-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May be harmful if swallowed.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Talc, not containing asbestiform fibres

GBZ 2.1 (China, 7/2024)

PC-TWA 8 hours: 3 mg/m³. Form: total dust.

PC-TWA 8 hours: 1 mg/m³. Form: respirable dust.

Recommended monitoring procedures

- : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection

- : Chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Red.
- Odor** : Characteristic.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: Not applicable.
- Lower and upper explosive (flammable) limits** : Not available.
- Relative density** : 1.57

Solubility(ies)

Media	Result
cold water	Not soluble

Viscosity

- : Dynamic (room temperature): Not available.
- : Kinematic (room temperature): Not available.
- : Kinematic (40°C): >21 mm²/s

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

Section 10. Stability and reactivity

- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose
bisphenol F diglycidyl ether, isomer mixture	Rat - Male, Female - Oral - LD50	>2000 mg/kg
-	Rat - Male, Female - Dermal - LD50	>2000 mg/kg
benzyl alcohol	Rabbit - Dermal - LD50	>2000 mg/kg
-	Rat - Oral - LD50	1200 mg/kg
-	Rat - Inhalation - LC50 Dusts and mists	>5 mg/l [4 hours]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Rat - Oral - LD50	>2000 mg/kg
-	Rat - Inhalation - LC50 Dusts and mists	5.05 mg/l [4 hours]

Product Conclusion : There are no data available on the mixture itself.

Skin corrosion/irritation

Conclusion/Summary : There are no data available on the mixture itself.

Serious eye damage/eye irritation

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory corrosion/irritation

Conclusion/Summary : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Species	Result
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Guinea pig - skin	<u>Result</u> : Sensitizing

Skin

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory

Conclusion/Summary : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

Product/ingredient name	Result
Talc , not containing asbestiform fibres	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Aspiration hazard

Product/ingredient name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

- Conclusion/Summary** : There are no data available on the mixture itself.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMASHIELD 1200 BASE RAL 3020	3708.3	2681.2	N/A	N/A	N/A
bisphenol F diglycidyl ether, isomer mixture	2500	2500	N/A	N/A	N/A
benzyl alcohol	1200	2500	N/A	N/A	N/A
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	2500	N/A	N/A	N/A	5.05

Other information :

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
bisphenol F diglycidyl ether, isomer mixture	LC50	Fish	2.54 mg/l [96 hours]
	EC50	Daphnia	>1000 mg/l [48 hours]
	EC50	Algae	>1.8 mg/l [72 hours]
	NOEC	Daphnia	0.3 mg/l [21 days]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute - LC50	Fish - <i>Oncorhynchus mykiss</i>	>10 mg/l [96 hours]
	Acute - EC50	Daphnia - <i>Daphnia magna</i>	>10 mg/l [48 hours]
	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i>	>100 mg/l [72 hours]

Conclusion/Summary : Not available.

Persistence/degradability

Product/ingredient name	Test	Result	Dose / Inoculum
bisphenol F diglycidyl ether, isomer mixture	-	0% [28 days] - Not readily	
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Ready Biodegradability - Closed Bottle Test	22% [28 days]	

Conclusion/Summary : Not available.

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bisphenol F diglycidyl ether, isomer mixture	-	-	Not readily
benzyl alcohol	-	-	Readily
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	-	-	Inherent

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
bisphenol F diglycidyl ether, isomer mixture	3.6	-	Low
benzyl alcohol	0.87	-	Low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	High

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F diglycidyl ether, isomer mixture)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F diglycidyl ether, isomer mixture)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F diglycidyl ether, isomer mixture)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F diglycidyl ether, isomer mixture)
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(bisphenol F diglycidyl ether, isomer mixture)	Not applicable.

Additional information

- CN** : None identified.
- UN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

China inventory (IECSC) : All components are listed or exempted.

- References** :
 - Production Safety Law of the People's Republic of China
 - Code of Occupational Disease Prevention of the People's Republic of China
 - Environmental Protection Law of the People's Republic of China
 - Fire Control Law of the People's Republic of China
 - Regulations on the Control over Safety of Dangerous Chemicals
 - Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1)
 - Specification for classification and labelling of chemicals according to Part 1: General rules (GB 30000.1-2024)
 - Safety data sheet for chemical products - Content and order of sections (GB/T16483)
 - Guidance on the compilation of safety data sheet for chemical products (GB/T17519)

Section 15. Regulatory information

General rule for preparation of precautionary label for chemicals (GB15258)
Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

Section 16. Other information

History

Date of issue/Date of revision	: 8 August 2025
Version	: 1.03
Date of previous issue	: 8/8/2025
First issue date	: 4/20/2025
Prepared by	: EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations



Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.