SAFETY DATA SHEET





Date of issue/Date of revision

9 August 2025

Version 3.01

Section 1. Chemical product and company identification

Product code : 00338305

Product name : AQUAPON WB Epoxy Semi Gloss Comp B
Product name : AQUAPON WB Epoxy Semi Gloss Comp B

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.

Use of the substance/

mixture

: Raw Material(s) for Paint; Coating.

Uses advised against : Not applicable.

Supplier's details : PPG Coatings (Kunshan) Co., Ltd

53 Jinyang Road, Lujia Town,

215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857

Emergency telephone number (with hours of

operation)

: 00 86 532 83889090

Section 2. Hazards identification

Classification of the substance or mixture according to GB 30000.1-2024 and GB 30000-2013

Emergency overview

Liquid.

Characteristic.

Causes mild skin irritation.

Prolonged or repeated contact may dry skin and cause irritation.

If skin irritation occurs: Get medical advice or attention.

See Section 12 for environmental precautions.

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 58.1%

GHS label elements

Signal word : Warning

Hazard statements: Causes mild skin irritation.

Precautionary statements

Prevention : Not applicable.

China Page: 1/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 2. Hazards identification

Response : If skin irritation occurs: Get medical advice or attention.

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Storage : Not applicable.

Disposal : Not applicable.

Physical and chemical

hazards

: No known significant effects or critical hazards.

Health hazards: Causes mild skin irritation. Prolonged or repeated contact may dry skin and cause

irritation

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

enecis

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Environmental hazards: No known significant effects or critical hazards.

Other hazards which do not

result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

China Page: 2/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
₹alc , not containing asbestiform fibres	10 - <25	14807-96-6
2-(propyloxy)ethanol	1 - <10	2807-30-9
2-butoxyethanol	1 - <10	111-76-2
glycidated alcohol	0.1 - <1	SUB141935
surfactant resin	0.1 - <1	SUB141936
2,4,7,9-tetramethyldec-5-yne-4,7-diol	0.1 - <1	126-86-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Causes mild skin irritation. Defatting to the skin.
 Ingestion
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

China Page: 3/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 4. First aid measures

Specific treatments

: No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

China Page: 4/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
ralc , not containing asbestiform fibres	GBZ 2.1 (China, 7/2024) PC-TWA 8 hours: 3 mg/m³. Form: total dust. PC-TWA 8 hours: 1 mg/m³. Form: respirable dust.
2-butoxyethanol	GBZ 2.1 (China, 7/2024) PC-TWA 8 hours: 97 mg/m³.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

> Page: 5/12 China

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection

Hand protection

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

Gloves: For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber, neoprene, PVC, butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Odor : Characteristic.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 93.33°C (200°F)

Lower and upper explosive

(flammable) limits

: Not available.

Relative density

: 1.23

Media

Solubility(ies)

cold water Partially soluble

Result

Viscosity

: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm²/s

China Page: 6/12

Product code 00338305 Version 3.01 Date of issue 9 August 2025

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 9. Physical and chemical properties

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

: Keep away from the following materials to prevent strong exothermic reactions: Incompatible materials

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose
2 -(propyloxy)ethanol	Rat - Oral - LD50	3089 mg/kg
- " ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	Rabbit - Dermal - LD50	1.337 g/kg
2-butoxyethanol	Rat - Oral - LD50	1200 mg/kg
-	Rat - Dermal - LD50	>2000 mg/kg
-	Rat - Inhalation - LC50 Vapor	3 mg/l [4 hours]
glycidated alcohol	Rat - Oral - LD50	17100 mg/kg
2,4,7,9-tetramethyldec-5-yne-4,7-diol	Rat - Oral - LD50	4.6 g/kg
-	Rabbit - Dermal - LD50	>2000 mg/kg
-	Rat - Inhalation - LC50 Dusts and	>20 mg/l [1 hours]
	mists	

Product Conclusion Skin corrosion/irritation

: There are no data available on the mixture itself.

5-yne-4,7-diol Grams

Product/ingredient name Species Dose Score 2-butoxyethanol Rabbit - Skin - Moderate Duration of treatment/exposure: 4 irritant Observation period: 28 days 2,4,7,9-tetramethyldec-Rabbit - Skin - Mild irritant Amount/concentration applied: 0.5

Conclusion/Summary : There are no data available on the mixture itself.

Serious eye damage/eye irritation

Product/ingredient name	Species	Dose	Score
2 -butoxyethanol	Rabbit - Eyes - Irritant	Duration of treatment/exposure:	-
		24 hours Observation period: 21 days	
2,4,7,9-tetramethyldec- 5-yne-4,7-diol	Rabbit - Eyes - Severe irritant	Amount/concentration applied: 0.1 Mililiters	-

China Page: 7/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 11. Toxicological information

Conclusion/Summary: There are no data available on the mixture itself.

Respiratory corrosion/irritation

Conclusion/Summary

: There are no data available on the mixture itself.

Sensitization

Skin

Conclusion/Summary: There are no data available on the mixture itself.

Respiratory

Conclusion/Summary: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary

Carcinogenicity

: There are no data available on the mixture itself.

Conclusion/Summary: There are no data available on the mixture itself.

Classification

Product/ingredient name	IARC
2 -butoxyethanol	3

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
r alc , not containing asbestiform fibres	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
surfactant resin	(Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Causes mild skin irritation. Defatting to the skin.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

Ingestion : No specific data.

China Page: 8/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary: There are no data available on the mixture itself.

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
QUAPON WB Epoxy Semi Gloss Comp B	26966.5	15053.0	N/A	56.8	N/A
2-(propyloxy)ethanol	3089	1337	N/A	N/A	N/A
2-butoxyethanol	1200	2500	N/A	3	N/A
glycidated alcohol	17100	N/A	N/A	N/A	N/A
2,4,7,9-tetramethyldec-5-yne-4,7-diol	4600	2500	N/A	N/A	N/A

Other information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
2-butoxyethanol	Acute - LC50	Fish	1474 mg/l [96 hours]
-	Chronic - NOEC	Fish	>100 mg/l [21 days]
glycidated alcohol	Acute - LC50	Fish	>1800 mg/l [96 hours]
	Acute - EC50	Daphnia	7.2 mg/l [48 hours]
	Acute - EC50	Algae	844 mg/l [72 hours]

Conclusion/Summary : Not available.

China	age: 9/12
-------	-----------

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 12. Ecological information

Persistence/degradability

Conclusion/Summary: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
(propyloxy)ethanol	0.673	-	Low
2-butoxyethanol glycidated alcohol	0.81 3.77	160 to 263160	Low High

Mobility in soil

Soil/Water partition

coefficient

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

China Page: 10/12

Product code 00338305 Version 3.01 Date of issue 9 August 2025

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 14. Transport information

Marine pollutant Not applicable. Not applicable. Not applicable. Not applicable. substances

Additional information

: None identified. CN UN : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

Section 15. Regulatory information

China inventory (IECSC) : All components are listed or exempted.

: Production Safety Law of the People's Republic of China References

Code of Occupational Disease Prevention of the People's Republic of China

Environmental Protection Law of the People's Republic of China

Fire Control Law of the People's Republic of China

Regulations on the Control over Safety of Dangerous Chemicals

Occupational exposure limits for hazardous agents in the workplace chemical

hazardous agents (GBZ2.1)

Specification for classification and labelling of chemicals according to Part 1:

General rules (GB 30000.1-2024)

Safety data sheet for chemical products - Content and order of sections (GB/

T16483)

Guidance on the compilation of safety data sheet for chemical products (GB/

T17519)

General rule for preparation of precautionary label for chemicals (GB15258)

Safety rules for classification, precautionary labeling and precautionary statements

of chemicals (GB30000.2-29)

Section 16. Other information

History

Date of issue/Date of : 9 August 2025

revision

Version : 3.01

Date of previous issue : 5/13/2025 First issue date : 10/30/2019

Prepared by : EHS

China Page: 11/12

Product name AQUAPON WB Epoxy Semi Gloss Comp B

Section 16. Other information

Key to abbreviations

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

7

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

China Page: 12/12