# SAFETY DATA SHEET

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013



Date of issue/Date of revision

11 August 2025

Version 2.04

### Section 1. Chemical product and company identification

Product code : 00472544

Product name : STEELGUARD 951 BLACK HARDENER
Product name : STEELGUARD 951 BLACK HARDENER

Product type : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against** 

: Not applicable.

**Supplier's details** : PPG Coatings (Kunshan) Co., Ltd

53 Jinyang Road, Lujia Town,

215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857

**Emergency telephone** number (with hours of

operation)

: 00 86 532 83889090

### Section 2. Hazards identification

Classification of the substance or mixture according to GB 30000.1-2024 and GB 30000-2013

#### **Emergency overview**

Liquid.

Gray.

Characteristic.

May be harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Causes serious eye damage.

Harmful if inhaled.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. (urinary system)

Harmful to aquatic life with long lasting effects.

Causes digestive tract burns.

IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Immediately call a POISON CENTER or doctor.

See Section 12 for environmental precautions.

China Page: 1/15

### Section 2. Hazards identification

### Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 5 ACUTE TOXICITY (dermal) - Category 5 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

AQUATIC HAZARD (LONG-TERM) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 1.6%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 58.5%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 28.3%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 4.1%

### **GHS** label elements **Hazard pictograms**







### Signal word

#### **Hazard statements**

- : Danger
- : May be harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Causes serious eye damage.

Harmful if inhaled.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. (urinary

Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

#### **Prevention**

### Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

#### Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

# Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

media

China Page: 2/15

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 2. Hazards identification

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Physical and chemical

hazards

: No known significant effects or critical hazards.

**Health hazards** 

: May be harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. Suspected of causing cancer. Suspected of damaging fertility or

the unborn child. Causes digestive tract burns.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** 

: Adverse symptoms may include the following:

pain watering redness

Inhalation

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact** 

: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion

: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

**Long term exposure** 

**Potential immediate** 

effects

: Not available.

Potential delayed effects : Not a

: Not available.

: Harmful to aquatic life with long lasting effects.

Other hazards which do not : Causes digestive tract burns. result in classification

**Environmental hazards** 

China Page: 3/15

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

| Ingredient name   | %        | CAS number |
|---|----------|------------|
| melamine  | 40 - <70 | 108-78-1   |
| Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine | 10 - <25 | 68082-29-1 |
| m-phenylenebis(methylamine)   | 10 - <25 | 1477-55-0  |
| 3,6-diazaoctanethylenediamin  | 1 - <10  | 112-24-3   |
| carbon  | 1 - <10  | 7440-44-0  |
| N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)  | 0.1 - <1 | 123-26-2   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

**Inhalation**: Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : Harmful if inhaled.

**Skin contact**: Causes severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

Ingestion : May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

### **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

China Page: 4/15

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 4. First aid measures

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

carbon oxides nitrogen oxides

mode

halogenated compounds metal oxide/oxides

**Special protective actions** for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

China Page: 5/15

Date of issue 11 August 2025 Version 2.04

Product code 00472544

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

> China Page: 6/15

**Product name STEELGUARD 951 BLACK HARDENER** 

# Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

| Ingredient name                                      | Exposure limits                         |
|--|---|
| m-phenylenebis(methylamine)                          | ACGIH TLV (United States, 1/2024)       |
|  | Absorbed through skin.                  |
|  | C: 0.018 ppm.                           |
| carbon   | GBZ 2.1 (China, 7/2024)                 |
|  | PC-TWA 8 hours: 3 mg/m³. Form: dust and |
|  | fiber, total fraction.                  |
| N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | ACGIH TLV (United States)               |
|  | TWA: 10 mg/m³. Form: Total dust.        |
|  | TWA: 3 mg/m³. Form: Respirable.         |

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering** controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye protection Skin protection**  : Chemical splash goggles and face shield.

China Page: 7/15

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 8. Exposure controls/personal protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** nitrile neoprene

Personal protective equipment for the body should be selected based on the task **Body protection** being performed and the risks involved and should be approved by a specialist

before handling this product.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: Respirator selection must be based on known or anticipated exposure levels, the **Respiratory protection** 

> hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Gray.

Odor : Characteristic. **Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: 200°C (392°F)

Lower and upper explosive

(flammable) limits

**Relative density** 1.28

Media

Solubility(ies) cold water Not soluble

**Viscosity** : Dynamic (room temperature): Not available.

: Not available.

Kinematic (room temperature): Not available.

Result

Kinematic (40°C): >21 mm<sup>2</sup>/s

# Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Page: 8/15 China

**Product name STEELGUARD 951 BLACK HARDENER** 

# Section 10. Stability and reactivity

Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

Depending on conditions, decomposition products may include the following

materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/

oxides

# Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

| Product/ingredient name   | Result                                  | Dose                  |
|---|---|-----------------------|
| melamine  | Rat - Oral - LD50                       | 3161 mg/kg            |
| -   | Rat - Inhalation - LC50 Dusts and mists | >5190 mg/m³ [4 hours] |
| Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine | Rat - Dermal - LD50                     | >2000 mg/kg           |
| -   | Rat - Oral - LD50                       | >2000 mg/kg           |
| m-phenylenebis(methylamine)   | Rat - Oral - LD50                       | 930 mg/kg             |
| -   | Rat - Male, Female - Dermal -<br>LD50   | >3100 mg/kg           |
| -   | Rat - Inhalation - LC50 Gas.            | 700 ppm [1 hours]     |
| 3,6-diazaoctanethylenediamin  | Rabbit - Dermal - LD50                  | 1465 mg/kg            |
| -   | Rat - Oral - LD50                       | 1716 mg/kg            |
| N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)  | Rat - Oral - LD50                       | >2000 mg/kg           |
| -   | Rat - Dermal - LD50                     | >2000 mg/kg           |
| -   | Rat - Inhalation - LC50 Dusts and mists | >5.11 mg/l [4 hours]  |

# **Product Conclusion Skin corrosion/irritation**

: There are no data available on the mixture itself.

| Product/ingredient name   | Species                      | Dose   | Score |
|---|------------------------------|--|-------|
| Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine | Human - Skin - Irritant      | -  | -     |
| m-phenylenebis<br>(methylamine)   | Rat - Skin - Severe irritant | Duration of treatment/exposure: 4 hours<br>Observation period: 4 hours | -     |

**Conclusion/Summary** 

: There are no data available on the mixture itself.

Serious eye damage/eye irritation

China Page: 9/15

**Product name STEELGUARD 951 BLACK HARDENER** 

# Section 11. Toxicological information

| Product/ingredient name      | Species                | Dose | Score |
|------------------------------|------------------------|------|-------|
| 1 2 1                        | Rabbit - Eyes - Severe | -    | -     |
| , ,                          | irritant               |      |       |
| products with tall-oil fatty |                        |      |       |
| acids and                    |                        |      |       |
| triethylenetetramine         |                        |      |       |

**Conclusion/Summary**: There are no data available on the mixture itself.

**Respiratory corrosion/irritation** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Sensitization** 

| Product/ingredient name   | Species                       | Result              |
|---|-------------------------------|---------------------|
| Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine | Mouse - skin                  | Result: Sensitizing |
| m-phenylenebis(methylamine)   | Mouse - skin<br>OECD 429      | Result: Sensitizing |
| 3,6-diazaoctanethylenediamin  | Guinea pig - skin<br>OECD 406 | Result: Sensitizing |

Skin

**Conclusion/Summary**: There are no data available on the mixture itself.

Respiratory

**Conclusion/Summary**: There are no data available on the mixture itself.

Mutagenicity

**Conclusion/Summary**: There are no data available on the mixture itself.

Carcinogenicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Classification** 

| Product/ingredient name | IARC |
|-------------------------|------|
| melamine                | 2B   |

#### Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

### **Specific target organ toxicity (single exposure)**

| Product/ingredient name | Result   |
|-------------------------|--|
| carbon                  | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) |
|                         | (Respiratory tract irritation) - Category 3      |

#### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Result   |
|-------------------------|--|
| melamine                | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) |
|                         | (urinary system) - Category 2                      |

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye damage.

China Page: 10/15

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 11. Toxicological information

Inhalation : Harmful if inhaled.

Causes severe burns. May be harmful in contact with skin. May cause an allergic Skin contact

skin reaction.

Ingestion : May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> pain watering redness

**Inhalation** : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact** : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

**Potential immediate** 

effects

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

**Potential immediate** 

: Not available.

Potential delayed effects

: Not available.

**Potential chronic health effects** 

**Conclusion/Summary** : There are no data available on the mixture itself.

General : May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Suspected of causing cancer. Risk of cancer depends on duration and level of Carcinogenicity

exposure.

Mutagenicity : No known significant effects or critical hazards. : Suspected of damaging fertility or the unborn child. Reproductive toxicity

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

China Page: 11/15

**Product name STEELGUARD 951 BLACK HARDENER** 

# **Section 11. Toxicological information**

| Product/ingredient name  | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | Inhalation<br>(vapors)<br>(mg/l) | Inhalation<br>(dusts<br>and<br>mists)<br>(mg/l) |
|--|------------------|-------------------|--------------------------------|----------------------------------|---|
| STEELGUARD 951 BLACK HARDENER melamine Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine | 2223.2           | 2457.6            | 19602.9                        | N/A                              | N/A   |
|  | 3161             | N/A               | N/A                            | N/A                              | N/A   |
|  | 2500             | 2500              | N/A                            | N/A                              | N/A   |
| m-phenylenebis(methylamine) 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)   | 930              | 2500              | 4500                           | N/A                              | N/A   |
|  | 1716             | 1465              | N/A                            | N/A                              | N/A   |
|  | 2500             | 2500              | N/A                            | N/A                              | N/A   |

#### Other information

Causes digestive tract burns. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

# Section 12. Ecological information

#### **Toxicity**

| Product/ingredient name   | Result               | Species                                 | Dose / Exposure                             |
|---|----------------------|---|---|
| melamine Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and | Acute - EC50<br>EC10 | Daphnia<br>Algae                        | 200 mg/l [48 hours]<br>1.78 mg/l [72 hours] |
| triethylenetetramine<br>N,N'-ethane-1,2-diylbis<br>(12-hydroxyoctadecan-<br>1-amide)                  | Acute - EC50         | Daphnia - <i>Daphnia magna</i>          | 94 mg/l [48 hours]                          |
| i-amac)   | Acute - EC50         | Algae - Pseudokirchneriella subcapitata | 29 to 43 mg/l [72 hours]                    |

**Conclusion/Summary**: Not available.

### Persistence/degradability

| Product/ingredient name                                      | Test | Result        | Dose / Inoculum |
|--|------|---------------|-----------------|
| N,N'-ethane-1,2-diylbis<br>(12-hydroxyoctadecan-<br>1-amide) | -    | 63% [28 days] |                 |

**Conclusion/Summary**: Not available.

China Page: 12/15

**Product name STEELGUARD 951 BLACK HARDENER** 

# **Section 12. Ecological information**

| Product/ingredient name   | Aquatic half-life | Photolysis | Biodegradability    |
|---|-------------------|------------|---------------------|
| Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) | -                 | -          | Not readily Readily |

#### **Bioaccumulative potential**

| Product/ingredient name                                      | LogPow | BCF  | Potential |
|--|--------|------|-----------|
| melamine   |        | 3.8  | Low       |
| m-phenylenebis   | 0.18   | 2.69 | Low       |
| (methylamine)  |        |      |           |
| 3,6-diazaoctanethylenediamin                                 |        | -    | Low       |
| N,N'-ethane-1,2-diylbis<br>(12-hydroxyoctadecan-<br>1-amide) | >6     | -    | High      |

### **Mobility in soil**

Soil/Water partition

coefficient

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

China Page: 13/15

**Product name STEELGUARD 951 BLACK HARDENER** 

# **Section 14. Transport information**

|                             | China           | UN              | IMDG            | IATA            |
|-----------------------------|-----------------|-----------------|-----------------|-----------------|
| UN number                   | UN3066          | UN3066          | UN3066          | UN3066          |
| UN proper shipping name     | PAINT           | PAINT           | PAINT           | PAINT           |
| Transport hazard class(es)  | 8               | 8               | 8               | 8               |
| Packing group               | II              | II              | II              | II              |
| Environmental hazards       | No.             | No.             | No.             | No.             |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

#### **Additional information**

CN : None identified. : None identified. UN **IMDG** : None identified. IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

# Section 15. Regulatory information

**China inventory (IECSC)** 

: All components are listed or exempted.

References

Production Safety Law of the People's Republic of China Code of Occupational Disease Prevention of the People's Republic of China Environmental Protection Law of the People's Republic of China

Fire Control Law of the People's Republic of China

Regulations on the Control over Safety of Dangerous Chemicals

Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1)

Specification for classification and labelling of chemicals according to Part 1: General rules (GB 30000.1-2024)

Safety data sheet for chemical products - Content and order of sections (GB/ T16483)

Guidance on the compilation of safety data sheet for chemical products (GB/ T17519)

General rule for preparation of precautionary label for chemicals (GB15258) Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

> China Page: 14/15

**Product name STEELGUARD 951 BLACK HARDENER** 

### Section 16. Other information

**History** 

Date of issue/Date of

revision

Version : 2.04

Date of previous issue : 7/7/2025

First issue date : 11/8/2023

Prepared by : EHS

**Key to abbreviations** : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

: 11 August 2025

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

China Page: 15/15