

# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 13 August 2025

Version 1.03

## Section 1. Identification

**Product code** : 000010023604  
**Product name** : SIGMASHIELD 880 BASE GREY 5177  
**Product type** : Liquid.  
**Other means of identification**  
00393281

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Coating.  
Professional applications, Used by spraying.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

**Company/undertaking identification** : PPG Industries Sales, Inc. and PPG Coatings (Philippines), Inc.  
3rd Floor First Life Center  
174 Salcedo St., Legaspi Village  
Makati City 1229, Philippines  
Tel # 00632- 752-6773/ Fax # 00632-752-6771

**Emergency telephone number** : CHEMTREC +(63) 2-395-3308 (CCN 17704)

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
ACUTE TOXICITY (dermal) - Category 5  
ACUTE TOXICITY (inhalation) - Category 4  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
TOXIC TO REPRODUCTION - Category 1B  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
AQUATIC HAZARD (ACUTE) - Category 3  
AQUATIC HAZARD (LONG-TERM) - Category 3  
Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 35.6%  
Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 82.8%  
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 54.7%

### GHS label elements

**Hazard pictograms** :



## Section 2. Hazards identification

**Signal word** : Danger

**Hazard statements** : Flammable liquid and vapor.  
May be harmful in contact with skin.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.  
May damage fertility or the unborn child.  
Harmful to aquatic life with long lasting effects.

Precautionary statements

**Prevention** : Obtain, read and follow all safety instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor. Wash hands thoroughly after handling. Do not touch eyes. Contaminated work clothing should not be allowed out of the workplace.

**Response** : IF exposed or concerned, get medical advice. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water. IF ON SKIN: Get medical help. Wash with plenty of water. If skin irritation or rash occurs: Get medical help. If skin irritation occurs: Get medical help. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help. Get medical help if you feel unwell.

**Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

CAS number/other identifiers

**CAS number** : Not applicable.

| Ingredient name                                              | %        | CAS number |
|--------------------------------------------------------------|----------|------------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin | 20 - <25 | 25068-38-6 |
| barium sulfate                                               | 10 - <20 | 7727-43-7  |
| Talc , not containing asbestiform fibres                     | 10 - <20 | 14807-96-6 |
| xylene                                                       | 5 - <10  | 1330-20-7  |
| Epoxy Resin (700<MW<=1100)                                   | 3 - <5   | 25036-25-3 |
| Phenol, methylstyrenated                                     | 3 - <5   | 68512-30-1 |
| 2-methylpropan-1-ol                                          | 1 - <3   | 78-83-1    |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.               | 1 - <3   | 68609-97-2 |
| Octadecanamide, N,N'-1,6-hexanediylbis[12-hydroxy-           | 1 - <3   | 55349-01-4 |
| ethylbenzene                                                 | 1 - <3   | 100-41-4   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 3. Composition/information on ingredients

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## Section 4. First aid measures

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

|                                          |                                                                                      |
|------------------------------------------|--------------------------------------------------------------------------------------|
| barium sulfate                           | ACGIH TLV (United States, 1/2024)<br>TWA 8 hours: 5 mg/m³. Form: Inhalable fraction. |
| Talc , not containing asbestiform fibres | TLV (Philippines, 4/2016)<br>TLV 8 hours: 20 mppcf. Form: Dust.                      |
| xylene                                   | TLV (Philippines, 4/2016) [Xylene]<br>TLV 8 hours: 0.1 mg/m³.                        |
| titanium dioxide                         | TLV (Philippines, 4/2016)<br>TLV 8 hours: 15 mg/m³.                                  |
| 2-methylpropan-1-ol                      | TLV (Philippines, 4/2016)                                                            |

## Section 8. Exposure controls/personal protection

ethylbenzene

TLV 8 hours: 300 mg/m<sup>3</sup>.

TLV 8 hours: 100 ppm.

**TLV (Philippines, 4/2016)**

TLV-Ceiling: 435 mg/m<sup>3</sup>.

TLV-Ceiling: 100 ppm.

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : >37.78°C (>100°F)
- Flammability** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Flash point** : Closed cup: 26°C (78.8°F)
- Auto-ignition temperature** :

| Ingredient name     | °C  | °F  | Method |
|---------------------|-----|-----|--------|
| 2-methylpropan-1-ol | 415 | 779 |        |

- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm²/s

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Partition coefficient: n-octanol/water** : Not applicable.
- Vapor pressure** :

| Ingredient name     | Vapor Pressure at 20°C |      |                | Vapor pressure at 50°C |     |        |
|---------------------|------------------------|------|----------------|------------------------|-----|--------|
|                     | mm Hg                  | kPa  | Method         | mm Hg                  | kPa | Method |
| 2-methylpropan-1-ol | <12.00102              | <1.6 | DIN EN 13016-2 |                        |     |        |

- Relative density** : 1.69
- Relative vapor density** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.
- Evaporation rate** : Not available.

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.



## Section 10. Stability and reactivity

- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                                      | Result                | Species | Dose        | Exposure |
|--------------------------------------------------------------|-----------------------|---------|-------------|----------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin | LD50 Dermal           | Rabbit  | >2 g/kg     | -        |
| barium sulfate                                               | LD50 Oral             | Rat     | >2 g/kg     | -        |
|                                                              | LD50 Dermal           | Rat     | >2000 mg/kg | -        |
|                                                              | LD50 Oral             | Rat     | >5000 mg/kg | -        |
| xylene                                                       | LD50 Dermal           | Rabbit  | 1.7 g/kg    | -        |
|                                                              | LD50 Oral             | Rat     | 4.3 g/kg    | -        |
| Epoxy Resin (700<MW <=1100)                                  | LD50 Dermal           | Rat     | >2000 mg/kg | -        |
| Phenol, methylstyrenated                                     | LD50 Oral             | Rat     | >2000 mg/kg | -        |
|                                                              | LD50 Dermal           | Rabbit  | >2000 mg/kg | -        |
|                                                              | LD50 Oral             | Rat     | >2000 mg/kg | -        |
| 2-methylpropan-1-ol                                          | LC50 Inhalation Vapor | Rat     | 24.6 mg/l   | 4 hours  |
|                                                              | LD50 Dermal           | Rabbit  | 2460 mg/kg  | -        |
|                                                              | LD50 Oral             | Rat     | 2830 mg/kg  | -        |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.               | LD50 Dermal           | Rabbit  | >4000 mg/kg | -        |
| ethylbenzene                                                 | LD50 Oral             | Rat     | 17100 mg/kg | -        |
|                                                              | LC50 Inhalation Vapor | Rat     | 17.8 mg/l   | 4 hours  |
|                                                              | LD50 Dermal           | Rabbit  | 17.8 g/kg   | -        |
|                                                              | LD50 Oral             | Rat     | 3.5 g/kg    | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

| Product/ingredient name                                      | Result                   | Species | Score | Exposure        | Observation |
|--------------------------------------------------------------|--------------------------|---------|-------|-----------------|-------------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin | Eyes - Mild irritant     | Rabbit  | -     | 100 mg          | -           |
|                                                              | Eyes - Moderate irritant | Rabbit  | -     | -               | -           |
|                                                              | Skin - Moderate irritant | Rabbit  | -     | -               | -           |
|                                                              | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 UI | -           |
|                                                              | Skin - Severe irritant   | Rabbit  | -     | 24 hours 2 mg   | -           |
| xylene                                                       | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |



## Section 11. Toxicological information

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

| Product/ingredient name                                      | Route of exposure | Species | Result      |
|--------------------------------------------------------------|-------------------|---------|-------------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin | skin              | Mouse   | Sensitizing |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name                                     | Category   | Route of exposure | Target organs                |
|------------------------------------------|------------|-------------------|------------------------------|
| Talc , not containing asbestiform fibres | Category 3 | -                 | Respiratory tract irritation |
| xylene                                   | Category 3 | -                 | Respiratory tract irritation |
| 2-methylpropan-1-ol                      | Category 3 | -                 | Respiratory tract irritation |
| -                                        | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Name         | Category   | Route of exposure | Target organs  |
|--------------|------------|-------------------|----------------|
| ethylbenzene | Category 2 | -                 | hearing organs |

### Aspiration hazard

| Name                | Result                         |
|---------------------|--------------------------------|
| xylene              | ASPIRATION HAZARD - Category 1 |
| 2-methylpropan-1-ol | ASPIRATION HAZARD - Category 2 |
| ethylbenzene        | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

## Section 11. Toxicological information

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage fertility or the unborn child.

### Numerical measures of toxicity

#### Acute toxicity estimates

## Section 11. Toxicological information

| Route                        | ATE value     |
|------------------------------|---------------|
| Oral                         | 7015.89 mg/kg |
| Dermal                       | 2694.68 mg/kg |
| Inhalation (vapors)          | 30.15 mg/l    |
| Inhalation (dusts and mists) | 3.87 mg/l     |

### Other information :

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

## Section 12. Ecological information

### Toxicity

| Product/ingredient name                                                                                                            | Result                          | Species                             | Exposure |
|------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------------------|----------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin<br>2-methylpropan-1-ol oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | Chronic NOEC 0.3 mg/l           | Daphnia                             | 21 days  |
|                                                                                                                                    | Acute EC50 1100 mg/l            | Daphnia                             | 48 hours |
|                                                                                                                                    | EC50 844 mg/l                   | Algae                               | 72 hours |
| ethylbenzene                                                                                                                       | EC50 7.2 mg/l                   | Daphnia                             | 48 hours |
|                                                                                                                                    | LC50 >1.8 mg/l                  | Fish                                | 96 hours |
|                                                                                                                                    | Acute EC50 1.8 mg/l Fresh water | Daphnia                             | 48 hours |
|                                                                                                                                    | Chronic NOEC 1 mg/l Fresh water | Daphnia - <i>Ceriodaphnia dubia</i> | -        |

### Persistence and degradability

| Product/ingredient name                                                                                        | Test                                                       | Result                   | Dose | Inoculum |
|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|--------------------------|------|----------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin<br>oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | OECD 301F                                                  | 5 % - 28 days            | -    | -        |
|                                                                                                                | OECD Ready Biodegradability - Manometric Respirometry Test | 87 % - Readily - 28 days | -    | -        |
| ethylbenzene                                                                                                   | -                                                          | 79 % - Readily - 10 days | -    | -        |

| Product/ingredient name                                      | Aquatic half-life | Photolysis | Biodegradability |
|--------------------------------------------------------------|-------------------|------------|------------------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin | -                 | -          | Not readily      |
| xylene                                                       | -                 | -          | Readily          |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.               | -                 | -          | Readily          |
| ethylbenzene                                                 | -                 | -          | Readily          |

### Bioaccumulative potential

Section 12. Ecological information

| Product/ingredient name                                      | LogP <sub>ow</sub> | BCF         | Potential |
|--------------------------------------------------------------|--------------------|-------------|-----------|
| reaction product: bisphenol-A-(epichlorohydrin); epoxy resin | 2.64 to 3.78       | 31          | Low       |
| xylene                                                       | 3.12               | 7.4 to 18.5 | Low       |
| Phenol, methylstyrenated                                     | 3.627              | -           | Low       |
| 2-methylpropan-1-ol                                          | 1                  | -           | Low       |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs.               | 3.77               | 160 to 263  | Low       |
| ethylbenzene                                                 | 3.6                | 79.43       | Low       |

Mobility in soil

Soil/Water partition coefficient

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

|                             | UN              | IMDG            | IATA            |
|-----------------------------|-----------------|-----------------|-----------------|
| UN number                   | UN1263          | UN1263          | UN1263          |
| UN proper shipping name     | PAINT           | PAINT           | PAINT           |
| Transport hazard class(es)  | 3               | 3               | 3               |
| Packing group               | III             | III             | III             |
| Environmental hazards       | No.             | No.             | No.             |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

Section 14. Transport information

UN

: None identified.

IMDG

: None identified.

IATA

: None identified.

Special precautions for user

:**Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments

: Not applicable.

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

History

Date of issue/Date of revision

: 13 August 2025

Date of previous issue

: 8/11/2025

Version

: 1.03

Prepared by

: EHS

Key to abbreviations

: ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

Procedure used to derive the classification

| Classification                                                                               | Justification         |
|----------------------------------------------------------------------------------------------|-----------------------|
| FLAMMABLE LIQUIDS - Category 3                                                               | On basis of test data |
| ACUTE TOXICITY (dermal) - Category 5                                                         | Calculation method    |
| ACUTE TOXICITY (inhalation) - Category 4                                                     | Calculation method    |
| SKIN CORROSION/IRRITATION - Category 2                                                       | Calculation method    |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A                                             | Calculation method    |
| SKIN SENSITIZATION - Category 1                                                              | Calculation method    |
| TOXIC TO REPRODUCTION - Category 1B                                                          | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 | Calculation method    |
| AQUATIC HAZARD (ACUTE) - Category 3                                                          | Calculation method    |
| AQUATIC HAZARD (LONG-TERM) - Category 3                                                      | Calculation method    |

Indicates information that has changed from previously issued version.

Notice to reader

## Section 16. Other information

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*