AFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 25 August 2025

Version 1.04

Section 1. Identification

: 000001189976 **Product code**

: PPG AQUACOVER ONE 645 (TINTED) **Product name**

Product type : Liquid.

Other means of identification

00452714; 00452715; 00454115; 00454116

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.

Professional applications, Used by spraying.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

Supplier's information : PPG Asian Paints Private Limited

c/o Simpliwork Offices, 4th Floor, Tower A

Godrej IT Park, 02 Building

Godrej Business District, LBS Marg

Vikhroli West Mumbai - 400079

India

Emergency telephone

number:

: +91 22 6815 8700

Section 2. Hazards identification

Classification of the substance or mixture : SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 30.6%

GHS label elements

Signal word : No signal word. **Hazard statements** Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Avoid release to the environment.

: Not applicable. Response **Storage** : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

result in classification

Other hazards which do not : Contains isothiazolinones. May cause allergic reaction.

Page: 1/11 India

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
2-(2-butoxyethoxy)ethanol	1 - <3	112-34-5
ammonia	0.1 - < 0.3	1336-21-6
3-iodo-2-propynyl butylcarbamate	<0.1	55406-53-6
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8- tridecafluorooctyl)	<0.1	SUB141402
phosphates, ammonium salt		
pyrithione zinc	<0.1	13463-41-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

India Page: 2/11

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

India Page: 3/11

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2-(2-butoxyethoxy)ethanol ammonia	ACGIH TLV (United States, 1/2024) TWA 8 hours: 10 ppm. Form: Inhalable fraction and vapor. ACGIH TLV (United States, 1/2024) [Ammonia]
	TWA 8 hours: 25 ppm. TWA 8 hours: 17 mg/m³. STEL 15 minutes: 35 ppm. STEL 15 minutes: 24 mg/m³.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

India Page: 4/11

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 8. Exposure controls/personal protection

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. Colour : Various **Odour** : Faint odour. **Odour threshold** : Not available. : Not available. **Melting point/freezing point Boiling point or initial** : >37.78°C (>100°F)

boiling point and boiling range

: Not available. **Flammability** Lower and upper explosive : Not available.

(flammable) limits

Closed cup: Not applicable. Flash point

Auto-ignition temperature °C °F Ingredient name Method 210 410 DIN 51794 2(2-butoxyethoxy)ethanol

Decomposition temperature Not available.

Hq 8.4

India Page: 5/11

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 9. Physical and chemical properties

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm²/s

Viscosity : > 100 s (ISO 6mm)

Solubility(ies) : Media Result

cold water Partially soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Vapour pressure :

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
<mark>w</mark> áter	17.5	2.3				

Relative density : 1.13

Relative vapour density

Particle characteristics Median particle size

: Not applicable.

: Not available.

Evaporation rate : Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

Hazardous decomposition

products

Hazardous polymerisation

: Depending on conditions, decomposition products may include the following

materials: carbon oxides metal oxide/oxides

: Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

India Page: 6/11

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
•	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	LC50 Inhalation Dusts and mists	Rat	0.047 mg/l	4 hours
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
3 -iodo-2-propynyl butvlcarbamate	Eyes - Severe irritant	Rabbit	-	-	-
pyrithione zinc	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours

Conclusion/Summary

Skin
 Eyes
 There are no data available on the mixture itself.
 Respiratory
 There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
ammonia	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

	India	Page: 7/11
--	-------	------------

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 11. Toxicological information

Name	3 3 3	Route of exposure	Target organs
3-iodo-2-propynyl butylcarbamate reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	Category 1 Category 2	-	trachea liver
pyrithione zinc	Category 1	-	-

Aspiration hazard

Not available.

Information on likely routes

of exposure

Potential acute health effects

: No known significant effects or critical hazards. **Eye contact** Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

: Not available.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
	181975.28 mg/kg 109185.17 mg/kg

	India	Page: 8/11
--	-------	------------

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 11. Toxicological information

Other information

Sanding and grinding dusts may be harmful if inhaled. Contains isothiazolinones. May cause allergic reaction.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
3 -iodo-2-propynyl butylcarbamate	Acute EC50 0.039 mg/l	Algae - Raphidocelis subcapitata - Exponential growth phase	72 hours
	Acute EC50 0.186 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic EC10 0.025 mg/l	Algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase	72 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours
pyrithione zinc	Acute EC50 5.513 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days

Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
3-iodo-2-propynyl butylcarbamate pyrithione zinc	-	25 % - Inhe	erent - 28 days days	-		-
Product/ingredient name	Aquatic half-life	Aquatic half-life		Photolysis		gradability
3-iodo-2-propynyl	-		-		Inhere	nt

50%; < 28 day(s)

Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
pyrithione zinc	0.9	0.9 [OECD 305 E]	Low

Mobility in soil

pyrithione zinc

Soil/water partition

coefficient

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill

India Page: 9/11

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 13. Disposal considerations

should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user :Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

History

Date of issue/Date of

: 25 August 2025

revision

Date of previous issue : 5/4/2025 **Version** 1.04 Prepared by : EHS

Page: 10/11 India

Product name PPG AQUACOVER ONE 645 (TINTED)

Section 16. Other information

ey to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Procedure used to derive the classification

Classification	Justification
, , , , , , , , , , , , , , , , , , , ,	Calculation method Calculation method

▼ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

India Page: 11/11