### SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 25 August 2025

Version 8.01

### **Section 1. Identification**

Product code : 00231309

Product name : SIGMAGLIDE 790 HARDENER

Product type : Liquid.

Other means of identification

Not available.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating

Professional applications, Used by spraying.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

**Supplier's information**: PPG Asian Paints Private Limited

c/o Simpliwork Offices, 4th Floor, Tower A

Godrej IT Park, 02 Building

Godrej Business District, LBS Marg

Vikhroli West Mumbai - 400079

India

**Emergency telephone** 

number:

: +91 22 6815 8700

### Section 2. Hazards identification

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 5

SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN SENSITISATION - Category 1

GERM CELL MUTAGENICITY - Category 2 REPRODUCTIVE TOXICITY - Category 1B

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity:

3.1%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal

toxicity: 96.6%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 96.6%

**GHS** label elements

Hazard pictograms









India Page: 1/12

**Product name SIGMAGLIDE 790 HARDENER** 

### Section 2. Hazards identification

Signal word

: Danger

**Hazard statements** 

: Harmful if swallowed.

May be harmful in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility or the unborn child. May cause damage to organs. (thymus)

May cause damage to organs through prolonged or repeated exposure. (immune

system)

Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

**Prevention** 

: Obtain, read and follow all safety instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Do not touch eyes. Contaminated work clothing should not be allowed out of the workplace.

Response

: Collect spillage. IF exposed or concerned, get medical advice. IF exposed or concerned: Get emergency medical help immediately. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. IF SWALLOWED: Get emergency medical help immediately. Get medical help. Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Get emergency medical help immediately. Get medical help. Wash with plenty of water. Take off immediately all contaminated clothing. Immediately rinse with water for several minutes. If skin irritation or rash occurs: Get medical help. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help. Get medical help if you feel unwell.

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : Causes digestive tract burns. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

### CAS number/other identifiers

**CAS** number : Not applicable.

Ingredient name	%	CAS number
riacetoxyethylsilane dibutyltin di(acetate) 1,1,3,3-Disiloxanetetrol, 1,3-diethyl-, tetraacetate	50 - 100 3 - <5 1 - <3	17689-77-9 1067-33-0 122842-90-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

India	Page: 2/12
India	Page: 2/12

**Product name SIGMAGLIDE 790 HARDENER** 

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May be harmful in contact with skin. May cause damage to

organs following a single exposure in contact with skin. May cause an allergic skin

reaction.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns. May cause

damage to organs following a single exposure if swallowed.

### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

India Page: 3/12

**Product name SIGMAGLIDE 790 HARDENER** 

### Section 5. Firefighting measures

### Extinguishing media

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

India Page: 4/12

Product code 00231309 Date of issue 25 August 2025 Version 8.01
Product name SIGMAGLIDE 790 HARDENER

# Section 7. Handling and storage

### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
thutyltin di(acetate)	ACGIH TLV (United States, 1/2024) [Tin, organic compounds] Absorbed through
	skin. TWA 8 hours: 0.1 mg/m³ (as Sn). STEL 15 minutes: 0.2 mg/m³ (as Sn).

# Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

## **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

India Page: 5/12

**Product name SIGMAGLIDE 790 HARDENER** 

### Section 8. Exposure controls/personal protection

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: nitrile neoprene

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### <u>Appearance</u>

Physical state : Liquid.
Colour : Not available.

Odour : Characteristic.

Odour threshold : Not available.

Melting point/freezing point : Not available.

Boiling point or initial : >37.78°C (>100°F)

boiling point and boiling

**Flammability** 

range

Not available.Not available.

Lower and upper explosive

(flammable) limits

Flash point : Closed cup: 109°C (228.2°F)

Auto-ignition temperature : 480°C (896°F)

Decomposition temperature : Not available.

pH : Not applicable.

India Page: 6/12

**Product name SIGMAGLIDE 790 HARDENER** 

### Section 9. Physical and chemical properties

**Viscosity** : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm<sup>2</sup>/s

Media Result Solubility(ies)

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Vapour pressure

	Vapour Pressure at 20°C		Vapou	ır pressu	re at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
triacetoxyethylsilane	0.7500615	0.1				

Relative density : 1.15 : 1.18 Bulk density (g/cm³)

Relative vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable. : Not available. **Evaporation rate** 

### Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

**Hazardous polymerisation** 

: Depending on conditions, decomposition products may include the following

materials: carbon oxides metal oxide/oxides

: Under normal conditions of storage and use, hazardous polymerisation will not

India

occur.

### Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
triacetoxyethylsilane	LD50 Oral	Rat	1.462 g/kg	-
dibutyltin di(acetate)	LD50 Dermal	Rabbit	2318 mg/kg	-

**Conclusion/Summary** 

**Irritation/Corrosion** 

: There are no data available on the mixture itself.

**Conclusion/Summary** 

Page: 7/12

**Product name SIGMAGLIDE 790 HARDENER** 

### **Section 11. Toxicological information**

**Skin**: There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

**Respiratory**: There are no data available on the mixture itself.

**Sensitisation** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Name	3.3	Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	oral	thymus

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	-	immune system

### **Aspiration hazard**

Not available.

Information on likely routes

of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May be harmful in contact with skin. May cause damage to

organs following a single exposure in contact with skin. May cause an allergic skin

reaction.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns. May cause

damage to organs following a single exposure if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

India Page: 8/12

**Product name SIGMAGLIDE 790 HARDENER** 

### **Section 11. Toxicological information**

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

stomach pains

reduced foetal weight increase in foetal deaths skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate :

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.Reproductive toxicity : May damage fertility or the unborn child.

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Route	ATE value
Oral	1444.19 mg/kg
Dermal	2586.3 mg/kg

#### Other information

Causes digestive tract burns.

India Page: 9/12

**Product name SIGMAGLIDE 790 HARDENER** 

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
, ,	Acute EC10 3.1 mg/l	Fish	72 hours
	Acute EC50 0.5 mg/l	Algae	72 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
dibutyltin di(acetate)	-	-	Not readily

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **Section 14. Transport information**

	UN	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(dibutyltin di(acetate))	Not applicable.

India Page: 10/12

**Product name SIGMAGLIDE 790 HARDENER** 

### **Section 14. Transport information**

#### **Additional information**

UN : None identified.

**IMDG**: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

Special precautions for user :Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

### Section 15. Regulatory information

### **International regulations**

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

### Section 16. Other information

**History** 

Date of issue/Date of

revision

Date of previous issue : 10/17/2024

Version : 8.01
Prepared by : EHS

tey to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

: 25 August 2025

#### Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
ACUTE TOXICITY (dermal) - Category 5	Calculation method
SKIN CORROSION/IRRITATION - Category 1B	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 2	Calculation method
REPRODUCTIVE TOXICITY - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2	Calculation method

India Page: 11/12

**Product name SIGMAGLIDE 790 HARDENER** 

### Section 16. Other information

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Calculation method

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

India Page: 12/12