

SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2023.

Date of issue/Date of revision 25 August 2025

Version 1

Section 1. Identification

Product name : PPG FLR 912 LV EPOXY PRIMER SAFETY RED - A
Product code : 00483653
Other means of identification : Not available.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/ mixture : Coating.
Uses advised against : Not applicable.

Supplier : PPG Canada Inc.
5676 Timberlea Blvd
Mississauga ON L4W 4M6
Canada
+1 905-629-7999

PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 888-977-4762

Section 2. Hazard identification

Classification of the substance or mixture : SKIN IRRITATION - Category 2
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1B
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 1B

GHS label elements
Hazard pictograms :

Signal word : Danger

Section 2. Hazard identification

Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer. May damage fertility or the unborn child.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Emits toxic fumes when heated. Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 3.8% (oral), 3.9% (dermal), 85.7% (inhalation)
Other hazards which do not result in classification	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: PPG FLR 912 LV EPOXY PRIMER SAFETY RED - A
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
bis-[4-(2,3-epoxipropoxy)phenyl]propane	2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)]bisoxirane; Oxirane, 2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)]bis-; Bisphenol A diglycidyl ether; Bisphenol A, diglycidyl ether; Bis-[4-(2,3-epoxypropoxy)phenyl]propane; 2,2-bis[4-(2,3-epoxypropoxy)phenyl]propane; Propane, 2,2-bis(p-(2,3-epoxypropoxy)phenyl)-; diglycidyl ether of bisphenol-A; 2,2-bis(4-hydroxyphenyl) propane bis (2,3-epoxypropyl) ether; Araldite; DIPHENYLOL PROPANE DIGLYCIDYL ETHER	60 - 80*	1675-54-3

Section 3. Composition/information on ingredients

benzyl alcohol	Benzenemethanol; .alpha.-Hydroxytoluene; Phenylcarbinol; Phenylmethanol; E 1519; α -hydroxytoluene; Phenylmethyl alcohol; toluenol, alpha-; (hydroxymethyl)benzene; BENZENECARBINOL; alpha-Hydroxytoluene	5 - 10*	100-51-6
Epoxy resin (MW \leq 700)	reaction product : bisphenol a- (epichlorhydrin) ; epoxy resin (number average molecular weight \leq 700)	3 - 7*	25068-38-6
[3-(2,3-epoxypropoxy)propyl] trimethoxysilane	Oxirane, 2-[[3-(trimethoxysilyl)propoxy] methyl]; Silane, trimethoxy[3-(oxiranymethoxy)propyl]-; 3-(2,3-Epoxypropoxy)propyltrimethoxysilane; (3-(2,3-Epoxypropoxy)propyl) trimethoxysilane; mixture consisting of: — 64 % or more, but not more than 74 % by weight of amorphous silica (CAS RN 7631-86-9) — 25 % or more, but not more than 35 % by weight of butanone (CAS RN 78-93-3) and — not more than 1 % by weight of 3-(2,3-epoxypropoxy) propyltrimethoxysilane (CAS RN 2530-83-8); Silane, 3-(2,3-epoxypropoxy) propyltrimethoxy-; Trimethoxy[3-(oxiran-2-ylmethoxy)propyl]silane; 2,3-Epoxy propoxy propyltrimethoxysilane; Coupling agent KH-560; Coupler KH-560; 2-{{3-(Trimethoxysilyl)propoxy} methyl}oxirane	1 - 5*	2530-83-8
Cashew, nutshell liq., 2-hydroxyethyl ethers	Cashew, nutshell liquid, 2-hydroxyethyl ethers	1 - 5*	232268-65-4
tetrahydro-2-furylmethanol	tetrahydro-2-furyl-methanol; tetrahydrofurfuryl alcohol; 2-Furanmethanol, tetrahydro-; 2-TETRAHYDROFURANMETHANOL; 2-(HYDROXYMETHYL) TETRAHYDROFURAN; Tetrahydro-2-furanylmethanol; THFA; Tetrahydro-2-furancarbinol; Tetrahydro-2-furanmethanol; FURFURYL ALCOHOL, TETRAHYDRO-; 2-Hydroxymethyl oxolane	0.1 - 1*	97-99-4
ethylbenzene	Benzene, ethyl-; Phenylethane; Ethylbenzol; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); EB; Mono-(or di-) methyl (ethyl,bromoallyl,	0.1 - 1*	100-41-4

Section 3. Composition/information on ingredients

	bromopropoxy carbonyl orchloropropoxy carbonyl) benzene		
--	--	--	--

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Section 4. First-aid measures

Ingestion

- : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

- : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

- : No specific treatment.

Protection of first-aiders

- : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

- : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

- : None known.

Specific hazards arising from the chemical

- : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

- : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters

- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

- : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene : Wash hands thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	None.
benzyl alcohol	None.
Epoxy resin (MW ≤ 700)	None.
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	None.
Cashew, nutshell liq., 2-hydroxyethyl ethers	None.
tetrahydro-2-furylmethanol	None.
ethylbenzene	CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 100 ppm. OEL 8 hours: 434 mg/m ³ . OEL 15 minutes: 543 mg/m ³ . OEL 15 minutes: 125 ppm. CA British Columbia Provincial (Canada, 9/2024) TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 20 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 20 ppm. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Chemical splash goggles and face shield.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Red.
Odor	: Odorless.
pH	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 118°C (244.4°F)
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.14
Density (lbs / gal)	: 9.51

Section 9. Physical and chemical properties

	Media	Result
Solubility(ies)	cold water	Not soluble
Partition coefficient: n-octanol/water	:	Not applicable.
Viscosity	:	Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm ² /s (>21 cSt)
% Solid. (w/w)	:	90.889
Particle characteristics		
Median particle size	:	Not applicable.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalies, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit - Dermal - LD50 Rat - Oral - LD50	23000 mg/kg 15000 mg/kg
benzyl alcohol	Rabbit - Dermal - LD50 Rat - Oral - LD50 Rat - Inhalation - LC50 Dusts and mists	>2000 mg/kg 1200 mg/kg >5 mg/l [4 hours]
Epoxy resin (MW ≤ 700)	Rat - Oral - LD50 Rabbit - Dermal - LD50	>2 g/kg >2 g/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rat - Oral - LD50 Rat - Inhalation - LC50 Dusts and mists	7.01 g/kg >5.3 mg/l [4 hours]
tetrahydro-2-furylmethanol	Rat - Oral - LD50 Rabbit - Dermal - LD50	1600 mg/kg 1.22 g/kg
ethylbenzene	Rat - Inhalation - LC50 Vapor Rat - Oral - LD50 Rabbit - Dermal - LD50	19630 mg/m ³ [4 hours] 3.5 g/kg 17.8 g/kg

Section 11. Toxicological information

	Rat - Inhalation - LC50 Vapor	17.8 mg/l [4 hours]
--	-------------------------------	---------------------

Product Conclusion : There are no data available on the mixture itself.

Skin corrosion/irritation

Product/ingredient name	Species	Dose	Score
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit - Skin - Erythema/Eschar	Duration of treatment/exposure: 4 hours	Irritation score: 0.8
	Rabbit - Skin - Edema	Duration of treatment/exposure: 4 hours	Irritation score: 0.5
	Rabbit - Skin - Mild irritant	Duration of treatment/exposure: 4 hours	-
Epoxy resin (MW ≤ 700)	Rabbit - Skin - Mild irritant	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Serious eye damage/eye irritation

Product/ingredient name	Species	Dose	Score
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit - Eyes - Redness of the conjunctivae	Duration of treatment/exposure: 24 hours	Irritation score: 0.4
	Rabbit - Eyes - Mild irritant	Duration of treatment/exposure: 24 hours	-
	Rabbit - Eyes - Mild irritant	Fully reversible in 7 days or less	-
Epoxy resin (MW ≤ 700)	Rabbit - Eyes - Mild irritant	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory corrosion/irritation

Conclusion/Summary : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Species	Result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Mouse - skin	Result: Sensitizing
Epoxy resin (MW ≤ 700)	Mouse - skin OECD 429	Result: Sensitizing

Skin

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory

Conclusion/Summary : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-epoxipropoxi)phenyl]propane	-	3	-
ethylbenzene	-	2B	-

Carcinogen Classification code: IARC: 1, 2A, 2B, 3, 4
NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen
OSHA: +
Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Product/ingredient name	Result
ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2

Target organs : Contains material which causes damage to the following organs: blood, liver, heart, brain.
Contains material which may cause damage to the following organs: kidneys, upper respiratory tract, eyes, central nervous system (CNS).

Aspiration hazard

Product/ingredient name	Result
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater

Section 11. Toxicological information

hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Conclusion/Summary : There are no data available on the mixture itself.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PPG FLR 912 LV EPOXY PRIMER SAFETY RED - A	11231.8	11167.9	N/A	N/A	N/A
bis-[4-(2,3-epoxipropoxy)phenyl]propane	15000	23000	N/A	N/A	N/A
benzyl alcohol	1200	2500	N/A	N/A	N/A
Epoxy resin (MW ≤ 700)	2500	2500	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	7010	N/A	N/A	N/A	N/A
Cashew, nutshell liq., 2-hydroxyethyl ethers	N/A	1100	N/A	N/A	N/A
tetrahydro-2-furylmethanol	1600	1220	N/A	19.63	N/A
ethylbenzene	3500	17800	N/A	17.8	1.5

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Chronic - NOEC 0.3 mg/l [21 days] Acute - LC50 - Fresh water 1.8 mg/l [48 hours]	Daphnia
Epoxy resin (MW ≤ 700)	Chronic - NOEC 0.3 mg/l [21 days] Acute - LC50 1.8 mg/l [48 hours]	Daphnia - <i>daphnia magna</i> Daphnia

Section 12. Ecological information

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Acute - EC50 - Fresh water 255 mg/l [72 hours] Acute - EC50 473 mg/l [48 hours] Acute - LC50 55 mg/l [96 hours] Acute - EC50 - Fresh water 1.8 mg/l [48 hours] Chronic - NOEC - Fresh water 1 mg/l	Algae Daphnia Fish Daphnia Daphnia - <i>Ceriodaphnia dubia</i>
ethylbenzene		

Conclusion/Summary : Not available.

Persistence and degradability

Product/ingredient name	Result
Epoxy resin (MW ≤ 700)	OECD 301F 5% [28 days]
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane ethylbenzene	37% [28 days] - Not readily 79% [10 days] - Readily

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
benzyl alcohol	0.87	-	Low
Epoxy resin (MW ≤ 700)	3	31	Low
ethylbenzene	3.6	79.43	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane, Epoxy resin (MW ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane, Epoxy resin (MW ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane, Epoxy resin (MW ≤ 700))
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards Marine pollutant substances	Yes. (bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Yes. (bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Yes. Not applicable.

Additional information

TDG : Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Proof of classification statement : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark).

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL) : At least one component is not listed in DSL but all such components are listed in NDSL.

Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications.

The customer is responsible for determining the PPE code for this material.

Date of issue/Date of revision 25 August 2025

Organization that prepared the SDS : EHS

Section 16. Other information

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

☒ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.